COMMERCIAL ITEM DESCRIPTION

ANODES, CADMIUM

The General Services Administration has authorized the use of this description in preference to Federal Specification QQ-A-671A.

This description covers anodes used in electroplating baths.

Salient characteristics.

Types. Anodes covered by this description shall be of the following types:

Type I - Ball anodes
Type II - Oval and rectangular cross sectional bar anodes
Type III - Stick anodes

Size, shape, length and weight. Type I anodes shall be 2 inches in diameter and shall weigh not less than 1-1/4 pounds per ball. Type II anodes of oval and rectangular cross section shall be of the length specified and shall weigh not less than 1 pound per linear inch. Type III anodes shall be furnished in 10 inch lengths and shall have a diameter of 1/2 inch and shall weight not less than .6 pounds.

Material. Anodes shall be of solid cadmium. They shall be either cast, rolled to size or cut from electrorefined castings or rolled plate.

Chemical composition. Chemical composition of cadmium anodes shall meet the chemical element composition requirements in Table I.

TABLE I. Chemical element composition.

Element	Per cent Composition
Cadmium	99.90, Min.
Zinc	0.035, Max.
Lead	0.025, Max.
Copper	0.015, Max.
Silver	0.01, Max.
Tin	0.01, Max.
Arsenic	0.003, Max.
Thallium	0.003, Max.
Antimony	0.001, Max.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:51Z
Check the source to verify that this is the current version before use.

Measurement system. All dimensions in this commercial item description are given in the English system of measurements. These dimensions can be converted to Metric system of equivalents by the use of ANSI/IEEE 268 for Department of Defense use or FED-STD-376 for Civil Agency use.

Workmanship. Anodes shall be clean and free from cracks, warps, inclusions, porosity, ragged edges, surface film or other defects which may adversely affect uniform corrosion in service.

Suspension. The method of suspension shall be in accordance with the manufacturers standard practice.

Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any inspections set forth in the CID where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

Acceptance inspection. The supplier shall randomly select the number of samples specified in Table II that is applicable to the quantity of items being purchased. Each sample shall be visually inspected, measured and tested, by the supplier, to determine conformance with all requirements specified herein. Any sample failing to meet all requirements specified herein shall be considered a defective item. If the number of defective items equals, or is less than the quantity specified under "Acceptance, Number Defective" in Table II, the supplier shall replace the defective samples with items that meet all of the requirements specified herein and the entire lot shall be considered acceptable for shipment. If the number of defective samples equals, or exceeds, the quantity specified in the "Rejection, Number Defective" column of Table II, the entire lot shall be considered defective and unsuitable for acceptance.

TABLE II. Sampling plan.

Quantity of items being purchased	Sample size	Acceptance, number defective	Rejection, number defective
2-8	2	0	1
9-15	3	0	1
16-25	5	0	1
26-50	8	1	2
51-90	13	1	2
91-150	20	2	3
151-280	32	3	4
281-500	50	5	6

Source: https://assist.dla.mil -- Downloaded: 202640-26T08:51Z
Check the source to verify that this is the currentversion before use.

Chemical composition test. Chemical composition of anodes shall be determined by standard method of chemical analysis for cadmium. One anode of the same lot being furnished shall be tested and analyzed to determine conformance with Table I. If the anode does not conform to the required chemical composition, the entire lot shall be rejected. The anodes used for this test shall not be part of the total lot to be furnished.

Regulatory requirements. The offeror/contractor is encouraged to use recovered materials in accordance with Public Law 94-580 to the maximum extent practical.

Preservation, packaging, packing, labeling and marking. Unless otherwise specified in the contract or order, preservation, packaging, packing, labeling and marking shall be in accordance with ASTM D-3951. When specified in the contract or order, preservation, packaging, packing, labeling and marking shall be in accordance with Military Specification MIL-D-6054 level as specified.

Note. Purchasing activities will specify required quantity, type and length as applicable for anodes to be furnished for a specific procurement.

MILITARY INTERESTS:

Custodians

Navy - SH
Air Force - 99

Review Activities

DLA - GS
Air Force - 84

User Activity

Navy - OS, SH

CIVIL AGENCY COORDINATING ACTIVITIES:

GSA - FSS

PREPARING ACTIVITY

DLA - IP

Project Number 3426-0035

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:51Z
Check the source to verify that this is the current version before use.