A-A-51128
2 July 1984

COMMERCIAL ITEM DESCRIPTION

TORCH KIT, SOLDERING
(Propane Gas)

The General Services Administration has authorized the use of this commercial item description in preference to Federal Specification GGG-T-00570A.

This description covers a soldering torch kit, designed to burn propane gas to produce a flame suitable for soldering and heating.

Salient characteristics.

Design. The soldering kit shall conform to the American National Standard Institute/Underwriters' Laboratory Standard (ANSI/UL) 147.

Components. The soldering kit shall consist of a disposable fuel cylinder (fully loaded), burner unit, pencil burner head, utility burner (heavy duty) head, soldering tip, flame spreader, flint lighter, and carrying case.

Cylinder. The fuel cylinder shall be of the disposable type having a nominal 14.1 ounces (400 grams) capacity. The neck of the cylinder shall be provided with a one inch diameter by 20 UNEF threads per inch fitting for connecting the burner unit.

Burner unit. Unless otherwise specified, the burner unit shall consist of a control valve assembly and a length of tubing. The tubing may be permanently attached to the valve assembly or attached by means of a compression nut. The opposite end shall be designed to accommodate the burner heads.

Pencil burner head. Unless otherwise specified, the pencil burner head shall be of brass or copper and shall contain a replaceable orifice which will produce a pencil point flame. The lower end of the pencil burner head shall be internally threaded for connecting to the burner unit.

Soldering tip. The soldering tip shall have a housing of brass or copper, with a copper tip. Means shall be provided for securing the soldering tip to the pencil burner head.

FSC 3439

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:51Z
Check the source to verify that this is the current version before use.

Flame spreader. The flame spreader shall be fan shaped to produce a wide flame to cover a wide area. Means shall be provided for securing the flame spreader to the utility burner head.

Flint lighter. The flint lighter shall contain a replaceable flint.

Carrying case. The carrying case shall be made of either metal or plastic and shall be of sufficient size to hold all components contained in the set.

Performance. The torch shall be capable of operating satisfactorily on the fuel for which it is designed. Lighting shall be instantaneous and without preheating, pumping, or priming. Burning shall be steady and without pulsation in any position. All tips shall operate satisfactorily with the torch.

Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any inspections set forth in the commercial item description where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

Acceptance inspection. The supplier shall randomly select the number of samples specified in table I that is applicable to the quantity of items being purchased. Each sample shall be visually inspected, measured, and performance tested, by the supplier, to determine conformance with all requirements specified herein. Any sample failing to meet all requirements specified herein shall be considered a defective item. If the number of defective items equals, or is less than the quantity specified under "Acceptance, number defective" in table I, the supplier shall replace the defective samples with items that meet all of the requirements specified herein and the entire lot shall be considered acceptable for shipment. If the number of defective samples equals, or exceeds, the quantity specified in the "Rejection, number defective" column of table I, the entire lot shall be considered defective and unsuitable for acceptance.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:51Z
Check the source to verify that this is the current version before use.

TABLE I. Sampling plan.

Lot size	Sample size	Acceptance, number defective	Rejection, number defective
2 to 8	2	0	1
9 to 15	3	0	1
16 to 25	5	0	1
26 to 50	8	1	2
51 to 90	13	1	2
91 to 150	20	2	3
151 to 280	32	3	4
281 to 500	50	5	6
501 to 1200	80	7	8

Regulatory requirements. The offeror/contractor is encouraged to use recovered materials in accordance with Public Law 94-580 to the maximum extent practical.

Preservation, packaging, packing, labeling, and marking. Unless otherwise specified in the contract or order, preservation, packaging, packing, labeling and marking shall be in accordance with ASTM-D-3951. When specified in the contract or order, preservation, packaging, packing, labeling, and marking shall be in accordance with MIL-W-45562, level as specified.

Notes: Purchaser will specify quantity of kits required for a specific purchase.

Military Standard MIL-W-45562, Welding and Soldering Equipment, Supplies and Accessories, Packaging of, should be obtained from the contracting activity or as directed by the contracting officer.

American Society for Testing and Materials (ASTM) Standard D-3951, Standard Practice for Commercial Packaging, is available from the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.

American National Standards Institute/Underwriters' Laboratory (ANSI/UL) 147 is available from the American National Standards Institute, ATTN: Sales Dept., 1430 Broadway, New York, NY 10018.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:51Z
Check the source to verify that this is the current version before use.

MILITARY INTEREST:

Custodians

Army - AL
Air Force - 99

Review activities

DLA - GS, DH
Air Force - 84

User activity

Navy - OS

CIVIL AGENCY COORDINATING ACTIVITY:

GSA-FSS

Preparing Activity

DLA-IP

Project Number 3439-0540

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:51Z
Check the source to verify that this is the current version before use.