A-A-51130
14 August 1984

COMMERCIAL ITEM DESCRIPTION

CUTTER BIT BLANKS AND CUT-OFF BLADES

The General Services Administration has authorized the use of this commercial item description in preference to Federal Specification 00-C-851A.

This description covers cutter bit blanks and straight cut-off blades of high speed tool steel that are designed to be supported by a tool holder for use in various machining operations.

Salient characteristics.

Classification.

Type I - Cutter bit blanks
  Style 1 - Square cross-section (table I)
  Style 2 - Rectangular cross-section (table II)

Type II - Cut-off blades
  Style 1 - Straight side clearance (table III)
  Style 2 - Armstrong style (table IV)

Grade A - General purpose
  Class - T-1, T-2, M-1, M-2, M-3 or M-10

Grade B - Heavy duty
  Class - T-4, T-5, T-6, T-8, T-15, M-30, M-34, M-41, M-42, M-43, M-44, or M-46

Dimensions. The dimensions of the cutter bit blanks and cut-off blades shall conform to tables I, II, III and IV. The tolerances for all dimensions shall be the manufacturers standard as specified on their part drawings.

FSC 3455

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:51Z
Check the source to verify that this is the current version before use.

TABLE I. Type I, style 1 cutter bit blanks.

Dimensions in inches	
Square cross-section	Length
3/16	2-1/2
1/4	2-1/2
5/16	2-1/2
3/8	3
7/16	3-1/2
1/2	4
5/8	4-1/2
3/4	5
1	7
1-1/4	6
1-1/4	7
1-1/4	9
1-1/2	10

TABLE II. Type I, style 2 cutter bit blanks.

Dimensions in inches		
Width	Height	Length
1/4	1/2	4
5/16	5/8	4
5/16	3/4	5
3/8	3/4	4
3/8	3/4	5
3/8	3/4	6
1/2	3/4	6
1/2	1	7
1/2	1	8
5/8	1-1/4	6
5/8	1-1/4	8
3/4	1-1/2	6
3/4	1-1/2	7
1	1-1/2	10
1	2	12

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:51Z
Check the source to verify that this is the current version before use.

TABLE III. Type II, style 1 cut-off blades.

Dimensions in inches		
Thickness	Height	Length
1/16	13/32	3
1/16	1/2	4-1/2
1/16	11/16	5
1/16	13/16	6
5/64	1/2	4-1/2
3/32	1/2	4-1/2
3/32	11/16	5
3/32	13/16	6
3/32	1	6-1/2
1/8	1/2	4-1/2
1/8	11/16	5
1/8	13/16	6
1/8	1	6-1/2
5/32	11/16	5
5/32	13/16	6
3/16	11/16	5
3/16	13/16	6
3/16	7/8	6
3/16	1	6-1/2
3/16	1-1/8	6-1/2
1/4	13/16	6
1/4	7/8	6
1/4	1	6-1/2
1/4	1-1/8	6-1/2
1/4	1-1/4	7

TABLE IV. Type II, style 2 cut-off blades.

Dimensions in inches			Top flat width	
Thickness	Height	Length	Minimum	Maximum
3/32	1/2	4-1/2	0.046	0.063
3/32	5/8	5	0.046	0.063
1/8	3/4	5	0.062	0.081
1/8	7/8	6	0.062	0.081
3/16	1	6-1/2	0.093	0.114
3/16	1-1/8	7	0.093	0.114
1/4	1-1/4	7	0.141	0.154
1/4	1-3/8	7	0.141	0.154

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:51Z
Check the source to verify that this is the current version before use.

Material and hardness. Cutter bits shall be high-speed tool steel alloy, hardened and multiple tempered to a Rockwell "C" hardness of not less than 63 with the grades and classes conforming to the requirements of ANSI/ASTM A 600 latest edition.

Type I cutter bits. Style 1 bits shall have a square cross-section with ends beveled parallel to each other at an angle of 20 degrees and style 2 bits shall have a rectangular cross-section with the ends squared.

Type II cut-off blades. Style 1 blade shall conform to ANSI B94.3, Type "B", and style 2 blade shall conform to ANSI B94.3, Type "F".

Measurement system. All dimensions in this commercial item description are given in the English system of measurement. These dimensions can be converted to Metric system of equivalents by the use of ANSI/IEEE 268 for Department of Defense use or FED-STD-376 for Civil Agency use.

Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the government. The government reserves the right to perform any inspections set forth in the commercial item description where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

Acceptance inspection. The supplier shall randomly select the number of samples specified in table V that is applicable to the quantity of items being purchased. Each sample shall be visually inspected, measured, and tested by the supplier, to determine conformance with all requirements specified herein. Any sample failing to meet these requirements shall be considered a defective item. If the number of defective items equals, or is less than the quantity specified under "Acceptance, number defective": column of table V, the supplier shall replace the defective samples with acceptable ones, and the entire lot shall be considered acceptable for shipment. If the number of defective samples equals, or exceeds, the quantity specified in the "Rejection, number defective" column of table V, the entire lot shall be considered defective and unsuitable for acceptance.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:51Z
Check the source to verify that this is the current version before use.

TABLE V. Sampling plan.

Quantity of items being purchased	Sample size	Acceptance, number defective	Rejection, number defective
2-8	2	0	1
9-15	3	0	1
16-25	5	0	1
26-50	8	0	1
51-90	13	1	2
91-150	20	2	3
151-280	32	3	4
281-500	50	5	6

Regulatory requirements. The offeror/contractor is encouraged to use recovered materials in accordance with Public Law 94-580 to the maximum extent practical.

Preservation, packaging, packing, labeling and marking. Unless otherwise specified in the contract or order, preservation, packaging, packing, labeling and marking shall be in accordance with ASTM D 3951. When specified in the contract or order, preservation, packaging, packing, labeling and marking shall be in accordance with Federal Specification PPP-T-1150, level as specified.

Notes. Purchaser will specify quantity, type, style, grade, class and size for a specific procurement.

American National Standards Institute ANSI/ASTM A 600 "Standard Specification for High Speed Tool Steel," ANSI B94.3 "Straight Cut-Off Blades for Lathes and Screw Machines" and ANSI/IEEE 268 "Metric Practice" are available from the American National Standards Institute, 1403 Broadway, New York, NY 10018.

American Society for Testing and Materials ASTM D 3951 "Commercial Packaging, Standard Practice for" are available from the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.

Copies of Federal Specification PPP-T-1150 "Tools and Tool Accessories for Power Driven, Metal and Woodworking Machinery, Packaging and Packing Of" and FED-STD-376 "Preferred Metric Units for General Use by the Federal Government" should be obtained from the contracting activity or as directed by the contracting officer.

Type, style, grade and class designations conform to type, style, grade and class designations of Federal Specification 00-C-851A.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:51Z
Check the source to verify that this is the current version before use.

MILITARY INTERESTS:

Custodians

Army - AL
Navy - SH
Air Force - 99

Review Activities

Air Force - 84

CIVIL AGENCY COORDINATING ACTIVITY:

GSA - FSS

PREPARING ACTIVITY:
DLA - IP

Project 3455-0093

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:51Z
Check the source to verify that this is the current version before use.