A-A-51131
2 July 1984

COMMERCIAL ITEM DESCRIPTION

TOOL HOLDER, EXTENSION, SHAPER

The General Services Administration has authorized the use of this commercial item description in preference to the Type VIII tool holders in Federal Specification 00-H-581.

Salient characteristics.

Classification. Tool holders covered by this description shall be furnished under the tool holder numbers specified in table I with the dimensional data conforming to table I. Extension bar numbers and dimensional data shall conform to table II. Bushing numbers and dimensional data shall conform to table III. The tolerances for all dimensional data shall be the manufacturer's standard as specified on their part drawings.

TABLE I. Shaper extension tool holder.

Tool holder number	Thickness of shank; inches	Height of shank; inches	Length of shank; inches	Diameter of bar hole; inches
J-S-3	3/8	7/8	4	3/4
J-S-0	1/2	1-1/8	5	3/4
J-S-1	5/8	1-3/8	5-3/4	15/16
J-S-2	3/4	1-5/8	7	1-1/8

TABLE II. Shaper extension bar.

Extension bar number	Diameter of extension bar; inches	Length of extension bar; inches	Size of square tool bit channel; inches
E-B-1	1/2	7-1/2	3/16
E-B-2	5/8	8-1/2	1/4
E-B-3	3/4	10	5/16
E-B-4	15/16	12	3/8
E-B-5	1-1/8	14	7/16

FSC 3460

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:51Z
Check the source to verify that this is the current version before use.

TABLE III. Bushing for shaper extension holder.

Bushing number	Outside work diameter; inches	Inside work diameter; inches	Length of bushing; inches	
			min.	max.
H-00	3/4	1/2	1-3/4	1-7/8
H-01	3/4	5/8	1-3/4	1-7/8
H-10	15/16	1/2	2-3/16	2-5/16
H-11	15/16	5/8	2-3/16	2-5/16
H-12	15/16	3/4	2-3/16	2-5/16
H-20	1-1/8	1/2	2-5/8	2-3/4
H-21	1-1/8	5/8	2-5/8	2-3/4
H-22	1-1/8	3/4	2-5/8	2-3/4
H-23	1-1/8	15/16	2-5/8	2-3/4

Components. Shaper extension bar tool holders shall consist of a body, extension bar, clamping device and, when specified, bushings.

Body. The body shall have an integral shank and a bar holding head, shall be of drop-forged alloy steel, heat-treated to a Rockwell "C" 40 to 48 hardness on the shank and Rockwell "C" 26 to 34 hardness on the head, or alloy steel surface hardened to a Rockwell "C" 50 to 55 on the shank and 40 to 45 on the head.

Bar holding head. The head shall be split spring section style to provide an adjustable support for the extension bar.

Extension bar. The extension bar shall be of steel with a tool bit channel 90 degrees to the axis and as near the end of the bar as practicable.

Clamping device. There shall be a clamping device for clamping the extension bar in the head and one for clamping the tool bit in the channel of the extension bar.

Bushing. The bushing shall be of steel and have a split section for adapting various sizes of extension bars to the holder.

Wrenches. One wrench to fit the clamping device of the tool holder and one to fit the clamping device of tool bit channel of the extension bar shall be furnished with each tool holder.

Measurement system. All dimensions in this commercial item description are given in the English system of measurement. These dimensions can be converted to Metric system equivalents by the use of ANSI/IEEE 268 for Department of Defense use or FED-STD-376 for Civil Agency use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:51Z
Check the source to verify that this is the current version before use.

Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any inspections set forth in this commercial item description where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

Acceptance inspection. The supplier shall randomly select the number of samples specified in table IV that is applicable to the quantity of items being purchased. Each sample shall be visually inspected, measured, and tested by the supplier, to determine conformance with all requirements specified herein. Any sample failing to meet all requirements specified herein shall be considered a defective item. If the number of defective items equals, or is less than the quantity specified under "Acceptance, number defective" column of table IV, the supplier shall replace the defective samples with items that meet all of the requirements specified herein and the entire lot shall be considered acceptable for shipment. If the number of defective samples equals, or exceeds, the quantity specified in the "Rejection, number defective" column of table IV, the entire lot shall be considered defective and unsuitable for acceptance.

TABLE IV. Sampling plan.

Quantity of items being purchased	Sample size	Acceptance, number defective	Rejection, number defective
2 - 8	2	0	1
9 - 15	3	0	1
16 - 25	5	0	1
26 - 50	8	0	1
51 - 90	13	1	2
91 - 150	20	2	3
151 - 280	32	3	4
281 - 500	50	5	6

Regulatory requirements. The offeror/contractor is encouraged to use recovered materials in accordance with Public Law 94-580 to the maximum extent possible.

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:51Z
Check the source to verify that this is the current version before use.

Preservation, packaging, packing, labeling and marking. Unless otherwise specified in the contract or order, preservation, packaging, packing, labeling and marking shall be in accordance with ASTM-D-3951. When specified in the contract or order, preservation, packaging, packing, labeling and marking shall be in accordance with Federal Specification PPP-T-1150, level as specified.

Notes. Purchaser should specify the quantity, tool number, extension bar number and bushing number, if required, in the contract or order.

When additional extension bars and bushings are desired, with or without holder(s), the number of the bar(s) and bushings should be specified in the contract or order.

ANSI/IEEE 268 "Metric Practice" is available from American National Standards Institute, 1430 Broadway, New York, NY 10018.

ASTM D-3951 "Packaging, Commercial" is available from American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.

FED-STD-376 "Preferred Metric Units for General Use by the Federal Government" and Federal Specification PPP-T-1150 "Tools and Tool Accessories for Power Driven Metal and Woodworking Machinery, Packaging and Packing of" should be obtained from the contracting activity or as directed by the contracting officer.

Tool numbers of this CID correspond with respective tool numbers of Type VIII tool holders of Federal Specification 00-H-581.

MILITARY INTERESTS:

Custodians

Army - AL
Air Force - 99

Review Activities

Air Force - 84
DLA - GS

User Activity

Navy - MC

CIVIL COORDINATING ACTIVITY:

GSA - FSS

Preparing Activity

DLA - IP

Project Number 3460-0117

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:51Z
Check the source to verify that this is the current version before use.