COMMERCIAL ITEM DESCRIPTION

SOCKET, TAPER - SHANK TOOL (MACHINE)

The General Services Administration has authorized the use of this commercial item description in preference to Federal Specification 00-S-550.

This description covers three types of sockets for holding various types of taper-shank cutting tools in machine spindles and turrets.

Salient characteristics.

Types and classes. This description covers sockets of the following types and classes.

Type I - Chucking sockets (turret tool holder)

Type II - Extension sockets

Type III - Reducing sockets (reducing sleeve)

Class 1 - American Standard Taper
Class 2 - Brown and Sharpe Taper
Class 3 - Flatted (Use-Em-Up)

Sizes. Sizes shall be as specified in tables I, II and III for the type and class required.

TABLE I. Type I, chucking sockets.

(Dimensions in inches)

Size	Diameter +0.002 -0.001	Internal taper	Length (min.)	Size	Diameter +0.002 -0.002	Internal taper	Length (min.)
1	0.999	1	2-3/8	10	1.499	3	3-9/16
2	1.249	1	2-3/8	11	1.749	3	3-9/16
3	1.499	1	2-3/8	12	1.999	3	3-9/16
4	0.999	2	2-7/8	13	2.249	3	3-9/16
5	1.249	2	2-7/8	14	2.499	3	3-9/16
6	1.499	2	2-7/8	15	1.499	4	4-1/2
7	1.749	2	2-7/8	16	1.749	4	4-1/2
8	1.999	2	2-7/8	17	1.999	4	4-1/2
9	1.249	3	3-9/16	18	2.249	4	4-1/2

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:51Z
Check the source to verify that this is the current version before use.

TABLE II. Type II, extension sockets.
(Dimensions in inches)

Size	Internal taper	Shank taper	Length (min.)	Size	Internal taper	Shank taper	Length (min.)
1	1	1	5-5/8	18	1	1	7-5/8
2	1	2	6-3/16	19	1	2	8-3/16
3	1	3	6-15/16	20	1	3	8-15/16
4	1	4	7-15/16	21	1	4	9-15/16
5	2	2	6-13/16	22	2	2	9-3/16
6	2	3	7-9/16	23	2	3	9-15/16
7	2	4	8-9/16	24	2	4	10-15/16
8	3	2	7-3/4	25	3	2	10-1/2
9	3	3	8-1/2	26	3	3	11-1/4
10	3	4	9-1/2	27	3	4	12-1/4
11	3	5	10-3/4	28	3	5	13-1/2
12	4	3	9-7/16	29	4	3	12-11/16
13	4	4	10-7/16	30	4	4	13-11/16
14	4	5	11-11/16	31	4	5	14-15/16
15	5	3	10-13/16	32	5	3	14-11/16
16	5	4	11-13/16	33	5	4	15-11/16
17	5	5	13-1/16	34	5	5	16-15/16

TABLE III. Type III, class 1, 2 and 3 reducing sockets.

	Class 1 and 3 American Standard taper			Class 2, Brown and Sharpe taper	
Size	Internal taper size	Shank taper size	Size	Internal taper size	Shank taper size
1	1	2	1	4	7
2	1	3	2	5	7
3	1	4	3	5	9
4	1	5	4	5	10
5	2	3	5	7	9
6	2	4	6	7	10
7	2	5	7	7	11
8	3	4	8	9	10
9	3	5	9	9	11
10	4	5	10	9	12
11	4	6	11	10	11
12	5	6	12	10	12

Length shall be the manufacturer's standard length for industrial tools or tooling.

Source: https://assist.dla.mil -- Downloaded: 202640-26T08:51Z
Check the source to verify that this is the currentversion before use.

Classification.

Type I chucking socket (turret tool holder). The type I chucking socket (turret tool holder) converts a tool with a tapered shank to a straight shank for use in turret tool holders or straight jaw chucks.

Type II extension socket. The type II extension socket extends the length of a taper shank tool.

Type III reducing socket. The type III reducing socket adapts small taper shank tools to larger size spindles.

Class 1, American Standard taper - A type III socket with a standard taper shank and a standard taper hole.

Class 2, Brown and Sharpe taper - A type III socket with a Brown and Sharpe taper shank and Brown and Sharpe taper hole.

Class 3, Flatted (Use-Em-Up) - A type III socket designed to hold cutting tools with broken tangs which have been flatted on the shank. They shall be similar to type III, class 1 and 2, except that the taper hole shall have a flatted side. Use-Em-Up is a term used in industry to identify this type of socket.

Design. All sockets shall be furnished with a drift keyslot. Type II and III sockets shall have drive tangs. Socket shank tapers, internal tapers, drift keyslots, and tangs shall conform to American National Standards Institute Standard B5.10.

Hardness. Unless otherwise specified, the type I chucking socket shall have a minimum hardness of Rockwell C45. Unless otherwise specified, the type II and III sockets shall be unhardened with the exception of the drive tangs which shall have a minimum hardness of Rockwell C30 or shall be undercut or relieved.

Concentricity. The shank shall be concentric with the internal taper. The external taper shall be concentric with the internal taper within a tolerance of 0.002 inch total indicator reading at a 2 inch projection from the mouth of the socket.

Finish. The finish of the sockets shall meet industry standards.

Material. The material used in the manufacture of the sockets shall be steel suitable for the purpose intended.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:51Z
Check the source to verify that this is the current version before use.

Identification marking. Each socket shall be permanently marked with the manufacturer's name or trademark of such known character that the source of manufacture may be identified. They shall also be permanently marked with the number of the taper hole and the number of the taper shank or the diameter of the shank in the case of the type I. When the taper is either a "Brown and Sharpe" or a "Use-Em-Up", the letters "B&S" or "F" shall be included following the number of the taper.

Measurement system. In this commercial item description, all dimensions are given in inch-pound units. These measurements may be converted to SI units through the use of the conversion factors and methods specified in ANSI/IEEE 268 for the Department of Defense and FED-STD-376 for Civil Agency use.

Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any inspections set forth in the commercial item description where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

Acceptance inspection. The supplier shall randomly select the number of samples specified in table IV that is applicable to the quantity of items being purchased. Each sample shall be visually inspected, measured and tested by the supplier, to determine conformance with the salient characteristics specified herein. Any sample failing to meet these characteristics shall be considered a defective item. If the number of defective items equals or is less than the quantity specified under "Acceptance, number defective" in table IV, the supplier shall replace the defective samples with acceptable items and the entire lot shall be considered acceptable for shipment. If the number of defective samples equals or exceeds the quantity specified in the "Rejection, number defective" column of table IV, the entire lot shall be considered defective.

TABLE IV. Sampling plan.

Lot size	Sample size	Acceptance, number defective	Rejection, number defective
2 to 8	2	0	1
9 to 15	3	0	1
16 to 25	5	0	1
26 to 50	8	1	2
51 to 90	13	1	2
91 to 150	20	2	3
151 to 280	32	3	4
281 to 500	50	5	6

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:51Z
Check the source to verify that this is the current version before use.

Regulatory requirements. The offeror/contractor is encouraged to use recovered materials in accordance with Public Law 94-580 to the maximum extent practical.

Preservation, packaging, packing, labeling and marking. Unless otherwise specified in the contract or order, preservation, packaging, packing, labeling, and marking shall be in accordance with ASTM-D-3951. When specified in the contract or order, preservation, packaging, packing, labeling and marking shall be in accordance with Federal Specification PPP-T-1150, level as specified.

Supersession data. The type III, class 4, styles A and B, listed in Military Specification 00-S-550B have been deleted from this commercial item description. All other types and classes remain the same.

Notes. Purchaser will specify quantity, type, class when applicable, and size sockets required for a specific procurement.

Copies of Federal and Military specifications required by manufacturers in connection with specific acquisitions should be obtained from the contracting activity or as directed by the contracting officer.

American National Standards Institute, ANSI/IEEE 268, Metric Practice and ANSI B5.10, Machine Tapers, is available from the American National Standards Institute, 1430 Braodway, New York, NY 10018.

American Society for Testing and Materials (ASTM) Standard D-3951 is available from the American Society for Testing and Materials, 1916 Race St., Philadelphia, PA 19103.

MILITARY INTERESTS:

Custodians

Army - AL
Navy - YD
Air Force - 99

Review Activities

Air Force - 84
DLA - GS

User Activity

Navy - MC, CG

CIVIL AGENCY COORDINATING ACTIVITY:

GSA - GSS

PREPARING ACTIVITY

DLA - IP

Project 3460-0101

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:51Z
Check the source to verify that this is the currentversion before use.