A-A-51136
15 August 198

COMMERCIAL ITEM DESCRIPTION

HOLDER, THREADING TOOL, LATHE

The General Services Administration has authorized the use of this commercial item description in preference to Type IV tool holders specified in Federal Specification 00-H-581.

This description covers threading tool holders that are designed to hold and support thread cutting tools that are used on lathes.

Salient characteristics.

Classification. The following types of tool holders are covered with tool numbers as listed in tables I and II.

Type I - Holder, threading tool, rigid (table I).

Type II - Holder, threading tool, spring or gooseneck form (table II).

Dimensional data. The dimensional data of the tool holders shall be as specified in tables I and II. The tolerances of all dimensional data shall conform to those as specified on manufacturers part drawings.

TABLE I. Rigid threading tool holder.

| Tool holder number | Thickness of shank, inches | Height of shank, inches | Length of holder, inches | Radial length of formed threading tool, inches, min. |
|---|---|---|---|---|
| E-L-0 | 3/8 | 7/8 | 3-1/8 | 13/16 |
| E-L-1 | 1/2 | 1-1/8 | 3-3/8 | 1 |
| E-L-2 | 5/8 | 1-3/8 | 4 | 1-7/32 |
| E-L-3 | 3/4 | 1-5/8 | 5 | 1-1/4 |
| E-L-4 | 7/8 | 1-3/4 | 5-3/4 | 1-1/4 |

FSC 34

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:51Z
Check the source to verify that this is the current version before use.

TABLE II. Spring threading tool holder.

| Tool holder number | Thickness of shank, inches | Height of shank, inches | Length of holder, inches | Radial length of formed threading tool, inches, min. |
|---|---|---|---|---|
| E-S-0 | 3/8 | 7/8 | 5-1/2 | 13/16 |
| E-S-1 | 1/2 | 1-1/8 | 6-1/2 | 1 |
| E-S-2 | 5/8 | 1-3/8 | 7-1/2 | 1-7/32 |
| E-S-3 | 3/4 | 1-5/8 | 8-1/8 | 1-1/4 |

Material and hardness. The holders shall be made of drop-forged alloy steel, heat-treated to a Rockwell "C" 40 to 48 hardness or alloy steel, surface hardened to a Rockwell "C" 50 to 55 hardness.

Clamping device. The clamping device shall firmly support the threading tool on the head.

Type I tool holder. Rigid tool holders shall have a tool holding head rotated clockwise 34 degrees from the shank with a horizontally tapped boss fitted with adjusting screw to control tool edge height.

Type II tool holder. The spring tool holders shall be the same as type I except they shall have a "gooseneck" form head to provide a resilient tool mounting.

Threading tool for type I and II tool holders. A threading tool shall be furnished with the types I and II tool holders. The threading tool shall be single point, radial form of high-speed tool steel hardened to a Rockwell "C" 63 to 67 hardness and shall be ground to an included angle of 60 degrees on the periphery that can be resharpened by grinding the top edge only.

Wrench. A wrench to fit the clamping device shall be furnished with each tool holder.

Measurement system. All dimensions in this description are given in the English system of measurement. These dimensions can be converted to the Metric system equivalents by the use of ANSI/IEEE 268 for Department of Defense use or FED-STD-376 for Civil Agency use.

Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:51Z
Check the source to verify that this is the current version before use.

requirements specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any inspections set forth in this description where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

Acceptance inspection. The supplier shall randomly select the number of samples specified in table III that is applicable to the quantity of items being purchased. Each sample shall be visually inspected, measured, and tested by the supplier, to determine conformance with all requirement specified herein. Any sample failing to meet these salient characteristics shall be considered a defective item. If the number of defective items equals, or is less than the quantity specified under "Acceptance, number defective" column of table III, the supplier shall replace the defective samples with items that conform to all the requirements as specified herein and the entire lot shall be considered acceptable for shipment. If the number of defective samples equals, or exceeds, the quantity specified in the "Rejection, number defective" column of table III, the entire lot shall be considered defective and unsuitable for acceptance.

TABLE III. Sampling plan.

| Quantity of items being purchased | Sample size | Acceptance, number defective | Rejection, number defective |
|---|---|---|---|
| 2-8 | 2 | 0 | 1 |
| 9-15 | 3 | 0 | 1 |
| 16-25 | 5 | 0 | 1 |
| 26-50 | 8 | 1 | 2 |
| 51-90 | 13 | 1 | 2 |
| 91-150 | 20 | 2 | 3 |
| 151-280 | 32 | 3 | 4 |
| 281-500 | 50 | 5 | 6 |

Regulatory requirements. The offeror/contractor is encouraged to use recovered materials in accordance with Public Law 94-580 to the maximum extent practical.

Preservation, packaging, packing, labeling, and marking. Unless otherwise specified in the contract or order, preservation, packaging, packing, labeling, and marking shall be in accordance with ASTM D 3951. When



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:51Z
Check the source to verify that this is the current version before use.

specified in the contract or order, preservation, packaging, packing, labeling, and marking shall be in accordance with Federal Specification PPP-T-1150, level as specified.

Notes. The purchaser should specify the quantity, type and tool number required for a specific procurement.

Tool holder numbers of this description correspond with tool holder numbers of type IV tool holders found in Federal Specification 00-H-581 except that type II tool holders in this description are spring type currently available from industry.

ANSI/IEEE 268 "Metric Practice" is available from American National Standards Institute, ATTN: Sales Dept., 1430 Broadway, New York, NY 10018.

ASTM D 3951 "Packaging, Commercial" is available from American Society for Testing and Materials, 1916 Race St., Philadelphia, PA 19103.

FED-STD-376 "Preferred Metric Units for General Use by the Federal Government" and Federal Specification PPP-T-1150 "Tools and Tool Accessories for Power Driven, Metal and Woodworking Machinery, Packaging and Packing Of" should be obtained from the procuring activity or as directed by the contracting officer.

MILITARY INTERESTS:

Custodians

Army - AL
Navy - SH
Air Force - 99

Review Activities

Air Force - 84
DLA - GS

User Activity

Navy - MC

CIVIL AGENCY COORDINATING ACTIVITY:

GSA - FSS

PREPARING ACTIVITY:

DLA - IP

Project 3460-0113



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:51Z
Check the source to verify that this is the current version before use.