INCH-POUND
A-A-51138A
25 July 2001
SUPERSEDING
A-A-51138
11 January 1985

COMMERCIAL ITEM DESCRIPTION

BRAZING AND SOLDERING SET (ACETYLENE GAS)

The General Services Administration has authorized the use of this commercial item description for all federal agencies.

1. SCOPE. This commercial item description (CID) covers brazing and soldering sets that are designed to burn acetylene gas in ambient air and intended for light brazing and soldering.

2. CLASSIFICATION. The brazing and soldering set shall be of the acetylene gas type as specified herein.

3. SALIENT CHARACTERISTICS

3.1 General requirements. The brazing and soldering set shall include some or all of the following: acetylene gas pressure regulator, torch body, torch tips, soldering iron tip, hose assembly, adaptor, wrench, flint lighter, and carrying case, as specified in 7.3, and other items considered by the manufacturer as standard for the set.

3.2 Components. The brazing and soldering set shall include, as a minimum, the following components:

3.2.1 Pressure regulator. The pressure regulator shall conform to the Underwriters Laboratory UL 252, "Standard for Safety for Compressed Gas Regulators" (DoD adopted). The inlet connector shall conform to Compressed Gas Association (CGA) V-1, "Standard for Compressed Gas Cylinder Valve Outlet and Inlet Connections" (DoD adopted), and fit a type B acetylene gas tank. The outlet connector shall be a type A conforming to CGA E-1, "Standard Connections for Regulator Outlets, Torches, and Fitted Hose for Welding and Cutting Equipment" (DoD adopted). The pressure regulator shall include a gauge indicating the content of the acetylene gas tank in at least four increments of 1/4, 1/2, 3/4, and FULL. The gauge shall have a minimum pressure rating of 400 pounds per square inch. The pressure regulator shall have a means to manually adjust the outlet pressure up to a maximum of 15 pounds per square inch.

Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any data that may improve this document should be sent to: Defense Supply Center Richmond (DSCR), ATTN: DSCR-VBD, 8000 Jefferson Davis Highway, Richmond, VA 23297-5610.

AMSC N/A FSC 3433

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:51Z
Check the source to verify that this is the current version before use.

3.2.2 Torch body. The design and materials of the torch body shall be those considered by the manufacturer as standard. The torch body shall be designed to accept interchangeable tips and have a type A inlet hose fitting. The torch body shall have a rear control shut-off valve, a front control shut-off valve, or a thumb control lever valve as specified (see 7.3(b)).

3.2.3 Torch tips. The torch tips shall be made of brass or bronze with end fittings compatible with the torch body. Unless otherwise specified (see 7.3(c)), one torch tip of each of the sizes shown in table I shall be provided.

TABLE I. Torch tips.

Tip size	Flame port diameter, inch (millimeters)	
	Minimum	Maximum
Fine	0.075 (2.0)	0.112 (3.0)
Small	0.125 (3.5)	0.170 (4.5)
Medium	0.185 (4.5)	0.215 (5.5)
Large	0.240 (6.0)	0.260 (6.5)
Soldering iron	0.080 (2.0)	0.250 (6.5)

3.2.4 Soldering iron tip. The soldering iron tip shall be pointed (pyramidal) and made from copper. Unless otherwise specified (see 7.3(d)), a soldering iron tip of the size shown in table I shall be provided.

3.2.5 Hose assembly. Unless otherwise specified (see 7.3(e)), the hose assembly shall consist of 12 1/2 feet of 3/16-inch-diameter acetylene gas grade hose with type A connectors to fit the torch body inlet and the pressure regulator outlet.

3.2.6 Adaptor. When specified (see 7.3(f)), an adaptor shall be provided to allow installation of the pressure regulator with a type B connector on a type MC tank.

3.2.7 Wrench. When specified (see 7.3(g)), a combination wrench shall be provided that fits the type B and MC tank valves, the pressure regulator, the adaptor, and the type A hose nuts.

3.2.8 Flint lighter. When specified (see 7.3(h)), a flint lighter with a replaceable flint and spare flints shall be provided.

3.2.9 Carrying case. When specified (see 7.3(i)), a metal or plastic carrying case shall be provided that has sufficient size to hold all of the components of the brazing and soldering set.

3.2.10 Optional accessories. Optional accessories shall be furnished as specified (see 7.3(j)).

4. REGULATORY REQUIREMENTS

4.1 Recovered materials. The offeror/contractor is encouraged to use recovered materials to the maximum extent practicable, in accordance with paragraph 23.403 of the Federal Acquisition Regulation (FAR).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:51Z
Check the source to verify that this is the current version before use.

5. PRODUCT CONFORMANCE PROVISIONS

5.1 Product conformance. The products shall meet the salient characteristics of this commercial item description; conform to the manufacturer's own drawings, specifications, standards, and quality assurance practices; and be the same product offered for sale in the commercial marketplace. The Government reserves the right to require proof of such conformance.

5.2 Warranty. Unless otherwise specified (see 7.3(k)), the manufacturer's standard commercial warranty, terms, and conditions shall apply.

6. PACKAGING. Unless otherwise specified (see 7.3(l)), preservation, packing, and marking shall be as specified in the contract or order.

7. NOTES

7.1 Part or identification number (PIN). The PIN procedure for this CID is AA51138-1. This is for Government purposes and does not constitute a requirement for the contractor.

7.2 Sources of documents.

7.2.1 FAR. The FAR may be obtained from the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402-0001.

7.2.2 CGA standards. Copies of CGA standards may be obtained from the Compressed Gas Association, 1725 Jefferson Davis Highway, Suite 1004, Arlington, VA 22202-4102.

7.2.3 UL standards. Copies of UL standards may be obtained from Underwriters Laboratories Inc., 333 Pfingsten Road, Northbrook, IL 60062.

7.3 Ordering data. Acquisition documents must specify the following:

a. CID document number, revision, and CID PIN.
b. Torch body shut-off valve, as specified (see 3.2.2).
c. Torch tips, if different (see 3.2.3).
d. Soldering iron tip, if different (see 3.2.4).
e. Hose assembly, if different (see 3.2.5).
f. Adaptor, if required (see 3.2.6).
g. Wrench, if required (see 3.2.7).
h. Flint lighter, if required (see 3.2.8).
i. Carrying case, if required (see 3.2.9).
j. Optional accessories, as specified (see 3.2.10).
k. Warranty, if different (see 5.2).
l. Packaging requirements, if different (see 6).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:51Z
Check the source to verify that this is the current version before use.

MILITARY INTERESTS:

Custodians:
Army - AR
Navy - SH
Air Force - 99

Reviewer:
Air Force - 84

CIVIL AGENCY
COORDINATING ACTIVITY:

GSA - 6FEE

Preparing activity:
DLA - GS6

(Project 3433-0153)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:51Z
Check the source to verify that this is the current version before use.