A-A-51139A
11 March 1986
SUPERSEDING
A-A-51139
31 October 1984

COMMERCIAL ITEM DESCRIPTION

HOLDER, TURNING TOOL, LATHE

The General Services Administration has authorized the use of this commercial item description in preference to the type I and type II tool holders covered by Federal specification OO-H-581a.

1. SCOPE

1.1 Scope. This description covers lathe turning tool holders of the standard commercial, heavy duty type which are used in a production environment.

1.2 Classification. Tool holders shall be of the following types, classes, styles, and the tool holder numbers listed in tables I, II, and III. The type, class, style, and tool holder number to be furnished shall be as specified (see 6.1).

Type I - Holder, turning tool, lathe, broached hole, or bit channel parallel to the base.

Class 1 - Straight shank (see table I).
Class 2 - Left-hand offset shank 34 degrees.
Style A - Rigid (single size) tool (see table I).
Style B - Multi-size tool (see table II).
Class 3 - Right-hand offset shank 34 degrees.
Style A - Rigid (single size) tool (see table I).
Style B - Multi-size tool (see table II).

Type II - Holder, turning tool, lathe, broached hole, or bit channel tilted 14 degrees from the base.

Class 1 - Straight shank (see table III).
Class 2 - Left-hand offset shank 34 degrees.
Style A - Rigid (single size) tool (see table III).
Style B - Multi-size tool (see table II).

AMSC N/A FSC 3460
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:51Z
Check the source to verify that this is the current version before use.

Class 3 - Right-hand offset shank 34 degrees.
Style A - Rigid (single size) tool (see table III).
Style B - Multi-size tool (see table II).

2. APPLICABLE DOCUMENTS

2.1 Documents. The following documents of the issue in effect on the date of invitation for bids or request for proposal, form a part of this description to the extent specified herein. The documents should be obtained from the contracting activity or as directed by the contracting officer.

Federal Specification PPP-T-1150	- Tools and Tool Accessories for Power Driven Metal and Woodworking Machinery, Packaging and Packing of.
Federal Standard FED-STD-376	- Preferred Metric Units for General Use by the Federal Government.
ASTM D 3951	- Standard Practice for Commercial Packaging.

3. SALIENT CHARACTERISTICS

3.1 Design. Holders shall be new and of the manufacturer's standard design in effect on the date of the solicitation. The holders shall meet the requirements specified herein and shall conform to current commercial industrial practice.

3.2 Materials and hardness. The holders shall be made of drop-forged alloy steel, heat treated to a Rockwell C 40 to 48, Brinell 2.85 to 3.15 hardness or alloy steel, surface hardened to a Rockwell C 50 to 55, Brinell 2.6 to 2.8 hardness.

3.3 Clamping device. The clamping device to secure the cutter bits in the holder shall have a heat treated screw that resists forces normally encountered.

3.4 Wrench. A wrench to fit the clamping screw shall be furnished with each holder.

3.5 Measurement system. All dimensions in this description are given in US units. These measurements may be converted to SI units through the use of the conversion factors and methods specified in FED-STD-376.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:51Z
Check the source to verify that this is the current version before use.

3.6 Regulatory requirements. The offeror/contractor is encouraged to use recovered materials to the maximum extent practical.

3.7 Workmanship. The workmanship of the tool holders shall be of a quality equal to that of comparable products furnished to the commercial market.

TABLE I. Type I, class 1, and class 2, style A and class 3, style A tool holders.

Tool holder number Type I			Square tool bit channel, inches	Thickness of shank, inches	Height of shank, inches	Overall length of holder, inches 1/
Class 1	Class 2 style A	Class 3 style A				
A-S-10	A-L-20	A-R-30	1/4	3/8	15/16	6
A-S-11	A-L-21	A-R-31	5/16	1/2	1 1/4	7
A-S-12	A-L-22	A-R-32	3/8	5/8	1 1/2	8
A-S-13	A-L-23	A-R-33	7/16	3/4	1 3/4	9
A-S-14	A-L-24	A-R-34	1/2	7/8	1 7/8	10
A-S-15	A-L-25	A-R-35	5/8	1	2 1/8	11

1/ Overall length not less than value of table; all other dimensional tolerances shall be in accordance with manufacturer's part drawings.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:51Z
Check the source to verify that this is the current version before use.

TABLE II. Types I and II, class 2, style B and class 3, style B tool holders.

Tool holder number				Size range of square, rectangular and dia. of cylindrical tool bits or boring bars, inches	Thickness of shank, inches	Height of shank, inches	Overall length of holder, inches
Type I		Type II					
Class 2 style B	Class 3 style B	Class 2 style B	Class 3 style B				
A-L-40	A-R-50	B-L-40	B-R-50	1/8, 3/16, 1/4, 5/16	3/8	7/8	5 1/2
A-L-41	A-R-51	B-L-41	B-R-51	3/16, 1/4, 5/16, 3/8	1/2	1 1/8	6 1/2
A-L-42	A-R-52	B-L-42	B-R-52	1/4, 5/16, 3/8, 7/16, 1/2	5/8	1 1/2	8
A-L-44	A-R-54	B-L-44	B-R-54	5/16, 3/8, 7/16, 1/2, 5/8	7/8	1 7/8	9 1/2
A-L-46	A-R-56	B-L-46	B-R-56	1/2, 9/16, 5/8, 11/16, 3/4, 7/8, 1	1 1/4	2 1/4	13

NOTE: The tolerance for all dimensional data shall be the manufacturer's standard as specified on their parts drawings.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:51Z
Check the source to verify that this is the current version before use.

TABLE III. Type II, class 1 and class 2, style A and class 3, style A tool holders.

Tool holder number			Square tool bit channel, inches	Thickness of shank, inches	Height of shank, inches	Overall length of tool holder, inches 1/
Type II						
Class 1	Class 2 style A	Class 3 style A				
B-S-4	B-L-5	B-R-6	3/16	5/16	1/2	4
B-S-10	B-L-20	B-R-30	1/4	3/8	7/8	5
B-S-11	B-L-21	B-R-31	5/16	1/2	1 1/8	6
B-S-12	B-L-22	B-R-32	3/8	5/8	1 3/8	7
B-S-13	B-L-23	B-R-33	7/16	3/4	1 5/8	8
B-S-14	B-L-24	B-R-34	1/2	7/8	1 3/4	9
B-S-15	B-L-25	B-R-35	5/8	1	2	11

1/ Overall length not less than value of table; all other dimensional tolerances shall be in accordance with manufacturer's part drawings.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:51Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection, examination, and test requirements specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this description where such tests are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Sampling inspection. The supplier shall randomly select the number of samples in table IV that is applicable to the quantity of items being purchased. Each sample item shall be inspected to determine conformance with the examination in 4.3, the dimensional inspection in 4.4, and hardness test in 4.5. Any sample failing to meet all requirements specified herein shall be considered a defective item. If the number of defective items is equal to or less than the quantity specified under the "Acceptance, number defective" column of table IV, the supplier shall replace the defective samples with items that meet all the requirements specified herein and the entire lot shall be considered acceptable for shipment. If the number of defective samples is equal to or greater than the quantity specified in the "Rejection, number defective" column of table IV the entire lot shall be considered defective and unsuitable for acceptance. A lot is defined as all tool holders of the same type, class, style, and tool holder number presented at one time for acceptance.

4.3 Examination. Each tool holder submitted for sample inspection shall be visually examined to determine conformance with all requirements of this description, except the hardness requirement.

4.4 Dimensional inspection. Each of the sample tool holders shall be inspected to assure conformance with the dimensions specified in tables I, II, or III as applicable to the holder specified.

4.5 Hardness test. After the sample inspection has been completed, a hardness test shall be performed on the nearest whole number to 10 percent of the samples. If any of the test samples fail to meet the applicable hardness specified herein, the total lot from which the samples were selected shall be rejected.

4.6 Packaging inspection. Packaging shall be inspected for conformance with section 5.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:51Z
Check the source to verify that this is the current version before use.

TABLE IV. Sampling plan.

Quantity of items being purchased	Sample size	Acceptance, number defective	Rejection, number defective
2 - 8	2	0	1
9 - 15	3	0	1
16 - 25	5	0	1
26 - 50	8	1	2
51 - 90	13	1	2
91 - 150	20	2	3
151 - 280	32	3	4
281 - 500	50	5	6

5. PACKAGING

5.1 Preservation, packing, and marking. Unless otherwise specified in the contract or order, preservation, packing, and marking shall be in accordance with ASTM D 3951. When specified (see 6.1), preservation, packing, and marking shall be in accordance with Federal Specification PPP-T-1150, level as specified.

6. NOTES

6.1 Acquisition. Acquisition documents should specify the following:

a. Title, number, and date of this commercial item description.

b. Type, class, style, tool holder number, and quantity required (see 1.2).

c. Packaging in accordance with PPP-T-1150 if required, specify level required (see 5.1).

6.2 Cross-reference data. The types, classes, styles, and tool holder numbers in this description correspond to the types, classes, styles, and tool holder numbers of types I and II tool holders as found in Federal specification OO-H-581a and commercial item description A-A-51139.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:51Z
Check the source to verify that this is the current version before use.

MILITARY INTERESTS:

Custodians

Army - AL
Air Force - 99

Review Activities

Air Force - 84
DLA - GS

User Activities

Navy - MC, SH

CIVIL AGENCY COORDINATING ACTIVITY:

GSA - FSS

PREPARING ACTIVITY:

DLA - IP

Project 3460-0120

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:51Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:51Z
Check the source to verify that this is the current version before use.