
MILITARY SPECIFICATION SHEET

COILS, RADIO FREQUENCY, CHIP, FIXED

This specification is approved for use by all Departments and Agencies of the Department of Defense.


The requirements for acquiring the coils described herein shall consist of this specification and the latest issue of MIL-C-83446.



	Inches	mm
A	.110 Max	2.79 Max
B	.105 Max	2.67 Max
C	.100 Max	2.54 Max
D	.030 ±.005	0.76 ±0.13
E	.040 ±.010	1.02 ±0.25
F	.018 ±.005	0.46 ±0.13
G	.038 ±.010	0.97 ±0.25
H	.005 ±.002	0.13 ±0.05

For dash numbers 01 thru 24

(With tabs)



	Inches	mm
A	.110 Max	2.79 Max
B	.105 Max	2.67 Max
C	.100 Max	2.54 Max
D	.030 ±.005	0.76 ±0.13
F	.018 ±.005	0 46 ±0.13
G	.038 ±.010	0.97 ±0.25
H	.005 ±.002	0.13 ±0.05

For dash numbers 25 thru 48

(Without tabs)

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.

FIGURE 1. Fixed, chip coil

Ⓒ denotes changes

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.
Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:09Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Dimensions and configuration: See figure 1.

Weight: 0.5 gram maximum.

Operating temperature range: -55°C to +125°C.

Temperature rise (at 90°C): 35°C.

Maximum operating temperature: 125°C.

Altitude: 70,000 feet.

© Dielectric withstanding voltage: Method 301 of MIL-STD-202, test voltage 300 volts rms.

Barometric pressure: Method 105, test condition C, MIL-STD-202 (70,000 feet), test voltage 200 volts rms.

Electrical characteristics (initial): See table I.

Electrical characteristics (final): See table II.

TABLE I. Electrical characteristics (initial) and dash numbers.


Dash number	Inductance ±10%	Q (min)	Q (typ)	Test frequency 1/	Self-resonant frequency (min)	DC resistance (max)	2/ Current (max)
	µH			MHz	MHz	Ohms	mA
01, 25	12.0	42	50	2.5	26	2.0	110
02, 26	15.0	44	52	"	24	2.2	105
03, 27	18.0	44	52	"	21	2.8	100
04, 28	22.0	48	55	"	20	3.5	85
05, 29	27.0	49	57	"	19	4.3	75
06, 30	33.0	50	58	"	14	5.5	68
07, 31	39.0	52	60	"	12	6.5	61
08, 32	47.0	53	62	"	11	8.5	54
09, 33	56.0	56	64	"	10	12.0	46
10, 34	68.0	53	62	"	9	13.0	42
11, 35	82.0	49	57	"	8	15.0	40
12, 36	100.0	49	57	"	7	18.0	36
13, 37	120.0	37	45	0.790	6	21.0	34
14, 38	150.0	30	38	"	5	26.0	31
15, 39	180.0	30	38	"	5	28.0	29
16, 40	220.0	26	32	"	4.5	32.0	28
17, 41	270.0	26	32	"	4.0	36.0	26
18, 42	330.0	24	30	"	3.7	42.0	24
19, 43	390.0	24	30	"	3.5	46.0	23
20, 44	470.0	24	30	"	3.0	68.0	19
21, 45	560.0	22	28	"	2.8	77.0	18
22, 46	680.0	20	26	"	2.5	85.0	17
23, 47	820.0	16	22	"	2.0	100.0	16
24, 48	1000.0	12	18	"	1.5	120.0	15

1/ Test frequency range: 0.25 through 25 MHz:

For electrical characteristics measurements use TF-260Q-1 test fixture, or equal (see figure 2). Fixture inductance (approximately 0.028 µH) and residual Q-meter inductance (approximately 0.01 µH) should be subtracted from indicated inductance.

2/ Maximum current allowed not to exceed the specified temperature rise.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:09Z
Check the source to verify that this is the current version before use.



NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Metric equivalents are in parentheses.

FIGURE 2. Typical chip coil test fixture.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:09Z
Check the source to verify that this is the current version before use.

TABLE II. Electrical characteristics (final).

Inspection group	Allowable variation from the initial measurements			
	Inductance	DC resistance	Self-resonant frequency	Q
Qualification inspection	Percent		Percent	Percent
Group II	±5	±(3% +0.001 ohm)	-8	-10
Group IV	±5	±(2% +0.001 ohm)	-10	-10
Group V	±2	---	---	-10
Quality conformance inspection				
Group C				
Subgroup II	±5	±(3% +0.001 ohm)	-8	-10
Subgroup IV	±5	±(3% +0.001 ohm)	-8	-10

Supersession data: A new part numbering system with codes for termination materials was incorporated with revision A, superseding MIL-I-83446/6, dated 1 March 1979.

M83446/06- (dash number from table I) C
supersedes M83446/6- (dash number from table I).

Examples:

M83446/06-21C supersedes M83446/6-21.
M83446/06-03C supersedes M83446/6-3.

Part number: The part number shall be in the following form.

M83446/06- 04 B

04: Sequentially assigned dash numbers (see table I)

B: Termination finish (see MIL-C-83446)

Custodians:
Army - ER
Navy - EC
Air Force - 85

Review activities:
Army - MI
Navy - AS
Air Force - 19
DLA - ES

User activities:
Navy - OS
Air Force - 11

Preparing activity:
Army - ER

Agent:
DLA - ES

(Project 5950-0699-2)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:09Z
Check the source to verify that this is the current version before use.