INCH - POUND

MIL-PRF-83446/6F
5 December 2013
SUPERSEDING
MIL-PRF-83446/6E
25 August 2006

PERFORMANCE SPECIFICATION SHEET

COILS, RADIO FREQUENCY, CHIP, FIXED

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the products described herein shall consist of this specification and MIL-PRF-83446.




FIGURE 1. Fixed, chip coil.

AMSC N/A

FSC 5950

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:09Z
Check the source to verify that this is the current version before use.

LTR	Dimensions for dash number -01 thru -24 (With tabs)		Dimensions for dash number -25 thru -48 (Without tabs)		Dimensions for dash number -49 thru -87 (With tabs)		Dimensions for dash number -88 thru -126 (Without tabs)	
	Inches	mm	Inches	mm	Inches	mm	Inches	mm
A	.110 max	2.79 max	.110 max	2.79 max	.074 ±.006	1.88 ±0.15	.074 ±.006	1.88 ±0.15
B	.105 max	2.67 max	.105 max	2.67 max	.084 ±.006	2.13 ±0.15	.084 ±.006	2.13 ±0.15
C	.100 max	2.54 max	.100 max	2.54 max	.050 max	1.27 max	.050 max	1.27 max
D	.030 ±.005	0.76 ±0.13	.030 ±.005	0.76 ±0.13	.021 ±.003	0.53 ±0.07	.021 ±.003	0.53 ±0.07
E	.040 ±.010	1.02 ±0.25	----	----	.040 ±.006	1.02 ±0.15	----	----
F	.018 ±.005	0.46 ±0.13	.018 ±.005	0.46 ±0.13	.020 ±.006	0.51 ±0.15	.020 ±.006	0.51 ±0.15
G	.038 ±.010	0.97 ±0.25	.038 ±.010	0.97 ±0.25	.022 ±.004	0.56 ±0.10	.022 ±.004	0.56 ±0.10
H	.005 ±.002	0.13 ±0.05	.005 ±.002	0.13 ±0.05	.004 ±.002	0.10 ±0.05	.004 ±.002	0.10 ±0.05

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.

FIGURE 1. Fixed, chip coil – Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:09Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Dimensions and configuration: See figure 1.

Weight: 0.02 ounce maximum.

Operating temperature range: -55°C to +125°C.

Temperature rise (at 90°C): 35°C.

Maximum operating temperature: 125°C.

Altitude: 70,000 feet.

Dielectric withstanding voltage: Method 301 of MIL-STD-202, test voltage 300 volts rms.

Barometric pressure: Method 105, test condition C, MIL-STD-202, (70,000 feet), test voltage 200 volts rms.

Electrical characteristics (initial): See table I.

Electrical characteristics (final): See table II.

Supersession data: A new part numbering system with codes for termination materials was incorporated with Revision A, superseding MIL-I-83446/6, dated 1 March 1979.

M83446/06-(dash number from table I) supersedes M83446/6-(dash number from table I).

Examples:

M83446/06-21A supersedes M83446/6-21.
M83446/06-03A supersedes M83446/6-3.

Part of Identifying Number (PIN): The part number shall be in the following form.

M83446/06-	04	B
	Sequentially assigned dash Numbers (see table I and II)	Termination finish (see MIL-PRF-83446)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:09Z
Check the source to verify that this is the current version before use.

TABLE I. Electrical characteristics (initial) for dash numbers 01 through 48.

Dash number	Inductance ±10% (μH)	Q (min)	Q (typ)	Test frequency (MHz) 1/	Self resonant frequency (min) MHz	DC resistance (max) ohms	Current (max) mA 2/
01, 25	12.0	42	50	2.5	26	2.0	110
02, 26	15.0	44	52	2.5	24	2.2	105
03, 27	18.0	44	52	2.5	21	2.8	100
04, 28	22.0	48	55	2.5	20	3.5	85
05, 29	27.0	49	57	2.5	19	4.3	75
06, 30	33.0	50	58	2.5	14	5.5	68
07, 31	39.0	52	60	2.5	12	6.5	61
08, 32	47.0	53	62	2.5	11	8.5	54
09, 33	56.0	56	64	2.5	10	12.0	46
10, 34	68.0	53	62	2.5	9	13.0	42
11, 35	82.0	49	57	2.5	8	15.0	40
12, 36	100.0	49	57	2.5	7	18.0	36
13, 37	120.0	37	45	.790	6	21.0	34
14, 38	150.0	30	38	.790	5	26.0	31
15, 39	180.0	30	38	.790	5	28.0	29
16, 40	220.0	26	32	.790	4.5	32.0	28
17, 41	270.0	26	32	.790	4.0	36.0	26
18, 42	330.0	24	30	.790	3.7	42.0	24
19, 43	390.0	24	30	.790	3.5	46.0	23
20, 44	470.0	24	3	.790	3.0	68.0	19
21, 45	560.0	22	28	.790	2.8	77.0	18
22, 46	680.0	20	26	.790	2.5	85.0	17
23, 47	820.0	16	22	.790	2.0	100.0	16
24, 48	1000.0	12	18	.790	1.5	120.0	15

1/ Test frequency range 0.25 through 25 MHz: For electrical characteristics measurements, use the test fixture as shown in figure 2 or equivalent. Fixture inductance (approximately 0.028 μH) and residual Q-meter inductance (approximately 0.01 μH) should be subtracted from indicated inductance.

2/ Maximum current allowed is not to exceed the specified temperature rise.


Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:09Z
Check the source to verify that this is the current version before use.

TABLE I. Electrical characteristics (initial) for dash numbers 49 through 126.

Dash number	Inductance ±10% (µH) 1/	Q (min)	Q (typ)	Test frequency (MHz) 2/	Self resonant frequency (min) MHz	DC resistance (max) ohms	Current (max) mA 3/
49, 88	0.005	32	40	200	1900	0.10	750
50, 89	0.008	32	40	200	1800	0.10	750
51, 90	0.010	32	40	150	1700	0.10	750
52, 91	0.012	32	40	150	1500	0.10	750
53, 92	0.015	29	37	150	1300	0.10	750
54, 93	0.018	29	37	150	1100	0.10	750
55, 94	0.022	35	43	100	900	0.10	750
56, 95	0.027	34	42	100	900	0.10	750
57, 96	0.033	32	41	100	800	0.10	600
58, 97	0.039	32	41	100	750	0.10	550
59, 98	0.047	32	41	100	750	0.10	500
60, 99	0.056	32	41	100	700	0.10	450
61, 100	0.068	32	41	100	700	0.12	400
62, 101	0.082	32	40	100	700	0.13	350
63, 102	0.10	32	40	50	600	0.14	350
64, 103	0.12	32	40	50	500	0.17	350
65, 104	0.15	32	40	50	500	0.18	350
66, 105	0.18	32	40	50	450	0.25	300
67, 106	0.22	32	40	50	400	0.30	300
68, 107	0.27	30	39	50	330	0.40	300
69, 108	0.33	30	39	50	270	0.50	300
70, 109	0.39	24	31	50	250	0.90	250
71, 110	0.47	24	31	25	200	0.90	250
72, 111	0.56	24	31	25	180	1.10	250
73, 112	0.68	24	31	25	150	1.20	250
74, 113	0.82	24	31	25	130	1.40	250
75, 114	1.0	24	31	25	110	1.40	250
76, 115	1.2	21	28	7.9	110	1.50	200
77, 116	1.5	21	28	7.9	110	1.50	200
78, 117	1.8	21	28	7.9	100	1.60	200
79, 118	2.2	21	28	7.9	90	1.60	150
80, 119	2.7	21	28	7.9	80	1.60	150
81, 120	3.3	21	28	7.9	75	1.60	150
82, 121	3.9	21	28	7.9	70	2.90	100
83, 122	4.7	21	28	7.9	63	2.90	100
84, 123	5.6	21	28	7.9	60	3.00	100
85, 124	6.8	21	28	7.9	50	3.75	100
86, 125	8.2	21	28	7.9	40	4.50	100
87, 126	10.0	21	28	7.9	30	5.60	100

1/ Tolerance for dash numbers 49, 88, 50 and 89 shall be ±20 percent.
2/ Test frequency range: 7.9 through 200 MHz: For electrical characteristics measurements of -49 through -126 use the test fixture as shown on figure 3 or equivalent.
3/ Maximum current allowed is not to exceed the specified temperature rise.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:09Z
Check the source to verify that this is the current version before use.



NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Metric equivalents are in parentheses.

FIGURE 2. Typical chip coil test fixture.
(for dash numbers 01 through 48)




FIGURE 3. Typical chip coil test fixture.
(for dash numbers 49 through 126

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:09Z
Check the source to verify that this is the current version before use.

TABLE II. Electrical characteristics (final).

Inspection group	Allowable variation from initial measurements			
	Inductance (Percent)	DC resistance	Self-resonant frequency (Percent)	Q (Percent)
Qualification inspection				
Group II	±5	±(3% +.001 ohm)	-8	-10
Group IV	±5	±(2% +.001 ohm)	-10	-10
Group V	±2	---	---	-10
Conformance inspection group C				
Subgroup II	±5	±(3% +.001 ohm)	-8	-10
Subgroup IV	±5	±(3% +.001 ohm)	-8	-10

Extent of qualification:

For manufacturers qualified to dash numbers M83446/06-01 through M83446/06-48, qualification to M83446/06-49 through M83446/06-126 can be granted by testing 24 samples of dash number M83446/06-87 to qualification inspection of MIL-PRF-83446.

Changes from previous issue. The margins of this specification are marked with vertical lines to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Referenced documents.

MIL-PRF-83446
MIL-STD-202

Custodians:
Army – CR
Navy - EC
Air Force - 85
DLA - CC

Review activities:
Army – MI
Navy – AS, OS
Air Force – 19

Preparing activity:
DLA – CC

Project 5950-2013-045

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:09Z
Check the source to verify that this is the current version before use.