TT-S-00230C(COM-NBS)
AMENDMENT-2
October 9, 1970
SUPERSEDING
AMENDMENT-1(COM-NBS)
May 20, 1970

AMENDMENT

TO

INTERIM FEDERAL SPECIFICATION

SEALING COMPOUND: ELASTOMERIC TYPE, SINGLE COMPONENT (FOR CALKING, SEALING, AND GLAZING IN BUILDING AND OTHER STRUCTURES)

This amendment was developed by the National Bureau of Standards, Washington, D. C. 20234, based upon currently available technical information. The General Services Administration has authorized the use of this amendment as a part of Interim Federal Specification TT-S-00230C(COM-NBS), dated February 2, 1970.

PAGE 1

Paragraph 1.2 Class A: Add "maximum after "50 percent". For Class B: Add "maximum after "25 percent" and add "joint" after "total".

Footnote 1/, line 1: Add "maximum" after "50 percent". Lines 7, 8, and 9 delete the sentence and substitute the following:

"The combinations might be 5 percent in extension and 45 percent in compression; 25 percent in extension and 25 percent in compression; 35 percent in extension and 15 percent in compression; or any other such combination of extension and compression totaling a maximum of 50 percent."

Paragraph 1.2, Type II, Class A: Delete "joing" and substitute "joint".

PAGE 2

Paragraph 2.2: Delete all reference to "National Classification Board:" and "Uniform Classification Committee"".

PAGE 3

Paragraph 3.4" Delete the second sentence and substitute the following:

"The manufacturer shall furnish a certificate of nontoxicity when used in accordance with manufacturer's instruction (see 6.3)".

Paragraph 3.5.4, line 4: Delete "35" and substitute "25".

PAGE 4

Paragraph 3.5.8: Add the following sentence:

"See 4.3.9.4.2.1 regarding the presence of air bubbles in the sealant".

Paragraph 4.2, line 1: Change "should" to "shall".

PAGE 5

Paragraph 4.3.4.2, line 3: Delete "75" and substitute "95".

FSC 8030

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:15Z
Check the source to verify that this is the current version before use.