MIL-T-19367A(SHIPS)
AMENDMENT-2
2 March 1962
SUPERSEDING
AMENDMENT-1
29 August 19661

MILITARY SPECIFICATION

TANKS, MASTER, X-RAY AND PHOTODOSIMETRIC FILM PROCESSING, MECHANICALLY COOLED, SELF-CONTAINED NAVAL SHIPBOARD

This amendment forms a part of Military Specification MIL-T-19367A(SHIPS), 22 April 1959.

Page 2, paragraph 2.1: Delete reference to Military Specification MIL-S-15291.

Page 5, paragraph 3.6.1: Delete the last two sentences.

Page 5, paragraph 3.6.2: Add as the last sentence: "An incoming power terminal block suitable for 3-wire power cable shall be provided."

Page 7, paragraph 3.12, line 2: Delete "types I and II" and substitute "class A or C and class B".

Page 7, paragraph 3.12.1: Delete and substitute:

"3.12.1 Assembly and component drawings shall be furnished as class A or C, or both. The drawings shall include outline and mounting dimensions, performance data or performance curves. Drawings shall be provided in sufficient detail to show design, construction, dimensions, and operation or function and identity of the parts, and shall not contain reference to the contract or ships concerned."

Page 7, paragraph 3.12.2; line 1: Delete "Type II" and substitute "Class B".

Page 7, paragraph 3.12.2.1, line 3: Delete "type I" and substitute "class A or C".

Page 7, paragraph 3.13: Delete the first sentence and substitute: "Technical manuals furnished shall be in accordance with Specification MIL-M-15071."

FSC 6635

Source: https://assist.dla.mil -- Downloaded: 202610-18T12:45Z
Check the source to verify that this is the currentversion before use.

Page 7, paragraph 3.14: Delete and substitute:

"3.14 Type I, X-ray film developing tank. - The X-ray film developing tank shall consist of a condensing unit with water cooled condenser, water cooling unit, controls, accessories, and three insert tanks all supported and enclosed in a metal cabinet. The inside dimensions of the insert tanks shall be 14-3/4 inches long by 20 inches high. Width shall be determined by the required capacity of the insert tanks."

Page 8, paragraph 4.1: Delete and substitute:

"4.1 Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. The government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements."

Page 9, paragraph 4.2.2: Delete and substitute:

"4.2.2 From each production lot sample units shall be selected in accordance with table II and each sample unit inspected for adjustment, fits, leaks, material, finish, and general conformance with the requirements of this specification. Each sample unit shall be subjected to the inspection specified in 4.4. If any unit is found nonconforming in any requirement, it shall be counted a defective unit and the lot shall be rejected."

Page 10, paragraph 4.4, lines 2 and 3: Delete the second sentence and substitute: "Units shall be tested to determine compliance with the following:"; also delete item (f) of paragraph 4.4.

Page 10, paragraph 4.5, last two lines: Delete "in the presence of a government inspector".

Page 10, paragraph 4.5.1: Delete and substitute:

"4.5.1 Structural strength test. - The unit shall be tested as required by Specification MIL-S-901. Failure to operate satisfactorily or evidence of breakage or disassembly at the conclusion of this test shall be cause for rejection."

Page 11, paragraph 5.1.1.1: Delete "of the Government inspector" and substitute "of the bureau or agency concerned".

Preparing activity:
Navy - Ships
(Project 6635-N007SH)

Source: https://assist.dla.mil -- Downloaded: 202610-18T12:45Z
Check the source to verify that this is the current version before use.