MIL-C-0050007C(MU)
AMENDMENT 1
12 June 1987

MILITARY SPECIFICATION

CHUTE, CONTAMINATED CLOTHING, M1

This amendment forms a part of MIL-C-0050007C(MU), dated 3 July 1973, and is approved for use within the Chemical Research, Development and Engineering Center, Department of the Army and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 2

2.1, line 27: Under Government Documents delete "D150-2-1" and its title.

PAGE 3

3.3(b): Delete paragraph in its entirety and substitute the following:

"(b) A force of 2.4 $\pm$ 0.2 pounds, when applied to the front of the door on its vertical center line and 1/2 inch above the top of the bottom door frame, shall be required to open the door a distance of 1/4 inch that is measured perpendicularly from the door to the inner edge of the gasket at the bottom door frame. This test shall be made in accordance with 4.2.4(b)."

PAGE 5

4.2.4(b): Delete paragraph in its entirety and substitute the following:

"(b) With the chute oriented as in (a), apply a force with a Chatillion Tension Testing Scale, Model No. 719-5 MRP or equivalent to the door at a point located on the vertical center line on the door and 1/2 inch above the top edge of the bottom door frame. Observe and record the force necessary to open the door 1/4 inch as specified in 3.3(b). The recorded force per door shall be the average of 10 readings."

Custodian:

Army - EA

Preparing activity:

Army - MU(EA)

(Project No. 4240-A916)

AMSC N/A

FSC 4240

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:13Z
Check the source to verify that this is the current version before use.