INCH-POUND

MIL-DTL-52525/10C
12 November 2008
SUPERSEDING
MIL-DTL-52525/10B
30 June 1998

DETAIL SPECIFICATION SHEET

FITTINGS, HOSE, SCREW-ON TO 4-BOLT SPLIT-FLANGE, STRAIGHT

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-DTL-52525.



FIGURE 1. Fitting, screw-on to 4-bolt split-flange, straight.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:22Z
Check the source to verify that this is the current version before use.

Part or Identifying Number (PIN)	Hose		Tube dash no.	Flange head		A max inches (mm)	B min inches (mm)	C max inches (mm)
	Hose dash no.	ID inches (mm)		Dash no.	inches (mm)			
M52525/10-8-8	-8	.500 (12.70)	-8	-8	.500 (12.70)	3.78 (96.01)	1.27 (32.26)	1.38 (35.05)
M52525/10-12-12	-12	.750 (19.05)	-12	-12	.750 (19.05)	4.25 (107.95)	1.36 (34.54)	1.75 (44.45)
M52525/10-16-16	-16	1.000 (25.40)	-16	-16	1.000 (25.40)	4.74 (120.40)	1.61 (40.89)	2.06 (52.32)
M52525/10-16-20	-16	1.000 (25.40)	-20	-20	1.250 (31.75)	4.74 (120.40)	1.61 (40.89)	2.06 (52.32)
M52525/10-20-20	-20	1.250 (31.75)	-20	-20	1.250 (31.75)	5.35 (135.89)	1.80 (45.72)	2.63 (66.80)
M52525/10-20-24	-20	1.250 (31.75)	-24	-24	1.500 (38.10)	5.35 (135.89)	1.80 (45.72)	2.63 (66.80)
M52525/10-24-24	-24	1.500 (38.10)	-24	-24	1.500 (38.10)	5.61 (142.49)	2.08 (52.83)	2.94 (74.68)
M52525/10-24-32	-24	1.500 (38.10)	-32	-32	2.000 (50.80)	5.61 (142.49)	2.08 (52.83)	2.94 (74.68)
M52525/10-32-32	-32	2.000 (50.80)	-32	-32	2.000 (50.80)	6.37 (161.80)	2.44 (61.98)	3.50 (88.90)

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for information only.
3. All dimensions not shown shall be in accordance with SAE-J516 and SAE-J518 as applicable.
4. These fittings are similar to SAE-J516 assemble with SAE-J517 hose and SAE-J518 flange to manufacturer MIL-DTL-52471 hose assembly.

FIGURE 1. Fitting, screw-on to 4-bolt split-flange, straight - Continued.

REQUIREMENTS:

Fittings shall be as specified in figure 1 and in tables I and II.

The fittings described herein are for use with MIL-DTL-52471/5, type 100R2, double wire braided hose and hose assemblies in accordance with MIL-DTL-52525/2.

If fittings are to be used on an oxygen hose, see MIL-DTL-52525.

Materials and finishes shall be in accordance with MIL-DTL-52525 and in table I. All finishes shall be capable of withstanding 96 hours minimum of salt spray.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:22Z
Check the source to verify that this is the current version before use.

TABLE I. Material and finish identification codes. 1/ 2/

PIN code material/plating finish	Material	Plating finish
A	Aluminum alloy 6061 or 7075	Anodize in accordance with MIL-A-8625, type II.
AN		Anodize in accordance with MIL-A-8625, type II and NAVAIR trivalent chromium pretreatment (TCP) in accordance with MIL-DTL-81706, type 2, class A.
BN		Bare aluminum with NAVAIR TCP in accordance with MIL-DTL-81706, type 2, class A.
C	Steel	Cadmium plating in accordance with SAE-AMS-C-81562, type II, class 3 or SAE-AMS-QQ-P-416, type II, class 2.
CN		Cadmium plating in accordance with SAE-AMS-C-81562, type II, class 3 or SAE-AMS-QQ-P-416, type II, class 2 and NAVAIR TCP in accordance with MIL-DTL-81706, type 2, class A.
YC	Chrome-molybdenum steel alloy 4130	Cadmium plating in accordance with SAE-AMS-C-81562, type II, class 3 or SAE-AMS-QQ-P-416, type II, class 2.
YN		Cadmium plating in accordance with SAE-AMS-C-81562, type II, class 3 or SAE-AMS-QQ-P-416, type II, class 2 and NAVAIR TCP in accordance with MIL-DTL-81706, type 2, class A.
F	Steel	NAVAIR TCP in accordance with MIL-DTL-81706, type 2, class A.
FN	Chrome-molybdenum steel alloy 4130	
G	Steel	Zinc plating with colorless passivate in accordance with ASTM B633, type V, Fe/Zn 25.
YG	Chrome-molybdenum steel alloy 4130	
H	Steel	Zinc phosphate finish in accordance MIL-DTL-16232, type Z, class1. 3/
YH	Chrome-molybdenum steel alloy 4130	
J	Steel	Zinc plating with chromate conversion in accordance with ASTM B633; type II or III, Fe/Zn 5, or ASTM B695, type II, class 5.
YJ	Chrome-molybdenum steel alloy 4130	
K	Nickel-copper alloy UNS N04400	No additional finish.
M	High-chromium nickel alloy UNS N06690	No additional finish.
N	Steel	Zinc aluminum in accordance with ASTM F1136, grade 3, NC.
YN	Chrome-molybdenum steel alloy 4130	
P	Steel	Zinc plating with colorless passivate in accordance with ASTM B633, type VI, Fe/Zn 5.
YP	Chrome-molybdenum steel alloy 4130	
S	Corrosion resistant steel	No additional finish. Passivation in accordance with SAE-AMS2700, type 6 or 7.
SN		Passivation above and NAVAIR TCP in accordance with MIL-DTL-81706, type 2, class A.
T	Titanium	Anodize in accordance with SAE-AMS2488, type 2.
V	Steel	Zinc-nickel in accordance with SAE-AMS2417, type 1.
W	Steel	Any zinc plating above.
YW	Chrome-molybdenum steel alloy 4130	
Z	Steel	Any zinc plating above with NAVAIR TCP in accordance with MIL-DTL-81706, type 2, class A.
YZ	Chrome-molybdenum steel alloy 4130	

1/ All materials and finishes shall be in accordance with MIL-DTL-52525.
2/ Embitterment test need not be run.
3/ Zinc phosphate finish is hexavalent chromium free.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:22Z
Check the source to verify that this is the current version before use.

Maximum operating pressure shall be as specified in table II. Maximum operating pressures are for low carbon steel fittings consult manufacturer for values on other materials.

TABLE II. Maximum operating pressures of fittings. 1/ 2/

SAE dash size	Hose ID inches (mm)	psi	MPa
-8	.500 (12.70)	3500	24.1
-12	.750 (19.05)	2250	15.5
-16	1.000 (25.40)	2000	13.8
-20	1.250 (31.75)	1625	11.2
-24	1.500 (38.10)	1250	8.6
-32	2.000 (50.80)	1125	7.8

1/ Dimensions are in inches.
2/ Metric equivalents are given for information only.

PIN: The PIN consists of the letter “M” the specification sheet number, a dash, a number for hose size, a dash, a number for tube size, a dash, a number for flange, and a material finish designator.



PIN example: M52525/10-20-24A, describes a split flange for a 1.250 inch (31.75 mm) hose, with a 1.500 inch (38.10 mm) flange, aluminum with an anodized finish.

To the users of this document, it is recommended that the use of carbon steel material with cadmium plating be used only when the other materials and finishes specified in this document cannot meet performance requirements.

Color identification. Color identification shall be in accordance with SAE-AS4841.

Marking shall include the manufacturer’s name or trademark, size, and hose identifier R2. Location of marking is optional.

Harmonization to SAE-J516 and SAE-J518 cross reference PIN in table III is for reference only. SAE style fittings may not have the same material/finish as required by MIL-DTL-52525 and legacy with MIL-DTL-52471.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:22Z
Check the source to verify that this is the current version before use.

TABLE III. Harmonization to SAE-J516 and SAE-J518 cross reference PIN. 1/

PIN	SAE-J516 PIN
M52525/10-8-8	SAE J516 8-8 F390154
M52525/10-12-12	SAE J516 12-12 F390154
M52525/10-16-16	SAE J516 16-16 F390154
M52525/10-16-20	SAE J516 16-20 F390154
M52525/10-20-20	SAE J516 20-20 F390154
M52525/10-20-24	SAE J516 20-24 F390154
M52525/10-24-24	SAE J516 24-24 F390154
M52525/10-24-32	SAE J516 24-32 F390154
M52525/10-32-32	SAE J516 32-32 F390154

1/ Material and finish designators are omitted from PIN's see table I and SAE-J846.

Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue, due to the extent of the changes.

Referenced documents. In addition to MIL-DTL-52525, this document references the following:

MIL-A-8625	MIL-DTL-81706	SAE-AMS2488
MIL-DTL-16232	ASTM B633	SAE-AMS2700
MIL-DTL-52471	ASTM B695	SAE-AS4841
MIL-DTL-52471/5	ASTM F1136	SAE-J516
MIL-DTL-52525/2	SAE-AMS-C-81562	SAE-J517
MIL-DTL-52525/16	SAE-AMS-QQ-P-416	SAE-J518
MIL-DTL-52525/17	SAE-AMS2417	SAE-J846

CONLUDING MATERIAL

Custodians:
Army - AT
Navy - SH
Air Force - 99
DLA - CC

Preparing activity:
DLA - CC

(Project 4730-2007-078)

Review activities:
Army - CR4
Navy - AS, CG, MC, SA, YD

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at http://assist.daps.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:22Z
Check the source to verify that this is the current version before use.