INCH-POUND

MIL-DTL-83723/50D
23 May 2003
SUPERSEDING
MIL-C-83723/50C(USAF)
8 July 1974

DETAIL SPECIFICATION SHEET

CONNECTOR, ELECTRICAL, CIRCULAR, ENVIRONMENT RESISTING, BACKSHELL, STRAIGHT, 90°, AND 45° WITH DIELECTRIC STRAIN RELIEF, FOR SERIES 2 CONNECTORS.

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification and MIL-DTL-83723.

Inactive for new design as of
14 September 1993




FIGURE 1. Type R, straight strain relief, rotatable support arm.

DISTRIBUTION STATEMENT A. Approved for public release, distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:20Z
Check the source to verify that this is the current version before use.

Shell size	MIL-DTL-5015 size shell	A dia max	B dia	C dia	D dia	E max	F dia max
8	8S	.617	.445 .440	.300 .178	.255 .245	1.41	.517
10	10S	.734	.520 .500	.380 .341	.308 .300	1.41	.580
11	10SL	.734	.580 .560	.430 .408	.388 .380	1.41	.642
13	12S	.658	.645 .625	.480 .459	.413 .405	1.47	.705
12	12	.858	.645 .625	.480 .459	.413 .405	1.63	.705
15	14S	.984	.770 .750	.584 .362	.495 .487	1.66	.830
14	14	.984	.770 .750	.584 .582	.495 .487	1.81	.830
17	165	1.112	.895 .875	.710 .588	.614 .608	1.65	.955
16	16	1.112	.895 .875	.710 .688	.614 .608	1.81	.955
18	18	1.218	1.020 1.000	.627 .805	.735 .727	1.85	1.080
20	20	1.345	1.145 1.125	.964 .942	.875 .867	1.99	1.205
22	22	1.468	1.270 1.280	1.095 1.073	.983 .975	2.11	1.330
24	24	1.593	1.395 1.375	1.202 1.180	1.100 1.087	2.17	1.458
28	28	1.969	1.645 1.625	1.423 1.401	1.256 1.246	2.20	1.705

FIGURE 1. Type R, straight strain relief, rotatable support arm – Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:20Z
Check the source to verify that this is the current version before use.

Shell size	MIL-DTL-5015 size shell	G	H	J	K max	M thread class 2B	Number of teeth
8	8S	.365 .335	.350	.285 .272	.240	.4375-28UNEF	8
10	10S	.365 .335	.350	.285 .272	.295	.500-28UNEF	10
11	10SL	.365 .335	.350	.285 .272	.375	.5625-24 UNEF	12
13	12S	.365 .335	.350	.285 .272	.400	.625-24 UNEF	14
12	12	.365 .335	.505	.441 .428	.400	.625-24 UNEF	14
15	14S	.365 .335	.356	.285 .272	.482	.750-20 UNEF	16
14	14	.365 .335	.510	.441 .428	.482	.750-20 UNEF	16
17	165	.365 .335	.350	.285 .272	.601	.675-20 UNEF	20
16	16	.365 .335	.510	.441 .428	.601	.675020 UNEF	20
18	18	.380 .330	.490	.441 .428	.722	1.000-20 UNEF	24
20	20	.370 .340	.495	.044 .428	.862	1.125-18 UNEF	28
22	22	.370 .340	.495	.441 .428	.970	1.250-18 UNEF	32
24	24	.310 .280	.486	.423 .410	1.082	1.375-18 UNEF	32
28	28	.310 .280	.485	.423 .410	1.241	1.625-18 UNEF	36

FIGURE 1. Type R, straight strain relief, rotatable support arm – Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:20Z
Check the source to verify that this is the current version before use.




FIGURE 2. Type A, 90° strain relief.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:20Z
Check the source to verify that this is the current version before use.

Shell size	MIL-DTL-5015 size shell	A dia max	B dia	C dia	D dia	E max	F dia max	G
8	8S	.687	.455 .440	.300 .279	.255 .245	1.060	.551	.365 .335
10	10S	.782	.520 .500	.380 .341	.308 .300	1.060	.576	.365 .335
11	10SL	.782	.580 .560	.430 .408	.388 .390	1.060	.676	.365 .335
13	12S	.937	.645 .625	.480 .459	.413 .405	1.060	.812	.365 .335
12	12	.937	.845 .828	.480 .459	.413 .405	1.215	.812	.365 .335
16	145	1.050	.770 .750	.584 .562	.495 .487	1.065	.926	.365 .335
14	14	1.050	.770 .750	.584 .562	.495 .487	1.220	.926	.365 .335
17	168	1.239	.895 .875	.710 .688	.614 .606	1.060	1.052	.365 .335
16	16	1.239	.895 .875	.710 .688	.614 .606	1.220	1.052	.365 .335
18	18	1.375	1.020 1.000	.827 .805	.735 .727	1.220	1.178	.360 .330
20	20	1.500	1.145 1.128	.964 .942	.875 .887	1.235	1.312	.370 .340
22	22	1.831	1.270 1.250	1.095 1.073	.983 .975	1.188	1.437	.370 .340
24	24	1.750	1.395 1.375	1.202 1.180	1.100 1.087	1.121	1.551	.310 .280
28	28	1.921	1.845 1.625	1.423 1.401	1.256 1.246	1.121	1.780	.310 .280

FIGURE 2. Type A, 90° strain relief – Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:20Z
Check the source to verify that this is the current version before use.

Shell size	MIL-DTL-5015 size shell	H max	J	K max	L max	M thread class 2B	Number of teeth
8	8S	.350	.285 .272	.240	.88	.4375-28 UNEF	8
10	10S	.350	.285 .272	.295	.94	.500-28 UNEF	10
11	10SL	.350	.285 .272	.375	.94	.5625-24 UNEF	12
13	12S	.350	.285 .272	.400	1.00	.625-24 UNEF	14
12	12	.505	.441 .428	.400	1.00	.625.24 UNEF	14
16	145	.355	.285 .272	.462	1.32	.750-20 UNEF	16
14	14	.510	.441 .428	.482	1.32	.750-20 UNEF	18
17	168	.350	.285 .272	.601	1.37	.875-20 UNEF	20
16	16	.510	.441 .428	.601	1.37	.875-20 UNEF	20
18	18	.490	.441 .428	.722	1.42	1.000-20 UNEF	24
20	20	.495	.441 .428	.862	1.51	1.125-18 UNEF	28
22	22	.495	.441 .428	.970	1.57	1.250-18 UNEF	32
24	24	.488	.423 .410	1.082	1.64	1.375-18 UNEF	32
28	28	.488	.423 .410	1.241	1.71	1.625-18 UNEF	36

FIGURE 2. Type A, 90° strain relief – Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:20Z
Check the source to verify that this is the current version before use.




FIGURE 3. Type B, 45° strain relief.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:20Z
Check the source to verify that this is the current version before use.

Shell size	MIL-DTL-5015 size shell	A dia max	B dia	C dia	D dia	E max	F dia max	G
8	8S	.684	.455 .440	.300 .279	.255 .248	1.085	.551	.365 .335
10	10S	.782	.520 .500	.380 .341	.308 .300	1.085	.676	.365 .335
11	10SL	.782	.580 .560	.430 .408	.388 .380	1.085	.678	.365 .335
13	12S	.937	.645 .625	.480 .459	.413 .405	1.085	.812	.365 .335
12	12	.937	.645 .625	.480 .459	.413 .405	2.01	.812	.365 .335
15	14S	1.050	.770 .750	.584 .582	.495 .487	2.37	.926	.365 .335
14	14	1.050	.770 .750	.584 .582	.495 .487	2.52	.926	.365 .335
17	18S	1.239	.895 .875	.710 .688	.814 .808	2.38	1.052	.365 .335
18	18	1.239	.895 .875	.710 .688	.814 .606	2.52	1.082	.365 .335
18	18	1.378	1.020 1.000	.827 .805	.735 .727	2.66	1.176	.360 .330
20	20	1.500	1.145 1.125	.964 .942	.875 .867	2.74	1.312	.370 .340
22	22	1.831	1.270 1.250	1.095 1.073	.983 .975	2.74	1.437	.370 .340
24	24	1.750	1.395 1.375	1.202 1.180	1.100 1.087	2.82	1.551	.310 .280
28	28	1.921	1.645 1.625	1.423 1.401	1.256 1.246	2.82	1.750	.310 .280

FIGURE 3. Type B, 45° strain relief – Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:20Z
Check the source to verify that this is the current version before use.

Shell size	MIL-DTL-5015 size shell	H max	J	K max	L max	M thread class 2B	Number of teeth
8	8S	.360	.285 .272	.240	.76	4375-28 UNEF	8
10	10S	.360	.285 .272	.295	.82	.500-28 UNEF	10
11	10SL	.360	.285 .272	.375	.82	.5625-24 UNEF	12
13	12S	.350	.285 .272	.400	.88	.625-24 UNEF	14
12	12	.505	.441 .428	.400	.88	.625-24 UNEF	14
15	14S	.355	.285 .272	.482	1.12	.750-20 UNEF	16
14	14	.510	.441 .428	.482	1.12	.750-20 UNEF	16
17	18S	.350	.285 .272	.601	1.18	.875-20 UNEF	20
18	18	.510	.441 .428	.601	1.18	875-20 UNEF	20
18	18	.480	.441 .428	.722	1.27	1.000-20 UNEF	24
20	20	.495	.441 .428	.662	1.31	1.125-18 UNEF	28
22	22	.495	.441 .428	.970	1.37	1.250-18 UNEF	32
24	24	.488	.423 .410	1.082	1.44	1.375-18 UNEF	32
28	28	.488	.423 .410	1.241	1.57	1.625-18 UNEF	36

FIGURE 3. Type B, 45° strain relief – Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:20Z
Check the source to verify that this is the current version before use.

REQUIREMENTS

Type, 'R', 'A', & 'B': Complete strain relief consists of an accessory nut and a follower; the accessory nut shall be captivated to, and free to rotate on, the follower. Strain relief includes one set screw for positive orientation of strain relief to connectors.

Materials: Aluminum alloy in accordance with SAE-AMS-QQ-A-225 (or ASTM-B211) or the appropriate portions of ASTM-B85, ASTM-B26, ASTM-B108 & SAE-J452, SAE-J453, SAE-AMS4290, SAE-AMS4291.

Finish: (see Part or Identifying Number (PIN)) "N" electroless nickel in accordance with MIL-DTL-26074, class 3, grade A. "A" anodic coating in accordance with MIL-A-8625, type (optional), class 2 black. (Dimensions apply after finishing).

Strain relief unit is to be used with SAE-AS33671 plastic strap, MIL-T-713 lacing twine or A-A-52080 thru A-A-52084 Lacing tape.

Parts shall be marked in accordance with MIL-STD-1285.

Type 'R', 'A', & 'B': Type items described herein are covered by US patents 3,603,913 and/or 3,732,527.


Any portion of this standard which may be covered by copyrights owned by Glenair, Inc. is reprinted with the express permission of said company.

M83723/50 strain reliefs are not recommended for use with connectors containing number 8 AWG or larger conductors.

Preproduction tests shall consist of visual and mechanical examination, vibration, physical shock, and salt spray.

Acceptance tests: Acceptance tests shall consist of visual and mechanical examination.

Example of PIN:



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:20Z
Check the source to verify that this is the current version before use.

CONCLUDING MATERIAL

Custodians:
Army – CR
Navy – AS
Air Force – 11
DLA – CC

Review activity:
Air Force – 99

Preparing activity:
DLA – CC

(Project 5935–4415–004)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:20Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. **The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.**
2. **The submitter of this form must complete blocks 4, 5, 6, and 7, and send to preparing activity.**
3 **The preparing activity must provide a reply within 30 days from receipt of the form.**

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	**1.** DOCUMENT NUMBER **MIL-DTL-83723/50D**	**2.** DOCUMENT DATE *(YYYYMMDD)* **2003/05/23**

3. DOCUMENT TITLE
CONNECTOR, ELECTRICAL, CIRCULAR, ENVIRONMENT RESISTING, BACKSHELL, STRAIGHT, 90°, AND 45° WITH DIELECTRIC STRAIN RELIEF, FOR SERIES 2 CONNECTORS

4. NATURE OF CHANGE *(Identify paragraph number and include proposed rewrite, if possible.*
Attach extra sheets as needed.)

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME *(Last, First, Middle Initial)*	b. ORGANIZATION	
c. ADDRESS *(Include zip code)*	d. TELEPHONE *(Include Area Code)* (1) Commercial (2) DSN *(if applicable)*	**7.** DATE SUBMITTED *(YYYYMMDD)*

8. PREPARING ACTIVITY

a. NAME Defense Logistics Agency Defense Supply Center, Columbus	b. TELEPHONE *(Include Area Code)* (1) Commercial **614-692-0565** (2) DSN **850-0565**
c. ADDRESS *(Include Zip Code)* DSCC-VAI 3990 E. Broad St. Columbus, Ohio 43213	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Standardization Program Office (DLSC-LM) 8725 John J. Kingman Road,Suite 2533 Fort Belvoir, Virginia 22060-6621 Telephone (703) 767-6888 DSN 427-6888

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:20Z
Check the source to verify that this is the current version before use.