The documentation and process conversion measures necessary to comply with this amendment shall be completed by 12 May 1996

INCH-POUND

MIL-S-19500/464B
AMENDMENT 1
12 February 1996

MILITARY SPECIFICATION

SEMICONDUCTOR DEVICE, TRANSISTOR, NPN, SILICON POWER
TYPES 2N5685 AND 2N5686, JANTX AND JANTXV

This amendment forms a part of MIL-S-19500/464B, dated 25 May 1994, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 4

4.4.1, Delete "Electrical measurements (end-points) shall be in accordance with the applicable steps of table I, group A, subgroup 2 herein" and substitute: "Electrical measurements (end-points) shall be in accordance with the applicable steps of table II herein".

PAGE 5

4.4.2 Delete "Electrical measurements (end-points) shall be in accordance with the applicable steps of table I, group A, subgroup 2 herein" and substitute: "Electrical measurements (end-points) shall be in accordance with the applicable steps of table II herein".

4.4.3 Delete "Electrical measurements (end-points) shall be in accordance with the applicable steps of table I, group A, subgroup 2 herein" and substitute: "Electrical measurements (end-points) shall be in accordance with the applicable steps of table II herein".

PAGE 9

Table I, subgroup 5, conditions column; delete "See table I, subgroup 2" and substitute "See table II, steps 1 and 3".

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 20261O-19T02:14Z
Check the source to verify that this is the current version before use.

Following page 9 add the following table and footnotes:

" TABLE II. Groups A, B, and C electrical end-point measurements. 1/ 2/

Step	Inspection	MIL-STD-750		Symbol	Limits		Unit
		Method	Conditions		Min	Max	
1.	Collector to emitter cutoff current	3041	Bias condition A, V_{BE} = 1.5 V dc	I_{CEX1}		500	µA dc
	2N5685		V_{CE} = 60 V dc				
	2N5686		V_{CE} = 80 V dc				
2.	Collector to emitter cutoff current	3041	Bias condition A, V_{BE} = 1.5 V dc, T_A = +150°C	I_{CEX2}		5	mA dc
	2N5685		V_{CE} = 60 V dc				
	2N5686		V_{CE} = 80 V dc				
3.	Forward-current transfer ratio	3076	V_{CE} = 2.0 V dc, I_C = 25 A dc, pulsed(see 4.5.1)	h_{FE2}	15	60	
4.	Forward-current transfer ratio	3076	V_{CE} = 2.0 V dc, I_C = 25 A dc, pulsed(see 4.5.1)	Δh_{FE2}	± 25 percent of initial value.		
5.	Thermal response	3131	I_C = 25 A dc,	V_{BE}			

1/ The electrical measurements for table IVb (JANTX and JANTXV) of MIL-S-19500 are as follows:

a. Subgroup 2, see table II herein, steps 1 and 3.

b. Subgroup 3, see table II herein, steps 2, 4, and 5.

c. Subgroup 6, see table II herein, steps 2 and 4.

2/ The electrical measurements for table V of MIL-S-19500 are as follows:

a. Subgroup 2, see table II herein, steps 1 and 3.

b. Subgroup 3, see table II herein, steps 1 and 3.

c. Subgroup 6, see table II herein, steps 2, 4, and 5."

CONCLUDING MATERIAL

Custodians:
Army - ER
Navy - EC
Air Force - 17

Review activities:
Army - MI
Air Force - 13, 19, 70, 80, 85, 99

Preparing activity:
DLA - ES

(Project 5961-1802)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:14Z
Check the source to verify that this is the current version before use.