MIL-G-8602A
AMENDMENT 2
31 MAY 1957

SUPERSEDING
AMENDMENT 1
24 OCTOBER 1956

MILITARY SPECIFICATION

GLASS, LAMINATED, FLAT, AIRCRAFT

This amendment forms a part of Military Specification MIL-G-8602A, dated 6 April 1956, has been approved by the Department of Defense and is mandatory for use by the Departments of the Army, the Navy, and the Air Force.

Page 1, FSC number: Delete "5620" and substitute "9340."

Page 2, Standards: Add the following:

"MIL-STD-130 — Identification Marking of U.S. Military Property."

Page 2, paragraph 3.1.2: At the end of the paragraph add the following:

"Different amounts of plasticizer and types of plasticizer may be used if so specified by the procuring activity."

Page 2, paragraph 3.3.1, line 10: Delete "shell cullet," and substitute "small cullet, dirt spots,".

Page 3, paragraph 3.7: At the end of the paragraph add the following:

"Class II assemblies having tempered plies shall be allowed relaxed optical deviation in the area inscribed in a 2-inch radius from each tong mark."

Page 4, paragraph 3.11: Delete and substitute:

"3.11 Identification of Product. — Each glass assembly shall be indelibly marked in accordance with MIL-STD-130 and to the following form by etching or sandblasting on the glass surface. Unless otherwise specified, the marking shall not extend more than 5/8 inch from the edge of the daylight opening, nor be more than 3 inches in length. The identification marking shall be located so as to be legible when the glass unit is installed. Location of the marking shall be specified on the contract drawing. This requirement shall apply only to class II glass.

Identification form:

Part Number Date of Manufacture (month-year)	Specification Number Manufacturer's Trademark	Class, Type and Grade Serial Number (if required) [1]
	Example:	
22-1067-1 10-55	8602 XYZ	IIA2N 774210

[1] When the serial number is included in the marking, the procuring activity shall furnish the contractor a detailed explanation of the code to be used."

Page 7, paragraph 4.3.4: Line 9, delete "No. 220" and substitute "No. 20." Line 18, delete "+100°C (212°F) and substitute "+72°C (+161.6°F)."

Page 7, paragraph 4.3.6, line 9: After "circulating air" add "at +72° plus or minus 2.2°C (+161.6° plus or minus 4°F) for 2 hours. After".

FSC 9340

Source: https://assist.dla.mil -- Downloaded: 2026-01-17 10:40Z
Check the source to verify that this is the current version before use.

Page 7, paragraph 5.1.1: Delete the second sentence and substitute the following:

"Each individual assembly of laminated glass shall have its surfaces covered with newsprint or pressure-sensitive tape and shall be wrapped, when practical, in 80-pound or heavier kraft paper conforming to Specification UU–P–268."

Page 8, paragraph 5.2.2, line 14: Delete "500 pounds." and substitute "200 pounds."

Page 9, paragraph 6.2.2, line 3: After "part number" add "marking of serial number, if required."

Custodians:
Army—Transportation Corps
Navy—Bureau of Aeronautics
Air Force

Other interests:
Army—CQ
Navy—OrS

Preparing Activity:
Air Force

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T10:40Z
Check the source to verify that this is the current version before use.