INCH-POUND

MIL-T-8598B
11 October 1990
SUPERSEDING
MIL-B-8598A
10 Nov 1989

MILITARY SPECIFICATION

TRANSMITTER, TEMPERATURE, ELECTRICAL RESISTANCE, FLUSH-MOUNTED, FREE AIR

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the requirements for flush-mounted electrical resistance transmitter, with temperature-resistance characteristics.

1.2 Classification. The transmitters shall be of the following types, as specified herein:

Accuracy 1.0°C - Part No. MS28038-1

Accuracy 0.5°C - Part No. MS28038-2

1.2.1 The Air Force designates the Part No. MS28038-1 transmitter as type B-1 and the Part No. MS28038-2 transmitter as type B-3. These designations are not applicable to Navy activities.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

* 2.1.1. Specifications and standards. The following specifications and standards form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation.

SPECIFICATIONS

FEDERAL

PPP-B-601 Boxes, Wood, Cleated Plywood.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: the Support Division, San Antonio ALC/MMDEM, Kelly AFB, TX 78241 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 6685

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T10:39Z
Check the source to verify that this is the current version before use.

PPP-B-636	Box, Shipping, Fiberboard.

MILITARY

MIL-R-6855	Rubber, Synthetic Sheets, Strips, Molded or Extruded Shapes, General Specification for.
MIL-S-7742	Screw Threads, Standard, Optimum Selected Series: General Specification for.

STANDARDS

MILITARY

DOD-D-1000	Drawing, Engineering, and Associated List.
MIL-STD-105	Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129	Marking for Shipment and Storage.
MIL-STD-130	Identification Marking of U.S. Military Property.
MIL-STD-147	Palletized Unit Loads
MIL-STD-810	Environmental Test Methods and Engineering Guidelines.
MIL-STD-970	Standards and Specifications, Order of Preference for the Selection of.
MIL-STD-1186	Cushioning, Anchoring, Bracing, Blocking and Waterproofing; with Appropriate Test Methods.
MIL-STD-2073-1	DOD Materiel Procedures for Development and Application of Packaging Requirements
MS24693	Screw, Machine, Flat Countersunk Head, Recessed, UNC-2A and UNF-2A.
MS28038	Transmitter, Temperature, Electrical Resistance

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Standardization Documents Order Desk, Building 4D, 700 Robbins Avenue, Philadelphia, VA 19111-5094.)

2.1.2 Other Government documents, drawings, and publications. The following Government documents, drawings, and publications form a part of this specification to the extent specified herein. Unless otherwise specified, the issues shall be those in effect on the date of the solication.

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

ASTM-D-3951	Standard Practice for Commercial Packaging.

(Application for copies of this ASTM should be addressed to American Society for Testing Materials, 1916 Race Street, Philadelphia PA 19103)

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T10:39Z
Check the source to verify that this is the current version before use.

2.2 Other publications. The following document forms a part of this specification to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted shall be those listed in the issue of the DODISS specified in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS shall be the issue of the nongovernment documents which is current on the date of the solicitation.

UNIFORM CLASSIFICATION COMMITTEE

Uniform Freight Classification Rules

(Application for copies should be addressed to the Uniform Classification Committee, 222 South Riverside Plaza, Room 1106, Chicago, IL 60606).

(Nongovernment standards and other publications are normally available from the organizations which prepare or which distribute the documents. These documents also may be available in or through libraries or other informational services.)

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein (except for associated detail specifications, specification sheets or MS standards), the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 First article. When specified in the contract or purchase order, a sample shall be subjected to first article inspection (see 4.4 and 6.3).

3.2 Materials.

3.2.1 Metals. Metals shall be of the corrosion-resistant type, unless suitably protected to resist corrosion during normal service life.

3.2.2 Synthetic materials. Synthetic materials shall be of the thermal-setting type composed of a suitable filler and phenol condensation product binder.

3.2.3 Fungus-proof materials. Materials which are not nutrients for fungi shall be used to the greatest extent practicable. In cases where materials that are nutrients for fungi must be used, such materials shall be treated with a fungicidal agent as approved by the procuring activity.

3.2.4 Protective treatment. When materials are used in construction of the transmitter that are subject to deterioraton when exposed to climatic and environmental conditions likely to occur during service usage, they shall be protected against such deterioration in a manner that will in no way prevent compliance with the performance requirements of this specification. The use of any protective coating that will crack, chip, or scale with age or extremes of climatic and environmental conditions shall be avoided.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T10:39Z
Check the source to verify that this is the current version before use.

3.2.5 Selection of materials. Specifications and standards for all materials, parts, and Government certification and approval of processes and equipment, which are not specifically designated herein and which are necessary for the execution of this specification, shall be selected in accordance with MIL-STD-970, except as provided in the following paragraph.

3.2.5.1 Standard parts. Standard parts (MS or AN) shall be used wherever they are suitable for the purpose, and shall be identified on the drawing by their part number. Commercial utility parts such as screws, bolts, nuts, cotter pins, et cetera, may be used, provided they possess suitable properties and are replaceable by the standard parts (MS or AN) without alteration, and provided the corresponding standard part numbers are referenced in the parts list and, if practicable, on the contractor's drawings. In the event there is no suitable corresponding standard part in effect on date of invitation for bids, commercial parts may be used provided they conform to all the requirements of this specification.

3.3 Design and construction. The transmitter shall conform to MS28038.

3.3.1 The transmitter shall be so constructed that no parts will work loose in service. It shall be built to withstand the strains, jars, vibrations, and other conditions incident to shipping, storage, installation, and service, without failure.

3.3.2 Temperature-resistance characteristics. The temperature-resistance characteristics of the transmitter shall conform to table I.

TABLE I. Temperature resistance characteristics aircraft thermometer transmitter.

°C	(°F)	Ohms Resistance	Tolerance-Ohms	
			MS28038-1	MS28038-2
-70	(-94)	68.27	±0.50	±0.20
-60	(-76)	71.19	±0.50	±0.20
-50	(-58)	74.24	±0.40	±0.20
-40	(-40)	77.39	±0.40	±0.20
-30	(-22)	80.56	±0.40	±0.20
-20	(- 4)	83.77	±0.40	±0.20
-10	(-14)	87.04	±0.40	±0.20
0	(+32)	90.38	±0.40	±0.20
+10	(+50)	93.80	±0.40	±0.20
+20	(+68)	97.31	±0.40	±0.20
+30	(+86)	100.91	±0.40	±0.20
+40	(+104)	104.60	±0.40	±0.20
+50	(+122)	108.39	±0.40	±0.20
+60	(+140)	112.28	±0.50	±0.20
+70	(+158)	116.27	±0.50	±0.20

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T10:39Z
Check the source to verify that this is the current version before use.

3.3.3 Resistance element. The resistance element shall be sealed to withstand immersion of the transmitter in liquid baths as specified in the applicable tests of section 4.

* 3.4 Interchangeability. All parts having the same manufacturer's part number shall be directly and completely interchangeable with each other with respect to installation and performance. Changes in manufacturer's part numbers shall be governed by the drawing number requirements of DOD-D-1000.

3.5 Finish. All metals shall be suitably protected to meet the requirements of this specification.

* 3.6 Weight. The weight of the complete transmitter shall not exceed 0.25 pound (113.40 grams (G)).

* 3.7 Screw threads. The threads of all machine screws greater than 0.060 inch (1.524 millimeter (MM)) in diameter shall conform to MIL-S-7742.

3.8 Gaskets. Three gaskets constructed from black molded gasket rubber in accordance with MIL-R-6855, class III, grade 60, of each type as shown on MS28038 shall be furnished with each bulb.

3.9 Mounting lugs and screws. Each mounting lug shall be fitted with a self-locking nut, with No. 6-32 NF-2B threads; securely attached to prevent rotation when the screw is installed. The contractor shall furnish sufficient MS24693 screws for installing the bulb.

3.10 Performance. The transmitter shall be capable of meeting the requirements specified in section 4, when subjected to the applicable test.

3.11 Identification of product. The transmitter shall be marked for identification in accordance with MIL-STD-130. The following information shall be legibly and permanently marked on the flat of the boss upon which the electrical receptacle is mounted, or on a nameplate in such a manner as to be clearly seen when the transmitter is installed:

MS part no.
1/
Manufacturer's part no.
Manufacturer's serial no.
Contract or order no.
Manufacturer's name or trade-mark

1/ For Air Force procurement only, insert type B-1, or type B-3, as applicable.

3.11.1 Use of AN or MIL designations. AN or MIL designations shall not be applied to a product, except for qualification test samples, nor referred to in correspondence, until notice of approval has been received from the activity responsible for qualification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T10:39Z
Check the source to verify that this is the current version before use.

3.12 Envelope. An envelope, containing the mounting screws and gaskets, shall be furnished with each transmitter. The following information shall be printed on the face of the envelope:

IMPORTANT
THIS ENVELOPE CONTAINS MOUNTING SCREWS AND GASKETS

3.13 Workmanship. The transmitter, including all parts and accessories, shall be constructed and finished in a thoroughly workmanlike manner. Particular attention shall be given to neatness, marking of parts and assemblies, and freedom of parts from burrs and sharp edges.

3.14 Reclaimed materiels. The use of reclaimed materiels shall be encouraged to the maximum extent possible.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Classification of inspection. The examination and testing of the transmitter shall be classified as follows:

a. First article inspection (see 4.4).

b. Quality conformance inspection (see 4.5).

4.3 Test conditions.

4.3.1 Standard atmospheric conditions. Unless otherwise specified, all tests shall be made at an atmospheric pressure of approximately 29.92 inches (76 Centimeter (cm)) mercury and at a temperature of approximately +25°C (+77°F). When tests are made with atmospheric pressure and temperature substantially different from the above values, proper allowance shall be made for the difference from the specified conditions.

4.3.2 Resistance values. Whenever practicable, the resistance values given for test results shall be the averages of direct and reversed readings to eliminate thermal-electric potential errors.

4.3.3. Transmitter. For test purposes, the sensitive portion of the transmitter shall be considered as from the front of the transmitter to the front of the mounting flange as shown on MS28038. The head of the transmitter shall be considered as from the front of the mounting flange to the top of the electrical receptacle as shown on MS28038.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T10:39Z
Check the source to verify that this is the current version before use.

4.3.4 Temperature-resistance measurements. Unless otherwise specified, all temperature-resistance measurements shall be made in an agitated liquid bath with the sensitive portion of the transmitter immersed.

4.3.5 Test voltage. Unless otherwise specified, all resistance measurements shall be made with 1.5 ±0.2 volts direct current (DC) applied to the bulb.

4.3.6 Master. The master shall be defined as a temperature-measuring device with known calibration.

4.4 First article inspection. The first article inspection shall consist of all the tests specified herein.

4.5 Quality conformance inspection. The inspection shall consist of individual tests (4.5.1), sampling tests (4.5.2), and special tests (4.5.3).

4.5.1 Individual tests. Each transmitter submitted for acceptance under contract shall be subjected to the following examination and test.

4.5.1.1 Examination of product. The transmitter shall be inspected to determine compliance with the requirements specified herein with respect to material, workmanship, and marking.

4.5.1.2 Transmitter adjustment test. The resistance of the transmitter shall be measured at room temperature. The measured resistance shall be within 0.40 ohm for the part no. MS28038-1, and within 0.20 ohm for the part no. MS28038-2 of the resistance specified in table I for the exact temperature of the master, interpolation of the values given in table I may be necessary. To determine the true resistance equivalent to the temperture of the master.

4.5.2 Sampling plan A tests. Sampling shall be performed in accordance with MIL-STD-105, inspection level II AQL 2.5 percent.

4.5.2.1 Transmitter resistance. The resistance of each transmitter shall be measured at temperatures of -50° ±5°C, 0° ±5°C, and +50°C in an agitated liquid bath. If desired by the inspector, resistance measurements at any other points in table I may also be made. The measured resistance shall be within the tolerances specified in table I for the exact temperature of the master. To determine the true resistance equivalent to the temperature of the master, interpolation of the values given in table I may be necessary.

* 4.5.2.2 Vibration. The transmitter shall be subjected to vibrations tests in accordance with MIL-STD-810, Method 514.3, Procedure I, Category 5 equipment, with W_o = 0.02 g^2/Hz. An indicator or a wheatstone bridge shall be connected to the transmitter during the test. Induced pointer oscillation or variation greater than 2.0 degrees (0.80 ohm) for part no. MS28038-1, or 1.0 degree (0.40 ohm) for part no. MS28038-2 shall be cause for failure. Following vibration, the transmitter shall be subjected to the transmitter adjustment test (4.5.1.2). The measured resistance shall be within 0.40 ohm for part no. MS28038-1 and within 0.20 ohm for part no MS28038-2 of the resistance specified in the table I

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T10:39Z
Check the source to verify that this is the current version before use.

for the exact temperature of the master. In addition, no looseness nor damage to any part of the transmitter shall result from this test. (In accordance with recommended test levels according to MIL-STD-810 for aircraft equipment location as stated in 6.1).

4.5.3 Sampling plan B tests. Sampling shall be in accordance with MIL-STD-105, special inspection level S-1, AQL 6.5 percent.

4.5.3.1 Detail examination. The transmitter shall be critically examined to determine full compliance with regard to weight, physical dimensions, markings, and similar detail requirements.

4.5.3.2 Response time. The transmitter, with sensitive portion immersed, shall be quenched from an agitated liquid bath at 70°C to an ice bath at 0°C. The transmitter shall be agitated in the ice bath. The time required for the transmitter temperature to fall from 70C° to 10°C shall be noted. The time required for the transmitter temperature to change from 70C° to 10°C shall not exceed 3 seconds.

4.5.3.3 Thermal conductivity. With heated air, the head of the transmitter shall be maintained at a temperature of 70° ±2°C. The sensitive portion of the transmitter shall be subjected to a temperature of -50° ±2°C in an agitated liquid bath. The measured resistance of the transmitter shall not differ by more than 1 ohm from the resistance determined in the transmitter resistance test (4.5.1.2) for the exact temperature of the master.

4.5.3.4 Self-heating. The transmitter shall be placed in an agitated liquid bath at a temperature of 25° ±2°C. A current of 150 milliampere (mA) shall be applied to the bulb for a minimum period of 2 minutes and the maximum rise in resistance measured during this period. The rise shall not exceed 3 ohms.

4.5.3.5 Thermoelectric potential. The potential produced in the transmitter winding measured with a potentiometer when the sensitive portion of the transmitter is subjected to a temperature of 70° ±2°C in an agitated liquid bath shall not exceed 1 millivolt (mV).

4.5.3.6 Cold resistance. The transmitter shall be subjected to a temperature of -65°C (-80°F) for a period of 15 hours. With the transmitter at -65°C, it shall be subjected to vibration, as specified herein, for a period of 10 minutes. The vibration frequency shall be 3,000 cycles per minute (cpm) for this test. There shall be no damage to the transmitter as a result of this test.

4.5.3.7 High temperature. The transmitter shall be subjected to a temperature of 71°C (158°F) for a period of 15 hours. With the transmitter at 71°C, it shall be subjected to vibration, as specified herein, for a period of 10 minutes. The vibration frequency shall be 3,000 (cpm) for this test. There shall be no change to the transmitter as a result of this test.

* 4.5.3.8 Humidity. The transmitter shall be subjected to humidity tests in accordance with MIL-STD-810, Method 507.2, Procedure III. There shall be no rusting or erosion of the transmitter or any other damage as a result of this test.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T10:39Z
Check the source to verify that this is the current version before use.

4.5.3.8.1 Insulation leakage after humidity. A potential of 100 volts DC shall be applied between any electrical receptacle pin contact and any metal part of the transmitter. Air drying of the transmitter receptacle connecting leads and outer housing prior to conducting this is permissible. The insulation resistance measured between any pin and any metal part of the transmitter shall be equal to or greater than 20 megahertz (MHz).

* 4.5.3.9 Fungus. Fungus test in accordance with MIL-STD-810, Method 508.3. Upon completion of the test, there shall be no signs of fungus growth on the transmitter.

4.5.3.10 Transmitter adjustment. Following the completion of the foregoing tests, the transmitter adjustment test (See 4.5.1.2) shall be performed. The resistance shall be within 0.40 ohm for part no. MS28038-1, and within 0.20 ohm for part no. MS28038-2 of the resistance specified in table I for the exact temperature of the master.

4.5.3.11 Tensile strength. The mounting flange of the transmitter with the sensitive element removed shall be mounted on the movable head of an amsler testing machine, or equivalent apparatus, with the diameter of the transmitter in a horizontal plane so that the mounting lugs receive no added support. A suitable pin shall be inserted through the hole in the mounting nut and attached to a pull strap in the stationary head of the machine. Each mounting lug of the completely assembled transmitter shall withstand for 1 minute, without fracture, a load of 175 pounds (78.38 Kilogram (kg)) applied along the insert nut axis and toward the sensitive portion of the transmitter.

4.5.3.12 Mounting nuts. Each mounting lug shall have a load of 25 pounds applied to the nut in a manner tending to pull the nut out of the lug toward the rear of the transmitter. The mounting nut shall not become loose in the lug and shall not rotate more than a fraction of a turn under a torque of 10 pound-inches.

4.5.3.13 Shock. The transmitter, operating, shall be subjected to procedure 1, method 516.3, shock test of MIL-STD-810. The wave form of the shocks and time duration shall be in accordance with figure 516.3-1, procedure 1 for flight equipment. Following this test the transmitter shall be subjected to the transmitter adjustment (4.5.1.2). The tolerance requirements of 4.5.1.2 shall apply.

4.5.3.14 Salt fog. The transmitter shall be subjected to a salt fog test in accordance with method 509.2 of MIL-STD-810. External connections shall be made to the transmitter in such a manner as to simulate installed conditions. Following the salt fog exposure, the transmitter shall be washed with distilled water. Following the 48-hour storage the transmitter shall be subjected to and meet the requirements of the transmitter adjustment test (4.5.1.2) and the insulation leakage after humidity test (4.5.3.8.1). In addition evidence of corrosion shall be cause for failure.

4.5.4 Rejection and retest. When sampling tests (4.5.2) are specified on a number of items that are selected as representative of a certain lot, and one or more of this number fail to meet the specified test(s), acceptance of

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T10:39Z
Check the source to verify that this is the current version before use.

all items shall be withheld until the extent and cause of failure is determined. For operational reasons, individual tests (4.5.1) may be continued pending investigation of a sampling test failure, but the final acceptance of the product is contingent upon the inspector's decision regarding the over-all conformance of the product to the specification requirements. If investigation indicates that the defects may exist on items previously accepted, full particulars concerning the defect(s) found, including recommendations for correction, will be furnished to the procuring activity.

4.5.5 First article failure. Failure of a first article sample to pass any of the tests specified herein shall be cause for Government disapproval of first article samples. No production transmitters shall be delivered prior to approval of the first article samples.

4.5.6 First article approval. Approval of the first article sample shall be by the procuring activity and shall be granted upon satisfactory completion of all tests.

4.6 Preservation, packaging, packing, and marking. Preparation for delivery shall be inspected for conformance to section 5.

5. PACKAGING

5.1 Preservation. Preservation shall be level A or commercial as specified (see 6.2).

5.1.1 Level A. Each transmitter shall be preserved to the MIL-STD-2073-1 requirements for this level.

5.1.2 Level C. Each transmitter shall be preserved to the MIL-STD-2073-1 requirements for this level.

5.1.3 Commercial. Each transmitter shall be preserved in accordance with applicable requirements of ASTM D 3951.

5.2 Packing. Packing shall be level A, B, C, or Commercial as specified (see 6.2).

5.2.1 Level A. Each transmitter that has been preserved and packaged as specified in 5.1 shall be packed in exterior-type shipping containers that conform to PPP-B-601, overseas type. The closure of the shipping container shall be in accordance with the appendix of the applicable shipping container specification.

5.2.2 Level B. Each transmitter that has been preserved and packaged as specified in 5.1 shall be packed in exterior-type shipping containers that conform to PPP-B-636, class weather resistant. The closure of the shipping container shall be in accoradance with the appendix of the applicable shipping container specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T10:39Z
Check the source to verify that this is the current version before use.

5.2.3 Level C. Each transmitter that has been preserved and packaged as specified in 5.1 shall be packed in accordance with the requirements of MIL-STD-2073-1.

5.2.4 Commercial. Each transmitter that has been preserved and packaged as specified in 5.1 shall be packed in accordance with the requirements of ASTM D 3951.

5.3 Marking. Interior and exterior containers shall be marked in accordance with MIL-STD-129.

5.4 Palletization. Unitized loads, commensurate with the level of packaging specified in the contract or order shall be palletized in accordance with MIL-STD-147. Palletized loads shall be uniform in size and quanities to the greatest extent possible. If the container is of a size which does not conform to any of the pallet patterns specified in MIL-STD-147, the pallet pattern shall first be approved by the contracting officer.

6. NOTES

6.1 Intended use. The temperature transmitter covered by this specification is intended for mounting flush on aircraft skins for precision free air temperature measurement.

6.2 Ordering data.

6.2.1. Acquisition requirements. Acquisition documents should specify the following:

a. Title, number, and date of this specification.

b. Selection of applicable levels of preservation, packaging, packing, marking and commercial/industrial (see 5.1, 5.2 and 5.3).

c. When palletization is required (See 5.4).

6.3 First article. When a first article inspection is required, the item will be tested and should be a first article sample or it may be a standard production item from the contractor's current inventory. The first article shall consist of three units. The contracting officer shall include specific instructions in acquisition documents regarding arrangements for examinations, approval of first article test results and disposition of first articles. Invitations for bids should provide that the Government reserves the right to waive the requirement for samples for first article inspection to those bidders offering a product which has been previously acquired or tested by the Government, and that bidders offering such products, who wish to rely on such production or test, must furnish evidence with the bid that prior Government approval is presently appropriate for the pending contract.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T10:39Z
Check the source to verify that this is the current version before use.

* 6.4 Subject term (key words) listing.

Aircraft Free Air Temperature Transmitter
Transmitter, Electrical Resistance
Electrical Resistance Transmitter
Free Air Temperature Transmitter
Resistance, Electrical, Transmitter
Transmitter, Electrical Resistance

Custodian:
Air Force - 99

Review activities:
Air Force - 11
Navy - SH

Preparing activity:
Air Force - 82

(Project 6685-0859)

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T10:39Z
Check the source to verify that this is the current version before use.