INCH-POUND

MIL-DTL-19688D(MC)
16 October 1997
SUPERSEDING
MIL-C-19688C(MC)
15 September 1994

DETAIL SPECIFICATION

CUMMERBUND, MAN'S - BLACK

This specification is approved for use by U.S. Marine Corps, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1. Scope. This specification covers requirements for a man's black cummerbund.

1.2. Classification. The cummerbund will be of one type and size with elastic strap adjustment.

2. APPLICABLE DOCUMENTS

2.1. General. The documents listed in this section are specified in sections 3 and 4 of this specification. This section does not include documents cited in other sections of this specification or recommended for additional information or as examples. While every effort has been made to ensure the completeness of this

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to the Commander (PSE-D), Marine Corps Systems Command, Quantico, VA 22134-5010 by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 8405

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T06:32Z
Check the source to verify that this is the current version before use.

list, document users are cautioned that they must meet all specified requirements documents cited in sections 3 and 4 of this specification, whether or not they are listed.

2.2. Government documents.

2.2.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DoDISS) and supplement thereto, cited in the solicitation (see 6.2).

SPECIFICATIONS

FEDERAL

A-A-50196	- Thread, Silk
A-A-52094	- Thread, Cotton
CCC-C-426	- Cloth, Cotton, Drill
DDD-L-20	- Label: For Clothing, Equipage, and Tentage, (General Use)

DEPARTMENT OF DEFENSE

MIL-C-368	- Cloth, Satin, Rayon and Cloth, Twill, Rayon

STANDARDS

FEDERAL

FED-STD-191	- Textile Test Methods
FED-STD-751	- Stitches, Seams, and Stitching

(Unless otherwise indicated, copies of the above specifications, standards, handbooks are available from the Standardization Document Order Desk, 700 Robbins Avenue, Building 4D, Philadelphia, PA 19111-5094.)

2.3. Non-Government publications. The following document(s) form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DoD adopted are those listed in the issue of the DoDISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DoDISS are the issues of the documents cited in the solicitation (see 6.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T06:32Z
Check the source to verify that this is the current version before use.

ANSI/ASQC Z1.4 - Sampling Procedures and Tables for Inspection by Attributes

(Application for copies should be addressed to The American National Standards Institute, 11 West 42nd Street, New York, NY 10036)

Department of Defense (DoD) Standard Color Card of Official Standardized Shades for Sewing Thread 1968

(Application for copies should be addressed to The Color Association of the United States, Inc., 409 W. 44th Street, New York, NY 10016-0927.)

2.4. Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1. Standard sample. Standard samples are furnished solely for guidance and information to the contractor (see 6.3). Variation from this specification may appear in the standard sample, in which case the specification shall govern.

3.2. First article. When specified (see 6.2), a sample shall be subjected to first article inspection in accordance with 4.3.

3.3. Material.

3.3.1 Basic material. The basic material shall be cloth, satin, rayon, 3.7 ounce, conforming to class 1 of MIL-C-368. The color shall be black, shade 3202.

3.3.2 Cotton, drill. The body of the cummerbund shall be interlined with cloth, cotton, drill, 7.0 ounces per square yard, unbleached, conforming to type I, class 2 of CCC-C-426. As an alternate, cloth, fusible interlining may be used. Woven Kufner style #G35, National style 200 FL or Crown style 241 or equal.

3.3.3 Elastic webbing. The elastic webbing shall be made of rayon yarn of suitable grade and denier to meet the requirements specified below, and natural or synthetic rubber strands of a

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T06:32Z
Check the source to verify that this is the current version before use.

suitable gage to meet the requirements specific below. The webbing shall be composed of two ground warps (one face and one back), one elastic warp, and one filling. The ground warps shall weave in a three up and one down order, with one continuous filling so as to produce a right twill effect on the face and back of the fabric. The elastic strands shall weave in such a manner as to be over all the back picks and under all the face picks. The finished webbing shall conform to the following:

Width (inches)	1-1/8 ± 1/16
Weight per linear yd (ounces)	0.96 minimum
Total warp	170 minimum
Elastic strands	22 minimum
Picks per inch	56 minimum

The color of the webbing shall be black, showing good fastness to laundering, wet (dry) cleaning, crocking and perspiration when tested as specified in Table III.

3.3.4 Thread.

3.3.4.1. Silk thread. The silk thread for machine sewing shall conform to type I, ticket No. A, 3-ply of A-A-50196 for all outside seaming and stitching. The thread for hand sewing shall conform to type III, ticket No. C, 2-ply of A-A-50196.

3.3.4.2. Cotton thread. Thread for inside seaming and stitching shall be cotton, mercerized finish, ticket No. A, 3-ply, conforming to type III of A-A-52094. Basting thread shall be a good commercial grade.

3.3.4.3. Color and colorfastness. The cotton and silk thread, except thread for basting, shall be black. The thread shall show good fastness to wet (dry) cleaning, laundry and light when tested as specified in the applicable thread specification (see DoD Standard Color Card of Official Standardized Shades for Sewing Threads 1968).

3.3.5 Hardware. The buckle and slide shall be made of brass or bronze, nickel plated, and shall conform to the design and dimensions shown on Figure 2.

3.3.6 Label. Each cummerbund shall be provided with an identification label, conforming to type VI, class 1 of DDD-L-20.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T06:32Z
Check the source to verify that this is the current version before use.

The label shall measure not less than 2-1/2 by 1-1/2 inches. The content and format shall be as follows:

Nomenclature: (item description)
Contract number:
Name of contractor:
Fiber production identification:

NOTE: Size of characters for "Name of contractor" shall be minimum 6 point (approximately 1/16 inch).

3.4. Design. The cummerbund shall be the U.S. Marine Corps design shown on Figure 1 having a one-piece front with four horizontal pleats and an interlining, a plain extension piece, a plain two-piece back lining provided with an elastic webbing strap at each end, a clasp type metal buckle at the end of the elastic straps, and a metal adjusting slide on both straps.

3.5. Patterns. Standards patterns will be furnished to the contractor by the Government. The standard patterns shall not be altered in any way and shall be used only as a guide for cutting the contractor's working patterns. The standard patterns provide a 1/4 inch allowance for front and interlining seams and 3/8 inch allowance for front and lining seams and pockets, unless otherwise specified in Table I. Standard patterns shall show seam allowances and directional lines for cutting, and shall be marked or notched for proper placement and assembly of the component parts.

3.5.1 List of pattern parts. The cummerbunds shall be cut from the materials specified in accordance with the pattern parts indicated below:

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T06:32Z
Check the source to verify that this is the current version before use.

ITEM	PATTERN NOMENCLATURE	NO. OF CUT PARTS
	Material: Cloth, satin, rayon	
1	Front, center	1
2	Side front, extensions	2
3	Back, lining	1
4	Back lining extension piece	1
	Material: Cloth, cotton, drill	
5	Front, interlining	1
6	Front extension interlining	2
	Material: Cloth, fusible (optional)	
7	Front interlining, fusible	1
8	Front extension interlining, fusible	2
	Marker	
9	Front	-

3.6. Construction.

3.6.1 Manufacturing requirements. The cummerbunds shall be manufactured in accordance with the operations and the stitch, seam, and stitching types specified in Table I.

3.6.1.1. Operations. The contractor is not required to follow the exact sequence of operations as listed in Table I, but all operations specified shall be used to manufacture the cummerbunds.

3.6.1.2. Stitches, seams, and stitchings. The stitch, seam, and stitching types specified in Table I shall conform to FED-STD-751. The number of stitches per inch as specified in Table I indicates the minimum and maximum number permitted.

3.6.1.2.1 Tacking and backstitching. Ends of seams and stitching produced with 301 type stitch, when not caught in other seams or stitchings, shall be securely backtacked not less than 1/4 inch. Thread breaks (all stitch types) shall be secured by stitching back of break not less than 1/2 inch.

3.6.1.3. Shade marking. The component parts of the cummerbund shall be shade marked to ensure a uniform shade and size throughout the garment. Any method of shade marking may be used except:

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T06:32Z
Check the source to verify that this is the current version before use.

a. Metal fastening devices.
b. Sew-on shade tickets.
c. Adhesive type tickets which show discoloration or leave traces of paper or adhesive mass to the material upon removal of the tickets.

TABLE I. Manufacturing requirements.

NO	OPERATION	STCH TYPE	SEAM/ STCH TYPE	STCH/IN	NDL	BOB/ LPR
1	Cutting. a. Cut cummerbund in strict accordance with the patterns furnished. b. Cut all materials in the direction indicated by directional lines on pattern. c. Cut all component parts of the cummerbund from one piece of basic material. d. Cut the elastic webbing for the left side of the cummerbund 8 inches long and for the right side 15 inches long. e. The use of drill holes is prohibited.					
2	Replacement of damaged parts. a. Replace at time of cutting any part containing damages, such as holes, or seriously weakening defects, such as smashes, multiple floats, and slubs likely to develop into holes. b. Replace any part damaged during the manufacturing process by needle chews, which may be expected to develop into a hole, scissors or knife cuts, tears, holes, mends and burns.					
3	Shade marking. a. Mark or ticket (see 3.6.1.3) all component parts cut from basic material in order to ensure proper assembly and a uniform shade throughout the cummerbund.					

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T06:32Z
Check the source to verify that this is the current version before use.

TABLE I. Manufacturing requirements - Continued.

NO	OPERATION	STCH TYPE	SEAM/ STCH TYPE	STCH/IN	NDL	BOB/ LPR
3	Shade marking. (cont'd)					
	b. Adhesive tickets, when used, shall be adhered to the inside of the cummerbund.					
4	Sew on identification label.					
	Finished appearance. The label shall be properly positioned and sewn to the back of the cummerbund.					
	a. Position the identification label at the center of the back lining, with the top edge 1 inch from the top edge of the back. Sew the label to the back lining with a single row of stitches 1/16 inch from each edge.	301	SSa-1	10-14	A	A
5	Make center front.					
	Finished appearance. All pleats and joining seams shall finish smooth and flat without distortions. The seams shall start and finish evenly. The pleats shall finish with the outside folded edge towards the top of the front.					
	a. The front shall be made of one ply of rayon satin material and one ply of interlining material. When the cotton drill interlining is used, the front shall be pleated first and have side extensions joined before shaping of canvas. When fusible interlining is used, the front shall be fused before pleating.					
	b. Fold the center front lengthwise, inside out, in accordance with notches on the patterns, forming the pleats. Stitch each pleat from end to end with a continuous row of stitches. The stitching at the ends of the pleat shall be 1 inch from the lower folded edge and shall extend for a distance of approximately 2 inches from each end. The stitching for the remainder of the pleat shall be 1/2 inch from the folded edge.	301	OSf-1	6-10	A	A

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T06:32Z
Check the source to verify that this is the current version before use.

TABLE I. Manufacturing requirements - Continued.

NO	OPERATION	STCH TYPE	SEAM/ STCH TYPE	STCH/IN	NDL	BOB/ LPR
5	Make center front. (cont'd)					
	c. Press front with the outside folded edge of each pleat towards the top of the cummerbund.					
	d. Position the front over the interlining with the upper raw edges even. Stitch each pleat on the underside of the front through the interlining, end to end, 3/8 inch above the lower folded edge.	301	LSae-1	8-10	A	A
	e. Seam the front and interlining together on each edge with a 1/4 inch seam.	301	SSa-1	8-10	A	A
	f. Mark and trim the front in accordance with the pattern marker. Mark the upper edge for the position of two pockets.					
6	Make right buckle strap.					
	Finished appearance. The buckle and adjustment slides shall be positioned and secured to the buckle strap.					
	a. The buckle strap shall consist of one elastic webbing each for right and left ends of cummerbund. The male half of the buckle and an adjustment slide shall be secured to the right buckle strap. The female half of the buckle and an adjustment slide shall be seamed to the left strap.					
	b. Insert one end of the elastic webbing through the adjustment slide. Pull enough webbing through the slide to form a 1-1/4 to 1-1/2 inch loop. Turn under the end of the webbing 1/4 to 3/8 inch and stitch to the body of the webbing 1/16 to 1/8 inch from folded edge, catching the turned under portion in the stitching.	301	SSb-1	10-14	A	A
	c. Insert the loose end of the webbing through the male and female halves of the buckle and through the adjustment slide as shown on Figure 2.					

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T06:32Z
Check the source to verify that this is the current version before use.

TABLE I. Manufacturing requirements - Continued.

NO	OPERATION	STCH TYPE	SEAM/ STCH TYPE	STCH/IN	NDL	BOB/ LPR
7	Make side front extensions.					
	The extension pieces shall be made from one ply of rayon satin material and one ply of interlining.					
	a. Stitch the two plies together at side and bottom edge 1/8 inch from the edge.	301	SSa-1	10-14	A	A
8	Join extensions to center front.					
	a. Position the center front and extensions face to face, even at the side edges, and seam together 1/4 inch from the raw edge.	301	LSq-2 (a)	10-14	A	A
	b. Turn the extension and raise stitch 1/16 to 1/8 inch from seamed edge.	301	LSq-2 (b)	10-14	A	A
9	Assemble cummerbund.					
	Finished appearance. The assembled cummerbund shall be uniform in appearance and finish and shall be smooth and flat. Seams shall be without puckers, pleats or distortions. The buckles shall be properly aligned.					
	a. Position the right and left buckle strap, assembled as indicated in Figure 2, on the outside of the cummerbund, with the ends even with the corresponding end of the cummerbund. Join the webbing to the front 1/8 to 3/16 inch from the ends.	301	SSa-1	10-14	A	A
	b. Position the lining and the lining tunnel extension on the outside of the cummerbund and seam to the front through the interlining, 3/8 inch from the top edge.	301	LSq-2 (a)	10-14	A	A
	c. Turn the lining and topstitch 1/16 to 1/8 inch from the seamed edge.	301	LSq-2 (b)	10-14	A	A

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T06:32Z
Check the source to verify that this is the current version before use.

TABLE I. Manufacturing requirements - Continued.

NO	OPERATION	STCH TYPE	SEAM/ STCH TYPE	STCH/IN	NDL	BOB/ LPR
	d. Seam the lining to the front at the bottom the length of cummerbund with a 3/8 inch seam except for a distance of approximately 3-1/2 inches which is left open for turning or turning may be accomplished through the extension lining tunnel piece.	301	SSa-1	10-14	A	A
9	Assemble cummerbund. (cont'd)					
	e. Turn the seamed edges of the extensions inward as close as possible to the elastic webbing. Stitch each end of the extension with a 3/8 inch seam, catching the webbing in the stitching.	301	SSj-1	10-14	A	A
	f. Trim the corners and raw edges of seams for proper turning.					
	g. Turn cummerbund right side out, forcing out all corners and seamed edges.					
	h. Baste edges to hold desired shape.	301 or Hopper				
	i. Close the opening with felling. The lining shall not be exposed on the outside of the cummerbund.	Hand		2-3	C (silk)	
10	Press cummerbund.					
	Finished appearance. Pressing shall be done on a heated pressing iron or pressing machine of a type suitable to obtain the desired appearance in accordance with good manufacturing practice.					
	a. Press the entire cummerbund, removing all wrinkles.					
	b. Finish press.					
11	Clean cummerbund.					
	a. Remove bastings, trim all ends of stitchings and remove all loose threads from the cummerbund. Remove all spots, shade tickets, markers and stains from the cummerbund without injury to the material.					

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T06:32Z
Check the source to verify that this is the current version before use.

3.7. Finished measurements. Finished measurements of the cummerbund shall be as shown in Figure 1. The finished length (dimension "A" in Figure 1) shall be 24-1/2 inches ± 3/8 inch.

3.8. Workmanship. The finished cummerbunds shall conform to the quality and grade of product established by this specification.

3.9. Recycled, recovered, or environmentally preferable materials. Recycled, recovered, or environmentally preferable materials should be used to the maximum extent possible provided that the material meets or exceeds the operational and maintenance requirements, and promotes economically advantageous life cycle costs.

4. VERIFICATION

4.1. Classification of inspection. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).
b. Conformance inspection (see 4.4).

4.2. Inspection conditions. Unless otherwise specified, all inspections shall be performed in accordance with the provisions set forth in ANSI/ASQC Z1.4.

4.3. First article inspection. When a first article is required (see 6.2), it shall be examined for the defects specified in 4.4.2.1 through 4.4.2.3. The presence of any defect or failure to pass any test shall be cause for rejection of the first article.

4.4. Conformance inspection.

4.4.1 Testing of components. Testing of components shall be in accordance with applicable subsidiary specifications and standards to the extent applicable, except that this specification shall govern in the event of conflict. The method of testing specified in ANSI/ASQC Z1.4 and FED-STD-191, wherever applicable, and as listed in Table II shall be followed. All requirements are applicable to sample units. When the data as to number of determinations per sample unit and the results reported are not as specified in Table II, they shall be as required by the reference test method.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T06:32Z
Check the source to verify that this is the current version before use.

TABLE II. Test methods.

Components	Characteristics	Reqmt. para	Test method	No. det. per sample unit	Results reported as
Elastic webbing	Width	3.3.3	Visual	1	Pass or fail
	Weight/linear yard	3.3.3	5041 1/	5	Avg. of 5 det. to the nearest 0.01 oz.
	Total warp	3.3.3	Visual	1	Pass or fail
	Elastic strands	3.3.3	Visual	1	Pass or fail
	Pick per inch	3.3.3	Visual	1	Pass or fail
	Weave	3.3.3	Visual	1	Pass or fail
	Material identification	3.3.3			
Buckle and slide	Material identification	3.3.5			
	Plating identification	3.3.5			

1/ Except that a full width specimen 4 inches in length shall be used.

4.4.1.1. Sampling for testing. Unless otherwise specified in subsidiary specifications, sampling shall be in accordance with ANSI/ASQC Z1.4. The unit for expressing lot size and sample unit for testing each component shall be in accordance with the applicable subsidiary specification and as follows:

Component	Expressed as	Sample unit for testing
Elastic webbing	yard	two continuous yards
Buckle	buckle and slide (each)	one buckle and one slide

4.4.1.2. In-process inspection. Inspections shall be performed during the manufacturing of the end item to ascertain that the operations are performed as specified herein. The Government reserves the right to determine the acceptability of construction methods not performed in accordance with specified requirements for operations and subassemblies.

4.4.2 Examination of the end item. The end item shall be examined for defects listed in 4.4.2.1 through 4.4.2.3. The sample unit for the examination shall be one cummerbund.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T06:32Z
Check the source to verify that this is the current version before use.

4.4.2.1. General defects. General defects shall be classified as follows:

Examine	Defects	Classification		
		Major	Minor A	Minor B
Material defects and damages	a. Any hole.	101		
	b. Any weakening defect such as a smash, multiple float, or loose slub.	102		
	c. Shade bar or unsightly slub: - on outside.	103		
	- on inside.			301
	d. Needle chew, cut, tear or mend.	104		
NOTE: Material defects and workmanship damages are to be classified as indicated above only when the condition is one which weakens the fabric or garment or when it is so conspicuously located as to be clearly noticeable. Non-weakening conditions which are inconspicuous shall not be classified as defects.				
Shaded parts	a. Rayon satin badly shaded.	105		
Cleanness	a. Basting thread not removed.		201	
	b. Two or more shade tickets.			302
	c. Any spot or stain clearly noticeable: - on outside of cummerbund.	106		
	- on inside of cummerbund.			303
	d. Thread end or loose threads not removed throughout.			304
Component and assembly	a. Any part or required operation omitted (unless otherwise classified herein).	107		
	b. Any component not as specified.	108		
Cutting	a. Any component part not cut in accordance with specification requirements.	109		
Pressing	a. Burned or scorched.	110		
Pressing (cont'd)	b. Omitted over entire cummerbund.		202	

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T06:32Z
Check the source to verify that this is the current version before use.

Examine	Defects	Classification		
		Major	Minor A	Minor B
	c. Poorly pressed.			305
Seams and stitching	a. Accuracy of seaming.			
	1. Seams twisted, puckered or pleated (unless otherwise classified herein).			306
	2. Part of material caught in unrelated operation or stitching:			
	- up to a distance of 1/4 inch inclusive.		203	
	- for a distance greater than 1/4 inch.	111		
	3. End of stitching when not caught in other seams or stitching backtacked less than 1/4 inch.		204	
	4. Stitching overlapping the ends of thread break less than 1/2 inch.			307
	b. Gage of stitching.			
	1. Irregular, i.e., unevenly gaged or corresponding stitchings not uniform (to be scored only when the condition exists on major portion of seam).		205	
	2. Not within range of gage specified, or varies more than 1/16 inch when no range is specified.			308
	c. Stitches broken or missing in joining seams, edge stitching and top stitching:			
	- up to 1/4 inch inclusive.			309
	- more than 1/4 inch but not more than 1/2 inch.		206	
	- more than 1/2 inch.	112		
Seams and stitching (cont'd)	d. Skipped stitches:			
	- 1/4 inch to 1/2 inch long.			310
	- more than 1/2 inch.		207	

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T06:32Z
Check the source to verify that this is the current version before use.

Examine	Defects	Classification		
		Major	Minor A	Minor B
	e. Runoff:			
	- 1/4 inch to 1/2 inch long.			311
	- more than 1/2 inch long.		208	
	f. Raw edge:			
	- 1/8 inch up to 1/4 inch inclusive.			312
	- more than 1/4 inch up to 3/4 inch inclusive.		209	
	- more than 3/4 inch.	113		
	g. Seam type or stitch type not as specified.		210	
	h. Stitch tension.			
	1. Loose tension, resulting in a loose seam.	114		
	2. Loose tension on edge or raised stitching, resulting in loosely exposed bobbin or top thread.		211	
	3. Tight tension (stitches break when normal strain is applied to seam or stitching).	115		
NOTE: Puckering is evidence of tight tension. When puckering is evident, seam shall be tested by exerting pull in lengthwise direction of seam.				
	i. Stitches per inch - to be scored only if the condition exists on major portion (i.e., over one half or more) of seam.			
	1. Less than specified:			
	- one stitch.			313
	- two stitches.		212	
	- three or more stitches.	116		
	2. More than maximum specified.			314
Buckle and slide	a. Missing, broken, bent, cracked, or otherwise defective, affecting appearance or function.	117		

Source: https://assist.dla.mil -- Downloaded: 202610-19T06:32Z
Check the source to verify that this is the current version before use.

Examine	Defects	Classification		
		Major	Minor A	Minor B
	b. Type, size, color, or finish other than specified.	118		

4.4.2.2. Detailed defects. Detailed defects applicable to specific parts shall be classified as follows:

Examine	Defects	Classification		
		Major	Minor A	Minor B
Fronts	a. Pleats.			
	1. Outside folded edge of one or more pleats not toward top of finished cummerbund.	119		
	2. One or more pleats set on crookedly, affecting appearance.		213	
	3. One or more pleats uneven in width by 1/4 inch or more.	120		
	4. One or more pleats twisted, affecting appearance.		214	
	b. Interlining tight, short, or twisted, causing fullness or twist on front.	121		
Fitting of back lining	a. Back lining tight or short, causing fullness on outside of cummerbund.	122		
	b. Back lining exposed on outside for a distance of:			
	- more than 1 inch but not more than 2 inches.			315
	- more than 2 inches.		215	
Buckle strap assembly	a. Improperly threaded, i.e., the male half of the buckle placed on the left buckle strap and the female half of the buckle placed on the right buckle strap.		216	

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T06:32Z
Check the source to verify that this is the current version before use.

Examine	Defects	Classification		
		Major	Minor A	Minor B
	b. Improperly threaded, i.e., causing buckle to finish on reverse side or to function improperly.	123		

4.4.2.3. Finished measurements. Any measurement deviating from the nominal dimensions and tolerances specified in 3.7 and Figure 1 shall be classified as a size measurement defect.

5. PACKAGING

5.1. Packaging. For acquisition purposes, the packaging requirements shall be as specified in the contract or order (see 6.2). When actual packaging of material is to be performed by Department of Defense (DoD) personnel, these personnel need to contact the responsible packaging activity to ascertain requisite packaging requirements. Packaging requirements are maintained by the Inventory Control Point's packaging activity within the Military Department of Defense Agency, or within the Military Department's Systems Command. Packaging data retrieval is available from the managing Military Department's or Defense Agency's automated packaging files, CD-ROM products, or by contacting the responsible packaging activity.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1. Intended use. The cummerbund covered by this specification is intended to be worn by officers and those stewards on special assignment as authorized by the Commandant of the Marine Corps.

6.2. Acquisition requirements. Acquisition documents must specify the following:

a. Title, number, and date of the specification.
b. Issue of DoDISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T06:32Z
Check the source to verify that this is the current version before use.

c. Packaging requirements (see 5.1).
d. Whether first article is required (see 3.2).

6.3. Standard sample. For information regarding availability of standard samples of the cummerbund and of standard shades specified, address inquiry to the procuring activity issuing the invitation for bids (see 3.1).

6.4. Figures. Figures 1 through 3 are furnished for information purposes only. To the extent of any inconsistencies between the written specification and the figure, the written specification will govern.

6.5. Subject term (keyword) listing.

Dress
Enlisted
Steward

6.6. Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Preparing Activity:
Navy - MC
Project No. 8405-N317

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T06:32Z
Check the source to verify that this is the current version before use.




Figure 1. Cummerbund, Man's - Black

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T06:32Z
Check the source to verify that this is the current version before use.




Figure 2. Cummerbund, Man's - Black

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T06:32Z
Check the source to verify that this is the current version before use.




Figure 3. Cummerbund, Man's - Black

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T06:32Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.

2. The submitter of this form must complete blocks 4, 5, 6, and 7.

3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	**1. DOCUMENT NUMBER** MIL-DTL-19688D	**2. DOCUMENT DATE (YYMMDD)** 971016

3. DOCUMENT TITLE CUMMERBUND, MAN'S - BLACK

4. NATURE OF CHANGE *(Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)*

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME *(Last, First, Middle Initial)*	b. ORGANIZATION	
c. ADDRESS *(Include Zip Code)*	d. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON *(if applicable)*	**7.DATE SUBMITTED** (YYMMDD)

8. PREPARING ACTIVITY

a. NAME COMMANDER, MARCORSYSCOM, PSE-D	b. TELEPHONE *Include Area Code)* (1) Commercial (703) 784-4584 (2) AUTOVON 278-4584
c. ADDRESS *(Include Zip Code)* 2033 BARNETT AVE, SUITE 315, QUANTICO, VA 22134-5010	**IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT:** DEFENSE QUALITY AND STANDARDIZATION OFFICE 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22401-3466 Telephone (703) 756-2340 AUTOVON 289-2340

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T06:32Z
Check the source to verify that this is the current version before use.