MILITARY SPECIFICATION

LIGHT, MARKER, PORTABLE, EMERGENCY, AIRFIELD, BATTERY OPERATED, GENERAL SPECIFICATION FOR

This amendment forms a part of Military Specification MIL-L-19661A, dated 22 May 1962, and is mandatory for use by all Departments and Agencies of the Department of Defense.

Page 1

* 1.2, delete "Type I - Dry battery operated, precision optical system" and substitute the following:

"Type IA - Dry battery operated, precision optical system, sheet steel or aluminum case.

"Type IB - Dry battery operated, precision optical system, plastic case."

1.2, delete Type III A and Type III B.

Page 2

* 2.1, delete "MIL-T-9107" and substitute "MIL-STD-831".

* 2.1, delete "MIL-D-70327" and substitute "MIL-D-1000".

2.1, add: "MS 24655 Switches, Toggle-Miniature, Single Pole, One Hole Mounting, Type 1."

* 2.1: Under "Drawings" delete 13207E8810, 13207E8820, and 13207E8840.

FSC 6230

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T06:30Z
Check the source to verify that this is the current version before use.

Page 3

* 3.5.1, Line 1: After "types of lights" add "except Type IB".

* 3.5.1: After first sentence add:"Type IB cases shall be constructed of a suitable plastic".

* 3.5.1, Line 8: Delete "watertight" and substitute "raintight".

* 3.5.1: Delete last sentence.

Page 4

* Delete Table I and substitute the following new Table I.

Page 5

3.5.3, delete and substitute the following:

"3.5.3 Operating life - The operating life of the marker light assembly shall meet the requirements of Table I without a battery or lamp change when tested as specified in 4.5.4. The operating life shall be considered as the period from the time the light is switched on to the time it stops flashing or the cell voltage drops to 1.0 volt, whichever occurs first."

* 3.5.6.2, delete in its entirety.

Page 6

Figure 1: Lower upper candlepower requirement from 10 to 7.5 and change caption to read, "Figure 1. Light Distribution, Type I and Type II Light".

Page 7

Figure 2: Delete Figure 2 completely.

Page 9

* 3.7, Lines 7 and 8: Delete "Specification MIL-D-70327" and substitute "MIL-D-1000".

* 3.8, Line 1: Add "metal" before "case".

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T06:30Z
Check the source to verify that this is the current version before use.

TABLE I. Major components and characteristics of marker lights

Components	Type IA	Type IB	Type II	Type IV
Batteries	Dry battery - BA - 200/U 4 batteries	Dry Battery - BA - 200/U 4 batteries	Mercury battery BA - 1030/U 4 batt	Dry battery, 1 or more
Flasher	Built-in unit (max) - 130 flashes/minute (min) - 60 flashes/minute			Built-in unit 60 ± 10 flashes/minute
Switch	MS 24655-211 Labeled ON, OFF, and FLASH			2-position. Labeled ON and OFF
Lamp	2 GE PR-12, 1 for spare	2 GE PR-12, 1 for spare	2 GE PR-13, 1 for spare	Optional
Lens	Clear Fresnel lens, class D of MIL-C-7989			Red Fresnel lens class D of MIL-C-7989 and aviation red of MIL-C-25050 1/
Color filters	4 aviation colors - type I grade B, of MIL-C-25050			None
Hood	To restrict light: (horiz.) (15 to 30 degrees) (vert.) (15 to 30 degrees)			None
Socket	Single contact miniature flanged			Single contact, prefocus
Drawing lists	. . .	. . .	. . .	. . .
Weight (max)	4 1/2 pounds	4 1/2 pounds	Hold to minimum	(+batteries) 18 pounds
Dimensions (max. size)	9 by 7 1/2 by 6 in. approx. 400 cu. in.	9 by 7 1/2 by 6 5/8 approx. 420 cu. in.	Hold to minimum	1,000 cubic inches
Operating life (min)	75 hours flashing	75 hours flashing	50 hours flashing	250 hours flashing

1/ The transmittance of the lens need not be specified as the intensity of the light with colored lens specified

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T06:30Z
Check the source to verify that this is the current version before use.

Page 9 (Continued)

4.3.1 and 4.3.1.1, delete and substitute the following:

"4.3.1 Preproduction inspection sample - Preproduction inspection shall be made on marker lights representative of the production lights to be supplied under contract. The government inspector and procuring agency shall be advised when the inspections are to be conducted so that a representative may be designated to witness or supervise the inspections when so desired. Contractors not having adequate facilities to conduct all required inspections shall obtain the services of a commercial testing laboratory acceptable to the procuring activity."

Page 10

4.3.3, Line 4: Delete "Specification MIL-T-9107" and substitute "MIL-STD-831".

4.5.4, delete and substitute the following:

"4.5.4 Operating life - With a new set of batteries conforming to MIL-B-18 installed, the light shall be operated at room temperature in the flash position to determine compliance with 3.5.3."

Changes from previous issue. The outside margins of this document have been marked "*" to indicate where changes (deletions, additions, etc.) from the previous issue have been made. This has been done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders are cautioned to evaluate the requirements of this document based on the entire content as written irrespective of the marginal notations and relationship to the last previous issue.

Custodians:
Army - ME
Navy - AS
Air Force - 82

Preparing activity:
Navy - AS
(Project No. 6230-0144)

Review activities:
Army - ME
Navy - AS
Air Force - 82

Review and User information is current as of the date of this document. For future coordination of changes to this document, draft circulation should be based on the information in the current Federal Supply Classification Listing of DOD Documents.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T06:30Z
Check the source to verify that this is the current version before use.