DOD-STD-35-78A(MI)
3 AUGUST 1978
SUPERSEDING
MIL-STD-35-78(MI)
17 MARCH 1975

MILITARY STANDARD

ADHESIVES

AUTOMATED ENGINEERING DOCUMENT PREPARATION SYSTEM

FSC EDS

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

DEPARTMENT OF THE ARMY
U.S. ARMY MATERIEL
DEVELOPMENT AND READINESS COMMAND
ALEXANDRIA, VA 22333

Adhesives
Automated Engineering
Document Preparation System

DOD-STD-35-78A(MI)

1. This Military Standard is approved for use by DARCOM, Department of the Army and is available for use by all Departments and Agencies of the Department of Defense.

2. Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to Commander, U.S. Army Missile Research and Development Command, ATTN: DRDMI-ESD, Redstone Arsenal, Alabama 35809, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

FOREWORD

1. The purpose of DOD-STD-35-78A(MI) is to provide instructions for the preparation of Specification Requirements Sheets (SRS) in order to produce Military Specification Exceptions for Adhesives.

2. In order to properly utilize this document, it is necessary to have a complete and thorough understanding of the DOD-STD-35.

3. It is important that the procedures described in the basic document (DOD-STD-35D and subsequent revisions) be followed explicitly in order to produce a document suitable for procurement. Information which is standard for all dash-numbered parts has been included in the basic document at the issuance of DOD-STD-35D. This information is not repeated in each dash-numbered part.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

CONTENTS

			Page
Paragraph	1.	SCOPE	1
	1.1	General	1
	1.2	Purpose	1
	1.3	Utilization	1
	1.4	Military Specification Exception Title Index	1
	2.	REFERENCED DOCUMENTS	5
	2.1	Issues of documents	5
	2.2	Other publications	8
	3.	DEFINITIONS	11
	4.	GENERAL REQUIREMENTS	13
	4.1	Introduction	13
	4.2	Specification Requirement Sheet (SRS)	13
	4.3	Units of measure	13
	5.	DETAILED REQUIREMENTS	15
	5.1	Introduction	15
	5.2	MSE Formats	15
	5.3	Referenced documents	15
	5.4	Test matrix	15
	5.5	Tabulation	18
	5.6	Keyword Code Index (KCI) and Standard Paragraphs	19
	5.6.1	Interrelationship of Codes	19
	5.6.2	Automatic MSE Data	19
	5.6.3	DOD-STD-35 Tables	19

TABLES

Table	I.	Title Index	2
	II.	Test matrix	16
	III.	Tabulation candidates	18

APPENDIX

Appendix	A	Characteristic Code Index	119
		Index	125

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

1. SCOPE

1.1 General. This dash-numbered part of the Automated Engineering Document Preparation System (AEDPS), provides detailed requirements for the preparation of Military Specification Exception (MSE) documentation for Adhesives.

1.2 Purpose. This military standard provides the necessary information to prepare a Specification Requirement Sheet (SRS) which will be used to generate an MSE by automated data processing.

1.3 Utilization. General instructions, quality assurance provisions, packaging, and notes, applicable to all AEDPS dash-numbered parts have been included in the basic document (DOD-STD-35) to avoid redundancy. Unless otherwise specified in this dash-numbered part, the following list contains additional subjects that are applicable to all AEDPS dash-numbered parts and are included in DOD-STD-35:

a. Writing Methodology
b. Document and Part Numbering
c. Applicable Documents
d. Single and Multi-item Specifications (Tabulation)
e. Keyword Code Index (KCI)
f. General Requirements of AEDPS

1.4 Military Specification Exception Title Index. The title code for an MSE shall be selected from one of the MSE titles listed in the Title Index (see table I). Data bases have been established for the generation of MSE's for the MSE titles indicated. If a suitable title code is not contained in the Title Index, leave the title code spaces on the SRS blank, and attach a request for the assignment of a title code. Include in the request the desired title and the base document identifier. A code will be assigned and the code, title, and base document will be made a part of the Title Index.

One of the six-digit codes listed in the Title Index, entered on an SRS, will specify that the title of the MSE will be the title shown in the Title Index.

Each MSE title listed in the Title Index is compatible with the document(s) listed with that title under base document. The list of base documents may or may not be a complete listing. The information shown under coverage is intended for the user's reference; when more than one document is listed for an MSE title, this information will be found useful in determining which of the documents is most suitable for use as the base document.

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:24Z
Check the source to verify that this is the current version before use.

The MSE title may or may not be the same as the title used in DODISS, FIIG, or the base document. In general, the MSE title uses the basic federal item name listed in Cataloging Handbook H6. However, titles with additional modifying and identifying words are provided to assist in defining the scope of the MSE. Also, less restrictive titles are provided to prevent exclusion of items.

TABLE I. TITLE INDEX.

MSE TITLE	TITLE CODE	BASE DOCUMENT NUMBER	BASE DOCUMENT COVERAGE
ADHESIVE, AMMUNITION	601016	MMM-A-132	HEAT RESIST
		MMM-A-134	EPOXY
		MIL-A-3167	PLASTIC
		MIL-A-13374	DEXTRIN
		MIL-A-22397	MARINE
		MIL-A-22895	METAL
		MIL-A-23940	SILICONE RUBBER
		MIL-A-45059	CHIPBOARD TO TERNEPLATE
		MIL-A-50926	MR-23
		MIL-A-60091	DEMOLITION
		MIL-A-82484	SEALINE CMPD
ADHESIVE, GENERAL PURPOSE	601019	MMM-A-100	GLUE
		MMM-A-110	ASPHALT
		MMM-A-115	ASPHALT
		MMM-A-121	SYNTHETIC
		MMM-A-122	BUTADIENE
		MMM-A-125	CASEIN TYPE
		MMM-A-131	GLASS TO METAL
		MMM-A-137	LINOLEUM
		MMM-A-180	POLYVINYL ACTT
		MMM-A-181	PHENOL
		MMM-A-182	RUBBER
		MMM-A-187	SYNTHETIC
		MMM-A-188	UREA-RESIN
		MMM-A-189	SYNTHETIC
		MMM-A-193	VINYL
		MMM-A-1058	RUBBER BASE
		MMM-A-1934	EPOXY, FILLED
		MIL-A-3316	FIRE RESISTANT
		MIL-A-3469	BALSAM
		MIL-A-3920	OPTICAL
		MIL-A-14042	EPOXY
		MIL-A-22010	SOLVENT TYPE
		MIL-A-22434	POLYESTER
		MIL-A-23092	CEMENT

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:24Z
Check the source to verify that this is the current version before use.

TABLE I. TITLE INDEX. (CONT)

MSE TITLE	TITLE CODE	BASE DOCUMENT NUMBER	BASE DOCUMENT COVERAGE
ADHESIVE, GENERAL PURPOSE	601019 (CONT)	MIL-A-23941	EPOXY
		MIL-A-24179	FLEXIBLE
		MIL-A-25457	SILICONE RUBBER
		MIL-A-46050	CYANOACRYLATE, RAPID ROOM
		MIL-A-46091	BRAKE LINING
		MIL-A-46864	EPOXY
		MIL-A-46869	TEMP. CURING
		MIL-A-47074	METAL BONDING
		MIL-A-47089	METAL FILLED
		MIL-A-47126	EPOXY
		MIL-A-47284	RESIN
		MIL-A-81236	EPOXY
		MIL-A-81253	EPOXY
		MIL-A-81270	SYNTH RUBBER
		MIL-A-82569	NEOPRENE
ADHESIVE, PACKAGING AND PACKING	601002	MMM-A-178	PAPER LABEL
		MMM-A-179	EMULSION
		MMM-A-250	FIBERBOARD BOXES
		MMM-A-260	SEALING WATER PROOFED PAPER
		MIL-G-413	GLUE
		MIL-A-17682	STARCH
		MIL-A-47282	HEAT PASTE
		MIL-A-47283	ELEV. TEMP.
ADHESIVE, PLASTIC	601008	MMM-A-130	CONTACT
		MIL-A-8576	ACRY. PASTE
		MIL-A-14064	GRIND DISK CEM.
		MIL-A-18065	HI INITIAL BOND
		MIL-A-21016	POLYVINYL
		MIL-A-21366	TABLE TOP
		MIL-A-24456	VIBRATION
		MIL-A-47073	PLASTIC RESIN
		MIL-A-52194	BONDING GLASS
ADHESIVE, SEALING	601018	MMM-A-105	CELLULOSE BASE
		MMM-A-139	SYNTHETIC
		MIL-C-2399	PATCHING

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

TABLE I. TITLE INDEX. (CONT)

MSE TITLE	TITLE CODE	BASE DOCUMENT NUMBER	BASE DOCUMENT COVERAGE
ADHESIVE, SEALING	601018 (CONT)	MIL-A-3562	FILTERS SEAL
		MIL-A-5540	POLYCHLOROPRENE
		MIL-A-9117	AROMATIC FUEL
		MIL-A-43316	PATCHING
		MIL-A-43346	PATCHING
		MIL-A-46106	ELECT. AND MECH.
		MIL-A-46146	SILICONE, RTV
		MIL-A-47040	SILICONE, RTV HI TEMP.
		MIL-A-52685	BONDING
ADHESIVE, STRUCTURAL	601022	MMM-A-138	METAL TO WOOD
		MIL-A-25463	SANDWICH CONST.
CEMENT, CONDUCTIVE, ROOM TEMPERATURE CURING TWO COMPONENT	601023	MIL-A-47089	METAL FILLED

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

2. REFERENCED DOCUMENTS

2.1 Issues of documents. The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this standard to the extent specified herein.

SPECIFICATIONS

FEDERAL

MMM-A-100	Adhesive, Animal Glue
MMM-A-105	Adhesive and Sealing Compounds Cellulose Nitrate Base, Solvent Type
MMM-A-121	Adhesive, Bonding Vulcanized Synthetic Rubber to Steel
MMM-A-122	Adhesive, Butadiene Acrylonitrile Base, Medium Solids, General Purpose
MMM-A-131	Adhesive: Glass-to-Metal (for Bonding of Optical Elements)
MMM-A-134	Adhesive, Epoxy Resin, Metal to Metal Structural Bonding
MMM-A-137	Adhesive, Linoleum
MMM-A-138	Adhesive, Metal to Wood, Structural
MMM-A-139	Adhesive, Natural or Synthetic-Natural Rubber
MMM-A-177	Adhesive, Paste, Office and Photomounting
MMM-A-178	Adhesive, Paper Label, Water-Resistant
MMM-A-179	Adhesive: Paper Label, Water-Resistant, Water Emulsion Type
MMM-A-180	Adhesive, Polyvinyl Acetate Resin Emulsion (alkali Dispersable)
MMM-A-181	Adhesive, Phenol, Resorcinol, or Melamine Base
MMM-A-182	Adhesive, Rubber

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

MMM-A-187	Adhesive, Epoxy Resin Base Low and Intermediate Strength, General Purpose
MMM-A-188	Adhesive; Urea-Resin-Type (Liquid and Powder)
MMM-A-250	Adhesive, Water-Resistant
MMM-A-260	Adhesive, Water-Resistant, (for Sealing Waterproofed Paper)
MMM-A-1617	Adhesive, Rubber Base, General Purpose
MMM-A-1754	Adhesive and Sealing Compound, Epoxy, Metal Filled
MMM-A-1931	Adhesive, Epoxy, Silver Filled, Conductive

MILITARY

MIL-A-3316	Adhesive, Fire-Resistant, Thermal Insulation
MIL-A-3920	Adhesive, Optical Thermosetting
MIL-A-14042	Adhesive, Epoxy
MIL-A-18065	Adhesive, High Initial Bond
MIL-A-21016	Adhesive, Resilient Deck Covering
MIL-A-23940	Adhesive, Silicone Rubber for Igniter Mark 265
MIL-A-23941	Adhesive, Epoxy Type, Two Part
MIL-A-25457	Adhesive, Air-Drying, Silicone Rubber
MIL-A-25463	Adhesive, Metallic Structural Sandwich Construction
MIL-A-43316	Adhesive, Patching for Chloroprene Coated or Chlorosulphonated Polyethylene Coated Fabrics
MIL-A-43346	Adhesive (for Field Repair of Tents, Vinyl Coated Fabric)
MIL-A-45059	Adhesive for Bonding Chipboard to Teyneplate, Tinplate, and Zincplate
MIL-A-46050	Adhesive, Cyanoacrylate, Rapid Room-Temperature Curing, Solventless

Source: https://assist.dla.mil -- Downloaded: 202640-26T07:24Z
Check the source to verify that this is the currentversion before use.

MIL-A-46106	Adhesive-Sealants, Silicone, RTV, General-Purpose
MIL-A-46146	Adhesive-Sealants, Silicone, RTV, Non-Corrosive
MIL-A-46864	Adhesive, Epoxy, Modified, Flexible, Two Component
MIL-A-47040	Adhesive-Sealant, Silicone, RTV, High Temperature
MIL-A-47074	Adhesive System, Epoxy, For Dissimilar Metal Bonding
MIL-A-47089	Adhesive, Metal Filled, Conductive, Electrical and Thermal
MIL-A-47126	Adhesive (Viscous), Epoxy Resin, Metal to Metal Bonding and Sealing
MIL-A-47172	Adhesive, Modified Epoxy
MIL-A-47280	Adhesive, Epoxy
MIL-A-47282	Adhesive, Paste, Heat Resistant
MIL-A-47284	Adhesive, Epoxy Resin Base
MIL-A-47295	Adhesive Composition, HA-Polymer
MIL-A-50926	Adhesive MR-23
MIL-A-52194	Adhesive, Epoxy (for Bonding Glass Reinforced Polyester)
MIL-A-52685	Adhesive, Bonding, Celoroprene, Air Field Membrane Surfacing
MIL-A-82569	Adhesive, Neoprene Base, Medium Viscosity
MIL-A-82636	Adhesive, Butyl, Two-Component

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

STANDARDS

FEDERAL

FED-STD-141	Paint, Varnish, Lacquer, and Related Materials; Methods of Inspection, Sampling, and Testing
FED-STD-175	Adhesive, Methods of Testing

MILITARY

DOD-STD-35	Automated Engineering Document Preparation System
MIL-STD-810	Environmental Test Methods

(Copies of specifications, standards, drawing, and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this standard to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

ASTMD150	A-C Loss Characteristics and Dielectric Constant (Permittivity) of Solid Electrical Insulating Materials
ASTMD257	D-C Resistance or Conductance of Insulating Materials
ASTMD412	Tension Testing of Vulcanized Rubber
ASTMD568	Flammability of Flexible Plastics
ASTMD573	Accelerated Aging of Vulcanized Rubber by the Oven Method
ASTMD695	Compressive Properties of Rigid Plastics
ASTMD746	Brittleness Temperature of Plastics and Elastomers by Impact
ASTMD1062	Test for Cleavage Strength of Metal-to-Metal Adhesive Bonds

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:24Z
Check the source to verify that this is the current version before use.

ASTMD1583	Test for Hydrogen Ion Concentration of Dry Adhesive Films
ASTMD1875	Test for Density of Adhesives in Fluid Form (Tentative)
ASTMD2240	Indentation Hardness of Rubber and Plastics by Means of a Durometer
ASTMD2730	Sag Flow of Highly Viscous Materials, Test for
ASTME380	Metric Practice Guide

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race St., Philadelphia, Pa. 19103.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

3. DEFINITIONS

Definitions contained in DOD-STD-35 are applicable to Adhesives.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

4. GENERAL REQUIREMENTS

4.1 Introduction. In order to properly prepare an SRS for Adhesives, it is necessary to use DOD-STD-35 in conjunction with this dash-numbered part. In the event the instructions or the writing methodology are not followed, an AEDPS edit routine will print error messages rather than the desired MSE document.

4.2 Specification Requirement Sheet (SRS). SRS requirements described in DOD-STD-35 are applicable to Adhesives.

4.3 Units of measure. The International System of Units (SI) or inch-pound units (U.S.), may be used to specify characteristics (e.g. weight, dimensions). Refer to ASTME380 for guidance in using SI. However, when different units of measure are available for specifying a characteristic, only one may be used. Both units of measure cannot appear in the same MSE.

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:24Z
Check the source to verify that this is the current version before use.

5. DETAILED REQUIREMENTS

5.1 Introduction. This section provides instructions for completion of the SRS and references for instructions on specific requirements contained in DOD-STD-35.

5.2 MSE formats. AEDPS has the capability to prepare a six-section or a single-section document. The six-section document appears similar to a six-section military specification. The single-section document appears similar to a military specification sheet. Specification requirements described in DOD-STD-35 are applicable to either of the formats selected. It is mandatory that one of the two following codes and an "X" be entered on the SRS to create the desired MSE format:

a. 0700 for a six-section format

b. 0800 for a single-section format

5.3 Referenced documents. Section 2 of the MSE may contain a list of all referenced documents within Sections 3, 4, and 5 of the MSE. Instructions for referencing documents to appear in Section 2 of the forthcoming MSE are contained in DOD-STD-35.

5.4 Test matrix. A test matrix is supplied as a guide for selecting documents to specify tests (see table II). The test matrix presents documents most applicable for use to satisfy the statement "TEST PER (DOC DES)". Any document listed in the Title Index may be used to satisfy the statement. However, the selected document from the Title Index must contain the desired test. Government test method documents and approved industry standards such as ASTM test methods may also be used to satisfy the statement "TEST PER (DOC DES)".

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

TABLE II. TEST MATRIX.

DOCUMENT	TEST CODE	1964	2660	1668	1994	1690	2126	2220	2256	2284	2302	2901	2328	2374	2414	2530
		Test Specimen Preparation	Adhesion	Brushing Properties	Chemical Composition	Corrosion of Metal	Flammability	Hydrolytic Stability	Immersion	Peel Strength	Pot Life	Salt Spray	Tear Strength	Temperature, High	Temperature, Low	Viscosity
MMM-A-139				X					X							
MMM-A-250		X		X												
MMM-A-1617		X		X					X							
MIL-A-47040		X							X	X						
MMM-A-134		X										X		X	X	
MMM-A-100		X											X			X
MIL-A-82636		X	X	X												
MMM-A-179		X	X	X										X	X	
MIL-A-47295		X			X					X						
MIL-A-47074		X			X					X			X			
MIL-A-46864		X				X			X				X			
MIL-A-46050		X											X			
MIL-A-45059		X											X			
MMM-A-130		X											X			
MMM-A-182			X													
MMM-A-260			X						X						X	
MMM-A-137			X													
MMM-A-121			X													X
MIL-A-82484			X										X			X
MMM-A-177			X													
MMM-A-178			X				X									X
MMM-A-138		X											X			
MIL-A-43346					X								X			
MIL-A-46146						X		X		X						
MIL-A-23940						X					X					X
MMM-A-1913						X										
MIL-A-3316							X									

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

TABLE II. TEST MATRIX. (CONT)

DOCUMENT	CODE TEST	1964 Test Specimen Preparation	2660 Adhesion	1668 Brushing Properties	1994 Chemical Composition	1690 Corrosion of Metal	2126 Flammability	2220 Hydrolytic Stability	2256 Immersion	2284 Peel Strength	2302 Pot Life	2901 Salt Spray	2328 Tear Strength	2374 Temperature, High	2414 Temperature, Low	2530 Viscosity
MIL-A-46106								X		X						
MMM-A-122									X						X	X
MMM-A-180										X						X
MIL-A-82569										X						X
MIL-A-52685										X	X		X			
MMM-A-187											X		X			X
MIL-A-47282											X					
MIL-A-47172											X		X			
MIL-A-47126											X					
MIL-A-14042												X	X		X	
MIL-A-21016							X									X
MIL-A-25463												X			X	
MMM-A-181													X			
MMM-A-188													X			
MMM-A-1931													X			X
MIL-A-52194													X			
MIL-A-50926													X			
MIL-A-47284													X			
MIL-A-41089													X			
MIL-A-18065													X			
MIL-A-23941													X			
MIL-A-43316													X		X	
MMM-A-1754													X			
MIL-A-47280													X			
MIL-A-25457														X		
MMM-A-131																X

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

5.5 Tabulation. Instructions for tabulation are provided in DOD-STD-35. Table III provides codes for column headings which may be used for adhesives characteristics. When different units of measure within one system (U.S. or SI) are available for specifying a characteristic, only one of the units may be tabulated; e.g. either ounces or pounds.

TABLE III. TABULATION CANDIDATES.

CODE	COLUMN HEADING	CODE	COLUMN HEADING	CODE	COLUMN HEADING
1900	TYPE (DES)	1902	CLASS (DES)	1924	COLOR (NAME)
1906	SOLIDS CONTENT (PCT	1904	GRADE	1948	TACK FREE TIME (MIN)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

5.6 Keyword Code Index (KCI) and Standard Paragraphs. The KCI provides codes, to be entered on an SRS, that are unique for the type part covered by this dash-numbered part of DOD-STD-35. The left-hand page presents the information in outline form using keywords and codes. The right-hand page presents the words that will appear in the MSE. To find the code to be entered on the SRS, find the subject in the index at the back of this dash-numbered part. Find the keyword on the KCI and its associated code. Enter, on the SRS, the code and the characteristic value required. After the part unique characteristics have been specified, refer to DOD-STD-35 when exceptions are required to Quality Assurance, Packaging, Notes, etc. Instructions are in DOD-STD-35 on how to enter any type characteristic value. Appendix A, Characteristic Code Index, provides a numerical list of codes used in this dash-numbered part. This index identifies the location of codes by page number.

5.6.1 Interrelationship of codes. The interrelationship of the codes is shown by the indentation level of characteristic names on the KCI. The kind of characteristic value is shown by a colon, parentheses, period or underline. The paragraph, of which the code is a part, is shown by the standard paragraph adjacent to the code on a right-hand page. When a characteristic value entered with a code becomes part of the paragraph, the code is shown in the paragraph where the characteristic value will print. The MSE will contain the exact entry as supplied with the code, except for "X" entries.

5.6.2 Automatic MSE data. Some statements, such as Altitude and Temperature, will appear in the printed MSE without having to make additional entries. These statements are linked by data base logic to characteristic codes listed under them and will print when one of the codes listed is used. Other statements may print automatically depending on the type MSE selected. Explanations are noted on the KCI as required.

5.6.3 DOD-STD-35 Tables. The KCI of this document contains references to tables in Appendix A of DOD-STD-35. Most of the tables are in preprinted form and should be reproduced, applicable data entered, and attached to the SRS for submittal. Refer to DOD-STD-35 for a general explanation in the generation of tables.

Source: https://assist.dla.mil -- Downloaded: 2026l0-26T07:24Z
Check the source to verify that this is the currentversion before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
*REQUESTER'S NAME	0101
*COMPANY NAME/COMMAND	0102
*STREET/BUILDING	0103
*CITY, STATE, ZIP	0104
*PHONE NUMBER, INCLUDE AREA CODE, AUTOVON IF APPLICABLE	0105
*DATE	1003
*REQUESTER FSCM	1004
*CONTRACT NUMBER/OFFICE SYMBOL	1005
*BASE DOCUMENT	1006
*SYSTEM APPLICATION	1008
*GOVERNMENT DESIGN ACTIVITY FSCM	6369
*FORMAT (SELECT ONE)	
SIX SECTION DOCUMENT.	0700
ONE SECTION DOCUMENT.	0800
*CONTROL (SELECT ONE)	
SOURCE.	6873

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
0101	0101.
0102	0102.
0103	0103.
0104	0104.
0105	0105.
1003	1003.
1004	USER(S) FSCM(S) 1004.
1005	CONTRACT NUMBER OR OFFICE SYMBOL 1005.
1006	THE COMPLETE REQUIREMENTS FOR PROCURING THE ITEM(S) DESCRIBED HEREIN SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT(S), 1006, EXCEPT AS SPECIFIED IN THIS DOCUMENT. IN THE EVENT OF CONFLICT, THIS DOCUMENT SHALL GOVERN.
1008	SYSTEM APPLICATION 1008.
6369	GOVERNMENT DESIGN ACTIVITY FSCM 6369.
0700	
0800	
	SOURCE(S).
6873	THE FOLLOWING SOURCE(S) SHOWN WITH THE PART NUMBER(S) IS/ARE THE ONLY APPROVED SOURCE(S) FOR THE ITEM(S) DESCRIBED BY THIS DOCUMENT. IDENTIFICATION OF THE APPROVED SOURCE(S) HEREIN IS NOT TO BE CONSTRUED AS A GUARANTEE OF PRESENT OR CONTINUED AVAILABILITY AS A SOURCE OF SUPPLY FOR THE ITEM DESCRIBED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
CONTROL (CONT)	
SPECIFICATION.	6874
*SOURCE TABLE	
NOTE: REFER TO TABLE V OF DOD-STD-35.	
APERTURE CARDS REQUIRED.	0107
REVISION OF AEDPS DOCUMENT (NUMBER)	0108
SCOPE	
NOTE: THIS ENTRY IS AUTOMATIC AND DETERMINED BY THE TITLE CODE USED.	
PART NUMBER	
NOTE: AUTOMATIC WITH A SINGLE ITEM MSE.	
NOTE: AUTOMATIC WITH A MULTI-ITEM MSE.	
UNITS OF MEASURE (SELECT ONE)	
U.S.	6941
SI.	6942

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR
CODE STANDARD PARAGRAPH

6874 THE FOLLOWING SUGGESTED SOURCE(S) SHOWN WITH THEIR PART NUMBER(S) HAVE BEEN KNOWN TO MEET THE REQUIREMENT(S) OF THIS DOCUMENT. IDENTIFICATION OF THE 'SUGGESTED SOURCE(S) OF SUPPLY' HEREIN IS NOT TO BE CONSTRUED AS A GUARANTEE OF PRESENT OR CONTINUED AVAILABILITY AS A SOURCE OF SUPPLY FOR THE ITEM(S).

0107

0108 0108.

SCOPE.

SCOPE. THIS DOCUMENT COVERS THE DETAILED REQUIREMENTS FOR TITLE CODE.

PART NUMBER. THE PART NUMBER FOR THE ITEM IS SUPPLIED BY COMPUTER.

PART NUMBER. THE PART NUMBER FOR THE ITEMS IS THE SAME AS THE NUMBER OF THIS DOCUMENT PLUS THE SUFFIX NUMBER FROM THE TABULATED CHARACTERISTIC TABLE. REVISION AND ACTIVITY SYMBOLS ARE NOT INCLUDED IN THE PART NUMBER.

6941 UNIT OF MEASURE. ALL UNITS OF MEASURE ARE IN INCH-POUND UNITS (U.S.) OR DEGREES.

6942 UNIT OF MEASURE. ALL UNITS OF MEASURE ARE IN INTERNATIONAL SYSTEM OF UNITS (SI) OR DEGREES.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
TEMPERATURE RATING	
MAXIMUM STORAGE (DEGREES CELSIUS)	7302
MAXIMUM SERVICE (DEGREES CELSIUS)	4905
MINIMUM STORAGE (DEGREES CELSIUS)	7301
MINIMUM SERVICE (DEGREES CELSIUS)	4904
NOMINAL STORAGE (DEGREES CELSIUS)	5048
TYPE	
BASE DOCUMENT TYPE (DESIGNATION)	1900
GRADE	
BASE DOCUMENT GRADE (DESIGNATION)	1904
CLASS	
BASE DOCUMENT CLASS (DESIGNATION)	1902
SOLIDS CONTENT	
(PERCENT)	1906
TOLERANCE (PERCENT)	1908
SOLVENTS	
(NAME)	1910

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
	TEMPERATURE RATING.
7302	THE MAXIMUM STORAGE TEMPERATURE RATING SHALL BE 7302 DEGREES CELSIUS.
4905	THE MAXIMUM SERVICE TEMPERATURE RATING SHALL BE 4905 DEGREES CELSIUS.
7301	THE MINIMUM STORAGE TEMPERATURE RATING SHALL BE 7301 DEGREES CELSIUS.
4904	THE MINIMUM SERVICE TEMPERATURE RATING SHALL BE 4904 DEGREES CELSIUS.
5048	THE NOMINAL STORAGE TEMPERATURE RATING SHALL BE 5048 DEGREES CELSIUS.
1900	TYPE. THE TYPE DESIGNATION SHALL BE 1900 IN ACCORDANCE WITH THE BASE DOCUMENT.
1904	GRADE. THE GRADE DESIGNATION SHALL BE 1904 IN ACCORDANCE WITH THE BASE DOCUMENT.
1902	CLASS. THE CLASS DESIGNATION SHALL BE 1902 IN ACCORDANCE WITH THE BASE DOCUMENT.
1906	SOLIDS CONTENT. THE SOLIDS CONTENT SHALL BE 1906 PERCENT.
1908	THE SOLIDS CONTENT TOLERANCE SHALL BE PLUS OR MINUS 1908 PERCENT.
1910	SOLVENTS. THE SOLVENT(S) SHALL BE 1910.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME

SOLVENTS (CONT)

(NAME) (CONT)

(DOC DES)

BONDING RANGE

(MINUTES)

CONSISTENCY

(NAME)

APPEARANCE

THE MATERIAL SHALL HAVE UNIFORM HOMOGENEOUS TEXTURE.

COMPOSITION

COMPOSITION, FORMULATION OR MIXTURE.

*INGREDIENT TABLE, (SEE TABLE XI, DOD-STD-35)

WEIGHT

MINIMUM (SELECT ONE)

(POUNDS PER GALLON)

(KILOGRAMS PER CUBIC METER)

Source: https://assist.dla.mil -- Downloaded: 202640-26T07:24Z
Check the source to verify that this is the currentversion before use.

CHAR CODE	CHAR CODE	STANDARD PARAGRAPH
1912	1912	THE SOLVENT(S) SHALL BE IN ACCORDANCE WITH 1912.
1914	1914	BONDING RANGE. THE BONDING RANGE SHALL BE 1914 MINUTE(S).
1916	1916	CONSISTENCY. THE CONSISTENCY SHALL BE 1916.
1918	1918	APPEARANCE. THE COMPOUND SHALL BE FREE OF LUMPS, COARSE PARTICLES, AND AIR BUBBLES BEFORE MOLDING OR POTTING, AND AFTER CURING IT SHALL HAVE AN EVEN TEXTURE FREE OF LUMPS AND AIR BUBBLES.
6375	6375	COMPOSITION. THE COMPOSITION, FORMULATION OR MIXTURE (AS APPLICABLE) SHALL BE AS SPECIFIED HEREIN. THE INGREDIENT QUANTITIES SHALL BE SHOWN IN INTERNATIONAL (SI) SYSTEM OF UNITS SUCH AS GRAMS, LITRES, ETC., OR U.S. STANDARDS SUCH AS PINTS, QUARTS OR GALLONS, AS SPECIFIED IN THE TABLE.
		WEIGHT.
1583	1583	THE WEIGHT SHALL BE NOT LESS THAN 1583 POUND(S) PER GALLON.
2601	2601	THE WEIGHT SHALL BE NOT LESS THAN 2601 KILOGRAM(S) PER CUBIC METER.

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
WEIGHT (CONT)	
NOMINAL (SELECT ONE)	
(POUNDS PER GALLON)	1581
(KILOGRAMS PER CUBIC METER)	2602
MAXIMUM (SELECT ONE)	
(POUNDS PER GALLON)	1589
(KILOGRAMS PER CUBIC METER)	2604
CURING DURATION	
MAXIMUM (SELECT ONE)	
(MINUTES)	1568
(HOURS)	1570
(DAYS)	1572
BONDING PRESSURE	
MAXIMUM (SELECT ONE)	
(POUNDS PER SQUARE INCH)	1920
(KILOPASCALS)	1922
COLOR	
(NAME)	1924
(DOC DES)	1926

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
1581	THE WEIGHT SHALL BE 1581 POUND(S) PER GALLON.
2602	THE WEIGHT SHALL BE 2602 KILOGRAM(S) PER CUBIC METER.
1589	THE WEIGHT SHALL BE NOT GREATER THAN 1589 POUND(S) PER GALLON.
2604	THE WEIGHT SHALL BE NOT GREATER THAN 2604 KILOGRAM(S) PER CUBIC METER.
1568	CURING DURATION. THE CURING DURATION SHALL BE NOT GREATER THAN 1568 MINUTE(S).
1570	CURING DURATION. THE CURING DURATION SHALL BE NOT GREATER THAN 1570 HOUR(S).
1572	CURING DURATION. THE CURING DURATION SHALL BE NOT GREATER THAN 1572 DAY(S).
1920	BONDING PRESSURE. THE BONDING PRESSURE SHALL BE NOT GREATER THAN 1920 POUND(S) PER SQUARE INCH.
1922	BONDING PRESSURE. THE BONDING PRESSURE SHALL BE NOT GREATER THAN 1922 KILOPASCAL(S).
1924	COLOR. THE COLOR SHALL BE 1924.
1926	THE COLOR SHALL BE IN ACCORDANCE WITH 1926.

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME

COLOR (CONT)

(DOC DES) (CONT)

(DESIGNATION)

(CLASS NUMBER)

MATERIALS

FILLER

(NAME)

(DOC DES)

PROMOTER

(NAME)

(DOC DES)

PRIMER

(NAME)

(DOC DES)

ACTIVATOR

(NAME)

(DOC DES)

CATALYST

(NAME)

(DOC DES)

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	CHAR CODE	STANDARD PARAGRAPH
1928	1928	THE COLOR DESIGNATION 1928 SHALL APPLY.
1930	1930	THE COLOR CLASS NUMBER 1930 SHALL APPLY.
		MATERIALS.
2614	2614	THE FILLER SHALL BE 2614.
2615	2615	THE FILLER SHALL BE IN ACCORDANCE WITH 2615.
2616	2616	THE PROMOTER SHALL BE 2616.
2617	2617	THE PROMOTER SHALL BE IN ACCORDANCE WITH 2617.
2618	2618	THE PRIMER SHALL BE 2618.
2619	2619	THE PRIMER SHALL BE IN ACCORDANCE WITH 2619.
2606	2606	THE ACTIVATOR SHALL BE 2606.
2605	2605	THE ACTIVATOR SHALL BE IN ACCORDANCE WITH 2605.
2608	2608	THE CATALYST SHALL BE 2608.
2607	2607	THE CATALYST SHALL BE IN ACCORDANCE WITH 2607.

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
MATERIALS (CONT)	
INHIBITING AGENT	
(NAME)	2610
(DOC DES)	2611
CURING AGENT	
(NAME)	2612
(DOC DES)	2613
CURING PRESSURE (SELECT ONE)	
(POUNDS PER SQUARE INCH)	2800
(KILOPASCALS)	2802
CURING TEMPERATURE	
(DEGREES CELSIUS)	2804
TOLERANCE (DEGREES CELSIUS)	2806
SHRINKAGE (SELECT ONE)	
MAXIMUM	
(PERCENT)	2812
LINEAR	
(INCHES)	2814
(MILLIMETERS)	2816

Source: https://assist.dla.mil -- Downloaded: 202640-26T07:24Z
Check the source to verify that this is the currentversion before use.

CHAR CODE	STANDARD PARAGRAPH
2610	THE INHIBITING AGENT SHALL BE 2610.
2611	THE INHIBITING AGENT SHALL BE IN ACCORDANCE WITH 2611.
2612	THE CURING AGENT SHALL BE 2612.
2613	THE CURING AGENT SHALL BE IN ACCORDANCE WITH 2613.
2800	CURING PRESSURE. THE CURING PRESSURE SHALL BE 2800 POUNDS PER SQUARE INCH.
2802	CURING PRESSURE. THE CURING PRESSURE SHALL BE 2802 KILOPASCAL(S).
2804	CURING TEMPERATURE. THE CURING TEMPERATURE SHALL BE 2804 DEGREES CELSIUS.
2806	THE CURING TEMPERATURE TOLERANCE SHALL BE PLUS OR MINUS 2806 DEGREES CELSIUS.
	SHRINKAGE.
2812	THE SHRINKAGE SHALL BE NOT GREATER THAN 2812 PERCENT.
2814	THE LINEAR SHRINKAGE SHALL BE NOT GREATER THAN 2814 INCH(S).
2816	THE LINEAR SHRINKAGE SHALL BE NOT GREATER THAN 2816 MILLIMETER(S).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
TOXICITY	
TOXICITY OF MATERIAL SHALL NOT PRESENT HEALTH HAZARD.	1932
COMPATIBILITY WITH EXPLOSIVES	
THE ADHESIVE SHALL BE SAFE TO USE WITH EXPLOSIVES.	1604
MOISTURE CONTENT	
MAXIMUM (PERCENT)	1602
APPLICATION METHOD (SELECT ONE)	
BRUSH.	1606
SPRAY.	1608

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
1932	TOXICITY. THE TOXICITY OF MATERIAL SHALL NOT PRESENT A HEALTH HAZARD.
1604	COMPATIBILITY WITH EXPLOSIVES. THE ADHESIVE SHALL BE SAFE TO USE WITH EXPLOSIVES.
1602	MOISTURE CONTENT. THE MATERIAL MOISTURE CONTENT SHALL BE NOT GREATER THAN 1602 PERCENT.
1606	APPLICATION METHOD. THE INTENDED METHOD OF APPLICATION SHALL BE BY BRUSH.
1608	APPLICATION METHOD. THE INTENDED METHOD OF APPLICATION SHALL BE BY SPRAY.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME

APPLICATION METHOD (CONT)

BLADE.

ROLLER.

TROWEL.

EXTRUSION FROM TUBE.

FLOW.

TACK-FREE TIME (SELECT ONE)

(MINUTES)

TOLERANCE (SECONDS)

TEST SPECIMEN PREPARATION (SELECT ONE)

PER BASE DOCUMENT EXCEPT ____

AS FOLLOWS:

PER DOCUMENT (DOC DES)

SPECIMEN LENGTH (SELECT ONE)

(INCHES)

(MILLIMETERS)

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	CHAR CODE	STANDARD PARAGRAPH
1610	1610	APPLICATION METHOD. THE INTENDED METHOD OF APPLICATION SHALL BE BY BLADE.
1612	1612	APPLICATION METHOD. THE INTENDED METHOD OF APPLICATION SHALL BE BY ROLLER.
1944	1944	APPLICATION METHOD. THE INTENDED METHOD OF APPLICATION SHALL BE BY TROWEL.
1614	1614	APPLICATION METHOD. THE INTENDED METHOD OF APPLICATION SHALL BE BY EXTRUSION FROM TUBE.
1946	1946	APPLICATION METHOD. THE INTENDED METHOD OF APPLICATION SHALL BE BY FLOW.
1948	1948	TACK-FREE TIME. THE TACK-FREE TIME SHALL BE 1948 MINUTE(S).
1950	1950	THE TACK-FREE TIME TOLERANCE SHALL BE PLUS OR MINUS 1950 SECOND(S).
1962	1962	TEST SPECIMEN PREPARATION. TEST SPECIMEN PREPARATION SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1962.
1964	1964	TEST SPECIMEN PREPARATION. TEST SPECIMEN PREPARATION SHALL BE AS FOLLOWS:
1987	1987	TEST SPECIMEN PREPARATION SHALL BE IN ACCORDANCE WITH 1987.
1952	1952	THE SPECIMEN LENGTH SHALL BE 1952 INCH(S).
1954	1954	THE SPECIMEN LENGTH SHALL BE 1954 MILLIMETER(S).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
TEST SPECIMEN PREPARATION (CONT)	
AS FOLLOWS: (CONT)	
SPECIMEN THICKNESS (SELECT ONE)	
(INCHES)	1970
(MILLIMETERS)	1972
SPECIMEN WIDTH (SELECT ONE)	
(INCHES)	1956
(MILLIMETERS)	1958
SPECIMEN AREA (SELECT ONE)	
(SQUARE INCHES)	1966
(SQUARE MILLIMETERS)	1968
CURING TEMPERATURE (DEGREES CELSIUS)	1974
TEMPERATURE TOLERANCE PLUS OR MINUS (DEGREES CELSIUS)	1976
CURE DURATION	
MINIMUM (SELECT ONE)	
(MINUTES)	1982
(HOURS)	1984
CURE DURATION	
MAXIMUM (SELECT ONE)	
(MINUTES)	1983
(HOURS)	1985

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
1970	THE SPECIMEN THICKNESS SHALL BE 1970 INCH(S).
1972	THE SPECIMEN THICKNESS SHALL BE 1972 MILLIMETER(S).
1956	THE SPECIMEN WIDTH SHALL BE 1956 INCH(S).
1958	THE SPECIMEN WIDTH SHALL BE 1958 MILLIMETER(S).
1966	THE SPECIMEN AREA SHALL BE 1966 SQUARE INCH(S).
1968	THE SPECIMEN AREA SHALL BE 1968 SQUARE MILLIMETER(S)
1974	THE CURING TEMPERATURE SHALL BE 1974 DEGREES CELSIUS.
1976	THE CURING TEMPERATURE TOLERANCE SHALL BE PLUS OR MINUS 1976 DEGREES CELSIUS.
1982	THE CURE DURATION SHALL BE NOT LESS THAN 1982 MINUTE(S).
1984	THE CURE DURATION SHALL BE NOT LESS THAN 1984 HOUR(S).
1983	THE CURE DURATION SHALL BE NOT GREATER THAN 1983 MINUTE(S).
1985	THE CURE DURATION SHALL BE NOT GREATER THAN 1985 HOUR(S).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
TEST SPECIMEN PREPARATION (CONT)	
AS FOLLOWS: (CONT)	
SPECIMEN CONDITIONING TEMPERATURE (DEGREES CELSIUS)	1978
NUMBER OF SPECIMENS TO BE TESTED (QUANTITY)	1980
PREPARED IN ACCORDANCE WITH MANUFACTURER'S INSTRUCTIONS.	1981
ACCELERATED AGING	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	1633
AS FOLLOWS:	1734
MAXIMUM ALLOWABLE CHANGE IN THE MINIMUM ALLOWABLE TENSILE STRENGTH (PERCENT)	1636
MAXIMUM ALLOWABLE CHANGE IN THE MINIMUM ALLOWABLE SHEAR STRENGTH (PERCENT)	1638
MAXIMUM ALLOWABLE CHANGE IN THE MINIMUM ALLOWABLE PEEL STRENGTH (PERCENT)	1640
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	1618
PER ASTMD573.	1620

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:24Z
Check the source to verify that this is the currenversion before use.

CHAR CODE	STANDARD PARAGRAPH
1978	THE CONDITIONING TEMPERATURE SHALL BE 1978 DEGREES CELSIUS.
1980	THE NUMBER OF SPECIMENS TO BE TESTED SHALL BE 1980.
1981	THE SPECIMEN SHALL BE PREPARED IN ACCORDANCE WITH THE MANUFACTURER'S INSTRUCTIONS.
1633	ACCELERATED AGING. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1633.
1734	ACCELERATED AGING. THE REQUIREMENT(S) SHALL BE AS FOLLOWS:
1636	THE MINIMUM ALLOWABLE TENSILE STRENGTH SHALL NOT CHANGE BY GREATER THAN 1636 PERCENT.
1638	THE MINIMUM ALLOWABLE SHEAR STRENGTH SHALL NOT CHANGE BY GREATER THAN 1638 PERCENT.
1640	THE MINIMUM ALLOWABLE PEEL STRENGTH SHALL NOT CHANGE BY GREATER THAN 1640 PERCENT.
1618	ACCELERATED AGING. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1618.
1620	ACCELERATED AGING. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH ASTMD573.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
ACCELERATED AGING (CONT)	
PER ASTMD573. (CONT)	
TEST DURATION (SELECT ONE)	
(MINUTES)	1746
(HOURS)	1622
(DAYS)	1626
TEST TEMPERATURE (DEGREES CELSIUS)	1628
TOLERANCE PLUS OR MINUS (DEGREES CELSIUS)	1630
ADHESION	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	2650
AS FOLLOWS:	2652
NO FLAKING, CHIPPING, OR POWDERING.	2654
MAXIMUM COHESIVE FAILURE (PERCENT)	2656
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	2658
PER DOCUMENT (DOC DES)	2660
TEMPERATURE EXPOSURE (DEGREES CELSIUS)	2662
TOLERANCE PLUS OR MINUS (DEGREES CELSIUS)	2664

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
1746	THE DURATION OF THE TEST SHALL BE 1746 MINUTE(S).
1622	THE DURATION OF THE TEST SHALL BE 1622 HOURS.
1626	THE DURATION OF THE TEST SHALL BE 1626 DAYS.
1628	THE TEST TEMPERATURE SHALL BE 1628 DEGREES CELSIUS.
1630	THE TEST TEMPERATURE TOLERANCE SHALL BE PLUS OR MINUS 1630 DEGREES CELSIUS.
2650	ADHESION. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2650.
2652	ADHESION. THE REQUIREMENT(S) SHALL BE AS FOLLOWS:
2654	THERE SHALL BE NO FLAKING, CHIPPING, OR POWDERING.
2656	THE COHESIVE FAILURE SHALL BE NOT GREATER THAN 2656 PERCENT.
2658	ADHESION. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2658.
2660	ADHESION. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH 2660.
2662	THE TEMPERATURE EXPOSURE SHALL BE 2662 DEGREES CELSIUS.
2664	THE TEMPERATURE TOLERANCE SHALL BE PLUS OR MINUS 2664 DEGREES CELSIUS.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
ADHESION (CONT)	
TEMPERATURE EXPOSURE (CONT)	
RELATIVE HUMIDITY	
(PERCENT)	2666
TOLERANCE PLUS OR MINUS (PERCENT)	2668
DURATION	
(HOURS)	2670
ELEVATED TEMPERATURE EXPOSURE (DEGREES CELSIUS)	2672
TOLERANCE (DEGREES CELSIUS)	2674
RELATIVE HUMIDITY (PERCENT)	2676
TOLERANCE PLUS OR MINUS (PERCENT)	2678
DURATION	
(HOURS)	2680
ASH CONTENT	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	1657
AS FOLLOWS:	1758
MAXIMUM ASH CONTENT (PERCENT)	1660
MAXIMUM NONVOLATILE CONTENT (PERCENT)	1662

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
2666	THE RELATIVE HUMIDITY SHALL BE 2666 PERCENT.
2668	THE TOLERANCE SHALL BE PLUS OR MINUS 2668 PERCENT.
2670	THE DURATION SHALL BE 2670 HOUR(S).
2672	THE ELEVATED TEMPERATURE EXPOSURE SHALL BE 2672 DEGREES CELSIUS.
2674	THE TOLERANCE SHALL BE PLUS OR MINUS 2674 DEGREES CELSIUS.
2676	THE RELATIVE HUMIDITY SHALL BE 2676 PERCENT.
2678	THE TOLERANCE SHALL BE PLUS OR MINUS 2678 PERCENT.
2680	THE DURATION SHALL BE 2680 HOUR(S).
1657	ASH CONTENT. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1657.
1758	ASH CONTENT. THE REQUIREMENT(S) SHALL BE AS FOLLOWS:
1660	THE ASH CONTENT SHALL BE NOT GREATER THAN 1660 PERCENT.
1662	THE NONVOLATILE CONTENT SHALL BE NOT GREATER THAN 1662 PERCENT.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
ASH CONTENT (CONT)	
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	1644
PER FED-STD-175, METHOD 4032.	1766
TEST PROCEDURE (LETTER)	1648
TEST TEMPERATURE (DEGREES CELSIUS)	1650
TOLERANCE PLUS OR MINUS (DEGREES CELSIUS)	1652
TEST DURATION (HOURS)	1654
BRITTLE POINT	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	2682
MAXIMUM TEMPERATURE (DEGREES CELSIUS)	2684
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	2686
PER ASTMD746, METHOD B.	2688
CURED DURATION (HOURS)	2690
TOLERANCE PLUS OR MINUS (HOURS)	2692

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
1644	ASH CONTENT. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1644.
1766	ASH CONTENT. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH METHOD 4032 OF FED-STD-175.
1648	THE TEST PROCEDURE LETTER 1648 SHALL APPLY.
1650	THE TEST TEMPERATURE SHALL BE 1650 DEGREES CELSIUS.
1652	THE TEST TEMPERATURE TOLERANCE SHALL BE PLUS OR MINUS 1652 DEGREES CELSIUS.
1654	THE DURATION OF THE TEST SHALL BE 1654 HOUR(S).
2682	BRITTLE POINT. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2682.
2684	BRITTLE POINT. THE TEMPERATURE SHALL BE NOT GREATER THAN 2684 DEGREES CELSIUS.
2686	BRITTLE POINT. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2686.
2688	BRITTLE POINT. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH ASTMD746, METHOD B.
2690	THE CURE DURATION SHALL BE 2690 HOUR(S).
2692	THE TOLERANCE SHALL BE PLUS OR MINUS 2692 HOUR(S).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
BRITTLE POINT (CONT)	
PER ASTMD746, METHOD B (CONT)	
RELATIVE HUMIDITY (PERCENT)	2694
TOLERANCE PLUS OR MINUS (PERCENT)	2696
BRUSHING PROPERTIES	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	1680
AS FOLLOWS:	1802
MATERIAL SHALL BE READILY BRUSHABLE.	1801
MATERIAL SHALL FLOW EASILY, SPREAD EVENLY AND COVER SURFACE ADEQUATELY.	1803
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	1666
PER DOCUMENT (DOC DES)	1668
TEST SPECIMEN TEMPERATURE (DEGREES CELSIUS)	1670
TOLERANCE PLUS OR MINUS (DEGREES CELSIUS)	1672

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
2694	THE RELATIVE HUMIDITY SHALL BE 2694 PERCENT.
2696	THE TOLERANCE SHALL BE PLUS OR MINUS 2696 PERCENT.
1680	BRUSHING PROPERTIES. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1680.
1802	BRUSHING PROPERTIES. THE BRUSHING PROPERTIES SHALL BE AS FOLLOWS:
1801	THE MATERIAL SHALL BE READILY BRUSHABLE.
1803	THE MATERIAL SHALL FLOW EASILY, SPREAD EVENLY, AND COVER SURFACE ADEQUATELY.
1666	BRUSHING PROPERTIES. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1666.
1668	BRUSHING PROPERTIES. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH 1668.
1670	THE TEST SPECIMEN TEMPERATURE SHALL BE 1670 DEGREES CELSIUS.
1672	THE TEST SPECIMEN TEMPERATURE TOLERANCE SHALL BE PLUS OR MINUS 1672 DEGREES CELSIUS.

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
CHEMICAL COMPOSITION	
REQUIREMENTS	
PER BASE DOCUMENT EXCEPT ____	1986
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	1990
SUPPLIERS CERTIFICATION INSTEAD OF TEST.	1992
PER DOCUMENT (DOC DES)	1994
TEST METHOD (DES)	1996
CLEAVAGE STRENGTH	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	2722
AS FOLLOWS:	2723
MINIMUM CLEAVAGE STRENGTH (SELECT ONE)	
(POUNDS)	2724
(NEWTONS)	2726

Source: https://assist.dla.mil -- Downloaded: 202640-26T07:24Z
Check the source to verify that this is the currentversion before use.

CHAR CODE	STANDARD PARAGRAPH
1986	CHEMICAL COMPOSITION. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1986.
1990	CHEMICAL COMPOSITION. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1990.
1992	CHEMICAL COMPOSITION. SUPPLIERS CERTIFICATE OF COMPLIANCE WITH THE CHEMICAL COMPOSITION REQUIREMENT(S) MAY BE ACCEPTED IN LIEU OF A SPECIFIC TEST.
1994	CHEMICAL COMPOSITION. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH 1994.
1996	TEST METHOD 1996 SHALL APPLY.
2722	CLEAVAGE STRENGTH. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2722.
2723	CLEAVAGE STRENGTH. THE REQUIREMENT(S) SHALL BE AS FOLLOWS:
2724	THE CLEAVAGE STRENGTH SHALL BE NOT LESS THAN 2724 POUND(S).
2726	THE CLEAVAGE STRENGTH SHALL BE NOT LESS THAN 2726 NEWTON(S).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
CLEAVAGE STRENGTH (CONT)	
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	2728
PER ASTMD1062.	2730
COMPRESSIVE STRENGTH	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	2732
AS FOLLOWS:	2733
MINIMUM COMPRESSIVE STRENGTH (SELECT ONE)	
(PSI)	2734
(KILOPASCALS)	2736
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	2738
PER ASTMD695.	2740
CORROSION OF METALS	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	1694

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
2728	CLEAVAGE STRENGTH. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2728.
2730	CLEAVAGE STRENGTH. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH ASTMD1062.
2732	COMPRESSIVE STRENGTH. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2732.
2733	COMPRESSIVE STRENGTH. THE REQUIREMENT(S) SHALL BE AS FOLLOWS:
2734	THE COMPRESSIVE STRENGTH SHALL BE NOT LESS THAN 2734 POUNDS PER SQUARE INCH.
2736	THE COMPRESSIVE STRENGTH SHALL BE NOT LESS THAN 2736 KILOPASCAL(S).
2738	COMPRESSIVE STRENGTH. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2738.
2740	COMPRESSIVE STRENGTH. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH ASTMD695.
1694	CORROSION OF METALS. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1694.

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
CORROSION OF METALS (CONT)	
REQUIREMENTS (CONT)	
THE ADHESIVE SHALL NOT CAUSE DISCOLORATION OR CORROSION.	1696
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	1688
PER DOCUMENT (DOC DES)	1690
TEST METHODS	
BRASS OVER WATER.	1839
STEEL OVER WATER.	1841
ALUMINUM OVER WATER.	1843
COPPER WIRE BY DIRECT CONTACT.	1845
STEEL AND ALUMINUM BY DIRECT CONTACT.	1847
DENSITY	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	1706
PER ASTMD1875.	1842
AS FOLLOWS:	1844
DENSITY OF ADHESIVE (SELECT ONE)	
(POUNDS PER GALLON)	1846

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:24Z
Check the source to verify that this is the currentversion before use.

CHAR CODE	STANDARD PARAGRAPH
1696	CORROSION OF METALS. THE ADHESIVE SHALL NOT CAUSE DISCOLORATION OR CORROSION.
1688	CORROSION OF METALS. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1688.
1690	CORROSION OF METALS. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH 1690.
	TEST METHODS SHALL BE AS FOLLOWS:
1839	BRASS OVER WATER.
1841	STEEL OVER WATER.
1843	ALUMINUM OVER WATER.
1845	COPPER WIRE BY DIRECT CONTACT.
1847	STEEL AND ALUMINUM BY DIRECT CONTACT.
1706	DENSITY. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1706.
1842	DENSITY. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH ASTMD1875.
1844	DENSITY. THE REQUIREMENT(S) SHALL BE AS FOLLOWS:
1846	THE DENSITY OF THE MATERIAL SHALL BE 1846 POUNDS PER GALLON.

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
DENSITY (CONT)	
DENSITY OF ADHESIVE (CONT)	
(KILOGRAMS PER CUBIC METER)	1850
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	1700
PER ASTMD1875.	1702
DIELECTRIC CONSTANT	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	2000
AS FOLLOWS:	2002
MAXIMUM DIELECTRIC CONSTANT AT 60 HERTZ (VALUE)	2004
MAXIMUM DIELECTRIC CONSTANT AT 1 KILOHERTZ (VALUE)	2006
MAXIMUM DIELECTRIC CONSTANT AT 1 MEGAHERTZ (VALUE)	2008
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	2010
PER ASTMD568.	2012

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
1850	THE DENSITY OF THE MATERIAL SHALL BE 1850 KILOGRAM(S) PER CUBIC METER.
1700	DENSITY. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1700.
1702	DENSITY. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH ASTMD1875.
2000	DIELECTRIC CONSTANT. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2000.
2002	DIELECTRIC CONSTANT. THE REQUIREMENT(S) SHALL BE AS FOLLOWS:
2004	THE DIELECTRIC CONSTANT AT 60 HERTZ SHALL BE NOT GREATER THAN 2004.
2006	THE DIELECTRIC CONSTANT AT 1 KILOHERTZ SHALL BE NOT GREATER THAN 2006.
2008	THE DIELECTRIC CONSTANT AT 1 MEGAHERTZ SHALL BE NOT GREATER THAN 2008.
2010	DIELECTRIC CONSTANT. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2010.
2012	DIELECTRIC CONSTANT. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH ASTMD568.

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
DIELECTRIC STRENGTH	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	2032
AS FOLLOWS:	2034
MINIMUM DIELECTRIC STRENGTH (SELECT ONE)	
(VOLTS PER 0.001 INCH)	2036
(VOLTS PER MILLIMETER)	2038
MINIMUM BREAKDOWN VOLTAGE (VOLTS)	2040
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	2042
PER ASTMD568.	2044
NUMBER OF SPECIMENS TO BE TESTED (QUANTITY)	2046
TEST TEMPERATURE (DEGREES CELSIUS)	2048
TOLERANCE PLUS OR MINUS (DEGREES CELSIUS)	2050
DISSIPATION FACTOR	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	2052

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
2032	DIELECTRIC STRENGTH. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2032.
2034	DIELECTRIC STRENGTH. THE REQUIREMENT(S) SHALL BE AS FOLLOWS:
2036	THE DIELECTRIC STRENGTH SHALL BE NOT LESS THAN 2036. VOLTS PER 0.001 INCH.
2038	THE DIELECTRIC STRENGTH SHALL BE NOT LESS THAN 2038 VOLTS PER MILLIMETER.
2040	THE BREAKDOWN VOLTAGE SHALL BE NOT LESS THAN 2040 VOLT(S).
2042	DIELECTRIC STRENGTH. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2042.
2044	DIELECTRIC STRENGTH. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH ASTMD568.
2046	THERE SHALL BE 2046 SPECIMEN(S) TESTED.
2048	THE TEST TEMPERATURE SHALL BE 2048 DEGREES CELSIUS.
2050	THE TEST TEMPERATURE TOLERANCE SHALL BE PLUS OR MINUS 2050 DEGREES CELSIUS.
2052	DISSIPATION FACTOR. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2052.

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
DISSIPATION FACTOR (CONT)	
REQUIREMENTS (CONT)	
AS FOLLOWS:	2054
MINIMUM DISSIPATION FACTOR AT 60 HERTZ (VALUE)	2056
MINIMUM DISSIPATION FACTOR AT 1 KILOHERTZ (VALUE)	2055
MINIMUM DISSIPATION FACTOR AT 1 MEGAHERTZ (VALUE)	2060
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	2062
PER ASTMD150.	2064
NUMBER OF SPECIMENS TO BE TESTED (QUANTITY)	2066
SPECIMEN WIDTH (SELECT ONE)	
(INCHES)	2068
(MILLIMETERS)	2070
SPECIMEN THICKNESS (SELECT ONE)	
(INCHES)	2072
(MILLIMETERS)	2074

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
2054	DISSIPATION FACTOR. THE REQUIREMENT(S) SHALL BE AS FOLLOWS:
2056	THE DISSIPATION FACTOR AT 60 HERTZ SHALL BE NOT LESS THAN 2056.
2055	THE DISSIPATION FACTOR AT 1 KILOHERTZ SHALL BE NOT LESS THAN 2055.
2060	THE DISSIPATION FACTOR AT 1 MEGAHERTZ SHALL BE NOT LESS THAN 2060.
2062	DISSIPATION FACTOR. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2062.
2064	DISSIPATION FACTOR. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH ASTMD150.
2066	THERE SHALL BE 2066 SPECIMEN(S) TESTED.
2068	THE TEST SPECIMEN SHALL BE 2068 INCH(S) IN WIDTH.
2070	THE TEST SPECIMEN SHALL BE 2070 MILLIMETER(S) IN WIDTH.
2072	THE TEST SPECIMEN SHALL BE 2072 INCH(S) IN THICKNESS.
2074	THE TEST SPECIMEN SHALL BE 2074 MILLIMETER(S) IN THICKNESS.

Source: https://assist.dla.mil -- Downloaded: 202640-26T07:24Z
Check the source to verify that this is the currentversion before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
DISSIPATION FACTOR (CONT)	
PER ASTMD150. (CONT)	
SPECIMEN LENGTH (SELECT ONE)	
(INCHES)	2076
(MILLIMETERS)	2078
SPECIMEN DIAMETER (SELECT ONE)	
(INCHES)	2080
(MILLIMETERS)	2082
ELONGATION	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	2084
MINIMUM ELONGATION (PERCENT)	2086
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	2088
PER ASTMD412.	2090
FLAMMABILITY	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	2112
AS FOLLOWS:	2114

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
2076	THE TEST SPECIMEN SHALL BE 2076 INCH(S) IN LENGTH.
2078	THE TEST SPECIMEN SHALL BE 2078 MILLIMETER(S) IN LENGTH.
2080	THE TEST SPECIMEN SHALL BE 2080 INCH(S) IN DIAMETER.
2082	THE TEST SPECIMEN SHALL BE 2082 MILLIMETER(S) IN DIAMETER.
2084	ELONGATION. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2084.
2086	ELONGATION. THE ELONGATION SHALL BE NOT LESS THAN 2086 PERCENT.
2088	ELONGATION. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2088.
2090	ELONGATION. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH ASTMD412.
2112	FLAMMABILITY. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2112.
2114	FLAMMABILITY. THE REQUIREMENT(S) SHALL BE AS FOLLOWS:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
FLAMMABILITY (CONT)	
AS FOLLOWS: (CONT)	
MAXIMUM BURN DISTANCE	
(INCHES)	2116
(MILLIMETERS)	2118
MAXIMUM BURN PERIOD (SECONDS)	2120
MINIMUM FLASH POINT TEMPERATURE (DEGREES CELSIUS)	2122
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	2124
PER DOCUMENT (DOC DES)	2126
TEST METHOD (DESIGNATION)	2128
SPECIMEN WIDTH (SELECT ONE)	
(INCHES)	2130
(MILLIMETERS)	2132
SPECIMEN THICKNESS (SELECT ONE)	
(INCHES)	2134
(MILLIMETERS)	2136
SPECIMEN LENGTH (SELECT ONE)	
(INCHES)	2138
(MILLIMETERS)	2140

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
2116	THE BURNING DISTANCE SHALL BE NOT GREATER THAN 2116 INCH(S).
2118	THE BURNING DISTANCE SHALL BE NOT GREATER THAN 2118 MILLIMETER(S).
2120	THE BURNING PERIOD SHALL BE NOT GREATER THAN 2120 SECOND(S).
2122	THE FLASH POINT SHALL BE NOT LESS THAN 2122 DEGREES CELSIUS.
2124	FLAMMABILITY. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2124.
2126	FLAMMABILITY. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH 2126.
2128	TEST METHOD 2128 SHALL APPLY.
2130	THE TEST SPECIMEN SHALL BE 2130 INCH(S) IN WIDTH.
2132	THE TEST SPECIMEN SHALL BE 2132 MILLIMETER(S) IN WIDTH.
2134	THE TEST SPECIMEN SHALL BE 2134 INCH(S) IN THICKNESS.
2136	THE TEST SPECIMEN SHALL BE 2136 MILLIMETER(S) IN THICKNESS.
2138	THE TEST SPECIMEN SHALL BE 2138 INCH(S) IN LENGTH.
2140	THE TEST SPECIMEN SHALL BE 2140 MILLIMETER(S) IN LENGTH.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
FLAMMABILITY (CONT)	
PER DOCUMENT (CONT)	
SPECIMEN DIAMETER (SELECT ONE)	
(INCHES)	2142
(MILLIMETERS)	2144
NUMBER OF SPECIMENS TO BE TESTED (QUANTITY)	2146
SPECIMEN WEIGHT (SELECT ONE)	
(GRAMS)	2148
(OUNCES)	2150
TIMES FLAME APPLIED (QUANTITY)	2152
FLAME APPLICATION PERIOD (SECONDS)	2154
FLEXIBILITY	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	2706
THERE SHALL BE NO CRACKING OR FLAKING.	2708
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	2710
PER FED-STD-141, METHOD 6222.	2712
CURING DURATIONS (HOURS)	2714

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
2142	THE TEST SPECIMEN SHALL BE 2142 INCH(S) IN LENGTH.
2144	THE TEST SPECIMEN SHALL BE 2144 MILLIMETER(S) IN DIAMETER.
2146	THERE SHALL BE 2146 SPECIMEN(S) TESTED.
2148	THE TEST SPECIMEN WEIGHT SHALL BE 2148 GRAM(S).
2150	THE TEST SPECIMEN WEIGHT SHALL BE 2150 OUNCE(S).
2152	THE FLAME SHALL BE APPLIED TO THE SPECIMEN 2152 TIME(S).
2154	THE FLAME SHALL BE APPLIED FOR A DURATION OF 2154 SECOND(S).
2706	FLEXIBILITY. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2706.
2708	FLEXIBILITY. THERE SHALL BE NO CRACKING OR FLAKING.
2710	FLEXIBILITY. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2710.
2712	FLEXIBILITY. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH FED-STD-141, METHOD 6222.
2714	THE CURING DURATION SHALL BE 2714 HOUR(S).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
FLEXIBILITY (CONT)	
PER FED-STD-141, METHOD 6222. (CONT)	
CURING TEMPERATURE (DEGREES CELSIUS)	2716
TOLERANCE PLUS OR MINUS (DEGREES CELSIUS)	2718
MANDREL DIAMETER (INCHES)	2720
FREEZE-THAW	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	2628
AS FOLLOWS:	2630
MAXIMUM VISCOSITY CHANGE (PERCENT)	2632
SHALL REMAIN HOMOGENEOUS.	2634
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	2636
PER ASTMD244.	2638
TEST TEMPERATURE (DEGREES CELSIUS)	2640
TOLERANCE PLUS OR MINUS (DEGREES CELSIUS)	2642

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
2716	THE CURING TEMPERATURE SHALL BE 2716 DEGREES CELSIUS.
2718	THE TOLERANCE SHALL BE PLUS OR MINUS 2718 DEGREES CELSIUS.
2720	THE MANDREL DIAMETER SHALL BE 2720 INCH(S).
2628	FREEZE-THAW. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2628.
2630	FREEZE-THAW. THE REQUIREMENT(S) SHALL BE AS FOLLOWS:
2632	THE VISCOSITY CHANGE SHALL BE NOT GREATER THAN 2632 PERCENT.
2634	THE MATERIAL SHALL REMAIN HOMOGENEOUS.
2636	FREEZE-THAW. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2636.
2638	FREEZE-THAW. TESTING SHALL BE IN ACCORDANCE WITH ASTMD244.
2640	THE TEST TEMPERATURE SHALL BE 2640 DEGREES CELSIUS.
2642	THE TOLERANCE SHALL BE PLUS OR MINUS 2642 DEGREES CELSIUS.

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
FREEZE-THAW (CONT)	
PER ASTMD244. (CONT)	
DURATION OF TESTS	
(HOURS)	2644
THAW TEMPERATURE (DEGREES CELSIUS)	2646
DURATION	
(HOURS)	2648
TEST CYCLES (QUANTITY)	2649
FUNGUS	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	4760
FUNGUS RESISTANCE BY CERTIFICATION OR BY TEST.	4761
NO EVIDENCE OF FUNGUS GROWTH BY TEST.	4762

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR
CODE STANDARD PARAGRAPH

2644 THE DURATION OF TESTS SHALL BE 2644 HOUR(S).

2646 THE THAW TEMPERATURE SHALL BE 2646 DEGREES CELSIUS.

2648 THE DURATION SHALL BE 2648 HOUR(S).

2649 THE NUMBER OF TEST CYCLES SHALL BE 2649.

4760 FUNGUS. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 4760.

4761 FUNGUS. ALL EXTERNAL MATERIALS SHALL BE NONNUTRIENT TO FUNGUS GROWTH OR SHALL BE SUITABLY TREATED TO RETARD FUNGUS GROWTH. THE MANUFACTURER SHALL VERIFY BY CERTIFICATION THAT ALL EXTERNAL MATERIALS ARE FUNGUS RESISTANT OR SHALL PERFORM THE FUNGUS TEST. WHEN THE FUNGUS TEST IS PERFORMED, THERE SHALL BE NO EVIDENCE OF FUNGUS GROWTH ON THE EXTERNAL SURFACES.

4762 FUNGUS. ALL EXTERNAL MATERIALS SHALL BE NONNUTRIENT TO FUNGUS GROWTH OR SHALL BE SUITABLY TREATED TO RETARD FUNGUS GROWTH. THERE SHALL BE NO EVIDENCE OF FUNGUS GROWTH ON THE EXTERNAL SURFACES.

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
FUNGUS (CONT)	
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	4754
PER MIL-STD-810 METHOD 508.	4755
TEST PERIOD (DAYS)	4756
TEST METHOD (DESIGNATION)	2156
NUMBER OF SPECIMENS TO BE TESTED (QUANTITY)	2158
HARDNESS	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	2160
AS FOLLOWS:	2162
MINIMUM AVERAGE DUROMETER READING (NUMBER)	2164
MINIMUM DUROMETER READINGS (NUMBER)	2166
APPLICABLE DUROMETER SCALE (LETTER)	2168

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
4754	FUNGUS. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 4754.
4755	FUNGUS. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH METHOD 508 OF MIL-STD-810.
4756	TEST PERIOD SHALL BE 4756 DAY(S).
2156	THE TEST METHOD SHALL BE 2156.
2158	THE NUMBER OF SPECIMENS TO BE TESTED SHALL BE 2158.
2160	HARDNESS. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2160.
2162	HARDNESS. THE REQUIREMENT(S) SHALL BE AS FOLLOWS:
2164	THE AVERAGE DUROMETER READING SHALL BE NOT LESS THAN 2164.
2166	THERE SHALL BE NOT LESS THAN 2166 DUROMETER READINGS.
2168	DUROMETER SCALE LETTER 2168 SHALL APPLY.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
HARDNESS (CONT)	
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	2170
PER ASTMD2240.	2172
HUMIDITY	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	4798
MAXIMUM MOISTURE ABSORPTION (PERCENT)	2198
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	4788
PER MIL-A-3920.	2200
EXPOSURE TO RELATIVE HUMIDITY (PERCENT)	4789
TEST TEMPERATURE (DEGREES CELSIUS)	2202
TOLERANCE PLUS OR MINUS (DEGREES CELSIUS)	2204

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
2170	HARDNESS. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2170.
2172	HARDNESS. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH ASTMD2240.
4798	HUMIDITY. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 4798.
2198	HUMIDITY. THE MOISTURE ABSORPTION SHALL BE NOT GREATER THAN 2198 PERCENT.
4788	HUMIDITY. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 4788.
2200	HUMIDITY. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH MIL-A-3920.
4789	THE RELATIVE HUMIDITY SHALL BE 4789 PERCENT.
2202	THE TEST TEMPERATURE SHALL BE 2202 DEGREES CELSIUS.
2204	THE TOLERANCE SHALL BE PLUS OR MINUS 2204 DEGREES CELSIUS.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
HUMIDITY (CONT)	
EXPOSURE TO RELATIVE HUMIDITY (CONT)	
DURATION (SELECT ONE)	
(MINUTES)	2206
(HOURS)	2208
(DAYS)	2210
HYDROGEN ION CONCENTRATION (PH)	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	1772
AS FOLLOWS:	2141
MAXIMUM VALUE	1774
MINIMUM VALUE	1776
NOMINAL VALUE	1778
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	1765
PER ASTMD1583.	1768
HYDROLYTIC STABILITY	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	2212

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:24Z
Check the source to verify that this is the currentversion before use.

CHAR CODE	STANDARD PARAGRAPH
2206	THE DURATION SHALL BE 2206 MINUTE(S).
2208	THE DURATION SHALL BE 2208 HOUR(S).
2210	THE DURATION SHALL BE 2210 DAY(S).
1772	HYDROGEN ION CONCENTRATION (PH). THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1772.
2141	HYDROGEN ION CONCENTRATION (PH). THE REQUIREMENT(S) SHALL BE AS FOLLOWS:
1774	THE PH VALUE SHALL BE NOT GREATER THAN 1774.
1776	THE PH VALUE SHALL BE NOT LESS THAN 1776.
1778	THE PH VALUE SHALL BE 1778.
1765	HYDROGEN ION CONCENTRATION (PH). TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1765.
1768	HYDROGEN ION CONCENTRATION (PH). TESTING SHALL BE PERFORMED IN ACCORDANCE WITH ASTMD1583.
2212	HYDROLYTIC STABILITY. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2212.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE (KCI)

CHARACTERISTIC NAME	CHAR CODE
HYDROLYTIC STABILITY (CONT)	
REQUIREMENTS (CONT)	
AS FOLLOWS:	2213
MINIMUM TENSILE STRENGTH (SELECT ONE)	
(POUNDS PER SQUARE INCH)	2214
(KILOPASCALS)	2216
MINIMUM HARDNESS READING (SHORE A)	2217
REMAIN WITHIN SPECIFIED HARDNESS.	2215
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	2218
PER DOCUMENT (DOC DES)	2220
IMMERSION	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	4819
AS FOLLOWS:	2900
MINIMUM PEEL STRENGTH (SELECT ONE)	
(POUNDS PER INCH WIDTH)	2257
(KILOGRAMS PER MILLIMETER WIDTH)	2259

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
2213	HYDROLYTIC STABILITY. THE REQUIREMENT(S) SHALL BE AS FOLLOWS:
2214	THE TENSILE STRENGTH SHALL BE NOT LESS THAN 2214 POUNDS PER SQUARE INCH.
2216	THE TENSILE STRENGTH SHALL BE NOT LESS THAN 2216 KILOPASCAL(S).
2217	THE HARDNESS READING SHALL BE NOT LESS THAN 2217 SHORE A.
2215	THE MATERIAL SHALL REMAIN WITHIN THE SPECIFIED HARDNESS.
2218	HYDROLYTIC STABILITY. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2218.
2220	HYDROLYTIC STABILITY. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH 2220.
4819	IMMERSION. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 4819.
2900	IMMERSION. THE REQUIREMENT(S) SHALL BE AS FOLLOWS:
2257	THE PEEL STRENGTH SHALL BE NOT LESS THAN 2257 POUNDS PER INCH WIDTH.
2259	THE PEEL STRENGTH SHALL BE NOT LESS THAN 2259 KILOGRAMS PER MILLIMETER WIDTH.

Source: https://assist.dla.mil -- Downloaded: 202640-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
IMMERSION (CONT)	
AS FOLLOWS: (CONT)	
NO EVIDENCE OF PHYSICAL DAMAGE.	4820
MAXIMUM MEDIA ABSORPTION (PERCENT)	2263
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	4809
PER DOCUMENT (DOC DES)	2256
TEST MEDIA (NAME)	2258
(DOC DES)	2260
TEST TEMPERATURE (DEGREES CELSIUS)	2262
DURATION (MINUTES)	2264
IMMERSION DURATION (SELECT ONE)	
(MINUTES)	2266
(HOURS)	2268
AIR DRIED DURATION (SELECT ONE)	
(MINUTES)	2270
(HOURS)	2272
LOW TEMPERATURE FLEXIBILITY	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	1800

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
4820	THERE SHALL BE NO EVIDENCE OF PHYSICAL DAMAGE.
2263	THE MEDIA ABSORPTION SHALL BE NOT GREATER THAN 2263 PERCENT.
4809	IMMERSION. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 4809.
2256	IMMERSION. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH 2256.
2258	THE TEST MEDIA SHALL BE 2258.
2260	THE TEST MEDIA SHALL BE IN ACCORDANCE WITH 2260.
2262	THE TEST TEMPERATURE SHALL BE 2262 DEGREES CELSIUS.
2264	THE DURATION SHALL BE 2264 MINUTES.
2266	THE IMMERSION DURATION SHALL BE 2266 MINUTE(S).
2268	THE IMMERSION DURATION SHALL BE 2268 HOUR(S).
2270	THE AIR DRIED DURATION SHALL BE 2270 MINUTE(S).
2272	THE AIR DRIED DURATION SHALL BE 2272 HOUR(S).
1800	LOW TEMPERATURE FLEXIBILITY. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1800.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
LOW TEMPERATURE FLEXIBILITY (CONT)	
REQUIREMENTS (CONT)	
NO CRACKING OR FLAKING.	1804
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	1782
PER MMM-A-105.	1784
BAKE DURATION (HOURS)	1786
BAKE TEMPERATURE (DEGREES CELSIUS)	1788
TEMPERATURE TOLERANCE PLUS OR MINUS (DEGREES CELSIUS)	1790
COLD BOX TEMPERATURE (DEGREES CELSIUS)	1792
TEMPERATURE TOLERANCE PLUS OR MINUS (DEGREES CELSIUS)	1794
MANDREL DIAMETER (SELECT ONE)	
(INCHES)	1796
(MILLIMETERS)	1798
ODOR	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	1814
THE ADHESIVE SHALL BE FREE FROM OBNOXIOUS OR OBJECTIONABLE ODOR.	1816

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR
CODE STANDARD PARAGRAPH

1804 LOW TEMPERATURE FLEXIBILITY. THERE SHALL BE NO CRACKING OR FLAKING OF THE ADHESIVE.

1782 LOW TEMPERATURE FLEXIBILITY. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1782.

1784 LOW TEMPERATURE FLEXIBILITY. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH MMM-A-105.

1786 THE BAKING TIME SHALL BE 1786 HOURS.

1788 THE BAKING TEMPERATURE SHALL BE 1788 DEGREES CELSIUS.

1790 THE BAKING TEMPERATURE TOLERANCE SHALL BE PLUS OR MINUS 1790 DEGREES CELSIUS.

1792 THE COLD BOX TEMPERATURE SHALL BE 1792 DEGREES CELSIUS.

1794 THE COLD BOX TEMPERATURE TOLERANCE SHALL BE PLUS OR MINUS 1794 DEGREES CELSIUS.

1796 THE MANDREL DIAMETER SHALL BE 1796 INCH(S).

1798 THE MANDREL DIAMETER SHALL BE 1798 MILLIMETER(S).

1814 ODOR. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1814.

1816 ODOR. THE ADHESIVE SHALL BE FREE FROM OBNOXIOUS OR OBJECTIONABLE ODOR.

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
ODOR (CONT)	
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	1808
PER FED-STD-141, METHOD 4401.	1810
PEEL STRENGTH	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	2274
AS FOLLOWS:	2276
MINIMUM PEEL STRENGTH, WIDTH (SELECT ONE)	
(POUNDS PER INCH OF WIDTH)	2278
(NEWTONS PER MILLIMETER OF WIDTH)	2280
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	2282
PER DOCUMENT (DOC DES)	2284
TEST SPECIMEN TEMPERATURE (DEGREES CELSIUS)	2286
TOLERANCE PLUS OR MINUS (DEGREES CELSIUS)	2288

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
1808	ODOR. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1808.
1810	ODOR. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH METHOD 4401 OF FED-STD-141.
2274	PEEL STRENGTH. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2274.
2276	PEEL STRENGTH. THE REQUIREMENT(S) SHALL BE AS FOLLOWS:
2278	THE PEEL STRENGTH SHALL BE NOT LESS THAN 2278 POUND(S) PER INCH OF WIDTH.
2280	THE PEEL STRENGTH SHALL BE NOT LESS THAN 2280 NEWTON(S) PER MILLIMETER OF WIDTH.
2282	PEEL STRENGTH. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2282.
2284	PEEL STRENGTH. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH 2284.
2286	THE TEST SPECIMEN TEMPERATURE SHALL BE 2286 DEGREES CELSIUS.
2288	THE TEST SPECIMEN TEMPERATURE TOLERANCE SHALL BE PLUS OR MINUS 2288 DEGREES CELSIUS.

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
POT LIFE	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	2290
POT LIFE	
MINIMUM (SELECT ONE)	
(MINUTES)	2291
(HOURS)	2292
TEMPERATURE (DEGREES CELSIUS)	2294
TOLERANCE PLUS OR MINUS (DEGREES CELSIUS)	2293
FREE OF CRACKS AND BUBBLES.	2296
PROPER MIXING INSTRUCTION BY MANUFACTURER.	2298
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	2300
TESTING SHALL BE ____	2301
PER DOCUMENT (DOC DES)	2302
SAMPLE SIZE (SELECT ONE)	
(MILLIMETERS)	2304
(OUNCES)	2306
(GRAMS)	2307

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
2290	POT LIFE. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2290.
2291	POT LIFE. THE POT LIFE SHALL BE NOT LESS THAN 2291 MINUTE(S).
2292	POT LIFE. THE POT LIFE SHALL BE NOT LESS THAN 2292 HOUR(S).
2294	THE TEMPERATURE SHALL BE 2294 DEGREES CELSIUS.
2293	THE TOLERANCE SHALL BE PLUS OR MINUS 2293 DEGREES CELSIUS.
2296	THE COMPOUND SHALL BE FREE OF CRACKS AND BUBBLES.
2298	PROPER MIXING INSTRUCTIONS SHALL BE FURNISHED BY THE MANUFACTURER.
2300	POT LIFE. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2300.
2301	POT LIFE. TESTING SHALL BE 2301.
2302	POT LIFE. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH 2302.
2304	THE SAMPLE SIZE SHALL BE 2304 MILLIMETER(S).
2306	THE SAMPLE SIZE SHALL BE 2306 OUNCE(S).
2307	THE SAMPLE SIZE SHALL BE 2307 GRAM(S).

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
SAG	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	2698
MAXIMUM SAG FLOW (INCHES)	2700
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	2702
PER ASTMD2730.	2704
SALT SPRAY	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	4878
THE MATERIAL SHALL SHOW NO LOSS OF ADHESION AND SHALL NOT BECOME TACKY.	2310
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	4770
PER DOCUMENT (DOC DES)	2901
SHEAR STRENGTH	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	2318
AS FOLLOWS:	2320

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
2698	SAG. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2698.
2700	SAG. THE SAG FLOW SHALL BE NOT GREATER THAN 2700 INCH(S).
2702	SAG. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2702.
2704	SAG. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH ASTMD2730.
4878	SALT SPRAY. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 4878.
2310	SALT SPRAY. THE MATERIAL SHALL SHOW NO LOSS OF ADHESION AND SHALL NOT BECOME TACKY.
4770	SALT SPRAY. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 4770.
2901	SALT SPRAY. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH 2901.
2318	SHEAR STRENGTH. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2318.
2320	SHEAR STRENGTH. THE REQUIREMENT(S) SHALL BE AS FOLLOWS:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDES (KCI)

CHARACTERISTIC NAME	CHAR CODE
SHEAR STRENGTH (CONT)	
AS FOLLOWS: (CONT)	
AVERAGE SHEAR STRENGTH (SELECT ONE)	
(POUNDS PER SQUARE INCH)	2322
(KILOPASCALS)	2324
MINIMUM SHEAR STRENGTH (SELECT ONE)	
(POUNDS PER SQUARE INCH)	2321
(KILOPASCALS)	2323
SHEAR STRENGTH TEMPERATURE (DEGREES CELSIUS)	2902
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	2326
PER DOCUMENT (DOC DES)	2328
TEST SPECIMEN TEMPERATURE (DEGREES CELSIUS)	2330
TOLERANCE PLUS OR MINUS (DEGREES CELSIUS)	2332
TEST RELATIVE HUMIDITY (PERCENT)	2334
TOLERANCE PLUS OR MINUS (PERCENT)	2336
PER FED-STD-175, METHOD 1033.1.	3000

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
2322	THE MATERIAL SHALL HAVE AN AVERAGE SHEAR STRENGTH OF 2322 POUNDS PER SQUARE INCH.
2324	THE AVERAGE SHEAR STRENGTH SHALL BE 2324 KILOPASCAL(S).
2321	THE SHEAR STRENGTH SHALL BE NOT LESS THAN 2321 POUNDS PER SQUARE INCH.
2323	THE SHEAR STRENGTH SHALL BE NOT LESS THAN 2323 KILOPASCAL(S).
2902	THE SHEAR STRENGTH TEMPERATURE SHALL BE 2902 DEGREES CELSIUS.
2326	SHEAR STRENGTH. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2326.
2328	SHEAR STRENGTH. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH 2328.
2330	THE TEST SPECIMEN TEMPERATURE SHALL BE 2330 DEGREES CELSIUS.
2332	THE TEST SPECIMEN TEMPERATURE TOLERANCE SHALL BE PLUS OR MINUS 2332 DEGREES CELSIUS.
2334	THE RELATIVE HUMIDITY DURING TESTING SHALL BE 2334 PERCENT.
2336	THE RELATIVE HUMIDITY TOLERANCE SHALL BE PLUS OR MINUS 2336 PERCENT.
3000	SHEAR STRENGTH. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH FED-STD-175, METHOD 1033.1.

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
SHEAR STRENGTH (CONT)	
PER FED-STD-175, METHOD 1033.1. (CONT)	
SPECIAL PREPARATION ____	3001
CONDITIONING DURATION (SELECT ONE)	
(HOURS)	3002
(MINUTES)	3003
CONDITIONING TEMPERATURE (DEGREES CELSIUS)	3004
CURING DURATION (HOURS)	3005
CURING TEMPERATURE (DEGREES CELSIUS)	3006
SHELF LIFE (STORAGE)	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	1934
AS FOLLOWS:	1936
BOTH PARTS A AND B SHALL MEET ALL REQUIREMENTS AFTER TESTS.	1938
THE COMPONENTS SHALL MEET ALL REQUIREMENTS AFTER TESTS.	1940
THE UNMIXED COMPONENTS, IN UNOPENED CONTAINERS SHALL MEET ALL REQUIREMENTS AFTER STORAGE.	1942
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	1943
PER DOCUMENT (DOC DES)	1945

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
3001	SPECIAL PREPARATION SHALL BE 3001.
3002	THE CONDITIONING DURATION SHALL BE 3002 HOUR(S).
3003	THE CONDITIONING DURATION SHALL BE 3003 MINUTE(S).
3004	THE CONDITIONING TEMPERATURE SHALL BE 3004 DEGREES CELSIUS.
3005	THE CURING DURATION SHALL BE 3005 HOUR(S).
3006	THE CURING TEMPERATURE SHALL BE 3006 DEGREES CELSIUS.
1934	SHELF LIFE (STORAGE). THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1934.
1936	SHELF LIFE (STORAGE). THE REQUIREMENT(S) SHALL BE AS FOLLOWS:
1938	BOTH PARTS A AND B SHALL MEET ALL REQUIREMENTS AFTER TESTS.
1940	THE COMPONENTS SHALL MEET ALL REQUIREMENTS AFTER TESTS.
1942	THE UNMIXED COMPONENTS, IN UNOPENED CONTAINERS SHALL MEET ALL REQUIREMENTS AFTER STORAGE.
1943	SHELF LIFE (STORAGE.). TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1943.
1945	SHELF LIFE (STORAGE.). TESTING SHALL BE PERFORMED IN ACCORDANCE WITH 1945.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
SHELF LIFE (STORAGE) (CONT)	
TEST METHODS (CONT)	
TEST AS FOLLOWS:	1941
STORAGE DURATION (SELECT ONE)	
(MINUTES)	1947
(HOURS)	1949
(WEEKS)	1951
(MONTHS)	1953
(YEARS)	1955
STORAGE TEMPERATURE (DEGREES CELSIUS)	1957
TOLERANCE (DEGREES CELSIUS)	1959
TEAR RESISTANCE	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	2338
AS FOLLOWS:	2340
MINIMUM (SELECT ONE)	
(POUNDS PER INCH OF THICKNESS)	2342
(NEWTONS PER MILLIMETER OF THICKNESS)	2344
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	2346

Source: https://assist.dla.mil -- Downloaded: 202640-26T07:24Z
Check the source to verify that this is the currentversion before use.

CHAR CODE | STANDARD PARAGRAPH

1941 SHELF LIFE (STORAGE). TESTING SHALL BE AS FOLLOWS:

1947 THE STORAGE DURATION SHALL BE 1947 MINUTE(S).

1949 THE STORAGE DURATION SHALL BE 1949 HOUR(S).

1951 THE STORAGE DURATION SHALL BE 1951 WEEK(S).

1953 THE STORAGE DURATION SHALL BE 1953 MONTH(S).

1955 THE STORAGE DURATION SHALL BE 1955 YEAR(S).

1957 THE STORAGE TEMPERATURE SHALL BE 1957 DEGREES CELSIUS.

1959 THE STORAGE TEMPERATURE TOLERANCE SHALL BE 1959 DEGREES CELSIUS.

2338 TEAR RESISTANCE. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2338.

2340 TEAR RESISTANCE. THE REQUIREMENT(S) SHALL BE AS FOLLOWS:

2342 THE MATERIAL SHALL WITHSTAND A FORCE OF NOT LESS THAN 2342 POUND(S) PER INCH OF THICKNESS.

2344 THE MATERIAL SHALL WITHSTAND A FORCE OF NOT LESS THAN 2344 NEWTON(S) PER MILLIMETER OF THICKNESS.

2346 TEAR RESISTANCE. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2346.

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
TEAR RESISTANCE (CONT)	
TEST METHODS (CONT)	
PER MIL-A-47040.	2348
TEST SPECIMEN CONDITIONING PERIOD (HOURS)	2354
CONDITIONING TEMPERATURE (DEGREES CELSIUS)	2356
TOLERANCE PLUS OR MINUS (DEGREES CELSIUS)	2358
RELATIVE HUMIDITY (PERCENT)	2360
TOLERANCE PLUS OR MINUS (PERCENT)	2362
TEMPERATURE, HIGH	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	6228
NO EVIDENCE OF PHYSICAL DAMAGE.	6229

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
2348	TEAR RESISTANCE. TESTING SHALL BE IN ACCORDANCE WITH MIL-A-47040.
2354	CONDITIONING PERIOD SHALL BE 2354 HOUR(S).
2356	CONDITIONING TEMPERATURE SHALL BE 2356 DEGREES CELSIUS.
2358	CONDITIONING TEMPERATURE TOLERANCE SHALL BE PLUS OR MINUS 2358 DEGREES CELSIUS.
2360	RELATIVE HUMIDITY SHALL BE 2360 PERCENT.
2362	RELATIVE HUMIDITY TOLERANCE SHALL BE PLUS OR MINUS 2362 PERCENT.
6228	TEMPERATURE, HIGH. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 6228.
6229	TEMPERATURE, HIGH. THERE SHALL BE NO EVIDENCE OF PHYSICAL DAMAGE.

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
TEMPERATURE, HIGH (CONT)	
NO EVIDENCE OF PHYSICAL DAMAGE. (CONT)	
MINIMUM SHORE "A" HARDNESS (NUMBER)	2368
MINIMUM TENSILE STRENGTH (SELECT ONE)	
(POUNDS PER SQUARE INCH)	2370
(KILOPASCALS)	2372
NO LOSS OF ADHESION.	2371
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	6217
PER DOCUMENT (DOC DES)	2374

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
2368	THE SHORE "A" HARDNESS SHALL BE NOT LESS THAN 2368.
2370	THE TENSILE STRENGTH SHALL BE NOT LESS THAN 2370 POUNDS PER SQUARE INCH.
2372	THE TENSILE STRENGTH SHALL BE NOT LESS THAN 2372 KILOPASCAL(S).
2371	THERE SHALL BE NO LOSS OF ADHESION.
6217	TEMPERATURE, HIGH. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 6217.
2374	TEMPERATURE, HIGH. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH 2374.

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
TEMPERATURE, HIGH (CONT)	
PER DOCUMENT (CONT)	
TEST TEMPERATURE (DEGREES CELSIUS)	2394
TOLERANCE PLUS OR MINUS (DEGREES CELSIUS)	2396
DURATION AT HIGH TEMPERATURE (HOURS)	2398
COOLING TEMPERATURE (DEGREES CELSIUS)	2400
TOLERANCE PLUS OR MINUS (DEGREES CELSIUS)	2402
COOLING DURATION (SELECT ONE)	
(MINUTES)	2404
(HOURS)	2406
TEMPERATURE, LOW	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	6318
NO EVIDENCE OF PHYSICAL DAMAGE.	6319
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	6231
PER DOCUMENT (DOC DES)	2414
NUMBER OF CYCLES (QUANTITY)	2436

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
2394	THE TEST TEMPERATURE SHALL BE 2394 DEGREES CELSIUS.
2396	THE TOLERANCE SHALL BE PLUS OR MINUS 2396 DEGREES CELSIUS.
2398	THE DURATION AT HIGH TEMPERATURE SHALL BE 2398 HOUR(S).
2400	THE COOLING TEMPERATURE SHALL BE 2400 DEGREES CELSIUS.
2402	THE COOLING TEMPERATURE TOLERANCE SHALL BE PLUS OR MINUS 2402 DEGREES CELSIUS.
2404	THE COOLING DURATION SHALL BE 2404 MINUTE(S).
2406	THE COOLING DURATION SHALL BE 2406 HOUR(S).
6318	TEMPERATURE, LOW. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 6318.
6319	TEMPERATURE, LOW. THERE SHALL BE NO EVIDENCE OF PHYSICAL DAMAGE.
6231	TEMPERATURE, LOW. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 6231.
2414	TEMPERATURE, LOW. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH 2414.
2436	THERE SHALL BE 2436 TEST CYCLE(S).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
TEMPERATURE, LOW (CONT)	
PER DOCUMENT (CONT)	
IMMERSION SOLUTION AFTER CURING TEST (NAME)	2438
DURATION (SELECT ONE)	
(HOURS)	2440
(DAYS)	2442
(WEEKS)	2444
DURATION TOLERANCE PLUS OR MINUS (HOURS)	2446
TEST SPECIMEN PREPARATION AFTER CURE	
CONDITION TEMPERATURE (DEGREES CELSIUS)	2450
TOLERANCE PLUS OR MINUS (DEGREES CELSIUS)	2452
DURATION (HOURS)	2454
TENSILE STRENGTH	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	2456
AS FOLLOWS:	2458
MINIMUM TENSILE STRENGTH (SELECT ONE)	
(POUNDS PER SQUARE INCH)	2460
(KILOPASCALS)	2462

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
2438	THE IMMERSION SOLUTION AFTER CURING SHALL BE 2438.
2440	THE DURATION OF IMMERSION SHALL BE 2440 HOUR(S).
2442	THE DURATION OF IMMERSION SHALL BE 2442 DAY(S).
2444	THE DURATION OF IMMERSION SHALL BE 2444 WEEK(S).
2446	THE TOLERANCE SHALL BE PLUS OR MINUS 2446 HOUR(S).
2450	THE CONDITION TEMPERATURE SHALL BE 2450 DEGREES CELSIUS.
2452	THE TOLERANCE SHALL BE PLUS OR MINUS 2452 DEGREES CELSIUS.
2454	THE DURATION SHALL BE 2454 HOUR(S).
2456	TENSILE STRENGTH. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2456.
2458	TENSILE STRENGTH. THE REQUIREMENT(S) SHALL BE AS FOLLOWS:
2460	THE TENSILE STRENGTH SHALL BE NOT LESS THAN 2460 POUND(S) PER SQUARE INCH.
2462	THE TENSILE STRENGTH SHALL BE NOT LESS THAN 2462 KILOPASCAL(S).

Source: https://assist.dla.mil -- Downloaded: 202640-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
TENSILE STRENGTH (CONT)	
AS FOLLOWS: (CONT)	
TENSILE STRENGTH TEMPERATURE (DEGREES CELSIUS)	2461
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	2464
PER ASTMD412.	2466
TEST SPECIMEN TEMPERATURE (DEGREES CELSIUS)	2486
TOLERANCE PLUS OR MINUS (DEGREES CELSIUS)	2488
DIE PER ASTMD412 (LETTER)	2490
THERMAL CONDUCTIVITY	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	3008
MINIMUM THERMAL CONDUCTIVITY (SELECT ONE)	
(BRITISH THERMAL UNITS PER HOUR PER SQUARE FOOT PER DEGREE FAHRENHEIT PER INCH)	3010
(WATTS PER METER KELVIN)	3012

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
2461	THE TENSILE STRENGTH TEMPERATURE SHALL BE 2461 DEGREES CELSIUS.
2464	TENSILE STRENGTH. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2464.
2466	TENSILE STRENGTH. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH ASTMD412.
2486	THE TEST TEMPERATURE SHALL BE 2486 DEGREES CELSIUS.
2488	THE TEST TEMPERATURE TOLERANCE SHALL BE PLUS OR MINUS 2488 DEGREES CELSIUS.
2490	DIE LETTER 2490 OF ASTMD412 SHALL APPLY.
3008	THERMAL CONDUCTIVITY. THE REQUIREMENT(S) SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 3008.
3010	THERMAL CONDUCTIVITY. THE THERMAL CONDUCTIVITY SHALL BE NOT LESS THAN 3010 BRITISH THERMAL UNITS PER HOUR PER SQUARE FOOT PER DEGREE FAHRENHEIT PER INCH.
3012	THERMAL CONDUCTIVITY. THE THERMAL CONDUCTIVITY SHALL BE NOT LESS THAN 3012 WATTS PER METEP KELVIN.

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
THERMAL CONDUCTIVITY (CONT)	
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	3014
PER ASTMC518.	3015
ULTIMATE ELONGATION	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	2500
MINIMUM PERCENT OF ULTIMATE ELONGATION OF THE UNAGED SPECIMEN (PERCENT)	2502
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	2504
PER ASTMD412.	2506
NUMBER OF SPECIMENS TO BE TESTED (QUANTITY)	2508
TEST TEMPERATURE (DEGREES CELSIUS)	2510
TOLERANCE PLUS OR MINUS (DEGREES CELSIUS)	2512
DIE PER ASTMD412 (LETTER)	2514
VISCOSITY	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	2516

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:24Z
Check the source to verify that this is the currentversion before use.

CHAR CODE	STANDARD PARAGRAPH
3014	THERMAL CONDUCTIVITY. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 3014.
3015	THERMAL CONDUCTIVITY. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH ASTMC518.
2500	ULTIMATE ELONGATION. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2500.
2502	ULTIMATE ELONGATION. THE ULTIMATE ELONGATION OF THE UNAGED SPECIMEN SHALL BE NOT LESS THAN 2502 PERCENT.
2504	ULTIMATE ELONGATION. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2504.
2506	ULTIMATE ELONGATION. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH ASTMD412.
2508	THERE SHALL BE 2508 SPECIMEN(S) TESTED.
2510	THE TEST TEMPERATURE SHALL BE 2510 DEGREES CELSIUS.
2512	THE TEST TEMPERATURE TOLERANCE SHALL BE PLUS OR MINUS 2512 DEGREES CELSIUS.
2514	DIE LETTER 2514 OF ASTMD412 SHALL APPLY.
2516	VISCOSITY. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2516.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
VISCOSITY (CONT)	
REQUIREMENTS (CONT)	
AS FOLLOWS:	2518
MINIMUM VISCOSITY (SELECT ONE)	
(CENTIPOISE)	2520
(PASCAL SECONDS)	2524
MAXIMUM VISCOSITY (SELECT ONE)	
(CENTIPOISE)	2525
(PASCAL SECONDS)	2526
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	2528
PER DOCUMENT (DOC DES)	2530
TEST METHOD (LETTER)	2532
TEST SPECIMEN TEMPERATURE (DEGREES CELSIUS)	2534
TOLERANCE PLUS OR MINUS (DEGREES CELSIUS)	2536
RELATIVE HUMIDITY (PERCENT)	2538
TOLERANCE PLUS OR MINUS (PERCENT)	2540

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
2518	VISCOSITY. THE REQUIREMENT(S) SHALL BE AS FOLLOWS:
2520	THE VISCOSITY SHALL BE NOT LESS THAN 2520 CENTIPOISE.
2524	THE VISCOSITY SHALL BE NOT LESS THAN 2524 PASCAL SECONDS.
2525	THE VISCOSITY SHALL BE NOT GREATER THAN 2525 CENTIPOISE.
2526	THE VISCOSITY SHALL BE NOT GREATER THAN 2526 PASCAL SECONDS.
2528	VISCOSITY. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2528.
2530	VISCOSITY. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH 2530.
2532	TEST METHOD LETTER 2532 SHALL APPLY.
2534	THE TEST TEMPERATURE SHALL BE 2534 DEGREES CELSIUS.
2536	THE TEST TEMPERATURE TOLERANCE SHALL BE PLUS OR MINUS 2536 DEGREES CELSIUS.
2538	RELATIVE HUMIDITY SHALL BE 2538 PERCENT.
2540	RELATIVE HUMIDITY TOLERANCE SHALL BE PLUS OR MINUS 2540 PERCENT.

Source: https://assist.dla.mil -- Downloaded: 202640-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
VOLUME RESISTIVITY	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	2542
AS FOLLOWS:	2544
MINIMUM VOLUME RESISTIVITY AT INITIAL MEASUREMENT (SELECT ONE)	
(OHMS/INCH)	2548
(OHMS/CENTIMETER)	2550
MAXIMUM VOLUME RESISTIVITY AT INITIAL MEASUREMENT (SELECT ONE)	
(OHMS/INCH)	3018
(OHMS/CENTIMETER)	3020
MINIMUM VOLUME RESISTIVITY AFTER CONDITIONING (SELECT ONE)	
(OHMS/INCH)	2554
(OHMS/CENTIMETER)	2556
MAXIMUM VOLUME RESISTIVITY AFTER CONDITIONING (SELECT ONE)	
(OHMS/INCH)	3022
(OHMS/CENTIMETER)	3024

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
2542	VOLUME RESISTIVITY. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2542.
2544	VOLUME RESISTIVITY. THE REQUIREMENT(S) SHALL BE AS FOLLOWS:
2548	THE VOLUME RESISTIVITY AT THE INITIAL MEASUREMENT SHALL BE NOT LESS THAN 2548 OHM(S) PER INCH.
2550	THE VOLUME RESISTIVITY AT THE INTITAL MEASUREMENT SHALL BE NOT LESS THAN 2550 OHM(S) PER CENTIMETER.
3018	THE VOLUME RESISTIVITY AT THE INITIAL MEASUREMENT SHALL BE NOT GREATER THAN 3018 OHM(S) PER INCH.
3020	THE VOLUME RESISTIVITY AT THE INITIAL MEASUREMENT SHALL BE NOT GREATER THAN 3020 OHM(S) PER CENTIMETER.
2554	THE VOLUME RESISTIVITY AFTER CONDITIONING SHALL BE NOT LESS THAN 2554 OHM(S) PER INCH.
2556	THE VOLUME RESISTIVITY AFTER CONDITIONING SHALL BE NOT LESS THAN 2556 OHM(S) PER CENTIMETER.
3022	THE VOLUME RESISTIVITY AFTER CONDITIONING SHALL BE NOT GREATER THAN 3022 OHM(S) PER INCH.
3024	THE VOLUME RESISTIVITY AFTER CONDITIONING SHALL BE NOT GREATER THAN 3024 OHM(S) PER CENTIMETER.

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
VOLUME RESISTIVITY (CONT)	
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	2558
PER DOCUMENT (DOC DES)	2559
PER ASTMD257.	2560
TEST TEMPERATURE (DEGREES CELSIUS)	2580
TOLERANCE PLUS OR MINUS (DEGREES CELSIUS)	2582
CONDITIONING PERIOD (SELECT ONE)	
(HOURS)	2584
(DAYS)	2586
PER FED-STD-406, METHOD 4041.	3026
TEST TEMPERATURE (DEGREES CELSIUS)	3028
RELATIVE HUMIDITY (PERCENT)	3030
CONDITIONING DURATION (SELECT ONE)	
(HOURS)	3032
(DAYS)	3034
CONDITIONING TEMPERATURE (DEGREES CELSIUS)	3036
CURING DURATION (HOURS)	3038
CURING TEMPERATURE (DEGREES CELSIUS)	3040

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
2558	VOLUME RESISTIVITY. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2558.
2559	VOLUME RESISTIVITY. TESTING SHALL BE IN ACCORDANCE WITH 2559.
2560	VOLUME RESISTIVITY. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH ASTMD257.
2580	THE TEST TEMPERATURE SHALL BE 2580 DEGREES CELSIUS.
2582	THE TEST TEMPERATURE TOLERANCE SHALL BE PLUS OR MINUS 2582 DEGREES CELSIUS.
2584	THE CONDITIONING PERIOD SHALL BE 2584 HOUR(S).
2586	THE CONDITIONING PERIOD SHALL BE 2586 DAYS(S).
3026	VOLUME RESISTIVITY. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH FED-STD-406, METHOD 4041.
3028	THE TEST TEMPERATURE SHALL BE 3028 DEGREES CELSIUS.
3030	THE RELATIVE HUMIDITY SHALL BE 3030 PERCENT.
3032	THE CONDITIONING DURATION SHALL BE 3032 HOUR(S).
3034	THE CONDITIONING DURATION SHALL BE 3034 DAY(S).
3036	THE CONDITIONING TEMPERATURE SHALL BE 3036 DEGREES CELSIUS.
3038	THE CURING DURATION SHALL BE 3038 HOUR(S).
3040	THE CURING TEMPERATURE SHALL BE 3040 DEGREES CELSIUS.

Source: https://assist.dla.mil -- Downloaded: 202640-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
WORKMANSHIP	
(DOC DES)	6870
PARTS A AND B IN A WORKMANSHIP MANNER.	2565
ADDITIONAL REQUIREMENTS	
A____	7001
B____	7002
C____	7003
D____	7004
E____	7005
ADDITIONAL PART MARKING	
A____	6991
B____	6992
C____	6993
D____	6994
E____	6995

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
6870	WORKMANSHIP. WORKMANSHIP SHALL BE IN ACCORDANCE WITH 6870.
2565	WORKMANSHIP. PARTS A AND B SHALL BE PERFORMED AND PACKAGED IN A WORKMANSHIP MANNER. NO CONTAMINANTS SHALL BE PERMITTED IN THE MATERIAL. CONTAINERS SHALL BE TIGHTLY CLOSED TO PRECLUDE ENTRANCE OF CONTAMINANTS AND MOISTURE.
	ADDITIONAL REQUIREMENTS.
7001	(A) 7001.
7002	(B) 7002.
7003	(C) 7003.
7004	(D) 7004.
7005	(E) 7005.
	ADDITIONAL PART MARKING.
6991	(A) 6991.
6992	(B) 6992.
6993	(C) 6993.
6094	(D) 6994.
6995	(E) 6995.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
APPLICABLE DOCUMENTS (SEE DOD-STD-35)	
QUALITY ASSURANCE PROVISIONS (SEE DOD-STD-35)	
PACKAGING (SEE DOD-STD-35)	
NOTES (SEE DOD-STD-35)	
NOMENCLATURE (SEE DOD-STD-35)	
SUPERSEDED DOCUMENT (SEE DOD-STD-35)	
PART NUMBER CROSS-REFERENCE (SEE DOD-STD-35)	

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR
CODE STANDARD PARAGRAPH

Custodians:
Army-MI

Review activities:
Army-AT
Army-AV
Army-EL
Army-ME
Army-MR
Army-SG
Army-WC

User activity:
Army-MU

Preparing activity:
Army-MI

(Project EDS-A241)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

APPENDIX A

CHARACTERISTIC CODE INDEX

Source: https://assist.dla.mil -- Downloaded: 202640-26T07:24Z
Check the source to verify that this is the current version before use.

CHARACTERISTIC CODE INDEX

CHAR CODE	PAGE NO.	CHAR CODE	PAGE NO.	CHAR CODE	PAGE NO.	CHAR CODE	PAGE NO.
0101	20	1648	46	1802	48	1945	92
0102	20	1649	70	1803	48	1946	36
0103	20	1650	46	1804	82	1947	94
0104	20	1652	46	1808	84	1948	36
0105	20	1654	46	1810	84	1949	94
0107	22	1660	44	1814	82	1950	36
0108	22	1662	44	1816	82	1951	94
0700	20	1664	46	1839	54	1952	36
0801	20	1666	48	1841	54	1953	94
1003	20	1668	48	1842	54	1954	36
1004	20	1670	48	1843	54	1955	94
1005	20	1672	48	1844	54	1956	38
1006	20	1675	44	1845	54	1957	94
1009	20	1680	48	1846	54	1958	38
1172	76	1690	54	1847	54	1959	94
1568	28	1694	52	1850	56	1962	36
1570	28	1696	54	1900	24	1964	36
1572	28	1700	56	1902	24	1966	38
1581	28	1702	56	1904	24	1968	38
1583	26	1706	54	1906	24	1970	38
1589	28	1734	40	1908	24	1972	38
1602	34	1746	42	1910	24	1974	38
1604	34	1758	44	1912	26	1976	38
1606	34	1765	76	1914	26	1978	40
1608	34	1766	46	1916	26	1980	40
1610	36	1768	76	1918	26	1981	40
1612	36	1774	76	1920	28	1982	38
1614	36	1776	76	1922	28	1983	38
1618	40	1778	76	1924	28	1984	38
1620	40	1782	82	1926	28	1985	38
1622	42	1784	82	1928	30	1986	50
1626	42	1786	82	1930	30	1987	36
1628	42	1788	82	1932	34	1988	54
1630	42	1790	82	1934	92	1990	50
1632	34	1792	82	1936	34	1992	50
1633	40	1794	82	1938	34	1994	50
1634	34	1796	82	1940	34	1996	50
1636	40	1798	82	1941	94	2000	56
1638	40	1800	80	1942	34	2002	56
1640	40	1801	48	1943	92	2004	56

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

CHARACTERISTIC CODE INDEX (CONT)

CHAR CODE	PAGE NO.	CHAR CODE	PAGE NO.	CHAR CODE	PAGE NO.	CHAR CODE	PAGE NO.
2006	56	2124	64	2220	78	2324	90
2008	56	2126	64	2256	80	2326	90
2010	56	2128	64	2257	78	2328	90
2012	56	2130	64	2258	80	2330	90
2032	56	2132	64	2259	78	2332	90
2034	56	2134	64	2260	80	2334	90
2036	56	2136	64	2262	80	2336	90
2038	56	2138	64	2263	80	2338	94
2040	56	2140	64	2264	80	2340	94
2042	56	2141	76	2266	80	2342	94
2044	56	2142	66	2268	80	2344	94
2046	56	2144	66	2270	80	2346	94
2048	56	2146	66	2272	80	2348	96
2050	56	2148	66	2274	84	2354	96
2052	56	2150	66	2276	84	2356	96
2054	60	2152	66	2278	84	2358	96
2055	60	2154	66	2280	84	2360	96
2056	60	2156	72	2282	84	2362	96
2060	60	2158	72	2284	84	2368	98
2062	60	2160	72	2286	84	2370	98
2064	60	2162	72	2288	84	2371	98
2066	60	2164	72	2290	86	2372	98
2068	60	2166	72	2291	86	2374	98
2070	60	2168	72	2292	86	2394	100
2072	60	2170	74	2293	86	2396	100
2074	60	2172	74	2294	86	2398	100
2076	62	2198	74	2296	86	2400	100
2078	62	2200	74	2298	86	2402	100
2080	62	2202	74	2300	86	2404	100
2082	62	2204	74	2301	86	2406	100
2084	62	2206	76	2302	86	2414	100
2086	62	2208	76	2304	86	2436	100
2088	62	2210	76	2306	86	2438	102
2090	62	2212	76	2307	86	2440	102
2112	62	2213	78	2310	88	2442	102
2114	62	2214	78	2318	88	2444	102
2116	64	2215	78	2320	88	2446	102
2118	64	2216	78	2321	90	2450	102
2120	64	2217	78	2322	90	2452	102
2122	64	2218	78	2323	90	2454	102

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

CHARACTERISTIC CODE INDEX (CONT)

CHAR CODE	PAGE NO.	CHAR CODE	PAGE NO.	CHAR CODE	PAGE NO.	CHAR CODE	PAGE NO.
2456	102	2584	112	2672	44	2806	32
2458	102	2586	112	2674	44	2812	32
2460	102	2601	26	2676	44	2814	32
2461	104	2602	28	2678	44	2816	32
2462	102	2604	28	2680	44	2900	78
2464	104	2605	30	2682	46	2901	88
2466	104	2606	30	2684	46	2902	90
2486	104	2607	30	2686	46	2944	36
2488	104	2608	34	2688	46	3000	90
2490	104	2610	32	2690	46	3001	92
2501	106	2611	32	2692	46	3002	92
2502	106	2612	32	2694	48	3003	92
2504	106	2613	32	2696	48	3004	92
2506	106	2614	30	2698	88	3005	92
2508	106	2615	30	2700	88	3006	92
2510	106	2616	30	2702	88	3008	104
2512	106	2617	30	2704	88	3010	104
2514	106	2619	30	2706	66	3012	104
2516	106	2628	68	2708	66	3014	106
2518	108	2630	68	2710	66	3015	106
2520	108	2632	68	2712	66	3018	110
2524	108	2634	68	2714	66	3020	110
2525	108	2636	68	2716	68	3022	110
2526	108	2638	68	2718	68	3024	110
2528	108	2640	68	2720	68	3026	112
2530	108	2642	68	2722	50	3028	112
2532	108	2644	70	2723	50	3030	112
2534	108	2646	70	2724	50	3032	112
2536	108	2648	70	2726	50	3034	112
2538	108	2650	42	2728	52	3036	112
2540	108	2652	42	2730	52	3038	112
2542	110	2654	42	2732	52	3040	112
2544	110	2656	42	2733	52	4754	72
2548	110	2658	42	2734	52	4755	72
2550	110	2660	42	2736	52	4756	72
2554	110	2662	42	2738	52	4760	70
2556	110	2664	42	2740	52	4761	70
2558	112	2666	44	2800	32	4762	70
2560	112	2668	44	2802	32	4770	88
2582	112	2670	44	2804	32	4788	74

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

CHARACTERISTIC CODE INDEX (CONT)

CHAR CODE	PAGE NO.	CHAR CODE	PAGE NO.	CHAR CODE	PAGE NO.	CHAR CODE	PAGE NO.
4789	74						
4798	74						
4809	80						
4819	78						
4820	80						
4878	88						
4904	24						
4905	24						
5048	24						
6217	98						
6228	96						
6229	96						
6231	100						
6318	100						
6319	100						
6369	20						
6375	26						
6873	114						
6873	20						
6874	22						
6941	22						
6942	22						
6991	114						
6992	114						
6993	114						
6994	114						
6995	114						
7001	114						
7002	114						
7003	114						
7004	114						
7005	114						
7301	24						
7302	24						

Source: https://assist.dla.mil -- Downloaded: 202640-26T07:24Z
Check the source to verify that this is the current version before use.

INDEX

	Page
Accelerated Aging	40
Additional Part Marking	114
Additional Requirements	114
Adhesion	42
Aperture Cards Required	22
Appearance	26
Applicable Documents	116
Application Method	34
Ash Content	44
Base Document	20
Bonding Pressure	28
Bonding Range	26
Brittle Point	46
Brushing Properties	48
Chemical Composition	50
City, State, Zip	20
Class	24
Cleavage Strength	50
Color	28
Company Name/Command	20
Compatibility With Explosives	34
Composition	26
Compressive Strength	52
Consistency	26
Contract Number/Office Symbol	20
Control	20
Corrosion of Metals	52
Curing Duration	28
Curing Pressure	32
Curing Temperature	32
Date	20
Density	54
Dielectric Constant	56
Dielectric Strength	58
Dissipation Factor	58
Elongation	62
Flammability	62
Flexibility	66
Format	20
Freeze-Thaw	68
Fungus	70

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

INDEX (CONT)

	Page
Government Design Activity FSCM	20
Grade	24
Hardness	72
Humidity	74
Hydrogen Ion Concentration (pH)	76
Hydrolytic Stability	76
Immersion	78
Low Temperature Flexibility	80
Materials	30
Moisture Content	34
Nomenclature	116
Notes	116
Odor	82
Packaging	116
Part Number	22
Part Number Cross-Reference	116
Peel Strength	84
Phone Number	20
Pot Life	86
Quality Assurance Provisions	116
Requester FSCM	20
Requester's Name	20
Revision of AEDPS Document (Number)	22
Sag	88
Salt Spray	88
Scope	22
Shear Strength	88
Shelf Life (Storage)	92
Shrinkage	32
Solids Content	24
Solvents	24
Source Table	22
Storage Duration	34
Storage Temperature	34
Street/Building	20

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

INDEX (CONT)

	Page
Superseded Document	116
System Application	20
Tack-Free Time	36
Tear Resistance	94
Temperature, High	96
Temperature, Low	100
Temperature Rating	24
Tensile Strength	102
Test Specimen Preparation	36
Thermal Conductivity	104
Toxicity	34
Type	24
Ultimate Elongation	106
Units of Measure	22
Viscosity	106
Volume Resistivity	110
Weight	26
Workmanship	114

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:24Z
Check the source to verify that this is the current version before use.

The digital copy of DOD-STD-35-78A (MI), dated 3 Aug 1978 does not include the foldout pages for the Specification Requirement Sheet (SRS). Please call ASSIST SERVICE DESK at 215-737-8000 for copies of these pages.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

The digital copy of DOD-STD-35-78A (MI), dated 3 Aug 1978 does not include the foldout pages for the Specification Requirement Sheet (SRS). Please call ASSIST SERVICE DESK at 215-737-8000 for copies of these pages.

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:24Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.
NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE

DOD STD 35-78A

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*

TELEPHONE NO.

DATE

DD FORM 1426 1 OCT 76

Replaces edition of 1 Jan 72 which may be used.

S/N 0102-LF-001-4260

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.