MILITARY STANDARD

AUTOMATED ENGINEERING
DOCUMENT PREPARATION SYSTEM

ADHESIVES

TO ALL HOLDERS OF DOD-STD-35-78A(MI):

1. THE FOLLOWING PAGES OF DOD-STD-35-78A(MI) HAVE BEEN REVISED AND SUPERSEDE THE PAGES LISTED:

NEW PAGE	DATE	SUPERSEDED PAGE	DATE
1	3 August 1978	(Reprinted without change)	
2	7 November 1980	2	3 August 1978
3	7 November 1980	3	3 August 1978
4	7 November 1980	4	3 August 1978
5	3 August 1978	(Reprinted without change)	
6	7 November 1980	6	3 August 1978
27	3 August 1978	(Reprinted without change)	
28	7 November 1980	28	3 August 1978
29	7 November 1980	29	3 August 1978
30	3 August 1978	(Reprinted without change)	
55	3 August 1978	(Reprinted without change)	
56	7 November 1980	56	3 August 1978
57	7 November 1980	57	3 August 1978
58	7 November 1980	58	3 August 1978
59	7 November 1980	59	3 August 1978
60	3 August 1978	(Reprinted without change)	
73	3 August 1978	(Reprinted without change)	
74	7 November 1980	74	3 August 1978
79	3 August 1978	(Reprinted without change)	
80	7 November 1980	80	3 August 1978
81	7 November 1980	81	3 August 1978
82	3 August 1978	(Reprinted without change)	
85	3 August 1978	(Reprinted without change)	
86	7 November 1980	86	3 August 1978
87	7 November 1980	87	3 August 1978
88	3 August 1978	(Reprinted without change)	
93	7 November 1980	93	3 August 1978
94	3 August 1978	(Reprinted without change)	
97	7 November 1980	97	3 August 1978
98	3 August 1978	(Reprinted without change)	
119	3 August 1978	(Reprinted without change)	

AREA EDS

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:24Z
Check the source to verify that this is the current version before use.

NEW PAGE	DATE	SUPERSEDED PAGE	DATE
121	7 November 1980	121	3 August 1978
122	7 November 1980	122	3 August 1978
123	7 November 1980	123	3 August 1978
124	7 November 1980	124	3 August 1978

2. THE FOLLOWING PAGES HAVE BEEN ADDED:

NEW PAGE	DATE	NEW PAGE	DATE
29a	7 November 1980	29g	7 November 1980
29b	7 November 1980	29h	7 November 1980
29c	7 November 1980	29i	7 November 1980
29d	7 November 1980	29j	7 November 1980
29e	7 November 1980	120	7 November 1980
29f	7 November 1980		

3. RETAIN THIS NOTICE PAGE AND INSERT BEFORE THE TABLE OF CONTENTS.

4. Holders of DOD-STD-35-78A(MI) will verify that page changes and additions indicated above have been entered. The notice page will be retained as a check sheet. This issuance together with appended pages is a separate publication. Each notice is to be retained by stocking points until the Military Standard is completely revised or canceled.

Custodians:
Army

Review activities:
Army - AT
Army - AV
Army - ER
Army - ME
Army - MR
Army - SG
Army - CR

User activity:
Army - AR

Preparing activity:
Army - MI

(Project EDS-314)

Source: https://assist.dla.mil -- Downloaded: 202640-26T07:24Z
Check the source to verify that this is the current version before use.

1. SCOPE

1.1 General. This dash-numbered part of the Automated Engineering Document Preparation System (AEDPS), provides detailed requirements for the preparation of Military Specification Exception (MSE) documentation for Adhesives.

1.2 Purpose. This military standard provides the necessary information to prepare a Specification Requirement Sheet (SRS) which will be used to generate an MSE by automated data processing.

1.3 Utilization. General instructions, quality assurance provisions, packaging, and notes, applicable to all AEDPS dash-numbered parts have been included in the basic document (DOD-STD-35) to avoid redundancy. Unless otherwise specified in this dash-numbered part, the following list contains additional subjects that are applicable to all AEDPS dash-numbered parts and are included in DOD-STD-35:

a. Writing Methodology
b. Document and Part Numbering
c. Applicable Documents
d. Single and Multi-item Specifications (Tabulation)
e. Keyword Code Index (KCI)
f. General Requirements of AEDPS

1.4 Military Specification Exception Title Index. The title code for an MSE shall be selected from one of the MSE titles listed in the Title Index (see table I). Data bases have been established for the generation of MSE's for the MSE titles indicated. If a suitable title code is not contained in the Title Index, leave the title code spaces on the SRS blank, and attach a request for the assignment of a title code. Include in the request the desired title and the base document identifier. A code will be assigned and the code, title, and base document will be made a part of the Title Index.

One of the six-digit codes listed in the Title Index, entered on an SRS, will specify that the title of the MSE will be the title shown in the Title Index.

Each MSE title listed in the Title Index is compatible with the document(s) listed with that title under base document. The list of base documents may or may not be a complete listing. The information shown under coverage is intended for the user's reference; when more than one document is listed for an MSE title, this information will be found useful in determining which of the documents is most suitable for use as the base document.

Reprinted without change.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

The MSE title may or may not be the same as the title used in DODISS, FIIG, or the base document. In general, the MSE title uses the basic federal item name listed in Cataloging Handbook H6. However, titles with additional modifying and identifying words are provided to assist in defining the scope of the MSE. Also, less restrictive titles are provided to prevent exclusion of items.

TABLE I. TITLE INDEX.

MSE TITLE	TITLE CODE	BASE DOCUMENT NUMBER	BASE DOCUMENT COVERAGE
ADHESIVE, AMMUNITION	601016	MMM-A-132	HEAT RESIST
		MMM-A-134	EPOXY
		MIL-A-3167	PLASTIC
		MIL-A-13374	DEXTRIN
		MIL-A-22397	MARINE
		MIL-A-22895	METAL
		MIL-A-23940	SILICONE RUBBER
		MIL-A-45059	CHIPBOARD TO TERNEPLATE
		MIL-A-50926	MR-23
		MIL-A-60091	DEMOLITION
		MIL-A-82484	SEALING COMPD
ADHESIVE, GENERAL PURPOSE	601019	MMM-A-100	GLUE
		MMM-A-110	ASPHALT
		MMM-A-115	ASPHALT
		MMM-A-121	SYNTHETIC
		MMM-A-122	BUTADIENE
		MMM-A-125	CASEIN TYPE
		MMM-A-131	GLASS TO METAL
		MMM-A-137	LINOLEUM
		MMM-A-150	ACOUSTICAL MATL
		MMM-A-180	POLYVINYL ACIT
		MMM-A-181	PHENOL
		MMM-A-182	RUBBER
		MMM-A-185	RUBBER
		MMM-A-187	SYNTHETIC
		MMM-A-188	UREA-RESIN
		MMM-A-189	SYNTHETIC
		MMM-A-193	VINYL
		MMM-A-1058	RUBBER BASE
		MMM-A-1931	EPOXY, FILLED
		MMM-A-2015	STICK FORM
		MMM-A-2048	FIRE RESISTANT
		MIL-A-3316	FIRE RESISTANT
		MIL-A-3920	OPTICAL
		MIL-A-22010	SOLVENT TYPE

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:24Z
Check the source to verify that this is the current version before use.

TABLE I. TITLE INDEX. (CONT)

MSE TITLE	TITLE CODE	BASE DOCUMENT NUMBER	BASE DOCUMENT COVERAGE
ADHESIVE, GENERAL PURPOSE	601019 (CONT)	MIL-A-22434	POLYESTER
		MIL-A-23092	CEMENT
		MIL-A-23941	EPOXY
		MIL-A-24179	FLEXIBLE
		MIL-A-46050	CYANOACRYLATE
		MIL-A-46091	BRAKE LINING
		MIL-A-46864	EPOXY
		MIL-A-46869	TEMP CURING
		MIL-A-47074	METAL BONDING
		MIL-A-47089	METAL FILLED
		MIL-A-47126	EPOXY
		MIL-A-47172	MODIFIED EPOXY
		MIL-A-47280	EPOXY
		MIL-A-47281	HEAT RES PRIMER
		MIL-A-47284	RESIN
		MIL-A-47295	ROCKET MOTOR
		MIL-A-48611	GLASS TO METAL
		MIL-A-81236	EPOXY
		MIL-A-81253	EPOXY
		MIL-A-81270	SYNTH RUBBER
		MIL-A-82569	NEOPRENE
		MIL-A-82636	BUTYL
		MIL-A-87135	NON-CONDUCTIVE
ADHESIVE, PACKAGING AND PACKING	601002	MMM-A-178	PAPER LABEL
		MMM-A-179	EMULSION
		MMM-A-250	FBRBD BOXES
		MMM-A-260	SEG WTRPRFD PPR
		MIL-G-413	GLUE
		MIL-A-17682	STARCH
		MIL-A-47282	HEAT PASTE
		MIL-A-47283	ELEV TEMP
ADHESIVE, PLASTIC	601008	MMM-A-130	CONTACT
		MIL-A-8576	ACRY PASTE
		MIL-A-14064	GRIND DISK CEM
		MIL-A-21016	POLYVINYL
		MIL-A-21366	TABLE TOP
		MIL-A-24456	VIBRATION
		MIL-A-52194	BONDING GLASS
ADHESIVE, SEALING	601018	MMM-A-105	CELLULOSE BASE
		MMM-A-139	SYNTHETIC
		MMM-A-1754	METAL FILLED

Supersedes page 3 of 3 August 1978

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:24Z
Check the source to verify that this is the current version before use.

TABLE I. TITLE INDEX. (CONT)

MSE TITLE	TITLE CODE	BASE DOCUMENT NUMBER	BASE DOCUMENT COVERAGE
ADHESIVE, SEALING	601018 (CONT)	MMM-A-1993	FLEX, FILLED
		MIL-C-2399	PATCHING
		MIL-A-3562	FILTERS SEAL
		MIL-A-5540	POLYCHLOROPRENE
		MIL-A-9117	AROMATIC FUEL
		MIL-A-43316	PATCHING
		MIL-A-46106	ELEC AND MECH
		MIL-A-46146	SILICONE, RTV
		MIL-A-47040	SILICONE, RTV HTM
		MIL-A-52685	BONDING
ADHESIVE,STRUCTURAL	601022	MMM-A-138	METAL TO WOOD
		MIL-A-25463	SANDWICH CONSTR
CEMENT, CONDUCTIVE, ROOM TEMPERATURE CURING, TWO COMPONENT	601023	MIL-A-47089	METAL FILLED
ADHESIVE, ANAEROBIC	601025	MIL-S-46163	THREAD LOCKING
ADHESIVE, CONTACT	601026	MMM-A-1617	RUBBER BASE, GP
		MIL-A-87134	HELMET LINERS
PRIMER, ADHESIVE	601027	MIL-P-47125	FOR SILICONE
		MIL-P-47216	POLYURETHANE
		MIL-P-47275	SILICONE
		MIL-P-47276	BONDING
		MIL-P-47277	SPECIAL PURPOSE
		MIL-P-47278	SILICONE RUBBER
		MIL-P-47279	SILICONE

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:24Z
Check the source to verify that this is the current version before use.

2. REFERENCED DOCUMENTS

2.1 Issues of documents. The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this standard to the extent specified herein.

SPECIFICATIONS

FEDERAL

MMM-A-100	Adhesive, Animal Glue
MMM-A-105	Adhesive and Sealing Compounds Cellulose Nitrate Base, Solvent Type
MMM-A-121	Adhesive, Bonding Vulcanized Synthetic Rubber to Steel
MMM-A-122	Adhesive, Butadiene Acrylonitrile Base, Medium Solids, General Purpose
MMM-A-131	Adhesive: Glass-to-Metal (for Bonding of Optical Elements)
MMM-A-134	Adhesive, Epoxy Resin, Metal to Metal Structural Bonding
MMM-A-137	Adhesive, Linoleum
MMM-A-138	Adhesive, Metal to Wood, Structural
MMM-A-139	Adhesive, Natural or Synthetic-Natural Rubber
MMM-A-177	Adhesive, Paste, Office and Photomounting
MMM-A-178	Adhesive, Paper Label, Water-Resistant
MMM-A-179	Adhesive: Paper Label, Water-Resistant, Water Emulsion Type
MMM-A-180	Adhesive, Polyvinyl Acetate Resin Emulsion (alkali Dispersable)
MMM-A-181	Adhesive, Phenol, Resorcinol, or Melamine Base
MMM-A-182	Adhesive, Rubber

Reprinted without change
Source: https://assist.dla.mil -- Downloaded: 202610-26T07:24Z
Check the source to verify that this is the current version before use.

MMM-A-187	Adhesive, Epoxy Resin Base Low and Intermediate Strength, General Purpose
MMM-A-188	Adhesive; Urea-Resin-Type (Liquid and Powder)
MMM-A-250	Adhesive, Water-Resistant
MMM-A-260	Adhesive, Water-Resistant, (for Sealing Waterproofed Paper)
MMM-A-1617	Adhesive, Rubber Base, General Purpose
MMM-A-1754	Adhesive and Sealing Compound, Epoxy, Metal Filled
MMM-A-1931	Adhesive, Epoxy, Silver Filled, Conductive

MILITARY

MIL-A-3316	Adhesive, Fire-Resistant, Thermal Insulation
MIL-A-3920	Adhesive, Optical Thermosetting.
MIL-A-21016	Adhesive, Resilient Deck Covering
MIL-A-23940	Adhesive, Silicone Rubber for Igniter Mark 265
MIL-A-23941	Adhesive, Epoxy Type, Two Part
MIL-A-25463	Adhesive, Metallic Structural Sandwich Construction
MIL-A-43316	Adhesive, Patching for Chloroprene Coated or Chlorosulphonated Polyethylene Coated Fabrics
MIL-A-45059	Adhesive for Bonding Chipboard to Teyneplate, Tinplate, and Zincplate
MIL-A-46050	Adhesive, Cyanoacrylate, Rapid Room-Temperature Curing Solventless

Source: https://quist.dla.mil -- Downloaded: 202610-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
1912	THE SOLVENT(S) SHALL BE IN ACCORDANCE WITH 1912.
1914	BONDING RANGE. THE BONDING RANGE SHALL BE 1914 MINUTE(S).
1916	CONSISTENCY. THE CONSISTENCY SHALL BE 1916.
1918	APPEARANCE. THE COMPOUND SHALL BE FREE OF LUMPS, COARSE PARTICLES, AND AIR BUBBLES BEFORE MOLDING OR POTTING, AND AFTER CURING IT SHALL HAVE AN EVEN TEXTURE FREE OF LUMPS AND AIR BUBBLES.
6375	COMPOSITION. THE COMPOSITION, FORMULATION OR MIXTURE (AS APPLICABLE) SHALL BE AS SPECIFIED HEREIN. THE INGREDIENT QUANTITIES SHALL BE SHOWN IN INTERNATIONAL (SI) SYSTEM OF UNITS SUCH AS GRAMS, LITRES, ETC., OR U.S. STANDARDS SUCH AS PINTS, QUARTS OR GALLONS, AS SPECIFIED IN THE TABLE.
	WEIGHT.
1583	THE WEIGHT SHALL BE NOT LESS THAN 1583 POUND(S) PER GALLON.
2601	THE WEIGHT SHALL BE NOT LESS THAN 2601 KILOGRAM(S) PER CUBIC METER.

Reprinted without change
Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
WEIGHT (CONT)	
NOMINAL (SELECT ONE)	
(POUNDS PER GALLON)	1581
(KILOGRAMS PER CUBIC METER)	2602
MAXIMUM (SELECT ONE)	
(POUNDS PER GALLON)	1589
(KILOGRAMS PER CUBIC METER)	2604
CURING DURATION	
MAXIMUM (SELECT ONE)	
(MINUTES)	1568
(HOURS)	1570
(DAYS)	1572

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
1581	THE WEIGHT SHALL BE 1581 POUND(S) PER GALLON.
2602	THE WEIGHT SHALL BE 2602 KILOGRAM(S) PER CUBIC METER.
1589	THE WEIGHT SHALL BE NOT GREATER THAN 1589 POUND(S) PER GALLON.
2604	THE WEIGHT SHALL BE NOT GREATER THAN 2604 KILOGRAM(S) PER CUBIC METER.
1568	CURING DURATION. THE CURING DURATION SHALL BE NOT GREATER THAN 1568 MINUTE(S).
1570	CURING DURATION. THE CURING DURATION SHALL BE NOT GREATER THAN 1570 HOUR (S).
1572	CURING DURATION. THE CURING DURATION SHALL BE NOT GREATER THAN 1572 DAY(S).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
CURING DURATION (CONT)	
SEE CURING DURATION TABLE.	
TORQUE	
MINIMUM BREAKAWAY TORQUE	
SEE TORQUE TABLE.	

New page

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR
CODE STANDARD PARAGRAPH

CURING DURATION. THE CURING DURATION SHALL BE IN ACCORDANCE WITH THE CURING DURATION TABLE.

CURING DURATION TABLE

TYPE	GRADE	TIME AFTER APPLICATION MINUTES	TIME AFTER APPLICATION HOURS	MINIMUM BREAKAWAY TORQUE INCH-POUNDS
3301	3302	3303	3304	3305
3306	3307	3308	3309	3310
3311	3312	3313	3314	3315
3316	3317	3318	3319	3320
3321	3322	3323	3324	3325
3326	3327	3328	3329	3330

TORQUE.

THE MINIMUM BREAKAWAY TORQUE SHALL BE AS SPECIFIED IN THE TORQUE TABLE.

TORQUE TABLE

TYPE	GRADE	MINIMUM BREAKAWAY TORQUE- INCH-POUNDS CADMIUM	ZINC
3401	3402	3403	3404
3405	3406	3407	3408
3409	3410	3411	3412
3413	3414	3415	3416
3417	3418	3419	3420
3421	3422	3423	3424

New page

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
TORQUE (CONT)	
SEE TORQUE TABLE. (CONT)	
LOCKING TORQUE	3100
LOCKING TORQUE (PLATED METAL)	
SEE LOCKING TORQUE (PLATED METAL) TABLE.	

New page

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR
CODE STANDARD PARAGRAPH

NOTE A: 3495.

NOTE B: 3496.

NOTE C: 3497.

NOTE D: 3498.

NOTE E: 3499.

3100 LOCKING TORQUE. THE LOCKING TORQUE SHALL BE AS SPECIFIED IN THE FOLLOWING TABLE(S).

LOCKING TORQUE (PLATED METAL) TABLE

TYPE AND GRADE	PLATED STEEL (PRIMED)				VISCOSITY (CENTIPOISE)	COLOR
	CADMIUM		ZINC			
	BREAKAWAY	PREVAIL	BREAKAWAY	PREVAIL		
3101	3102	3103	3104	3105	3106	3107
3108	3109	3110	3111	3112	3113	3114
3115	3116	3117	3118	3119	3120	3121
3122	3123	3124	3125	3126	3127	3128
3129	3130	3131	3132	3133	3134	3135
3136	3137	3138	3139	3140	3141	3142

NOTE A: 3195.

NOTE B: 3196.

NOTE C: 3197.

NOTE D: 3198.

NOTE E: 3199.

New page

Source: https://assist.dla.mil -- Downloaded: 2026l0-26T07:24Z
Check the source to verify that this is the currentversion before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
TORQUE (CONT)	
LOCKING TORQUE (CONT)	
LOCKING TORQUE (UNPLATED METAL)	
SEE LOCKING TORQUE (UNPLATED METAL) TABLE.	

ADHESIVE CHARACTERISTICS	
SEE ADHESIVE CHARACTERISTICS TABLE.	

New page

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR
CODE STANDARD PARAGRAPH

LOCKING TORQUE (UNPLATED METAL) TABLE

TYPE AND GRADE	STEEL BREAKAWAY	STEEL PREVAIL	ALUMINUM BREAKAWAY	ALUMINUM PREVAIL	VISCOSITY (CENTIPOISE)	COLOR
3201	3202	3203	3204	3205	3206	3207
3208	3209	3210	3211	3212	3213	3214
3215	3216	3217	3218	3219	3220	3221
3222	3223	3224	3225	3226	3227	3228
3229	3230	3231	3232	3233	3234	3235
3236	3237	3238	3239	3240	3241	3242

NOTE A: 3295.

NOTE B: 3296.

NOTE C: 3297.

NOTE D: 3298.

NOTE E: 3299.

ADHESIVE CHARACTERISTICS. ADHESIVE CHARACTERISTICS SHALL BE IN ACCORDANCE WITH THE ADHESIVE CHARACTERISTICS TABLE.

ADHESIVE CHARACTERISTICS TABLE

CHARACTERISTIC	VALUE	TEST METHOD
ARC RESISTANCE (SECONDS)	3501	3502
ABRASION RESISTANCE (GRAMS PER 1000 CYCLES)	3503	3504
BEND STRENGTH (POUNDS)	3505	3506

New page

Source: https://assist.dla.mil -- Downloaded: 202640-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
ADHESIVE CHARACTERISTICS (CONT)	
SEE ADHESIVE CHARACTERISTICS TABLE. (CONT)	

New page

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR
CODE STANDARD PARAGRAPH

ADHESIVE CHARACTERISTICS TABLE (CONT)

CHARACTERISTIC	VALUE	TEST METHOD
COEF OF THERMAL EXPANSION (IN/IN/DEG C)	3507	3508
COEF OF THERMAL EXPANSION (IN/IN/DEG F)	3509	3510
COEF OF THERMAL EXPANSION (MM/MM/DEG C)	3511	3512
COEF OF THERMAL EXPANSION (CM/CM/DEG C)	3513	3514
FLASH POINT (DEG C)	3515	3516
FLEXURAL DEFORMATION TEMP (DEGREES C)	3517	3518
FLEXURAL STRENGTH (PSI)	3519	3520
FLEXURAL MODULUS OF ELASTICITY (PSI)	3521	3522
GAP FILLING ABILITY (INCH)	3523	3524
HEAT DISTORTION TEMP (DEGREES C)	3525	3526
IMPACT STRENGTH (FOOT-POUNDS)	3527	3528
IMPACT STRENGTH IZOD (FOOT-POUNDS/INCH)	3529	3530
MIXING RATIO (BY WEIGHT)	3531	3532
MIXING RATIO (BY VOLUME)	3533	3534
MODULUS OF RUPTURE (PSI)	3535	3536
POROSITY (PERCENT)	3537	3538
SHRINKAGE, CURE (INCH/INCH)	3539	3540
SHRINKAGE, LINEAR (PERCENT)	3541	3542
SHRINKAGE, LINEAR (INCH(S))	3543	3544
SHRINKAGE, VOLUME (PERCENT)	3545	3546
SPECIFIC GRAVITY	3547	3548
SURFACE RESISTIVITY (OHMS)	3549	3550
TENSILE MODULUS (PSI)	3551	3552
TENSILE SHEAR (LAP) STRENGTH (PSI)	3553	3554
WATER ABSORPTION (PERCENT)	3555	3556
3557	3558	3577
3559	3560	3578
3561	3562	3579
3563	3564	3580
3565	3566	3581
3567	3568	3582
3569	3570	3583
3571	3572	3584
3573	3574	3585
3575	3576	3586

New page

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
ADHESIVE CHARACTERISTICS (CONT)	
SEE ADHESIVE CHARACTERISTICS TABLE. (CONT)	
BONDING PRESSURE	
MAXIMUM (SELECT ONE)	
(POUNDS PER SQUARE INCH)	1920
(KILOPASCALS)	1922
COLOR	
(NAME)	1924
(DOC DES)	1926

New page

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR
CODE STANDARD PARAGRAPH

ADHESIVE CHARACTERISTICS TABLE (CONT)

CHARACTERISTIC	VALUE	TEST METHOD
NOTE A: 3590.		
NOTE B: 3591.		
NOTE C: 3592.		
NOTE D: 3593.		
NOTE E: 3594.		
NOTE F: 3595.		
NOTE G: 3596.		
NOTE H: 3597.		
NOTE I: 3598.		
NOTE J: 3599.		

1920 BONDING PRESSURE. THE BONDING PRESSURE SHALL BE NOT GREATER THAN 1920 POUND(S) PER SQUARE INCH.

1922 BONDING PRESSURE. THE BONDING PRESSURE SHALL BE NOT GREATER THAN 1922 KILOPASCAL(S).

1924 COLOR. THE COLOR SHALL BE 1924.

1926 THE COLOR SHALL BE IN ACCORDANCE WITH 1926.

New page

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
COLOR (CONT)	
(DOC DES) (CONT)	
(DESIGNATION)	1928
(CLASS NUMBER)	1930
MATERIALS	
FILLER	
(NAME)	2614
(DOC DES)	2615
PROMOTER	
(NAME)	2616
(DOC DES)	2617
PRIMER	
(NAME)	2618
(DOC DES)	2619
ACTIVATOR	
(NAME)	2606
(DOC DES)	2605
CATALYST	
(NAME)	2608
(DOC DES)	2607

Reprinted without change
Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR
CODE STANDARD PARAGRAPH

1696 CORROSION OF METALS. THE ADHESIVE SHALL NOT CAUSE DISCOLORATION OR CORROSION.

1688 CORROSION OF METALS. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1688.

1690 CORROSION OF METALS. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH 1690.

TEST METHODS SHALL BE AS FOLLOWS:

1839 BRASS OVER WATER.

1841 STEEL OVER WATER.

1843 ALUMINUM OVER WATER.

1845 COPPER WIRE BY DIRECT CONTACT.

1847 STEEL AND ALUMINUM BY DIRECT CONTACT.

1706 DENSITY. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1706.

1842 DENSITY. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH ASTMD1875.

1844 DENSITY. THE REQUIREMENT(S) SHALL BE AS FOLLOWS:

1846 THE DENSITY OF THE MATERIAL SHALL BE 1846 POUNDS PER GALLON.

Reprinted without change
Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
DENSITY (CONT)	
DENSITY OF ADHESIVE (CONT)	
(KILOGRAMS PER CUBIC METER)	1850
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	1700
PER ASTMD1875.	1702
DIELECTRIC CONSTANT	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	2000
AS FOLLOWS:	2002
MAXIMUM DIELECTRIC CONSTANT AT 60 HERTZ (VALUE)	2004
MAXIMUM DIELECTRIC CONSTANT AT 1 KILOHERTZ (VALUE)	2006
MAXIMUM DIELECTRIC CONSTANT AT 1 MEGAHERTZ (VALUE)	2008
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	2010
PER ASTMD150.	2012

Source: https://assist.dla.mil - Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
1850	THE DENSITY OF THE MATERIAL SHALL BE 1850 KILOGRAM(S) PER CUBIC METER.
1700	DENSITY. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1700.
1702	DENSITY. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH ASTMD1875.
2000	DIELECTRIC CONSTANT. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2000.
2002	DIELECTRIC CONSTANT. THE REQUIREMENT(S) SHALL BE AS FOLLOWS:
2004	THE DIELECTRIC CONSTANT AT 60 HERTZ SHALL BE NOT GREATER THAN 2004.
2006	THE DIELECTRIC CONSTANT AT 1 KILOHERTZ SHALL BE NOT GREATER THAN 2006.
2008	THE DIELECTRIC CONSTANT AT 1 MEGAHERTZ SHALL BE NOT GREATER THAN 2008.
2010	DIELECTRIC CONSTANT. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2010.
2012	DIELECTRIC CONSTANT. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH ASTMD150.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
DIELECTRIC STRENGTH	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	2032
AS FOLLOWS:	2034
MINIMUM DIELECTRIC STRENGTH (SELECT ONE)	
(VOLTS PER 0.001 INCH)	2036
(VOLTS PER MILLIMETER)	2038
MINIMUM BREAKDOWN VOLTAGE (VOLTS)	2040
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	2042
PER ASTMD149.	2044
NUMBER OF SPECIMENS TO BE TESTED (QUANTITY)	2046
TEST TEMPERATURE (DEGREES CELSIUS)	2048
TOLERANCE PLUS OR MINUS (DEGREES CELSIUS)	2050
DISSIPATION FACTOR	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	2052

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
2032	DIELECTRIC STRENGTH. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2032.
2034	DIELECTRIC STRENGTH. THE REQUIREMENT(S) SHALL BE AS FOLLOWS:
2036	THE DIELECTRIC STRENGTH SHALL BE NOT LESS THAN 2036. VOLTS PER 0.001 INCH.
2038	THE DIELECTRIC STRENGTH SHALL BE NOT LESS THAN 2038 VOLTS PER MILLIMETER.
2040	THE BREAKDOWN VOLTAGE SHALL BE NOT LESS THAN 2040 VOLT(S).
2042	DIELECTRIC STRENGTH. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2042.
2044	DIELECTRIC STRENGTH. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH ASTMD149.
2046	THERE SHALL BE 2046 SPECIMEN(S) TESTED.
2048	THE TEST TEMPERATURE SHALL BE 2048 DEGREES CELSIUS.
2050	THE TEST TEMPERATURE TOLERANCE SHALL BE PLUS OR MINUS 2050 DEGREES CELSIUS.
2052	DISSIPATION FACTOR. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2052.

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
DISSIPATION FACTOR (CONT)	
REQUIREMENTS (CONT)	
AS FOLLOWS:	2054
MINIMUM DISSIPATION FACTOR AT 60 HERTZ (VALUE)	2056
MINIMUM DISSIPATION FACTOR AT 1 KILOHERTZ (VALUE)	2055
MINIMUM DISSIPATION FACTOR AT 1 MEGAHERTZ (VALUE)	2060
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	2062
PER ASTMD150.	2064
NUMBER OF SPECIMENS TO BE TESTED (QUANTITY)	2066
SPECIMEN WIDTH (SELECT ONE)	
(INCHES)	2068
(MILLIMETERS)	2070
SPECIMEN THICKNESS (SELECT ONE)	
(INCHES)	2072
(MILLIMETERS)	2074

Reprinted without change
Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
4754	FUNGUS. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 4754.
4755	FUNGUS. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH METHOD 508 OF MIL-STD-810.
4756	TEST PERIOD SHALL BE 4756 DAY(S).
2156	THE TEST METHOD SHALL BE 2156.
2158	THE NUMBER OF SPECIMENS TO BE TESTED SHALL BE 2158.
2160	HARDNESS. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2160.
2162	HARDNESS. THE REQUIREMENT(S) SHALL BE AS FOLLOWS:
2164	THE AVERAGE DUROMETER READING SHALL BE NOT LESS THAN 2164.
2166	THERE SHALL BE NOT LESS THAN 2166 DUROMETER READINGS.
2168	DUROMETER SCALE LETTER 2168 SHALL APPLY.

Reprinted without change
Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
HARDNESS (CONT)	
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	2170
PER ASTMD2240.	2172
HUMIDITY	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	4798
MAXIMUM MOISTURE ABSORPTION (PERCENT)	2198
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	4788
PER MIL-A-3920.	2200
EXPOSURE TO RELATIVE HUMIDITY (PERCENT)	4789
TEST TEMPERATURE (DEGREES CELSIUS)	2202
TOLERANCE PLUS OR MINUS (DEGREES CELSIUS)	2204

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
2213	HYDROLYTIC STABILITY. THE REQUIREMENT(S) SHALL BE AS FOLLOWS:
2214	THE TENSILE STRENGTH SHALL BE NOT LESS THAN 2214 POUNDS PER SQUARE INCH.
2216	THE TENSILE STRENGTH SHALL BE NOT LESS THAN 2216 KILOPASCAL(S).
2217	THE HARDNESS READING SHALL BE NOT LESS THAN 2217 SHORE A.
2215	THE MATERIAL SHALL REMAIN WITHIN THE SPECIFIED HARDNESS.
2218	HYDROLYTIC STABILITY. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2218.
2220	HYDROLYTIC STABILITY. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH 2220.
4819	IMMERSION. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 4819.
2900	IMMERSION. THE REQUIREMENT(S) SHALL BE AS FOLLOWS:
2257	THE PEEL STRENGTH SHALL BE NOT LESS THAN 2257 POUNDS PER INCH WIDTH.
2259	THE PEEL STRENGTH SHALL BE NOT LESS THAN 2259 KILOGRAMS PER MILLIMETER WIDTH.

Reprinted without change

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
IMMERSION (CONT)	
AS FOLLOWS: (CONT)	
NO EVIDENCE OF PHYSICAL DAMAGE.	2261
MAXIMUM MEDIA ABSORPTION (PERCENT)	2263
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	4809
PER DOCUMENT (DOC DES)	2256
TEST MEDIA (NAME)	2258
(DOC DES)	2260
TEST TEMPERATURE (DEGREES CELSIUS)	2262
DURATION (MINUTES)	2264
IMMERSION DURATION (SELECT ONE)	
(MINUTES)	2266
(HOURS)	2268
AIR DRIED DURATION (SELECT ONE)	
(MINUTES)	2270
(HOURS)	2272
LOW TEMPERATURE FLEXIBILITY	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	1800

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
2261	THERE SHALL BE NO EVIDENCE OF PHYSICAL DAMAGE.
2263	THE MEDIA ABSORPTION SHALL BE NOT GREATER THAN 2263 PERCENT.
4809	IMMERSION. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 4809.
2256	IMMERSION. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH 2256.
2258	THE TEST MEDIA SHALL BE 2258.
2260	THE TEST MEDIA SHALL BE IN ACCORDANCE WITH 2260.
2262	THE TEST TEMPERATURE SHALL BE 2262 DEGREES CELSIUS.
2264	THE DURATION SHALL BE 2264 MINUTES.
2266	THE IMMERSION DURATION SHALL BE 2266 MINUTE(S).
2268	THE IMMERSION DURATION SHALL BE 2268 HOUR(S).
2270	THE AIR DRIED DURATION SHALL BE 2270 MINUTE(S).
2272	THE AIR DRIED DURATION SHALL BE 2272 HOUR(S).
1800	LOW TEMPERATURE FLEXIBILITY. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1800.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
LOW TEMPERATURE FLEXIBILITY (CONT)	
REQUIREMENTS (CONT)	
NO CRACKING OR FLAKING.	1804
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	1782
PER MMM-A-105.	1784
BAKE DURATION (HOURS)	1786
BAKE TEMPERATURE (DEGREES CELSIUS)	1788
TEMPERATURE TOLERANCE PLUS OR MINUS (DEGREES CELSIUS)	1790
COLD BOX TEMPERATURE (DEGREES CELSIUS)	1792
TEMPERATURE TOLERANCE PLUS OR MINUS (DEGREES CELSIUS)	1794
MANDREL DIAMETER (SELECT ONE)	
(INCHES)	1796
(MILLIMETERS)	1798
ODOR	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	1814
THE ADHESIVE SHALL BE FREE FROM OBNOXIOUS OR OBJECTIONABLE ODOR.	1816

Reprinted without change

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
1808	ODOR. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1808.
1810	ODOR. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH METHOD 4401 OF FED-STD-141.
2274	PEEL STRENGTH. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2274.
2276	PEEL STRENGTH. THE REQUIREMENT(S) SHALL BE AS FOLLOWS:
2278	THE PEEL STRENGTH SHALL BE NOT LESS THAN 2278 POUND(S) PER INCH OF WIDTH.
2280	THE PEEL STRENGTH SHALL BE NOT LESS THAN 2280 NEWTON(S) PER MILLIMETER OF WIDTH.
2282	PEEL STRENGTH. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2282.
2284	PEEL STRENGTH. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH 2284.
2286	THE TEST SPECIMEN TEMPERATURE SHALL BE 2286 DEGREES CELSIUS.
2288	THE TEST SPECIMEN TEMPERATURE TOLERANCE SHALL BE PLUS OR MINUS 2288 DEGREES CELSIUS.

Reprinted without change

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
POT LIFE	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	2290
POT LIFE	
MINIMUM (SELECT ONE)	
(MINUTES)	2291
(HOURS)	2292
TEMPERATURE (DEGREES CELSIUS)	2294
TOLERANCE PLUS OR MINUS (DEGREES CELSIUS)	2293
FREE OF CRACKS AND BUBBLES.	2296
PROPER MIXING INSTRUCTION BY MANUFACTURER.	2298
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	2300
TESTING SHALL BE ____	2301
PER DOCUMENT (DOC DES)	2302
SAMPLE SIZE (SELECT ONE)	
(MILLILITERS)	2304
(OUNCES)	2306
(GRAMS)	2307

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
2290	POT LIFE. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2290.
2291	POT LIFE. THE POT LIFE SHALL BE NOT LESS THAN 2291 MINUTE(S).
2292	POT LIFE. THE POT LIFE SHALL BE NOT LESS THAN 2292 HOUR(S).
2294	THE TEMPERATURE SHALL BE 2294 DEGREES CELSIUS.
2293	THE TOLERANCE SHALL BE PLUS OR MINUS 2293 DEGREES CELSIUS.
2296	THE COMPOUND SHALL BE FREE OF CRACKS AND BUBBLES.
2298	PROPER MIXING INSTRUCTIONS SHALL BE FURNISHED BY THE MANUFACTURER.
2300	POT LIFE. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2300.
2301	POT LIFE. TESTING SHALL BE 2301.
2302	POT LIFE. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH 2302.
2304	THE SAMPLE SIZE SHALL BE 2304 MILLILITER(S).
2306	THE SAMPLE SIZE SHALL BE 2306 OUNCE(S).
2307	THE SAMPLE SIZE SHALL BE 2307 GRAM(S).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
SAG	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	2698
MAXIMUM SAG FLOW (INCHES)	2700
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	2702
PER ASTMD2730.	2704
SALT SPRAY	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	4878
THE MATERIAL SHALL SHOW NO LOSS OF ADHESION AND SHALL NOT BECOME TACKY.	2310
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	4770
PER DOCUMENT (DOC DES)	2901
SHEAR STRENGTH	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	2318
AS FOLLOWS:	2320

Reprinted without change
Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
3001	SPECIAL PREPARATION SHALL BE 3001.
3002	THE CONDITIONING DURATION SHALL BE 3002 HOUR(S).
3003	THE CONDITIONING DURATION SHALL BE 3003 MINUTE(S).
3004	THE CONDITIONING TEMPERATURE SHALL BE 3004 DEGREES CELSIUS.
3005	THE CURING DURATION SHALL BE 3005 HOUR(S).
3006	THE CURING TEMPERATURE SHALL BE 3006 DEGREES CELSIUS.
1934	SHELF LIFE (STORAGE). THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1934.
1936	SHELF LIFE (STORAGE). THE REQUIREMENT(S) SHALL BE AS FOLLOWS:
1938	BOTH PARTS A AND B SHALL MEET ALL REQUIREMENTS AFTER TESTS.
1940	THE COMPONENTS SHALL MEET ALL REQUIREMENTS AFTER TESTS.
1942	THE UNMIXED COMPONENTS, IN UNOPENED CONTAINERS SHALL MEET ALL REQUIREMENTS AFTER STORAGE.
1943	SHELF LIFE (STORAGE). TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1943.
1945	SHELF LIFE (STORAGE). TESTING SHALL BE PERFORMED IN ACCORDANCE WITH 1945.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
SHELF LIFE (STORAGE) (CONT)	
TEST METHODS (CONT)	
TEST AS FOLLOWS:	1941
STORAGE DURATION (SELECT ONE)	
(MINUTES)	1947
(HOURS)	1949
(WEEKS)	1951
(MONTHS)	1953
(YEARS)	1955
STORAGE TEMPERATURE (DEGREES CELSIUS)	1957
TOLERANCE (DEGREES CELSIUS)	1959
TEAR RESISTANCE	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	2338
AS FOLLOWS:	2340
MINIMUM (SELECT ONE)	
(POUNDS PER INCH OF THICKNESS)	2342
(NEWTONS PER MILLIMETER OF THICKNESS)	2344
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	2346

Reprinted without change
Source: https://assist.dla.mil -- Downloaded: 202610-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
2348	TEAR RESISTANCE. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH MIL-A-47040.
2354	CONDITIONING PERIOD SHALL BE 2354 HOUR(S).
2356	CONDITIONING TEMPERATURE SHALL BE 2356 DEGREES CELSIUS.
2358	CONDITIONING TEMPERATURE TOLERANCE SHALL BE PLUS OR MINUS 2358 DEGREES CELSIUS.
2360	RELATIVE HUMIDITY SHALL BE 2360 PERCENT.
2362	RELATIVE HUMIDITY TOLERANCE SHALL BE PLUS OR MINUS 2362 PERCENT.
6228	TEMPERATURE, HIGH. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 6228.
6229	TEMPERATURE, HIGH. THERE SHALL BE NO EVIDENCE OF PHYSICAL DAMAGE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
TEMPERATURE, HIGH (CONT)	
NO EVIDENCE OF PHYSICAL DAMAGE. (CONT)	
MINIMUM SHORE "A" HARDNESS (NUMBER)	2368
MINIMUM TENSILE STRENGTH (SELECT ONE)	
(POUNDS PER SQUARE INCH)	2370
(KILOPASCALS)	2372
NO LOSS OF ADHESION.	2371
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	6217
PER DOCUMENT (DOC DES)	2374

Reprinted without change
Source: https://assist.dla.mil -- Downloaded: 202610-26T07:24Z
Check the source to verify that this is the current version before use.

APPENDIX A

CHARACTERISTIC CODE INDEX

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

CHARACTERISTIC CODE INDEX

CHAR CODE	PAGE NO.	CHAR CODE	PAGE NO.	CHAR CODE	PAGE NO.	CHAR CODE	PAGE NO.
0101	20	1650	46	1803	48	1945	92
0102	20	1652	46	1804	82	1946	36
0103	20	1654	46	1808	84	1947	94
0104	20	1657	44	1810	84	1948	36
0105	20	1660	44	1814	82	1949	94
0107	22	1662	44	1816	82	1950	36
0108	22	1666	48	1839	54	1951	94
0700	20	1668	48	1841	54	1952	36
0800	20	1670	48	1842	54	1953	94
1003	20	1672	48	1843	54	1954	36
1004	20	1680	48	1844	54	1955	94
1005	20	1688	54	1845	54	1956	38
100E	20	1690	54	1846	54	1957	94
1008	20	1694	52	1847	54	1958	38
1172	76	1696	54	1850	56	1959	94
156E	28	1700	56	1900	24	1962	36
1570	28	1702	56	1902	24	1964	36
157E	28	1706	54	1904	24	1966	38
1581	28	1734	40	1906	24	1968	38
158E	26	1746	42	1908	24	1970	38
1589	28	1758	44	1910	24	1972	38
1602	34	1765	76	1912	26	1974	38
1604	34	1766	46	1914	26	1976	38
1606	34	1768	76	1916	26	1978	40
1608	34	1772	76	1918	26I	1980	40
1610	36	1774	76	1920	29I	1981	40
1612	36	1776	76	1922	29I	1982	38
1614	36	1778	76	1924	29I	1983	38
1618	40	1782	82	1926	29	1984	38
1620	40	1784	82	1928	30	1985	38
1622	42	1786	82	1930	30	1986	50
162E	42	1788	82	1932	34	1987	36
1628	42	1790	82	1934	92	1990	50
1630	42	1792	82	1936	92	1992	50
1633	40	1794	82	1938	92	1994	50
1636	40	1796	82	1940	92	1996	50
1638	40	1798	82	1941	94	2000	56
1640	40	1800	80	1942	92	2002	56
1644	46	1801	48	1943	92	2004	56
1648	46	1802	48	1944	36	200E	56

New page

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

CHARACTERISTIC CODE INDEX (CONT)

CHAR CODE	PAGE NO.	CHAR CODE	PAGE NO.	CHAR CODE	PAGE NO.	CHAR CODE	PAGE NO.
2008	56	2126	64	2256	80	2324	90
2010	56	2128	64	2257	78	2326	90
2012	56	2130	64	2258	80	2328	90
2032	58	2132	64	2259	78	2330	90
2034	58	2134	64	2260	80	2332	90
203E	58	2136	64	2261	80	2334	90
2038	58	2138	64	2262	80	2336	90
2040	58	2140	64	2263	80	2338	94
2042	58	2141	76	2264	80	2340	94
2044	58	2142	66	2266	80	2342	94
204E	58	2144	66	2268	80	2344	94
2048	58	2146	66	2270	80	2346	94
2050	58	2148	66	2272	80	2348	96
2052	58	2150	66	2274	84	2354	96
2054	60	2152	66	2276	84	2356	96
2055	60	2154	66	2278	84	2358	96
2056	60	2156	72	2280	84	2360	96
2060	60	2158	72	2282	84	2362	96
2062	60	2160	72	2284	84	2368	98
2064	60	2162	72	2286	84	2370	98
2066	60	2164	72	2288	84	2371	98
2068	60	2166	72	2290	86	2372	98
2070	60	2168	72	2291	86	2374	98
2072	60	2170	74	2292	86	2394	100
2074	60	2172	74	2293	86	2396	100
2076	62	2198	74	2294	86	2398	100
2078	62	2200	74	2296	86	2400	100
2080	62	2202	74	2298	86	2402	100
2082	62	2204	74	2300	86	2404	100
2084	62	2206	76	2301	86	2406	100
2086	62	2208	76	2302	86	2414	100
2088	62	2210	76	2304	86	2436	100
2090	62	2212	76	2306	86	2438	102
2112	62	2213	78	2307	86	2440	102
2114	62	2214	78	2310	88	2442	102
211E	64	2215	78	2318	88	2444	102
211E	64	2216	78	2320	88	2446	102
2120	64	2217	78	2321	90	2450	102
2122	64	2218	78	2322	90	2452	102
2124	64	2220	78	2323	90	2454	102

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

CHARACTERISTIC CODE INDEX (CONT)

CHAR CODE	PAGE NO.	CHAR CODE	PAGE NO.	CHAR CODE	PAGE NO.	CHAR CODE	PAGE NO.
2456	102	2565	114	2662	42	2738	52
2458	102	2580	112	2664	42	2740	52
2460	102	2582	112	2666	44	2800	32
2461	104	2584	112	2668	44	2802	32
2462	102	2586	112	2670	44	2804	32
2464	104	2601	26	2672	44	2806	32
2466	104	2602	28	2674	44	2812	32
2486	104	2604	28	2676	44	2814	32
2488	104	2605	30	2678	44	2816	32
2490	104	2606	30	2680	44	2900	78
2500	106	2607	30	2682	46	2901	88
2502	106	2608	30	2684	46	2902	90
2504	106	2610	32	2686	46	3000	90
2506	106	2611	32	2688	46	3001	92
2508	106	2612	32	2690	46	3002	92
2510	106	2613	32	2692	46	3003	92
2512	106	2614	30	2694	48	3004	92
2514	106	2615	30	2696	48	3005	92
2516	106	2616	30	2698	88	3006	92
2518	108	2617	30	2700	88	3008	104
2520	108	2618	30	2702	88	3010	104
2524	108	2619	30	2704	88	3012	104
2525	108	2628	68	2706	66	3014	106
2526	108	2630	68	2708	66	3015	106
2528	108	2632	68	2710	66	3018	110
2530	108	2634	68	2712	66	3020	110
2532	108	2636	68	2714	66	3022	110
2534	108	2638	68	2716	68	3024	110
2536	108	2640	68	2718	68	3026	112
2538	108	2642	68	2720	68	3028	112
2540	108	2644	70	2722	50	3030	112
2542	110	2646	70	2723	50	3032	112
2544	110	2648	70	2724	50	3034	112
2548	110	2649	70	2726	50	3036	112
2550	110	2650	42	2728	52	3038	112
2554	110	2652	42	2730	52	3040	1128
2556	110	2654	42	2732	52	3043	29C
2558	112	2656	42	2733	52	3100	29D
2559	112	2658	42	2734	52	3101	29D
2560	112	2660	42	2736	52	3102	29D

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:24Z
Check the source to verify that this is the current version before use.

CHARACTERISTIC CODE INDEX (CONT)

CHAR CODE	PAGE NO.	CHAR CODE	PAGE NO.	CHAR CODE	PAGE NO.	CHAR CODE	PAGE NO.
3103	29D	3195	29D	3236	29F	3329	29B
3104	29D	3196	29D	3237	29F	3330	29B
3105	29D	3197	29D	3238	29F	3401	29B
3106	29D	3198	29D	3239	29F	3402	29B
3107	29D	3199	29F	3240	29F	3404	29B
3108	29D	3201	29F	3241	29F	3405	29B
3109	29D	3202	29F	3242	29F	3406	29B
3110	29D	3203	29F	3295	29F	3407	29B
3111	29D	3204	29F	3296	29F	3408	29B
3112	29D	3205	29F	3297	29F	3409	29B
3113	29D	3206	29F	3298	29F	3410	29B
3114	29D	3207	29F	3299	29B	3411	29B
3115	29D	3208	29F	3301	29B	3412	29B
3116	29D	3209	29F	3302	29B	3413	29B
3117	29D	3210	29F	3303	29B	3414	29B
3118	29D	3211	29F	3304	29B	3415	29B
3119	29D	3212	29F	3305	29B	3416	29B
3120	29D	3213	29F	3306	29B	3417	29B
3121	29D	3214	29F	3307	29B	3418	29B
3122	29D	3215	29F	3308	29B	3419	29B
3123	29D	3216	29F	3309	29B	3420	29B
3124	29D	3217	29F	3310	29B	3421	29B
3125	29D	3218	29F	3311	29B	3422	29B
3126	29D	3219	29F	3312	29B	3423	29B
3127	29D	3220	29F	3313	29B	3424	29D
3128	29D	3221	29F	3314	29B	3495	29D
3129	29D	3222	29F	3315	29B	3496	29D
3130	29D	3223	29F	3316	29B	3497	29D
3131	29D	3224	29F	3317	29B	3498	29D
3132	29D	3225	29F	3318	29B	3499	29F
3133	29D	3226	29F	3319	29B	3501	29F
3134	29D	3227	29F	3320	29B	3502	29F
3135	29D	3228	29F	3321	29B	3503	29F
3136	29D	3229	29F	3322	29B	3504	29F
3137	29D	3230	29F	3323	29B	3505	29F
3138	29D	3231	29F	3324	29B	3506	29H
3139	29D	3232	29F	3325	29B	3507	29H
3140	29D	3233	29F	3326	29B	3508	29H
3141	29D	3234	29F	3327	29B	3509	29H
3142	29D	3235	29F	3328	29B	3510	29H

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

CHARACTERISTIC CODE INDEX (CONT)

CHAR CODE	PAGE NO.	CHAR CODE	PAGE NO.	CHAR CODE	PAGE NO.	CHAR CODE	PAGE NO.
3511	29H	3552	29H	3595	29J	7002	114
3512	29H	3553	29H	3596	29J	7003	114
3513	29H	3554	29H	3597	29J	7004	114
3515	29H	3555	29H	3598	29J	7005	114
3516	29H	3556	29H	3599	29	7301	24
3517	29H	3557	29H	4754	72	7302	24
3518	29H	3558	29H	4755	72		
3519	29H	3559	29H	4756	72		
3520	29H	3560	29H	4760	70		
3521	29H	3561	29H	4761	70		
3522	29H	3562	29H	4762	70		
3523	29H	3563	29H	4770	88		
3524	29H	3564	29H	4788	74		
3525	29H	3565	29H	4789	74		
3526	29H	3566	29H	4798	74		
3527	29H	3567	29H	4809	80		
3528	29H	3568	29H	4819	78		
3529	29H	3569	29H	4878	88		
3530	29H	3570	29H	4904	24		
3531	29H	3571	29H	4905	24		
3532	29H	3572	29H	5048	24		
3533	29H	3573	29H	6217	98		
3534	29H	3574	29H	6228	96		
3535	29H	3575	29H	6229	96		
3536	29H	3576	29H	6231	100		
3537	29H	3577	29H	6318	100		
3538	29H	3578	29H	6319	100		
3539	29H	3579	29H	6369	20		
3540	29H	3580	29H	6375	26		
3541	29H	3581	29H	6870	114		
3542	29H	3582	29H	6873	20		
3543	29H	3583	29H	6874	22		
3544	29H	3584	29H	6941	22		
3545	29H	3585	29H	6942	22		
3546	29H	3586	29J	6991	114		
3547	29H	3590	29J	6992	114		
3548	29H	3591	29J	6993	114		
3549	29H	3592	29J	6994	114		
3550	29H	3593	29J	6995	114		
3551	29H	3594	29J	7001	114		

☆U.S. GOVERNMENT PRINTING OFFICE: 1980-703-023/38

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.