COMMERCIAL ITEM DESCRIPTION

LAMPS, MERCURY VAPOR (SAFETY)

The General Services Administration has authorized the use of this commercial item description.

This description covers safety mercury vapor lamps for general and street lighting.

Salient characteristics:

The base shall be made of brass.
The bulb shall be made of heat resistant glass.
The burning position shall be any.
Safety mercury vapor lamps shall be designed to prevent exposure to potential ultraviolet energy. If the outer glass is broken away, a special construction feature disconnects the electrical supply to the arc tube.
The lamp color shall be delux white.
The lamps shall be in accordance with ANSI C78.40, C78.380, C78.386, C78.1325, and C78.1330.
The lamps shall have the characteristics specified in Table I.

TABLE I

Type	ANSI Code	Watts	Bulb	Base	Max. Overall Length (inches	Finish	Average* Rated Life (hrs)	Approx. Lumens (Vertical Oper.) Initial **	Mean ***
1	H38JA-T100/DX	100	BT-25/E-23½	Mogul	7-1/2	Dix. White	24,000+	4,400	3,400
2	H39KC-T175/DX	175	E-28/BT-28	Mogul	8-5/16	Dix. White	24,000+	8,500	7,600
3	H37KC-T250/DX	250	E-28/BT-28	Mogul	8-5/16	Dix. White	24,000+	12,000	10,500
4	H33GL-T400/DX	400	E-37/BT-37	Mogul	11-1/2	Dix. White	24,000+	23,000	19,100
5	H36GW-T1000/DX	1000	BT-56	Mogul	15-3/8	Dix. White	24,000+	63,000	47,500

* The average rated life is for 10 hours per start.
**Initial lumen ratings are based upon 100 hour photometry readings burned on a reference ballast.
***Values shown are based on operation under specified test conditions with 10 or more burning hours per start. On lamps with rated life of 24,000+ hours, mean lumens are based on 16,000 hours of operation and are measured at 8,000 hours.

The issues of ANSI C78.40, C78.380, C78.386, C78.1325, and C78.1330 in effect on the date of the solicitation shall be used to determine compliance with these requirements.

Regulatory requirements. The manufacturer shall utilize recovered materials to the maximum extent practicable.

Packaging, packing, and marking. Packaging, packing, and marking shall be as specified in the contract or order.

ANSI C78.40, C78.380, C78.386, C78.1325, and C78.1330 are available from American National Standards Institute, Inc., 1430 Broadway, New York, NY 10018.

MILITARY INTERESTS:

User Activities

Navy - YD
Air Force - 99

CIVIL AGENCY COORDINATING ACTIVITY:

GSA - FSS

PREPARING ACTIVITY:

GSA - FSS

FSC 6240

GSA DC-01201852

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:16Z
Check the source to verify that this is the current version before use.