A-A-423
June 25, 1980

COMMERCIAL ITEM DESCRIPTION

PANS, FRYING

The General Services Administration has authorized the use of this commercial item description in lieu of Federal Specification RR-P-89.

This commercial item description covers the 6 and 12 inch frying pan for institutional and domestic use.

Salient characteristics:

The frying pans shall have the following dimensions:

Inside top diameter (inches) ± 3/8	Outside bottom diameter (inches) ± 5/16	Vertical ins. depth (inches) ± 3/16	Handle thickness (inches) ± .006	Handle length (inches) ± 1
6-3/8	4-7/16	1-5/16	0.109	6-1/2
12-3/8	9-5/16	2-3/16	0.125	11-1/4

The pan shall be formed seamless from a single piece of three ply stainless clad steel with a minimum bottom thickness of 0.070 inch after forming.

The handle shall be made from a single piece of stainless steel with a mounting hole provided at the end.

Must have National Sanitation Foundation (NSF) approval or certification by an independent testing laboratory, acceptable to the GSA indicating that the same model that is being furnished under this description has been inspected and tested and conforms to NSF Standard No. 2.

Workmanship All rust, dirt, grease, graphite, sharp edges, burrs, and slivers shall be removed. The pans shall be clean and free from any cracks, fractures, malforming, scale, pits and flux deposits. There shall be no defect which may impair serviceability, durability or appearance.

The issue of the NSF standard in effect on the date of the solicitation shall be used to determine compliance with stated requirements.

Certification. The contractor shall certify that the product offered meets the salient characteristics of this description and that the product conforms to the producer's own drawings, specifications, standards, and quality assurance practices and is the same product offered for sale in the commercial marketplace. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

Recovered materials. The manufacturer shall utilize recovered materials to the maximum extent practicable.

Packaging, packing, and marking. The packaging and packing shall be in accordance with normal commercial practice and shall assure acceptance by common carrier and provide product protection against loss and damage during multiple shipments, handling, and storage. The shipping container shall be as specified in the contract or order.

NSF Standard No. 2 is available from the National Sanitation Foundation, P.O. Box 1468, Ann Arbor, MI 48106.

FSC 7330

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:08Z
Check the source to verify that this is the current version before use.