A-A-491
September 27, 1979

COMMERCIAL ITEM DESCRIPTION

SANDER-FILER, PNEUMATIC

The General Services Administration has authorized the use of this commercial item description.

This commercial item description covers a pneumatic sander-filer used in heavy duty filing and sanding operations on metal, plastic and wood materials.

Salient characteristics:

Air powered horizontal reciprocating type.
Stroke - 1/4 inch minimum, 1-1/4 inches maximum.
Operating speed - 2400 minimum, 3200 maximum strokes per minute.
Operating pressure:
  For sanding - 90 psi minimum, 120 psi maximum.
  For filing - 120 psi minimum, 140 psi maximum.
Air consumption at operating pressure - 7 cfm minimum, 9 cfm maximum.
1/4 inch female NPTF air inlet size.
Length - 13 inches minimum, 6 inches maximum.
Width - 2-3/4 inches maximum.
Height - 5-3/4 inches minimum, 7 inches maximum.
Weight - 6-1/2 pounds minimum, 8-1/4 pounds maximum.
Provided with air line oiler, either built-in or separately attached.
Conversion from filing blade to sanding shoe shall not require the disassembly of any major part of the machine.
Supplied with manufacturer's standard operating and maintenance instructions.
Furnished with one each of the following attachments;
  Self-cleaning type filing blade with 8 to 13 teeth per inch; minimum of 13 inches long, and 1-1/2 inches wide, plus or minus 1/8 inch.
  Sanding shoe compatible for use with abrasive sheets 17-1/2 inches long and 2-3/4 inches wide.
Marked with manufacturer's name or trademark so that source of manufacture may be readily determined.
Assigned National Stock Number (NSN) 5130-00-937-5534.

Workmanship. The sander-filer, including all parts and accessories, shall be free from fins, burrs, rust, imperfections and any other defects which may impair serviceability, durability, or appearance.

Certification. The contractor shall certify that the product offered meets the salient characteristics of this description and that the product conforms to the producer's own drawings, specifications, standards and quality assurance practices, and is the same product offered for sale in the commercial marketplace. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

Recovered materials. The manufacturer shall utilize recovered materials to the maximum extent practicable.

Preservation, packaging, packing and marking. Each sander-filer, with accessory parts, shall be preserved and packaged in accordance with normal commercial practice and packed to assure acceptance by common carrier and provide product protection against loss and damage during multiple shipments, handling and storage. The shipping container shall be in compliance with National Motor Freight Classification and Uniform Freight Classification. Shipping containers shall be marked as specified in the contract or order.

FSC 5130

GSA DC-01000510

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:08Z
Check the source to verify that this is the current version before use.