[METRIC]
A-A-726A
May 8, 1992
SUPERSEDING
A-A-726
April 25, 1980

COMMERCIAL ITEM DESCRIPTION

TIMER, INTERVAL, MECHANICAL
(60 Minute maximum interval)

The General Services Administration has authorized the use of this commercial item description in preference to Federal Specification GG-T-416.

Salient characteristics.

General. Mechanically operated. Plastic body and selector knob. Acid-resistant, shatterproof, non-warping, Bell alarm.

Readability. The dial markings and time indicator shall contrast with the dial sufficiently to ensure readability at a distance of 1.5 meters in normal office light.

Marking. The markings shall be evenly spaced to indicate each minute, with larger marks for every 5 minutes and numbered at least every 15 minutes.

The reading on the timer shall indicate the time remaining in an interval.

Dimensions. The overall dimensions of the timer shall not exceed 18 cm in height, 15 cm in width and 13 cm in depth.

Workmanship. The timers shall be free from any defects which may impair their appearance, durability or serviceability.

QUALITY ASSURANCE PROVISIONS.

Responsibility for inspection and tests. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein.

Sampling. Sampling for visual inspection and testing shall be in accordance with the provisions of MIL-STD-105. Unless otherwise specified, Inspection Level II with AQL 2.5 percent defective for visual inspection and level S-2, AQL 1.5 percent defective for testing shall apply.

Inspection. Samples selected in accordance with the requirements herein shall be visually inspected to verify conformance to dimensional and workmanship requirements of the CID. Any departure from specified requirements may be grounds for rejection.

DISTRIBUTION STATEMENT A: Approved for public release; distribution is unlimited.

FSC 6645

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:10Z
Check the source to verify that this is the current version before use.

Testing.

Accuracy. The timer shall be accurate up to 3 seconds per minute on any time interval selected.

Alarm. The alarm shall sound only at the end of the desired interval and shall be audible from a distance of at least 8 meters and shall be easily set to any desired interval up to at least 60 minutes.

Regulatory requirements. In accordance with Section 23.403 of the Federal Acquisition Regulations (FAR), the Government's policy is to acquire items composed of the highest percentage of recovered materials practicable, consistent with maintaining a satisfactory level of competition without adversely affecting performance requirements or exposing supplier's employees to undue hazards from the recovered materials.

Preservation, packaging, packing, labeling and marking. The preservation, packaging, packing, labeling and marking shall be as specified in the contract or purchase order.

Copies of MIL-STD-105 can be obtained from the Naval Publications and Forms Center, 5801 Tabor Avenue, Philadelphia, PA 19120.

NOTE. Purchaser shall specify 6645-00-880-8045 when ordering.

PREPARING ACTIVITY:

GSA - FSS

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:10Z
Check the source to verify that this is the current version before use.