GGG-C-00137b(GSA-FSS)
January 9, 1968
INTERIM REVISION OF
Fed. Spec. GGG-C-137a
January 11, 1965

INTERIM FEDERAL SPECIFICATION

CAPS, VISE JAW

This Interim Federal Specification was developed by the General Services Administration, Federal Supply Service, Standardization Division, Washington, D. C. 20406, based upon currently available technical information. It is recommended that Federal agencies use it in procurement and forward recommendations for changes to the preparing activity at the address shown above.

The General Services Administration has authorized the use of this Interim Federal Specification as a valid exception to Federal Specification GGG-C-137a, dated January 11, 1965.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers vise jaw caps furnished in pairs for protecting the finish of the work held in the vise. The caps are of sizes to fit types V and VI vises covered by GGG-V-410.

1.2 Classification.

1.2.1 Type and sizes. The vise jaw caps covered by this specification shall be of one type, and of the following sizes as specified (see 6.1):

Size 2. - For 2-inch nominal width vise jaws.
Size 2-1/2. - For 2-1/2-inch nominal width vise jaws.
Size 3. - For 3-inch nominal width vise jaws.
Size 3-1/2. - For 3-1/2-inch nominal width vise jaws.
Size 4. - For 4-inch nominal width vise jaws.
Size 4-1/2. - For 4-1/2-inch nominal width vise jaws.
Size 5. - For 5-inch nominal width vise jaws.
Size 6. - For 6-inch nominal width vise jaws.
Size 8. - For 8-inch nominal width vise jaws.

2. APPLICABLE DOCUMENTS

2.1 The following specifications and standards, of the issues in effect on date of invitation for bids, or request for proposals, form a part of this specification:

Federal Specification:
GGG-V-410 - Vise, Bench, Clamp Base; Sheet Metal Worker's; Bench and Pipe; Jeweler's; Machinists' and Multiposition.

Federal Standard:
Fed. Std. No. 123 - Marking for Domestic Shipment (Civilian Agencies).

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications, Standards, and Handbooks and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U. S. Government Printing Office, Washington, D. C. 20402.

FSC 5120

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:37Z
Check the source to verify that this is the current version before use.

(Single copies of this specification and other product specifications required by activities outside the Federal Government for bidding purposes are available without charge at the General Services Administration Regional Offices in Boston, New York, Washington, D. C., Atlanta, Chicago, Kansas City, Mo., Fort Worth, Denver, San Francisco, Los Angeles, and Auburn, Washington.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications, Standards, and Handbooks from established distribution points in their agencies.)

Military Specification:
MIL-H-15424 - Hand Tools Packaging of.

Military Standards:
MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.

(Copies of Military Specifications and Standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Construction. The vise jaw caps shall be furnished in pairs - one cap shall fit the front jaw of the vise, and the other cap shall fit the rear jaw. The front and rear caps may be made identical. At the option of the manufacturer, each cap may be made of one or more parts. Any rivets, or other fasteners which may be used, shall be of a material as soft as the facings. Rivets or fasteners, if used, shall be flush or below the cap and facing surfaces. Each cap shall be provided with either two long, pliable extensions, or a deep, pliable flange for retaining the cap to the vise. In lieu of extensions or flanges, each cap may be provided with either a lug on each end for locating and retaining the cap on the vise jaw, or a pliable metal extension on each end for forming onto the side of the vise. At the option of the manufacturer, pliable portion(s) of each cap may be preformed to the general shape of the vise. The pliable portion(s) shall be made of a material that will not crack, tear, or break when the cap is fitted to the vise.

3.2 Material. The vise jaw cap facing shall be of copper, brass, aluminum, or plastic. The remainder of the cap shall be of the same, or other pliable material suitable for fitting the cap onto the vise.

3.3 Sizes and dimensional requirements. The vise jaw caps shall be of the sizes specified in 1.2.1 and 6.1. The cap facing shall be at least as long as the nominal width of the vise jaw. The height of the facing shall be at least one inch, and the thickness of the facing shall be at least 0.125 inch and uniform within 1/32 inch.

3.4 Marking. Each vise jaw cap shall be marked in a plain and permanent manner with the nominal size, and the manufacturer's name or with a trademark of such known character that the source of manufacture may be readily determined.

3.5 Workmanship. Workmanship shall be first class in every respect. Caps shall be free from burrs, cracks, or other defects which might impair serviceability.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:37Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.1.1 Inspection of materials and components. In accordance with 4.1, the supplier is responsible for insuring that materials and components used were manufactured, tested and inspected in accordance with the requirements of referenced subsidiary specifications and standards to the extent specified herein, or, if none, in accordance with this specification.

4.2 Sampling procedures. Sampling procedures shall be in accordance with MIL-STD-105. Data for sampling shall be as stated in table I.

TABLE I. Sampling data

Category	Sample unit	Inspection level	Acceptable quality level	AQL expressed in terms of	Reference
Visual examination	1 each	II	4.0	Defects per hundred units	4.3.1
Dimensional examination	1 each	S-3	4.0	Defects per hundred units	4.3.2
Preparation for delivery	1 container	S-2	4.0	Defects per hundred units	4.4

4.3 Examination.

4.3.1 Visual examination. Each sample unit shall be examined for any nonconformance in design, material, finish, construction, workmanship and marking.

4.3.2 Dimensional examination. Each sample unit shall be examined for any nonconformance with dimensional requirements.

4.4 Inspection of preparation for delivery. Preservation, packaging, packing, and marking shall be inspected in accordance with the requirements of MIL-H-15424 for the level specified (see 6.1).

5. PREPARATION FOR DELIVERY

5.1 Preservation, packaging, and packing. Unless otherwise specified (see 6.1), the vise jaw caps shall be preserved, packaged, and packed in accordance with MIL-H-15424. The level of preservation and packaging shall be A or C and the level of packing A, B, or C, as specified (see 6.1). If level B packaging is specified (see 6.2).

5.1.1 As part of the requirements of section 5 of this specification table II is considered a part of table I of MIL-H-15424.

Source: https://assist.dla.mil -- Downloaded: 202640-26T12:37Z
Check the source to verify that this is the current version before use.

TABLE II.

Col. 1	Col. 2	Col. 3	Col. 4	Col. 5	Col. 6	Col. 7
Cap, Vise Jaw:						
Size 4 and smaller	P-1 or grade 4 of MIL-C-16173	1A	1 pr.	6	10	60
Size 4-1/2 thru 6	Do.	1A	1 pr.	6	6	36
Size 8	Do.	1A	1 pr.	4	6	24

5.2 Marking. In addition to any special markings required by the contract or order, interior packages and shipping containers shall be marked in accordance with Fed. Std. No. 123 or MIL-H-15424, as applicable.

6. NOTES

6.1 Ordering data. Purchasers should select the preferred options permitted herein and include the following information in procurement documents:

(a) Title, number, and date of this specification.
(b) Size required (see 1.2.1 and 3.3).
(c) Selection of applicable level of preservation, packaging, and packing required (see 5.1 and 5.1.1).
(d) Marking required (see 5.2).

6.2 For civil agency procurement. When level B packaging is specified, the requirements in 5.1 for level A packaging shall apply.

GSA DC 68-9330

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:37Z
Check the source to verify that this is the current version before use.