GGG-C-137a
January 11, 1965
SUPERSEDING
Int. Fed. Spec. GGG-C-00137 (GSA-FSS)
January 29, 1964

FEDERAL SPECIFICATION

CAPS, VISE JAW

This specification was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers vise jaw caps furnished in pairs. One cap is fitted over the front jaw of a vise and the other cap over the rear jaw so as to protect the finish of the work held in the vise. The caps are of such sizes as to fit type VII Machinists' vises in GGG-V-436.

1.2 Classification.

1.2.1 *Type and sizes.* The vise jaw caps covered by this specification shall be of one type. The vise jaw caps shall be of the following sizes, as specified (see 6.1).

Size 2-1/2-inch—For 2-1/2-inch nominal width vise jaws.

Size 3-inch—For 3-inch nominal width vise jaws.

Size 3-1/2-inch—For 3-1/2-inch nominal width vise jaws.

Size 4-inch—For 4-inch nominal width vise jaws.

Size 4-1/2-inch—For 4-1/2-inch nominal width vise jaws.

Size 5-inch—For 5-inch nominal width vise jaws.

Size 6-inch—For 6-inch nominal width vise jaws.

Size 8-inch—For 8-inch nominal width vise jaws.

2 APPLICABLE SPECIFICATIONS AND STANDARDS

2.1 Specifications and standards. The following specifications and standards, of the issues in effect on date of invitation for bids, form a part of this specification.

Federal Specification:

GGG-V-436—Vises.

Federal Standards:

Fed. Std. No. 102—Preservation, Packaging, and Packing Levels.

Fed. Std. No. 123—Marking for Domestic Shipment (Civilian Agencies)

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U. S. Government Printing Office, Washington, D. C. 20402.

(Single copies of this specification and other product specifications required by activities outside the Federal Government for bidding purposes are available without charge at the General Services Administration Regional Offices in Boston, New York, Washington, D. C., Atlanta, Chicago, Kansas City, Mo., Dallas, Denver, San Francisco, Los Angeles, and Seattle, Wash.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

FSC 5120

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:37Z
Check the source to verify that this is the current version before use.

Military Specification:

MIL-H-15424—Hand Tools, Packaging Of.

Military Standards:

MIL-STD-105—Sampling Procedures and Tables for Inspection by Attributes.

MIL-STD-129—Marking for Shipment and Storage.

(Copies of Military Specifications and Standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Marking. Each vise jaw cap shall be marked in a plain and permanent manner with the manufacturer's name or with a trademark of such known character that the source of manufacture may be readily determined, and also the nominal size.

3.2 Material. The vise jaw cap facing shall be made either of copper or brass and the remainder of cap shall be made of the same or other pliable metal suitable for fitting the cap onto the vise with the aid of a hammer or mallet (see 3.4).

3.3 Finish. The vise jaw cap face shall be smoothly finished on the flat surface that contacts the work held in the vise, the remainder of the vise cap may be the natural finish of the material except that detrimental material such as dirt, scale, and sand shall be removed.

3.4 Construction. The vise jaw caps shall be furnished in pairs; one cap shall fit the front jaw of the vise and the other cap shall fit the rear jaw. The front jaw cap and rear jaw cap may be made identical. At the option of the manufacturer, each cap may be made of one or more parts. The cap facing shall be made of copper or brass, and any rivets or other fasteners which may be used, shall be made of a material as soft as the facings. Rivets or other fasteners, if used, shall be flush or below the cap and facing surfaces. Each cap shall be provided with either a lug on each end for locating and retaining the cap on the vise jaw, or a pliable metal extension on each end for forming onto the side of the vise. Each cap shall be provided either with two long pliable extensions or a deep pliable metal flange for the purpose of fitting the cap to the vise. At the option of the manufacturer, the pliable portion(s) of each cap may be preformed to the general shape of the vise. The pliable portion(s) of the cap shall be made of such metal that the metal will not crack or break when the cap is fitted to the vise.

3.5 Sizes and dimensional requirements. The vise jaw caps shall be of the sizes to fit type VII machinist vises in GGG-V-436 as specified (see 1.2.1 and 6.1). When fabricated end lugs are furnished, the width between the inside of the two end lugs shall be not less than 1/16-inch nor more than 3/16-inch greater than the nominal dimension of the vise jaw cap. Each end lug shall be at least 1/8-inch in height. If pliable extensions are furnished in lieu of end lugs, the extensions shall be of sufficient length to provide for forming the extensions over the sides of the vise, with the aid of a hammer or mallet. The cap facing shall be at least as long as the nominal length of the vise jaw cap, the height of the facing shall be at least one inch, and the thickness of the facing shall be at least 0.125-inch and uniform within 1/32-inch.

3.6 Workmanship. Workmanship shall be first class in every respect.

4. SAMPLING, INSPECTION, AND TEST PROCEDURES

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:37Z
Check the source to verify that this is the current version before use.

own or any other inspection facilities and services acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.2 Sampling for inspection and acceptance. Sampling for inspection and acceptance shall be performed in accordance with the provisions set forth in MIL-STD-105, except where otherwise indicated herein.

4.2.1 *Inspection of materials and components.* In accordance with 4.1, the supplier is responsible for insuring that materials and components used were manufactured, tested, and inspected in accordance with the requirements of referenced subsidiary specifications and standards to the extent specified herein, or, if none, in accordance with this specification.

4.2.2 *Inspection of the end item.* Inspection of the vise jaw caps shall be performed as specified in the following paragraphs. A lot shall consist of completely fabricated vise jaw caps of one size offered for inspection at one time. The sample unit shall be one pair of vise jaw caps.

4.2.2.1 *Visual examination.* Each sample unit shall be visually examined for the defects set forth below. The inspection level shall be level II, with an acceptable quality level (AQL) of 4.0 defects per 100 units.

Examine	Defects
Material	Not as specified.
Finish	Not as specified.
Construction and workmanship	Not as specified.
Marking	Missing, incorrect, not legible.

4.2.2.2 *Dimensional examination.* Each sample unit shall be examined for dimensions specified in applicable paragraphs. Any departure from specified requirements shall constitute a defect. The inspection level shall be level S-3 with an AQL of 4.0 defects per 100 units.

4.3 Inspection of preparation for delivery. Inspection to determine compliance with preparation for delivery requirements shall be accomplished in accordance with MIL-H-15424 for, "Parallel," up through 6 pounds.

5. PREPARATION FOR DELIVERY

(Civil agencies. Fed. Std. No. 102 should be referred to for definitions and applications of the various levels of packaging protection for supplies and equipment.)

5.1 Packaging.

5.1.1 *Level A.* Vise jaw caps shall be packaged in accordance with the level A requirements of MIL-H-15424, for "Parallels," up through 6 pounds.

5.1.2 *Level C.* Vise jaw caps shall be packaged in accordance with the manufacturer's commercial practice.

5.2 Packing.

5.2.1 *Level A.* Vise jaw caps shall be packed in accordance with the level A requirements of MIL-H-15424, for "Parallels," up through 6 pounds.

5.2.2 *Level B.* Vise jaw caps shall be packed in accordance with level B requirements of MIL-H-15424, for "Parallels," up through 6 pounds.

5.2.3 *Level C.* Vise jaw caps packaged for level A or C as specified (see 6.1), shall be packed in a manner which will insure acceptance and safe delivery at destination. Shipping containers shall comply with the rules or regulations as applicable to the mode of transportation.

5.3 Marking.

5.3.1 *Military agencies.* In addition to any special marking required by the contract,

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:37Z
Check the source to verify that this is the current version before use.

or order, or herein (see 6.1), interior and exterior shipping containers shall be marked in accordance with MIL-STD-129.

5.3.2 *Civil agencies.* In addition to any special marking specified in the contract or order (see 6.1), each unit and intermediate package and shipping container shall be marked in accordance with Fed. Std. No. 123.

6. NOTES

6.1 **Ordering data.** Purchasers should exercise any desired options offered herein, and procurement documents should specify the following.

(*a*) Title, number, and date of this specification.

(*b*) Size required (see 1.2.1).

(*c*) Level of packaging and packing required (see 5.1 and 5.2).

(*d*) Special marking, if required (see 5.3).

6.2 **Transportation description.** Transportation descriptions and minimum weights applicable to this commodity are:

Rail:

Tools, not otherwise indexed by name. Carload minimum weight 30,000 pounds.

Motor:

Tools, hand, not otherwise indexed. Truckload minimum weight 30,000 pounds, subject to Rule 115, National Motor Freight Classification.

MILITARY INTEREST:

	Custodians:	*Review activities*	*User activities*
Army	**GL**	**GL**	**SM**
Navy	**SH**	**SH**	**MC**
Air Force	**69**	**69**	

Review/user information is current as of the date of this document. For future coordination of changes to this document, draft, circulation should be based on the information in the current Federal Supply Classification Listing of DOD Standardization Documents.

☆ U.S. GOVERNMENT PRINTING OFFICE: 1965—783352/295

Copies of this specification may be purchased for 5 cents each.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:37Z
Check the source to verify that this is the current version before use.