GGG-H-131c
AMENDMENT—3
JANUARY 11, 1962

SUPERSEDING
Interim Amendment—2
May 8, 1961

FEDERAL SPECIFICATION

HATCHET (CLAW, HALF, LATHING, BROAD AND BARREL)

This amendment which forms a part of Federal Specification GGG-H-131c, dated May 31, 1957, was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

Pages 2 and 3, paragraph 3.3.5: Add at end of paragraph: "At the option of the manufacturer, handles may be secured and bonded to the head by means of a chemical adhesive that will prevent the handle from loosening under any normal working condition. Hatchets having such chemical adhesive shall be subjected to the pull-apart test specified in 4.4.4."

Page 5, paragraph 4.1.2, line 4: Delete "Government".

Page 5, paragraph 4.1.3, line 4: Delete "the appendix to".

Page 5, paragraph 4.2, line 5: Delete "Government".

Page 5, paragraph 4.2, third and fourth sentences: Delete.

Page 6, add as paragraph 4.4.4:

4.4.4 *Pull-apart test.*—The head and end of the handle shall be securely held in a standard tensile testing machine, or some other method may be employed. Hatchets shall not pull apart when subjected to a pulling pressure of 2,250 pounds.

Page 6, paragraph 4.5: Delete and substitute:

4.5 The supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own or any other inspection facilities and services acceptable to the Government. Inspection records of the examination and tests shall be kept complete and available to the Government as specified in the contract or order. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

Page 7, paragraph 6.5.1: Delete and substitute:

6.5.1 Transportation descriptions and minimum weights applicable to this commodity are:

Rail:
Hatchets.
Carload minimum weight 30,000 pounds.

Motor:
Hand tools, not otherwise indexed.
Truckload minimum weight 30,000 pounds, subject to Rule 34, National Motor Freight Classification.

Page 7: Delete "Military Interests" and substitute the following:

MILITARY CUSTODIANS:
Army—Q
Navy—Sh
Air Force—MOA

FSC 5110

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:37Z
Check the source to verify that this is the current version before use.