GGG-P-151a
October 18, 1953
SUPERSEDING
Int. Fed. Spec. GGG-P-151 (Navy-Ships)
21 January 1952

FEDERAL SPECIFICATION

PEAVY

This specification was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

1. SCOPE

1.1 This specification covers peavies used by loggers for rolling by clasping the hook around the log and for pushing and guiding logs.

2. APPLICABLE SPECIFICATIONS AND STANDARD

2.1 The following specifications and standard, of the issues in effect on date of invitation for bids, form a part of this specification:

Federal Specifications:

NN-H-93—Handles; Hickory, Striking-Tool.
NN-B-601—Boxes; Wood-Cleated-Plywood, for Domestic Shipment.
NN-B-621—Boxes; Wood, Nailed and Lock-Corner.
NN-B-631—Boxes; Wood, Wirebound (for Domestic Shipment).
QQ-S-633—Steel, Carbon; Bars (General Purpose).
TT-W-572—Wood-Preservative; Water-Repellant.
LLL-B-631—Boxes; Fiber, Corrugated (for Domestic Shipment).
LLL-B-636—Boxes; Fiber, Solid (for Domestic Shipment).

Military Standard:

MIL-STD-105—Sampling Procedures and Tables for Inspection by Attributes.

(Copies of Federal Specifications and the Index of Federal Specifications and Standards may be obtained upon application accompanied by check, money order, cash, or Government Printing Office coupons, to the General Services Administration, Business Service Center, Region 3, Seventh and D Streets SW., Washington 25, D. C. This office will also honor deposit account numbers issued by the Government Printing Office. Prices may be obtained from the Index of Federal Specifications and Standards or from the GSA Regional Offices. Single copies of this specification and other product specifications required for bidding purposes are available without charge at the GSA Regional Offices in Boston, New York, Atlanta, Chicago, Kansas City, Mo., Dallas, Denver, San Francisco, Los Angeles, Seattle, and Washington, D. C.

(Copies of the Military Standard referenced above required by contractors in connection with specific procurement functions should be obtained from the procuring agency or as directed by the contracting officer.)

2.2 Specifications applicable only to individual departments are listed in section 7.

3. REQUIREMENTS

3.1 **Materials.**—The materials used in the manufacture of the peavy shall be as specified herein. Materials shall be free from all defects and imperfections that may affect the serviceability of the finished product.

3.2 **Peavy.**—The peavy shall consist essentially of a socket, hook, and pike.

3.2.1 *Socket.*—The socket shall be of a good quality malleable iron or steel.

3.2.2 *Hook.*—The hook shall be of the duckbill type. It shall be forged from steel conforming to Federal Specification QQ-S-633, FS No. 1060 or No. 1070, and shall be quenched and tempered to a Brinell hardness of not less than 375 and not more than 415.

3.2.2.1 *Hook sizes.*—The hook sizes shall be either ⅞ by 7/16 by 8 inches, 1 by ½ by 10½ inches, or 1 by ½ by 18 inches, as specified in the contract or order (see 6.1).

3.2.3 *Pike.*—The pike shall be forged from

271923°—53—No. 67

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:38Z
Check the source to verify that this is the current version before use.

steel as specified for the hook. The point of the pike shall be properly sharpened ready for use.

3.2.4 *Finish.*—All metal parts shall be free from scale, burrs, fins, nodules, cracks, or any imperfections that may affect their serviceability.

3.2.4.1 *Coating.*—All metal parts shall be given a protective coating of black oxide.

3.3 **Handle.**—The peavy handle shall be straight, and shall conform to grade A of Federal Specification NN-H-93. The diameter shall be not less than 2½ inches at the top of the socket with tip end reduced and tapered to fit the socket of the peavy. The length shall be either 4 feet 6 inches or 5 feet, plus or minus 1 inch, as specified in the contract or order (see 6.1).

3.4 **Socket and handle assembly.**—The socket end of the handle, the length of the ferrule, shall be dipped in a wood preservative in accordance with composition A of Federal Specification TT-W-572 and shall be set into the socket under heavy pressure.

3.5 **Workmanship.**—The workmanship shall be of the highest grade throughout and equal in every respect to the best commercial practice.

4. SAMPLING, INSPECTION, AND TEST PROCEDURES

4.1 Sampling for lot acceptance.

4.1.1 *Inspection lot.*—All peavies presented at one time shall be considered a lot for purposes of acceptance, inspection, and tests.

4.1.2 *Sampling for inspection.*—A random sample of peavies as specified in table I shall be taken from each inspection lot of material offered for Government inspection of visual and dimensional characteristics with lot acceptance based on the sampling inspection requirements in accordance with the procedures of Military Standard MIL-STD-105.

4.1.3 *Sampling for hardness tests.*—A random sample of peavies shall be taken from each inspection lot in accordance with the following table and shall be subjected to the Brinell hardness test specified in 4.3.1 to determine conformance with the requirements specified in 3.2.2.

4.2 Inspection.

4.2.1 *Visual and dimensional inspection.*—Each of the sample peavies selected in accordance with table I shall be visually and dimensionally inspected by the Government inspector to verify compliance with this specification. Any peavy in the sample containing one or more visual or dimensional defects shall be rejected, and if the number of defective peavies in any sample exceeds the acceptance number for that sample, the lot represented by the sample shall be rejected.

TABLE I.—*Sampling for visual and dimensional inspection AQL (approx.)=2.5 percent defective*

Number of peavies in an inspection lot	Number of peavies in sample	Acceptance number (defectives)	Rejection number (defectives)
15 and under	7	0	1
16 to 40	10	0	1
41 to 110	15	1	2
111 to 300	25	1	2
301 to 500	35	2	3
501 to 800	50	3	4
801 to 1,300	75	4	5
1,301 and over	110	6	7

NOTE.—The Government inspector may institute tightened or reduced inspection in accordance with section 9 of Military Standard MIL-STD-105.

TABLE II.—*Sampling for lot hardness test AQL (approx.)=2.5 percent defective*

Number of peavies in inspection lot	Number of peavies in sample	Acceptance number (defectives)	Rejection number (defectives)
40 or under	5	0	1
41 to 110	7	0	1
111 to 800	10	0	1
801 to 800	15	1	2
801 and over	25	1	2

4.3 Lot acceptance tests.

4.3.1 *Hardness test.*—Hooks from each of the sample peavies selected in accordance with table II shall be subjected to a Brinell hardness test to verify compliance with this specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:38Z
Check the source to verify that this is the current version before use.

A hook from any sample peavy which does not meet the requirements for the hardness characteristics shall be rejected and, if the number of non-conforming peavies in any sample exceeds the acceptance number for that sample, the lot represented by the sample shall be rejected.

4.4 Peavies furnished under this specification shall be given such tests as may be necessary to determine compliance with the specification requirements. For all tests made prior to final acceptance, the contractor shall provide all necessary facilities and supplies required for the testing procedure.

5. PREPARATION FOR DELIVERY

5.1 **Cleaning and preservation.**—Unless otherwise specified, peavies shall be cleaned and preserved in accordance with the manufacturer's standard practice.

5.2 **Packaging.**—Unless otherwise specified, commercial packages are acceptable provided that only one size is contained in any one box or package.

5.3 **Packing.**—Unless otherwise specified, peavies packaged as specified in 5.1 and 5.2, shall be packed in wood-cleated plywood, nailed wood, wirebound wood, corrugated-fiber or solid-fiber boxes conforming to Federal Specification NN-B-601, NN-B-621, NN-B-631, LLL-B-631 or LLL-B-636, respectively. The gross weight of fiberboard boxes shall be subject to the limitation of the box specification.

5.4 **Marking.**

5.4.1 *Interior containers.*—Unless otherwise specified, each box or package shall be plainly marked with the name of the article, the size and the quantity contained therein, as defined by the contract or order under which shipment is made, and the name of the manufacturer.

5.4.2 *Exterior containers.*—Unless otherwise specified, shipping containers shall be marked with the name of the article, the size, the quantity contained therein, as defined by the contract or order under which shipment is made, the name of the contractor, and the number of the contract or order.

6. NOTES

6.1 **Ordering data.**—Procurement documents should specify the following and exercise any desired options offered herein (see 3.2.1, 3.2.2.1, 3.3).

(*a*) Title, number, and date of this specification.

(*b*) Hook size required (see 3.2.2.1).

(*c*) Length of handle required (see 3.3).

(*d*) Whether domestic or overseas shipment is required (see sec. 5 and 7.2.2).

6.2 **Transportation description.**—Transportation description applicable to these items is:

Logging tools or parts; peavies.
In packages; also carload or truckload, loose.
Carload weight 30,000 pounds.
Truckload weight 30,000 pounds.

Patent notice.—When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility nor any obligation whatsoever; and the fact that the Government may have formulated, furnished or in any way supplied the said drawings, specifications or other data, is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

7. DEPARTMENTAL REQUIREMENTS

7.1 The following specification of the issue in effect on date of invitation for bids, and special requirements, forms a part of this specification for purchases made under this specification by the respective departments.

7.2 **Army, Navy, and Air Force.**

7.2.1 ***Applicable specification.***

Military Specification:

MIL-P-15424—Packaging of Hand Tools; General Specification for Domestic and Overseas Preservation.

(Copies of specifications, standards, and drawings required by contractors in connection with specific procurement functions should be obtained from the procuring agency or as directed by the contracting officer.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:38Z
Check the source to verify that this is the current version before use.

7.2.2 *Preparation for delivery.*—Peavies shall be cleaned, preserved, packaged, packed and marked in accordance with Military Specification MIL-P-15424.

MILITARY INTEREST:

ARMY—E Sig T
NAVY—Sh MC S Y
AIR FORCE

This specification is a part of Section IV, Part 5, of the Federal Standard Stock Catalog.

Copies of this specification may be purchased for 5 cents.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:38Z
Check the source to verify that this is the current version before use.