FEDERAL SPECIFICATION

SCRIBERS, MACHINISTS'

This amendment, which forms a part of Federal Specification GGG-S-131e, dated October 12, 1965, was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

PAGE 3

Delete in its entirety and substitute the following:

3.7.1 *Class* 1, *nonrolling head.* Class 1 scriber shall terminate with a head not more than 9/16 inch in length either hexagonal or octagonal in cross section. The distance across the flats shall be not less than the diameter of the knurled portion of the body to prevent the scriber from rolling. Class 1 scribers shall conform to table I and be similar to figure 1. When specified (see 6.1), the scriber shall be furnished with a tungsten carbide point.

3.8 **Type II, double point, straight and bent.** Type II scribers shall have one straight and one bent tapered point. The straight tapered point shall coincide with the axis of the round body of the scribing point, and the bent tapered point shall be at 90° angle from the axis of the round body of the scribing point. The length of the bent tapered point shall be not less than 5/16 nor more than 1/2 inch from the round body of the bar.

3.8.1 *Class* 1, *adjustable sleeve.* Class 1 scriber shall have a scribing point of one-piece construction and a knurled adjustable sleeve which shall be a neat slip fit and adjustable along the body of the scribing point. The adjustable sleeve shall be provided with a chuck in which to secure the sleeve at any desired location along the body of the scribing point. Class 1 scribers shall conform to table II and be similar to figure 2.

TABLE II. *Type II, class* 1, *double point, straight and bent, adjustable sleeve*

Diameter of sleeve	Length of sleeve	Diameter of scribing point body (± 0.005 inch)	Length of scribing point
Inch	*Inches*	*Inch*	*Inches*
5/16	2-1/2 to 3	5/32	8 to 9



FIGURE 2. Type II, class 1, double point, straight and bent, adjustable sleeve.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:37Z
Check the source to verify that this is the current version before use.

3.8.2 *Class 2, removable.* Class 2 scriber shall have two removable scribing points. The scribing points shall be suitably threaded to engage the threaded holes in the body. The body, when assembled to the scribing points, shall be midway in the scriber. When an extra long scribing point with a bent tapered point is required for use with class 2 scriber, it shall be specified (see 6.1). Class 2 scribers shall conform to table III and be similar to figure 3.

TABLE III. *Type II, class 2, double point, straight and bent, removable*

Diameter of handle	Length of handle	Diameter of scribing point body	Total length with short bent point (assembled)	Total length with both points (assembled)
Inch	*Inches*	*Inch*	*Inches*	*Inches*
1/4 to 5/16	2-3/4 to 3-1/4	1/8 to 3/16	8 to 9	12 to 13



FIGURE 3. Type II, class 2, double point, straight and bent, removable.

3.9 **Workmanship.** Workmanship shall be of the highest grade throughout, and equal in every respect to good commercial practice. The scribers shall be free from rust, fins, and other defects which may impair their serviceability and durability.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:37Z
Check the source to verify that this is the current version before use.