INCH-POUND

MIL-DTL-32010(OS)
23 January 1998

DETAIL SPECIFICATION

FIRE EXTINGUISHER CARTRIDGE, CCU-90/A (MH92)

This specification is approved for use by the Naval Sea Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the requirements for the manufacture and acceptance of the CCU-90/A Fire Extinguisher Cartridge, referred to herein as the "cartridge."

2. APPLICABLE DOCUMENTS

2.1 General. The documents listed in this section are specified in sections 3 and 4 of this specification. This section does not include documents cited in other sections of this specification or documents recommended for additional information or as examples. While every effort has been made to ensure the completeness of this list, document users are cautioned that they must meet all specified requirements for documents referenced in sections 3 and 4 of this specification, whether or not those documents are listed in this section.

2.2 Government documents.

2.2.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplements thereto, cited in the solicitation (see 6.2).

SPECIFICATIONS

DEPARTMENT OF DEFENSE

MIL-D-21625 Design and Evaluation of Cartridges for Cartridge Actuated Devices

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, Indian Head Division, Naval Surface Warfare Center, Standardization Team (Code 8410T), 101 Strauss Avenue, Indian Head, MD 20640-5035, by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by sending a letter.

AMSC N/A FSC 1377

DISTRIBUTION STATEMENT A: Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T04:18Z
Check the source to verify that this is the current version before use.

STANDARDS

DEPARTMENT OF DEFENSE

MIL-STD-810C	Environmental Test Methods and Engineering Guidelines
MIL-STD-1168	Ammunition Lot Numbering
MS21044	Nut, Self-Locking, Hexagon, Regular Height, 250°F, 125 KSI FTU and 60 KSI FTU

(Unless otherwise indicated, copies of Federal and Military specifications and standards are available from: Standardization Documents Order Desk, Bldg. 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

2.2.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

DRAWINGS

NAVAL AIR SYSTEMS COMMAND (CAGE Code 30003)

DL1512AS105	CCU-90/A Cartridge, Fire Extinguisher
298AS105	Closed Chamber, 1.22 Cu. Inch Assembly

(Application for copies should be addressed to the Commander, Indian Head Division, Naval Surface Warfare Center, Data Control Team (Code 8410P), 101 Strauss Avenue, Indian Head, MD 20640-5035.)

2.3 Non-Government publications. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted are those listed in the issue of DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation (see 6.2).

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

ASTM E 1742	Standard Practice for Radiographic Examination

(Application for copies of ASTMs should be addressed to the American Society for Testing and Materials, 100 Barr Harbor Drive, West Conshohocken, PA 19428-2959.)

(Non-Government standards and other publications are normally available from organizations that prepare or distribute the documents. These documents also may be available in or through libraries or other informational services.)

2.4 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however supersedes applicable laws and regulations unless a specific exemption has been obtained.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T04:18Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 First article. When specified (see 6.3), a sample shall be subjected to first article inspection in accordance with 4.2.1.

3.2 Primary components. Only one lot of primary components shall be used in each lot of fire extinguisher cartridges, although a primary component lot may be used in more than one fire extinguisher cartridge lot. The squib subassembly and output charge in the squib subassembly are considered primary components.

3.3 Cartridge production. The cartridges shall be manufactured in accordance with DL1512AS105 and the documents listed thereon. Each squib subassembly shall meet the requirements of 3.3.1 through 3.3.1.3 and each cartridge shall meet the requirements of 3.3.2 through 3.3.2.4. Failure of any cartridge to meet the applicable requirements of 3.3 shall result in rejection of that unit.

3.3.1 Squib subassembly inspection.

3.3.1.1 Visual inspection. All squib subassemblies manufactured under contract shall be visually inspected and screened for defects as outlined in 4.3.1.

3.3.1.2 Leakage. Squib subassemblies shall not exhibit a leak rate in excess of 1×10^{-5} cubic centimeters per second (cm^3/s) of air when tested in accordance with 4.3.2.

3.3.1.3 Radiographic inspection. Each squib subassembly shall be examined radiographically in accordance with 4.3.3.1. Presence of the propellant, non-metal parts, no foreign hydrogenous materials and the proper assembly of pyrotechnic/non-metallic materials will be ensured. Any observable imperfections in assembly will be cause for rejection.

3.3.2 Cartridge inspection.

3.3.2.1 Visual inspection. All cartridges manufactured under contract shall be visually inspected and screened for defects as outlined in 4.3.1.

3.3.2.2 Radiographic inspection. Cartridges shall show proper assembly, presence of parts, and sealing when examined radiographically in accordance with 4.3.3.2.

3.3.2.3 Bridgewire resistance. Cartridges shall exhibit a bridgewire resistance between 0.90 and 1.40 ohms when tested in accordance with 4.3.4.

3.3.2.4 Torque. The crimp interface between the housing and insulator shall withstand 14 inch-pounds of torque without rotation of the insulator when tested in accordance with 4.3.5.

3.4 Cartridge performance. Cartridges shall be capable of meeting all requirements of 3.4.4.

3.4.1 Vibration. There shall be no evidence of deformation or derangement of components. The cartridge shall not autoignite, shall be safe to handle, and shall meet the requirements of 3.3.2.2 and 3.4.4 following vibration testing of 4.3.6.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T04:18Z
Check the source to verify that this is the current version before use.

3.4.2 Temperature and humidity (T & H) cycling. The cartridges shall meet the requirements of 3.3.2.2 and 3.4.4 after being exposed to the T & H cycle in accordance with 4.3.7.

3.4.3 Shock. The cartridges shall meet the requirements of 3.3.2.2 and 3.4.4 following shock testing of 4.3.8.

3.4.4 Ballistic requirements. Cartridges from each production and first article lot shall meet the requirements of 3.4.4.1 through 3.4.4.3 when subjected to the tests of 4.3.9.

3.4.4.1 Cartridge pressure. The cartridge shall provide:

a. The lower limit for maximum pressure when conditioned at –65°F shall be 475 psig.
b. The lower limit for maximum pressure when conditioned at +70°F shall be 600 psig.
c. The lower limit for maximum pressure when conditioned at +200°F shall be 670 psig.

3.4.4.2 Pressure rise time.

a. The maximum pressure lower limit of 3.4.4.1a shall be attained within 6 milliseconds.
b. The maximum pressure lower limit of 3.4.4.1b and 3.4.4.1c shall be attained within 4 milliseconds.

3.4.4.3 Ignition delay. The time from application of the firing current to first indication of pressure in the closed chamber shall be less than 25 milliseconds at all conditioning temperatures.

3.4.4.4 Misfire. There shall be no misfires.

4. VERIFICATION

4.1 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.2.1)
b. Production inspection (see 4.2.2)
c. Lot acceptance inspection (see 4.2.3)

4.2 Types of inspections.

4.2.1 First article inspection. Before entering into quantity production, an acceptable first article sample of 63 cartridges shall be prepared using the same procedures and methods proposed for the production lot. A first article sample acceptable for functional and environmental testing shall be defined as a sample which has met the applicable requirements of 3.2 through 3.4 of this specification. Sixty cartridges shall be expended in the tests listed in table I and three shall be retained for investigative purposes. The contractor shall deliver the cartridges to the activity designated by the contracting agency for tests. Any damage inflicted by the environmental treatments, which would adversely affect the performance of the item in service application shall cause rejection of the first article sample. Any further production prior to notification by the contracting agency of first article sample acceptability shall be at the contractor's risk. Failure of any cartridge to comply with the requirements of section 3 shall be cause for rejection of the first article represented.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T04:18Z
Check the source to verify that this is the current version before use.

TABLE I. First article test plan.

Test Sequence	Requirement paragraph	Test paragraph	Cartridge Groups						Total
			I	II	III	IV	V	VI	
Visual	3.3.1.1 3.3.2.1	4.3.1	6	6	12	12	12	12	60
Radiographic	3.3.1.3 3.3.2.2	4.3.3	6	6	12	12	12	12	60
Resistance	3.3.2.3	4.3.4	6	6	12	12	12	12	60
Torque	3.3.2.4	4.3.5	6	6	12	12	12	12	60
Shock	3.4.3	4.3.8	6						6
Vibration	3.4.1	4.3.6		6					6
Temperature and Humidity Cycling	3.4.2	4.3.7			12				12
Visual	3.3.2.1	4.3.1	6	6	12				24
Radiographic	3.3.2.2	4.3.3	6	6	12				24
Resistance	3.3.2.3	4.3.4	6	6	12				24
Torque	3.3.2.4	4.3.5	6	6	12				24
Ballistic test -65 ± 5°F +70 ± 5°F +200 ± 5°F	3.4.4	4.3.9	 6	 6	 12	 12 	 12	 12	 12 36 12

4.2.2 Production inspection. All production cartridges manufactured under contract shall be inspected and screened to requirements specified in 3.2 through 3.3.2.3. Any unit failing to meet the requirements listed in 3.2 through 3.3.2.3 shall be rejected and removed from the lot.

4.2.3 Lot acceptance inspection. Lot acceptance inspection shall consist of the examinations and tests specified in table II. Failure of any sample cartridge to comply with the requirements listed in table II shall be cause for rejection of the lot represented.

4.2.3.1 Sample size. A random sample from each production lot, including the retained sample for investigative purposes, shall be selected in accordance with table III for lot acceptance inspection. Test sample cartridges and cartridges retained for investigative purposes shall not be applied as part of the quantity specified for delivery by the contract or purchase order.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T04:18Z
Check the source to verify that this is the current version before use.

TABLE II. Lot acceptance inspections and tests.

Inspection/Test	Test Paragraph	Quantity
Visual	4.3	All
Radiographic	4.3.3.2	Al
Resistance	4.3.4	All
Torque	4.3.5	All
Ballistic test -65 ± 5°F +70 ± 5°F +200 ± 5°F	4.3.9	 1/3 test sample 1/3 test sample 1/3 test sample

TABLE III. Lot acceptance sampling.

Lot Size	Test Sample Size	Retained Sample Size
2 to 50	9	3
51 to 100	12	3
101 to 150	21	3
151 to 280	33	3
281 to 500	51	3

4.3 Inspections and tests.

4.3.1 Cartridge and squib subassembly visual inspection. Visually examine all squib subassemblies prior to cartridge assembly. Each assembled cartridge shall be visually examined. Reject those with inadequate or illegible descriptive markings or serial numbers, dents, deep scratches, or other defects which may prevent proper installation or function.

4.3.2 Squib subassembly leak test. Each squib subassembly produced shall be leak tested in a dry gas leak tester to determine conformance with 3.3.1.2. Units exhibiting a leak rate in excess of 1×10^{-5} standard cm^3/sec air at a pressure differential of 1.0 ± 0.1 atmosphere shall be rejected.

4.3.3 Radiographic examination.

4.3.3.1 Squib subassemblies examination. Radiographic examination of squib subassemblies shall be in accordance with ASTM E 1742. All squib subassemblies shall be identified with serial numbers beginning with 001 prior to examination. The squib subassemblies shall be arranged on trays or boards in consecutive numerical order with any missing serial numbers identified on the radiographic plate. The squib subassemblies shall be positioned for the most revealing exposure with the long axis perpendicular to the radiographic beam. Each radiograph shall carry a permanent identification of the items displayed thereon in a

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T04:18Z
Check the source to verify that this is the current version before use.

4 × 6 inch region maximum. The radiographic identification shall include the part number, the complete lot number, the contract number, and the span of serial numbers displayed. Radiographs of the entire production lot shall accompany the ballistic sample to the activity conducting the tests (see 6.2). Defective assemblies found during radiographic review are to be marked on the radiographic plate and removed from the production lot.

4.3.3.2 Cartridge examination. Radiographic examination of cartridges shall include x-ray in accordance with ASTM E 1742. All cartridges shall be identified with serial numbers beginning with 001 prior to examination. The cartridges shall be arranged on trays or boards in consecutive numerical order with any missing serial numbers identified on the radiographic plate. The cartridges shall be positioned for the most revealing exposure with the long axis perpendicular to the radiographic beam. Each radiograph shall carry a permanent identification of the items displayed thereon in a 4 × 6 inch region maximum. The radiographic identification shall include the drawing number, the complete lot number in accordance with MIL-STD-1168, the contract number, the DODIC, and the span of serial numbers displayed. Radiographs of the entire production lot shall accompany the ballistic sample to the activity conducting the tests (see 6.2). Defective cartridge assemblies found during radiographic review are to be marked on the radiographic plate and removed from the production lot. A marriage log shall be maintained that relates each squib subassembly by lot number and serial number to each lot and serial number of the cartridge.

4.3.4 Bridgewire resistance. Each cartridge in the ballistic sample shall be screened for proper bridgewire resistance by use of a resistance bridge or other suitable test circuit. Current shall be limited to 50 milliamperes maximum.

4.3.5 Torque. Each cartridge in the ballistic sample shall be subjected to a minimum torque of 14 inch-pounds. The torque shall be applied through the positive terminal of the cartridge using an MS21044-C06 nut and a calibrated torque wrench. No rotation of the insulator shall be allowed.

4.3.6 Vibration. Vibration shall be conducted in accordance with MIL-STD-810C, Method 514.2. Use Table 514.2-II, Curve H, except that cycling time shall be divided equally for vibration at –65, +70, and +200°F. The six cartridges shall be vibrated at the same time.

4.3.7 Temperature/humidity cycling. Temperature/humidity cycling shall be conducted in accordance with MIL-D-21625.

4.3.8 Shock. Shock shall be conducted in accordance with MIL-STD-810C, Method 516.2, Procedure I, and Figure 516.2-1. The six cartridges shall be shock tested at the same time.

4.3.9 Ballistic test. The cartridges shall be fired in a closed bomb test fixture, Drawing 298AS105, within 3 minutes after removal from temperature conditioning. If any cartridge is exposed to the temperature environment for greater than the time allowed or not fired within 3 minutes after removal, it shall be reexposed to the original environment for not less than 1 hour nor more than 24 hours before test firing. The reexposure may be performed as many times as necessary to complete the required ballistic test. Instrumentation shall be provided to measure and record the cartridge pressure (psig) in the test chamber, the ignition delay (milliseconds), and the rise time (milliseconds). The test chamber shall be thoroughly cleaned after each cartridge firing. The production lot shall be accepted if the sample fulfills the acceptance criteria of 4.3.9.1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T04:18Z
Check the source to verify that this is the current version before use.

4.3.9.1 Acceptance criteria.

4.3.9.1.1 Maximum pressure. The maximum pressure shall be measured at the point at which the pressure reaches its maximum in the test fixture. The lot shall be acceptable with respect to pressure limits if the ballistic sample meets the requirements of 3.4.4.1. The acceptance number of defects is zero and the rejection number of defects is one.

4.3.9.1.2 Ignition delay. The ignition delay shall be measured from the first application of 5 amps to the bridgewire circuit to first indication of pressure. The lot shall be acceptable with respect to ignition delay if the ballistic sample meets the requirements of 3.4.4.3. The acceptance number of defects is zero and the rejection number of defects is one.

4.3.9.1.3 Pressure rise time. The pressure rise time shall be measured from the first indication of pressure to the point at which the pressure reaches its minimum acceptable maximum pressure value in the test fixture as specified in 3.4.4.1. The lot shall be acceptable with respect to pressure rise if the ballistic sample meets the requirements of 3.4.4.2. The acceptance number of defects is zero and the rejection number of defects is one.

4.3.9.1.4 Misfire. A cartridge that does not fire under the conditions specified in 3.4.4 shall be considered defective and the lot considered unacceptable, unless the misfire is clearly attributable to faulty test equipment or procedure.

4.3.9.2 Retests. There shall be no retests.

4.3.9.3 Test failure. If test failure is attributable to an assignable cause, excluding the test cartridge, the original test results shall be discarded and that test reconducted.

5. PACKAGING

5.1 Packaging. For acquisition purposes, the packaging requirements shall be as specified in the contract or order (see 6.2). When actual packaging of materiel is to be performed by DOD personnel, these personnel need to contact the responsible packaging activity to ascertain requisite packaging requirements. Packaging requirements are maintained by the Inventory Control Point's packaging activity within the Military Department or Defense Agency, or within the Military Department's System Command. Packaging data retrieval is available from the managing Military Department's or Defense Agency's automated packaging files, CD-ROM products, or by contacting the responsible packaging activity.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful but is not mandatory).

6.1 Intended use. The fire extinguisher provides power to initiate the emergency fire extinguisher system in the Sikorsky SH-60B helicopter. The cartridge creates gas pressure which separates the split sleeve. Pressure from the fire extinguisher container forces the valve open and releases the fire extinguisher agent. The cartridge is designed for military helicopter use and has no equivalent commercial application.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T04:18Z
Check the source to verify that this is the current version before use.

6.2 Acquisition requirements. Acquisition documents must specify the following:

a. Title, number, and date of this specification.

b. Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.2.1, 2.2.2, and 2.3).

c. Whether first article inspection is required and, if so, specify the test activity (see 3.1 and 4.2.1).

d. Directions for shipping radiographs of entire production lot and marriage log (report indicating cartridge serial number to initiator serial number), along with the ballistic sample to the activity conducting the production lot acceptance tests (see 4.3.3.1 and 4.3.3.2).

e. That the safety precaution requirements of the "DoD Contractors' Safety Manual for Ammunition and Explosives," DoD 4145.26-M, are applicable and should be specified in the contract as required by Federal Acquisition Regulation (FAR) 23.3. NOTE: When this specification is used as part of the description of work to be accomplished by a Government activity the safety precaution requirements of "Ammunition and Explosives Ashore," OP 5, are applicable.

6.3 First article. When a first article inspection is required, the contracting officer should provide specific guidance to offerors whether the items should be a first article sample or a sample selected from the first production items (see 3.1), and the number of items to be tested as specified in 4.2.1. The contracting officer should also include specific instructions in acquisition documents regarding arrangements for examination, approval of first article test results, and disposition of first articles. Invitations for bids should provide that the Government reserves the right to waive the requirement for samples for first article inspection to those bidders offering a product which has been previously acquired or tested by the Government, and that bidders offering such products, who wish to rely on such production or test, must furnish evidence with the bid that prior Government approval is presently appropriate for the pending contract. Bidders should not submit alternate bids unless specifically requested to do so in the solicitation.

6.4 Subject term (keyword) list.

gas pressure
helicopter
SH-60B helicopter
Sikorsky helicopter

Preparing activity:
Navy - OS
(Project 1377-0064)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T04:18Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.

2. The submitter of this form must complete blocks 4, 5, 6, and 7.

3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	**1. DOCUMENT NUMBER** MIL-DTL-32010 (OS)	**2. DOCUMENT DATE (YYMMDD)** 980123

3. DOCUMENT TITLE **Fire Extinguisher Cartridge, CCU-90/A (MH92)**

4. NATURE OF CHANGE *(Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)*

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME *(Last, First, Middle Initial)*	b. ORGANIZATION	
c. ADDRESS *(Include Zip Code)*	d. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON *(if applicable)*	**7. DATE SUBMITTED** (YYMMDD)

8. PREPARING ACTIVITY

a. NAME COMMANDER, INDIAN HEAD DIVISION NAVAL SUREFACE WARFARE CTR (CODE 840M)	b. TELEPHONE *Include Area Code)* (1) Commercial 301-743-4700 (2) AUTOVON 354-4700
c. ADDRESS *(Include Zip Code)* 101 STRAUSS AVENUE INDIAN HEAD, MD 20640-5035	**IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT:** DEFENSE QUALITY AND STANDARDIZATION OFFICE 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22401-3466 Telephone (703) 756-2340 AUTOVON 289-2340

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T04:18Z
Check the source to verify that this is the current version before use.