INCH-POUND
MIL-DTL-32015(AS)
Amendment 1
22 May 2000

DETAIL SPECIFICATION SHEET

MICROPHONE, LINEAR GENERAL SPECIFICATION FOR

This amendment forms a part of MIL-DTL-32015(AS), dated 15 October 1999, and is approved for use by the Naval Air Systems Command, Department of Navy, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 7

Paragraph 3.8.2.2.2 Frequency response at altitude.

Change: "15,000 feet" to "25,000 feet"

PAGE 10

Add: Paragraph 3.8.4.15 and 3.8.4.16.

"3.8.4.15. Rapid decompression. When specified in the applicable specification sheet, the microphone shall be tested in accordance with the low-pressure altitude test of MIL-STD-810, Method 500.4, Procedure III and 4.5.5.15. The microphone shall withstand a simulated loss of cabin pressure from 8,000 to 40,000 feet in not more than 15 seconds. The microphone assembly shall fully recover without damage or degradation within 2.0 seconds following the decompression and meet the requirements of 3.8.2.1.1, 3.8.2.2.1 and 3.8.2.3.

3.8.4.16. Explosive decompression. When specified in the applicable specification sheet, the microphone shall be tested in accordance with the low-pressure altitude test of MIL-STD-810, Method 500.4, Procedure IV and 4.5.5.16. The microphone shall withstand a simulated loss of cabin pressure from 8,000 to 23,000 feet in 0.1 second and from 20,500 to 50,000 feet in 0.1 second. The microphone assembly shall fully recover without damage or degradation within 1.0 second following the decompression and meet the requirements of 3.8.2.1.1, 3.8.2.2.1 and 3.8.2.3."

DISTRIBUTION STATEMENT A: Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T04:18Z
Check the source to verify that this is the current version before use.

PAGE 14

Add to: TABLE I First article inspection under Subgroup C (1 sample)

Inspection	Requirement Paragraph	Test Method Paragraph
Rapid decompression	3.8.4.15	4.5.5.15
Explosive decompression	3.8.4.16	4.5.5.16

PAGE 30

Add: Paragraph 4.5.5.15 and 4.5.5.16.

"4.5.5.15 Rapid decompression. The microphone assembly shall be subjected to MIL-STD-810, Procedure III Method 500.4. The following conditions shall apply:

a. Initial cabin altitude: 8,000 feet standard atmosphere pressure.
b. Final altitude: 40,000 feet after decompression and appropriate pressure for 10 minutes minimum.
c. Decompression rate: not more than 15 seconds.
d. Test item configuration: The microphone assembly shall be assembled to a compatible helmet assembly placed in the test chamber. Listeners in an external room shall monitor the performance of the microphone assembly before, during and after the test. A continuous audio input shall be applied within ¼-inch of the 'TALK' side of the microphone element.
e. Failure criteria: The microphone assembly shall fully recover, without damage or degradation within 1.0 second of the decompression and meet the requirements of 3.8.2.1.1, 3.8.2.2.1 and 3.8.2.3 following the test.

4.5.5.16 Explosive decompression. The microphone assembly shall be subjected to MIL-STD-810, Procedure IV Method 500.4. The following conditions shall apply:

a. Initial cabin altitude: 20,500 feet standard atmosphere pressure.
b. Final altitude: 50,000 feet after decompression and appropriate pressure for 10 minutes minimum.
c. Decompression rate: not more than 0.1 second.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T04:18Z
Check the source to verify that this is the current version before use.

d. Test item configuration: The microphone assembly shall be assembled to a compatible oxygen mask assembly placed in the test chamber. Listeners in an external room shall monitor the performance of the microphone assembly before, during and after the test. A continuous audio input shall be applied within ¼-inch of the 'TALK' side of the microphone element.
e. The test shall be repeated with an initial cabin altitude of 8,000 at one atmosphere and 25 degrees C and final altitude of 23,000 feet after decompression and appropriate pressure for 10 minutes minimum. Decompression rate: not more than 0.1 second.
f. Failure criteria: The microphone assembly shall fully recover, without damage or degradation within 1.0 second of the decompression and meet the requirements of 3.8.2.1.1, 3.8.2.2.1 and 3.8.2.3 following the test."

Preparing activity:
Navy - AS
(Project No. 5965-0348)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T04:18Z
Check the source to verify that this is the current version before use.