NOT MEASUREMENT SENSITIVE

MIL-PRF-32014B
28 May 2025

SUPERSEDING
MIL-PRF-32014A
12 September 2006

PERFORMANCE SPECIFICATION

GREASE, AIRCRAFT AND INSTRUMENT

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the general requirements for a multipurpose, water-resistant, high-speed grease for use in the -54 °C to +177 °C temperature range.

2. APPLICABLE DOCUMENTS

2.1 General. The documents listed in this section are specified in sections 3 and 4 of this specification. This section does not include documents cited in other sections of this specification or recommended for additional information or as examples. While every effort has been made to ensure the completeness of this list, document users are cautioned that they must meet all specified requirements of documents cited in sections 3 and 4 of this specification, whether or not they are listed.

Comments, suggestions, or questions on this document should be addressed to AFPET/PTPS, 2430 C Street, Building 70, Area B, Wright-Patterson AFB, OH 45433 or e-mailed to AFPET.PTPS@us.af.mil. Since contact information can change, you may want to verify the currency of this address information using the ASSIST Online database at https://assist.dla.mil.

AMSC N/A FSC 9150

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T04:18Z
Check the source to verify that this is the current version before use.

2.2 Government documents.

2.2.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the solicitation or contract.

FEDERAL STANDARDS

FED-STD-791 - Testing Method of Lubricants, Liquid Fuels, and Related Products

(Copies of this document are available online at https://quicksearch.dla.mil/.)

2.2.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation or contract.

DEFENSE FORMS MANAGEMENT PROGRAM

DD Form 1718 - Certification of Qualified Products

(Copies of this document are available online at https://www.esd.whs.mil/DD/.)

DEFENSE STANDARDIZATION PROGRAM OFFICE

SD-6 - Provisions Governing Qualification

(Copies of this document are available online at https://quicksearch.dla.mil.)

2.3 Non-Government publications. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation or contract.

ASTM INTERNATIONAL

ASTM D97 - Standard Test Method for Pour Point of Petroleum Products

ASTM D217 - Standard Test Methods for Cone Penetration of Lubricating Grease

ASTM D445 - Standard Test Method for Kinematic Viscosity of Transparent and Opaque Liquids (and Calculation of Dynamic Viscosity)

ASTM D942 - Standard Test Method for Oxidation Stability of Lubricating Greases by the Oxygen Pressure Vessel Method

ASTM D1264 - Standard Test Method for Determining the Water Washout Characteristics of Lubricating Greases

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T04:18Z
Check the source to verify that this is the current version before use.

ASTM D1478	-	Standard Test Method for Low-Temperature Torque of Ball Bearing Grease
ASTM D2265	-	Standard Test Method for Dropping Point of Lubricating Grease Over Wide Temperature Range
ASTM D2266	-	Standard Test Method for Wear Preventive Characteristics of Lubricating Grease (Four-Ball Method)
ASTM D2595	-	Standard Test Method for Evaporation Loss of Lubricating Greases Over Wide-Temperature Range
ASTM D2596	-	Standard Test Method for Measurement of Extreme-Pressure Properties of Lubricating Grease (Four-Ball Method)
ASTM D3336	-	Standard Test Method for Life of Lubricating Greases in Ball Bearings at Elevated Temperatures
ASTM D4048	-	Standard Test Method for Detection of Copper Corrosion from Lubricating Grease
ASTM D5707	-	Standard Test Method for Measuring Friction and Wear Properties of Lubricating Grease Using a High-Frequency, Linear-Oscillation (SRV) Test Machine
ASTM D5949	-	Standard Test Method for Pour Point of Petroleum Products (Automatic Pressure Pulsing Method)
ASTM D6138	-	Standard Test Method for Determination of Corrosion-Preventive Properties of Lubricating Greases Under Dynamic Wet Conditions (Emcor Test)
ASTM D6184	-	Standard Test Method for Oil Separation from Lubricating Grease (Conical Sieve Method)

(Copies of these documents are available from https://www.astm.org.)

2.4 Order of precedence. Unless otherwise noted herein or in the contract, in the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in the document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Qualification. Items furnished under this specification shall be products that are authorized by the qualifying activity for listing in Qualified Products List QPL-32014 before contract award (see 4.2 and 6.3). Changes shall not be permitted in the formulation of an approved product unless specific, written approval of the qualifying activity is obtained.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T04:18Z
Check the source to verify that this is the current version before use.

3.2 Materials. The materials used in formulating this grease shall consist of a base oil conforming to requirements in Table I and suitable additives. A polyalphaolefin, lithium soap thickened formulation is recommended, but is not mandatory. The thickener system proposed shall be compatible with lithium soap thickened grease.

TABLE I. Properties of the base oil.

Property	Qualification	Re-qualification	Test Limits	ASTM Test Method
Viscosity				D445
at 40 °C, mm^2/s	X	X	max 140	
at 100 °C, mm^2/s	X	X	min 16	
Pour Point, °C	X	X	max -35	D97 or D5949 1/
NOTES:				
1. Referee test method.				

3.3 Finished grease. The properties of the finished grease shall be as specified in Table II.

TABLE II. Properties of the finished grease.

Property	Qualification	Re-qualification	Test Limits	Section	Test Methods	
					FED-STD-791 1/	ASTM
Workmanship	X	X	Pass	3.4		
Cone penetration	X	X				D217
Worked penetration (60 double strokes)	X	X	265 – 305			
worked stability (100,000 double strokes)	X	X	max 350			
Copper corrosion, rating 2/	X	X	max 1b			D4048
Corrosion Prevention						D6138
Emcor corrosion test, 3% synthetic sea water	X	X	Pass 3/			
Dirt, particle per mm of grease	X	X			3005	
25-74 µm, diameter	X	X	max 1000			
>75 µm, diameter	X	X	None			
Dropping point, °C	X	X	min 200			D2265
Evaporation loss, 177 °C ± 3 °C for 22 hours, percent	X	X	max 10			D2595

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T04:18Z
Check the source to verify that this is the current version before use.

TABLE II. Properties of the finished grease - (Continued).

Property	Qualification	Re-qualification	Test Limits	Section	Test Methods	
					FED-STD-791 1/	ASTM
Extreme pressure properties, wear scar, mm	X	X	max 0.80	4.4.4		D5707
High speed bearing performance	X			4.4.5		
High speed bearing performance, hours	X		min 25	4.4.5.2		
High speed bearing performance, after 6 mo. humidity storage, hours	X		min 25	4.4.5.3		
Life of lubrication greases at elevated temperature in ball bearings, 160 °C ± 2 °C, hours	X	X	min 400			D3336
Load wear index, kgf	X	X	min 30			D2596
Low temperature torque of ball bearings, -54 °C ± 1 °C start/run @ 1 hour, Newton-meter (N•m)	X	X	max 1.4 / max 0.5			D1478
Odor	X	X	Pass	3.5		
Oil separation, percent weight loss	X	X	max 8			D6184
Oxidation stability, after 500 hours, psi	X	X	max 35			D942
Storage stability, penetration, 2 mo., 20 °C to 25 °C	X				3467	
Worked (change from original), points	X		max 30			
Water washout, 41 °C ± 1 °C, percent	X	X	max 15			D1264
Wear preventative characteristics, wear scar average, mm	X	X	max 0.65			D2266
Compatibility	X	X	Pass	3.6		

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T04:18Z
Check the source to verify that this is the current version before use.

TABLE II. Properties of the finished grease - (Continued).

NOTES:	
1.	FED-STD-791 test methods listed in Table II: (i) Method 3005 "Dirt Content of Grease," (ii) Method 3467 "Storage Stability of Lubricating Grease"
2.	The grease shall show no green color in that portion contacting the copper strip. The copper strip shall not tarnish more than a classification of 1b when compared with the ASTM copper corrosion standards.
3.	A pass on the corrosion prevention test constitutes a maximum rating of 2 in duplicate per the Report section of ASTM D6138.

3.4 Workmanship. The grease, when examined visually, shall be a smooth and homogeneous mixture, free from lumps and extraneous materials.

3.5 Odor. The grease shall not have an odor of rancidity, perfume, or free alcohol.

3.6 Compatibility. The grease shall be compatible with all previously qualified greases listed in QPL-32014 when tested in accordance with 4.4.6. Immediately after mixing, and after undisturbed storage for seven days, the mixture shall not form resinous gums, sludge, or insoluble solid materials and shall comply with the worked penetration and worked stability requirements (see Table II). In the event of failure, the previously qualified grease (unmixed with other greases) shall be tested to verify that it meets the worked penetration and worked stability requirements under the conditions specified in 4.4.6. If the previously qualified sample fails to meet the worked penetration or worked stability requirement, a fresh sample shall be obtained and the compatibility test repeated. Additional mix ratios of 90 percent previously qualified and 10 percent new and vice versa may be used during qualification testing.

3.7 Recycled, recovered, environmentally preferable, or biobased materials. Recycled, recovered, environmentally preferable, or biobased materials should be used to the maximum extent possible, provided that the material meets or exceeds the operational and maintenance requirements, and promotes economically advantageous life cycle costs.

4. VERIFICATION

4.1 Classification of inspections. The examination and testing of the grease are classified as follows:

a. Qualification inspection (see 4.2).

b. Conformance inspection (see 4.3).

4.2 Qualification inspection. Qualification inspection shall consist of testing to all of the requirements specified in sections 3, 4.4 to 4.4.6, Table I, and Table II. When required by the qualifying activity, additional evaluations may be required on candidate formulations.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T04:18Z
Check the source to verify that this is the current version before use.

4.2.1 Qualification process. At the initiation of the qualification process, prospective suppliers will forward a written request for such action to the qualifying activity, Air Force Petroleum Office, AFPET/PTPS, 2430 C Street, Building 70, Area B, Wright-Patterson AFB, OH 45433 or via e-mail (AFPET.PTPS@us.af.mil). This request will contain general information on the proposed candidate material. The qualifying activity will reply in writing outlining the required information to be submitted, the governing regulations for qualified products, and the cost of testing. The information that will be submitted includes:

a. Letter stating the company will adhere to the appropriate provisions of the SD-6 on company letterhead.

b. Complete formulation of the candidate product (base oil, thickener, and additives), including chemical composition in weight percent, the manufacturer, the commercial trade name and CAS number, the purities, and use of each component.

c. Safety Data Sheet (SDS) for each component and final product. The SDS will not be older than 5 years.

d. Certified laboratory test data from the manufacturer, a commercial laboratory, or combination thereof showing quantitative results of all qualification tests required by this specification as identified in Table I and Table II documented on a signed Certificate of Analysis (COA).

    i. Qualification laboratory test data results covering Table I requirements for compatibility testing shall only be acceptable when performed by commercial or third-party laboratory and documented in a COA.

e. Verification that the System for Award Management (SAM) (CAGE Codes for the corporate office and each plant) is current. This can be viewed at https://sam.gov/.

f. Identification of the manufacturing site of the specific batch of test sample to be submitted.

g. A completed DD Form 1718.

4.2.2 Qualification samples. Qualification samples shall consist of four pounds (2 kilograms) of grease and one-half pint (0.5 liters) of base oil. The additives, in 4-ounce quantities, may be requested at the option of the qualifying activity.

4.2.3 Retention of qualification. To retain qualification of products approved for listing on the Qualified Products List (QPL), the manufacturer will be requested to verify by certification (DD Form 1718) to the qualifying activity that its product(s) comply with the requirements of this specification. The manufacturer shall also provide a recent Certificate of Analysis COA, to include all conformance inspection requirements (see 4.3), a current SDS, and formulation. Unless otherwise specified by the qualifying activity, the time of periodic verification by certification will be in 2½-year intervals from the date of original qualification and will be initiated by the manufacturer. The Government reserves the right to re-examine the qualified product whenever deemed necessary to determine that the product continues to meet any or all of the specification requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T04:18Z
Check the source to verify that this is the current version before use.

4.2.4 Requalification. Requalification shall be required every five (5) years or when any change is made in the source of manufacture, purity, or composition of the base oil or additives. A minor change in the grease formulation might not need requalification testing, but only after notification to, and approval by the qualifying activity (see 6.3). The documentation required for requalification are the same as requirements stated in section 4.2.1 and shall include product formulation, safety data sheet (SDS) for each component (base oil, thickener, and additives) and final product, and a COA showing compliance to the all of the requalification requirements specified in Table I and Table II, and four one-pound containers of grease and one-half pint of base oil from a recent production run. The SDS will not be older than five (5) years. The qualifying activity may, at its discretion, waive complete requalification or may require only partial requalification testing to determine the significance and acceptability of the proposed formulation change.

4.3 Conformance inspection. The quality conformance inspection shall consist of all of the tests listed in Table III. Samples shall be labeled completely with information that identifies the purposes of the sample, name of product, specification number, lot and batch number (see 6.4), date of manufacture, and date of sampling.

4.4 Method of inspection. Tests shall be performed in accordance with the methods specified in Table I, Table II, 4.4.1 through 4.4.5, and the contractual requirements (see 6.2). Physical and chemical values apply to the average of the determinations made on the samples.

4.4.1 Inspection. Unless otherwise specified, inspection testing shall be performed in accordance with 4.4.2 and the contractual requirements (see 6.2).

4.4.2 Grease. The grease shall conform to the requirements for base oil and finished grease that shall be determined by appropriate examination and testing in accordance with 4.4.3.

4.4.3 Physical and chemical values. Tests shall be performed in accordance with the applicable methods specified in Table I and Table II and 4.4.4 through 4.4.6. Physical and chemical values specified in section 3 apply to the arithmetic average of the determinations made on the samples for those values that fall within any stated repeatability or reproducibility limits of the applicable test method.

4.4.4 Modification of ASTM D5707 for the use of the reciprocating tribometer. Follow ASTM D5707 with these exceptions:

a. Use disks polished to 4 microns or less.

b. Use individual washings of hexane, acetone, and isopropanol, for ultrasonic cleaning.

c. Use 0.5 grams of test grease.

d. Preload 20N for run-in for 2 min.

e. 2.3 mm (± 0.2 mm) stroke length.

f. Manually load to 600 N after run-in and run at 600 N thereafter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T04:18Z
Check the source to verify that this is the current version before use.

g. Test time: 30 minutes total including run-in.

h. Run the test at 80 °C.

i. Report size of wear scar on ball using ASTM D2266 for ball measurements.

j. Graph coefficient of friction and contact resistance for each test, if possible.

TABLE III. Conformance properties and test methods.

Property	Test Limits	Test Method	
		FED-STD-791 /1	ASTM
Workmanship	Pass (section 3.4)		
Cone penetration			D217
Worked penetration	265-305		
Worked stability, 100,000 double strokes	max 350		
Copper corrosion, rating /2	max 1b		D4048
Corrosion Prevention			D6138
Synthetic sea water, 3%	Pass /3		
Dirt, particles per millimeter of grease		3005	
25-74 micrometers, diameter	1000 max		
>75 micrometers, diameter	None		
Dropping point, °C	min 200		D2265
Evaporation loss, 175 °C ± 3 °C for 22 hours, percent	max 10		D2595
Load wear index, Kgf	min 30		D2596
Odor	Pass (section 3.5)		
Oil separation, weight percent loss	max 8		D6184
Oxidation stability, after 500 hours, psi	max 35		D942
Water washout, 41°C ± 1 °C , percent	max 15		D1264
Wear preventative characteristics, wear scar average, mm	max 0.65		D2266

NOTES:

1.	FED-STD-791 test method listed in Table III: Method 3005 "Dirt Content of Grease"
2.	The grease shall show no green color in that portion contacting the copper strip. The copper strip shall not tarnish more than a classification of 1b when compared with the ASTM copper corrosion standards.
3.	A pass on the corrosion prevention test constitutes a maximum rating of 2 in duplicate per the Report section of ASTM D6138.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T04:18Z
Check the source to verify that this is the current version before use.

4.4.5 High speed bearing performance.

4.4.5.1 Apparatus. Performance shall be determined in a Marlin Rockwell 538°C grease testing unit developed for the CRC L-54 research technique, or equivalent, using ASTM D3336 test method with the following modifications: A variable-speed electric drive motor installed with a large balanced pulley and a light-weight flat belt to rotate a spindle supported by two ball bearings. The rig shall be modified to accommodate a 17 mm bore size 203 test ball bearing located at the opposite end of the spindle from the drive pulley. This bearing shall be made of M-50 tool steel and phenolic resin with aluminum side plates fastened with rivets. Dished side shields shall be used to retain additional lubricant. The spindle support bearing located next to the pulley shall be Marlin Rockwell type 204 S-17 or equivalent with races and balls made of M-50 tool steel and bore diameters of 20 mm or equivalent. The ball retainer shall be a stamped ribbon type made of silver plated beryllium copper. A thermocouple in contact with the outer race of the test bearing shall be connected to at temperature controller, a recorder, and a data logger. An oven capable of maintaining the test temperature is required. An air cylinder connected to a steel cable is required to apply thrust load to the test bearing housing.

4.4.5.2 Procedure. Prior to testing, the side shields of the 203 test bearing shall be removed and all the bearing components cleaned thoroughly with hexane. The bearing shall be packed with 0.535 grams ± 0.050 grams of test grease and 0.625 grams ± 0.050 grams of grease in each of the two shields. The shields shall then be replaced carefully. After installing on the tester, the test bearing shall be run at 30,000 rpm, thrust loading at 1769 N ± 9 N. The test is started at room temperature for four hours and then at a temperature of 115.5 °C ± 2 °C for a total test time of 25 hours.

4.4.5.3 High speed bearing performance after storage. A 203 size bearing is also packed as in 4.4.5.2 and stored vertically from nichrome wire in an oven at 71 °C ± 2 °C and 98 to 100 percent relative humidity. After six months, the bearing is removed and tested as in 4.4.5.2.

4.4.6 Compatibility. Fill standard grease cups with equal volumes of the grease being tested and previously qualified greases. The cup shall be filled by alternately adding 60 grams of each of the two greases being tested, until the cup is full (approximately 454 grams). Mix the two greases by working the sample for 60 double strokes in accordance with the worked penetration procedure of ASTM D217 and then let the mixture stand undisturbed for seven days at 19.0 °C to 29.5 °C (65 °F to 85 °F) and 50 ± 10 percent relative humidity. Examine the worked penetration and then the worked stability in accordance with Table II, using the same sample of grease mixture for both tests. Small amounts of fresh grease may be added to the worker cup just prior to the worked stability, as needed to maintain a full cup for testing.

5. PACKAGING

5.1 Packaging. For acquisition purposes, the packaging requirements shall be as specified in the contract or order (see 6.2). When packaging of materiel is to be performed by DoD or in-house contractor personnel, these personnel need to contact the responsible packaging activity to ascertain packaging requirements. Packaging requirements are maintained by the Inventory Control Point's packaging activities within the Military Service or Defense Agency, or within the military service's system commands. Packaging data retrieval is available from the managing

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T04:18Z
Check the source to verify that this is the current version before use.

Military Department's or Defense Agency's automated packaging files, CD-ROM products, or by contacting the responsible packaging activity.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. The grease covered by the specification is intended as a general-purpose aircraft lubricant and is used to lubricate main shaft bearings in missile engines. It provides water resistance and corrosion protection for aircraft and missiles over an extended period. It will be operational between -54 °C and +175 °C.

6.2 Acquisition requirements. Acquisition documents should specify the following:

a. Title, number, and date of this specification.

b. Type and size of containers.

c. Quantity required.

d. Packaging requirements (see 5.1).

6.3 Qualification. With respect to products requiring qualification, contract awards will be made only for such products that are, at the time of award of contract, qualified for inclusion in Qualified Products List QPL No. 32014 whether or not such products have actually been so listed by that date. The attention of the contractors is called to these requirements, and manufacturers are urged to arrange to have the products that they propose to offer to the Federal Government tested for qualification in order that they may be eligible to be awarded contracts or orders for the products covered by this specification. Information pertaining to qualification of products may be obtained from AFPET/PTPS, 2430 C Street, Building 70, Area B, Wright-Patterson AFB OH 45433; e-mail: AFPET.PTPS@us.af.mil. An online listing of products qualified to this specification may be found in the Qualified Products Database (QPD) at https://assist.dla.mil.

6.3.1 Qualification information. It is understood that the material furnished under this specification subsequent to final approval will be of the same composition and will be equal to products on which approval was originally granted. In the event that fluid furnished under contract is found to deviate from the composition of the approval product, or that the product fails to perform satisfactorily, approval of such products may be subjected to immediate withdrawal from the QPL at the discretion of the approving activity.

6.3.2 Proceed authorization notification. Upon successful review of the submitted information, the Air Force Petroleum Office will issue authorization to ship the qualification sample(s) for testing.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T04:18Z
Check the source to verify that this is the current version before use.

6.3.3 Qualification samples. Upon receiving authorization from the Air Force Petroleum Office, qualification sample(s) may be shipped to the qualification activity, as detailed in the authorization letter. Sample(s) should be accompanied by an SDS and a copy of the authorization letter. Each sample should be plainly identified by securely attached durable tags or labels marked with the following information:

a. QUALIFICATION SAMPLE
b. Grease, Aircraft and Instrument
c. MIL-PRF-32014
d. Name of Manufacturer
e. Product Code Number
f. Lot (Batch) Number
g. Date of Manufacture
h. Name of ingredient (for ingredient material)

6.3.4 Formulation sheet. An example of a satisfactory form for the formulation sheet, indicating the weight percentage and nature of each ingredient is as follows:

a. Base oil (chemical composition, CAS number, manufacturer's name and number) percentage
b. Thickener (chemical composition, CAS number, manufacturer's name and number) percentage
c. Each additive (chemical composition, CAS number, manufacturer's name and number) percentage

6.4 Definitions.

6.4.1 Packaged lot. A packaged lot is an indefinite number of 35-pound pails or smaller unit containers of identical size and type, offered for acceptance, and filled with a homogeneous material mixture from one isolated container or filled with a homogeneous material mixture manufactured is a single-plant run (not to exceed 48 hours), through the same processing equipment, with no change in ingredient material.

6.5 Shelf-life. This specification covers items where the assignment of a Federal shelf-life code is a consideration. Specific shelf-life requirements should be specified in the contract or purchase order, and should include, as a minimum, shelf-life code, shelf-life package markings IAW MIL-STD-129 or FED-STD-123, preparation of a materiel quality storage standard for type II (extendible) shelf-life items, and a minimum of 85 percent shelf-life remaining at time of receipt by the Government. These and other requirements, if necessary, are in DoDM 4140.27, Volume 1, *Shelf-Life Management Program: Program Administration*; and Volume 2, *Shelf-Life Management Program: Materiel Quality Control Storage Standards*. The shelf-life codes are in the Federal Logistics Information System Total Item Record. Additive information for shelf-life management may be obtained from DoDM 4140.27 Volumes 1 and 2, or the designated shelf-life Points of Contact (POC). The POC should be contacted in the following order: (1) the Inventory

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T04:18Z
Check the source to verify that this is the current version before use.

Control Points that manage the item and (2) the DoD Service and Agency administrators for the DoD Shelf-Life Program. Appropriate POCs for the DoD Shelf-Life Program can be contacted through the DoD Shelf-Life Management website: https://www.shelflife.dla.mil/.

6.6 Subject term (key word) listing.

General purpose grease

Missile engine grease

Water resistant grease

6.7 Conversion of metric units. Units of measure have been converted to the International System of Units (Metric) IAW IEEE/ASTM SI10 *American National Standard for Metric Practice*. If test results are obtained in units other than Metric or there is a requirement to report dual units, IEEE/ASTM SI10 or NIST SP 811 *Guide for the Use of the International System of Units (SI)* should be used to convert the units.

6.8 Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T04:18Z
Check the source to verify that this is the current version before use.

CONCLUDING MATERIAL

Custodians:
Army – CR4
Navy – AS
Air Force – 68

Preparing activity:
Air Force – 68
(Project 9150-2019-004)

Review activities:
Army – AR, AT, AV, EA, MI
Navy – SH
DLA – PS

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T04:18Z
Check the source to verify that this is the current version before use.