MIL-C-46907B (MU)
28 APRIL 1965
SUPERSEDING
MIL-C-46907A (MU)
5 DECEMBER 1963

MILITARY SPECIFICATION

CHARGE, PROPELLING, M36A1, BAG LOADING ASSEMBLY FOR

1. SCOPE.

1.1 This specification covers the Bag Loading Assembly for the M36A1 Propelling Charge for use in 4.2 Inch Mortar ammunition.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-A-2550 — Ammunition and Special Weapons; General Specification for

MIL-I-45607 — Inspection Equipment, Supply and Maintenance of

STANDARDS

MILITARY

MIL-STD-105 — Sampling Procedures and Tables for Inspection by Attributes (ABC-STD-105)

MIL-STD-109 — Quality Assurance Terms and Definitions

MIL-STD-1235 — Single and Multilevel Continuous Sampling Procedures and Tables for Inspection by Attributes

DRAWINGS

ORDNANCE CORPS

8863614 — Bag Loading Assembly

76-1-1039 — Drum, Metal, for 75MM, and 105MM Howitzer Propelling Charges

76-4-46 — Box, Packing, with Metal liner, M24, for Smokeless Powder, Assembly and Details

76-4-56 — Box, Packing, Metal-Wood, M17 for Smokeless Propellant

76-4-59 — Box, Packing, Metal-Wood, M18 for Smokeless Powder

7549033 — Container, Metal, Univer-

FSC 1315

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T07:14Z
Check the source to verify that this is the current version before use.

sal, M25 for Propellants and Explosives

8858577 – Marking Diagram and Sealing of Container, Metal, Universal M25 for Shipment of Propellants

8858848 — Marking Diagram and Sealing of Metal Lined Wooden Packing Boxes for Shipment of Propellants

PUBLICATIONS

ORDNANCE CORPS

IEL–8863614 — Index of Inspection Equipment Lists

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.

3. REQUIREMENTS

3.1 Material. Materials shall be in accordance with applicable drawings and specifications.

3.2 Bag loading assembly. The bag loading assembly shall comply with all requirements specified on Drawing (dwg.) 8863614 and with all requirements specified in applicable specifications.

3.3 Workmanship. All components and assemblies shall be fabricated and loaded in a thorough, workmanlike manner. They shall be free of dirt, grease and other foreign material. All required markings shall be neat and sharply defined.

4. QUALITY ASSURANCE PROVISIONS

4.1 General quality assurance provisions. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements. Reference shall be made to Standard MIL–STD–109 in order to define terms used herein. The provisions of Specification MIL–A–2550 shall apply.

4.1.1 *Submission of product.* At the time the completed lot of product is submitted to the Government for acceptance the contractor shall supply the following information accompanied by a certificate which attests that the information provided is correct and applicable to the product being submitted:

(a) A statement that the lot complies with all of the quality assurance provisions specified within this specification.

(b) Number of units of product inspected.

(c) Results obtained, by defect code, for all inspections performed.

(d) Drawing, specification number and date, together with an identification and date of changes.

(e) Certificates of compliance on all material purchased by the contractor when such material is controlled by Government specifications referenced in any of the contractual documents.

(f) Number of items in the lot.

(g) Date submitted.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T07:14Z
Check the source to verify that this is the current version before use.

The certificate shall be signed by a responsible agent of the certifying organization. The initial certificate submitted shall be substantiated by evidence of the agent's authority to bind his principal. Substantiation of the agent's authority will not be required with subsequent certificates unless, during the course of the contract, this authority is vested in another agent of the certifying organization.

4.1.2 *Government verification.* Using the contractor's written quality assurance procedure, this detail specification, the applicable drawings and other contractual documents as a guide, the Government inspector shall verify at unscheduled intervals all quality assurance operations performed by the contractor. Verification will be performed to the extent necessary to assure compliance with the contractual requirements. Severity of Government inspection of individual characteristics will be directly related to the seriousness of the classification assigned. In no instance will a characteristic classified "critical" be accepted solely on the basis of the contractor's records.

4.2 Inspection provisions

4.2.1 *Lot formation.* A lot shall consist of bag loading assemblies produced by one manufacturer in one unchanged process, in accordance with the same drawing, same drawing revision, same specification, and same specification revision. Drawing, specification, and process changes not affecting safety, performance or interchangeability, as determined by the Government, shall not necessitate changing the lot interfix number. Each lot shall contain propellant from not more than one lot. Lots shall be submitted for inspection in accordance with Standard MIL–STD–105 (or Standard MIL–STD–1235, when applicable).

4.2.2 *Examination.* Inspection for Critical defects shall be 100 percent. Sampling plans and procedures for Major and Minor defects shall be in accordance with MIL–STD–105 except that continuous sampling plans in accordance with Standard MIL–STD–1235 may be used if approved by the procuring activity. Also, at the option of the procuring activity, AQL's and sampling plans may be applied to individual characteristics listed using an AQL of 0.65 percent for each Minor defect and an AQL of 0.40 percent for each Minor defect and an AQL of 0.40 percent for each Major defect. Equipment necessary for the performance of the inspections listed shall be in accordance with 4.2.4.

4.2.2.1 *Body, Increment* (see dwg. 8863615 covering a detail of dwg. 8863614).

Categories	*Defects*	*Method of Inspection*	*Code No. (see 6.2)*
Critical:	None defined.		
Major:	None defined.		
Minor:	**AQL 0.65 percent**		
201.	Diameter of increment	Gage	01001

4.2.2.2 *Body assembly* (see dwg. 8863613 covering a detail of dwg. 8863614).

Categories	*Defects*	*Method of Inspection*	*Code No.*
Critical:	None defined.		

Source: https://assist.dla.mil -- Downloaded: 202610-22T07:14Z
Check the source to verify that this is the current version before use.

Categories	Defects	Method of Inspection	Code No.
Major:	None defined.		
Minor:	AQL 1.50 percent		
201.	Diameter of center hole	Gage	02001
202.	Diameter of assembly	Gage	02002
203.	Location of center hole	Gage	02003
204.	Evidence of poor workmanship (see 3.3)	Visual	02004

4.2.2.3 *Bag loading assembly* (see dwg. 8863614).

Categories	Defects	Method of inspection	Code No.
Critical:	None defined.		
Major:	AQL 0.40 percent		
101.	Assembly damaged or incompletely stitched to the extent that propellant can escape	Visual	03001
Minor:	AQL 1.50 percent		
201.	Any seam or opening incompletely stitched	Visual	03002
202.	Threads broken	Visual	03003
203.	Marking misleading or unidentifiable	Visual	03004
204.	Evidence of poor workmanship (see 3.3)	Visual	03005

4.2.2.4 *Box or container, prior to filling* (see dwg. 76–1–1039, 76–4–46, 76–4–56, 76–4–59 and 7549033, as applicable).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		
Major:	AQL 0.40 percent		
101.	Crack or hole in metal liner (when applicable)	Visual	04001
102.	Foreign matter on interior	Visual	04002
Minor:	None defined.		

4.2.2.5 *Sealed box or container* (see dwg. 76–1–1039, 76–4–46, 76–4–56, 76–4–59, 7549033, 8858577 and 8858848, as applicable).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		
Major:	AQL 0.65 percent		
101.	Cover incompletely closed	Visual-Manual	05001
102.	Gasket missing or broken	Visual	05002

Source: https://assist.dla.mil -- Downloaded: 202610-22T07:14Z
Check the source to verify that this is the current version before use.

Categories	Defects	Method of inspection	Code No.
103.	Wooden cover split or otherwise damaged (when applicable)	Visual	05003
104.	Crack or hole in metal container	Visual	05004
Minor:	AQL 1.50 percent		
201.	Car seal missing, unsealed or improperly positioned	Visual-Manual	05005
202.	Hardware improperly engaged	Visual	05006
203.	Marking misleading or unidentifiable	Visual	05007
204.	Bare areas in exterior coating of metal container the sum of which is in excess of ¼ square inch	Visual	05008

4.2.3 *Testing.*

4.2.3.1 *Propellant weight (see dwg. 8863614)—Major defect—Code No. 06001.* The propellant shall be weighed and check-weighed 100 percent (in accordance with 4.3.1). The check-weighing shall be accomplished independently of the original weighing using a different balance from that used to make the original weighing and, if performed manually, shall be performed by another operator. Any charge that fails to comply with the applicable requirement shall be classed defective and removed from the lot.

4.2.3.2 *Air pressure test (see dwg. 8858848)—Major defect—Code No. 04003.* The containers shall be tested 100 percent in accordance with 4.3.2. If any container fails to meet the requirement it shall be rejected and removed from the lot.

4.2.4 *Inspection Equipment.* Index of Inspection Equipment Number IEL–8863614 identifies the inspection equipment required to perform the examinations and tests prescribed in this section. The contractor shall design inspection equipment in accordance with the instructions in paragraph 6.3.

4.2.4.1 *Government rights to documentation.* Inspection equipment drawings and lists provided and revised in accordance with the requirements of the IEL may be used by DOD activities for design, procurement, manufacture, testing, evaluation, production and receiving inspection, overhaul, shipping, storage, identification of stock, ordering and storage of replacement parts, inspection of items at overhaul, general maintenance of equipment, construction, survey and whenever inspection equipment drawings are needed.

4.2.4.2 *Supply and maintenance.* Supply and maintenance of the equipment listed on the IEL shall be in accordance with Specification MIL–L–45607.

4.2.4.3 *Government use of contractor's inspection and test equipment.* The contractor shall make available to the Government all inspection and test equipment necessary for determining conformance with contract requirements. Personnel for operating the equipment, and verification of its accuracy, shall be supplied by the contractor for the performance of examination or test by the Government.

4.3 Test methods and procedures

4.3.1 *Weighing of propellant.* The propellant shall be weighed and check-weighed using an approved balance having a sensitivity of 0.1 gram (1½ grains) and observation made for compliance with the applicable requirement.

4.3.2 *Air pressure test for containers.* Each container shall be subjected to an internal pressure of ½ to 1 pound per square inch using inspection equipment in accord-

Source: https://assist.dla.mil -- Downloaded: 2026l0-22T07:14Z
Check the source to verify that this is the currentversion before use.

ance with paragraph 4.2.4. An equivalent pressure drop of 0.7 inches or more of water in 15 seconds shall be cause for rejection.

5. PREPARATION FOR DELIVERY

5.1 Packing

5.1.1 *Level B.* The bag loading assemblies shall be packed in containers complying with drawings 76–1–1039, 76–4–46, 76–4–56, 76–4–59 or 7549033.

5.2 **Marking.** The containers shall be marked in accordance with dwg. 8858577 or 8858848 as applicable.

5.3 **Data cards.** Data cards shall be prepared for each lot in accordance with the information specified in Specification MIL–A–2550.

6. NOTES

6.1 **Ordering data.** Procurement documents shall specify title, number and date of this specification.

6.2 **Inspection code numbers.** The five digit code numbers assigned to the inspections herein are to facilitate future data collection and analysis by the Government.

6.3 **Inspection equipment.** The contractor shall design inspection equipment as required by the referenced Inspection Equipment Lists (IEL) in accordance with the instructions of paragraphs 6.3.1 through 6.3.7.

6.3.1 *Inspection equipment lists.* Inspection equipment lists indicate the availability of inspection equipment designs by showing in the "number" column of the list of inspection equipment (00 Form 1243–3) the numbers of drawings of existing equipment designs or codes as indicated in paragraph 6.3.2. Design action required of the contractor with respect to the different types of drawings that may be listed is described in paragraphs 6.3.3 and 6.3.4. Action required by the contractor with respect to commercial inspection equipment is described in 6.3.5. The contractor will be required to prepare detailed drawings in accordance with 6.3.6 for all the equipment coded as "Contractor Design" in the number column. These contractor designs must be approved by the Government prior to fabrication or procuring of the equipment. Designs shall be submitted for approval as specified in 6.3.7.

6.3.2 *Inspection equipment list codes.* The inspection equipment as defined in 6.3.3, 6.3.4, 6.3.5 and 6.3.6 will be designated in the IEL by the following codes:

CDAF — Contractor's design responsibility on Army format in accordance with MIL–D–45608.

CDCF — Contractor's design responsibility on contractor format.

AD — Army design.

ADMU — Army design, mandatory for use.

CE — Commercial equipment.

SCD — Specification control drawing.

6.3.3 *Army designs.* Army designs are reflected on detailed drawings which completely depict all the information necessary for the fabrication of the item of inspection equipment. The contractor need provide no design when an Army design is listed for an item of inspection equipment. Army designs fall into two basic classifications, mandatory and non-mandatory. When an inspection equipment list references mandatory Army designs, the contractor shall comply with, and use these designs accordingly. The contractor may, however, in

Source: https://assist.dla.mil -- Downloaded: 202610-22T07:14Z
Check the source to verify that this is the current version before use.

connection with non-mandatory designs and with the approval of the Government, design alternate inspection equipment or use comparable commercial equipment to facilitate his operations. Such contractor prepared designs or commercial equipment selections must be approved by the Government prior to fabrication or procuring of the equipment. Designs shall be submitted for approval as specified in 6.3.7.

6.3.4 *Specification control drawing.* Specification control drawings depict the minimum equipment requirements in outline, descriptive, diagrammatic or pictorial form only and specify the required performance or other characteristics. Contractors must prepare detailed drawings (see 6.3.6) of their designs in support of specification control drawings. These contractor prepared designs must be approved by the Government prior to the fabrication or procuring of the equipment. Commercial equipment meeting the requirements of specification control drawings may be approved if described in sufficient detail to permit identification and evaluation by the Government. Designs shall be submitted for approval as specified in 6.3.7.

6.3.5 *Commercial equipment.* Commercial equipment is inspection equipment that has universal application for a specific function. It is comprised of items commonly used by industry and Government. Contractors are not required to furnish drawings of commercial inspection equipment, but a list of such equipment must be approved by the Government. Lists shall be submitted for approval to the inspection element of the agency administering the contract.

6.3.6 *Contractor designs.* Contractor designs are designs of inspection equipment for which the Government has assigned design responsibility to the contractor. Contractor designs shall be supported by detailed drawings which depict all information necessary to completely fabricate, calibrate and operate an item of inspection equipment. This requires that the necessary views, dimensions, materials, finish, notes, operating and calibration instructions be properly depicted in accordance with approved practices to the extent that further calculation or clarification will not be required. Contractor designs identified as CDCF may be developed on the format the contractor normally employs in his equipment design procedure provided such format reflects the detail and information specified above. Contractor designs identified as CDAF shall comply with the format and requirements of MIL–D–4560S, and in addition, contain the detail and information specified above. Final approved contractor designs identified as CDCF shall be suitable for microfiiming. They must be non-reproducible diazo or electrostatic prints of top quality full size with black line on white background and shall provide a legible print produced via the 25MM microfilm process. Contractor shall submit one copy of the final design as a rolled set or flat set.

6.3.7 *Submission of contractor designs.* Designs shall be submitted for approval to the Commanding Officer, Picatinny Arsenal, ATTN: SMUPA-ND. Design review will normally be accomplished within one month after receipt by Picatinny Arsenal. Partial submission of inspection equipment designs is permissible and encouraged. However, the Arsenal completion date for design review will be based on the date of the final submission of designs.

Custodian:

Army—MU

Preparing activity:

Army—MU

Project No. 1315–A445

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T07:14Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY
PICATINNY ARSENAL
DOVER, NEW JERSEY 07801

OFFICIAL BUSINESS

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY

COMMANDING OFFICER
United States Army
Picatinny Arsenal
ATTN: SMUPA-ND
Dover, New Jersey 07801

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T07:14Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 119-R004

INSTRUCTIONS

This sheet is to be filled out by personnel either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity.

SPECIFICATION

ORGANIZATION	CITY AND STATE

CONTRACT NO.	QUANTITY OF ITEMS PROCURED	DOLLAR AMOUNT
		$

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO IF "YES", IN WHAT WAY?

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity)*	DATE

DD FORM 1 OCT 64 1426

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T07:14Z
Check the source to verify that this is the current version before use.