INCH-POUND

MIL-C-46907B (AR)
AMENDMENT 8
3 April 1990
SUPERSEDING
AMENDMENT 7
28 July 1987

MILITARY SPECIFICATION

CHARGE, PROPELLING, M36A1,
BAG LOADING ASSEMBLY FOR

This Amendment forms a part of Military Specification MIL-C-46907B (MU), dated 28 April 1965, and is approved for use withing the U.S. Army Armament, Munitions and Chemical Command and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

2.1, Specifications, add:

"FEDERAL

PPP-B-26 - Bag, Plastic (General Purpose)
PPP-T-97 - Tape, Pressure-sensitive Adhesive, Filament Reinforced"

2.1 Specifications, Military, add:

"MIL-B-117 - Bag, Sleeve and Tubing-Interior Packaging
MIL-B-2427 - Box Ammunition Packing, Wood Nailed
* MIL-T-43036 - Tape, Pressure-sensitive Adhesive Plastic Film, (For Sealing Fiber Containers and Cans)
* MIL-F-50449 - Filler Sheet Form (For Use in Ammunition Containers.)"

2.1 Standards, add:

"FEDERAL

FED-STD-101 - Test Procedures For Packaging Materials
FED-STD-406 - Plastics, Methods of Testing"

FSC 1315

AMSC N/A

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T07:13Z
Check the source to verify that this is the current version before use.

to a high temperature environment

PAGE 2

2.1, Drawings, Ordnance Corps, add:

"7548645	- Box Fiberboard, Packing, Reusable Collapsible For High Explosives
8796522	- Marking Diagram and Sealing for Wooden Packing Boxes
9241693	Packing and Marking of Fiberboard Cartons for Shoipment of Propellant Increments"

Add new paragraph 3.4 as follows:

3.4 Weight of propellant. The weight of propellant, and its tolerance, loaded into the bag loading assembly, shall be as specified on dwg. 8863614. Weighing shall be in accordance with 4.2.3.1.

Add new paragraph 3.5 as follows:

"3.5 Gross weight of propellant and bag. The weight of the bag loading assembly (see dwg. 8863614) within each lot shall not vary more than plus three or minus three grains from the established loaded bag weight (assessed propellant weight plus propellant bag average or actual weight (see 4.2.3.3)."

PAGE 4

4.2.2.3:

Minor 202: Delete in its entirety.
Minor 203: Delete: "Location of center opening" and substitute "Length of bar tack."

4.2.2.4: Add "7548645"

4.2.2.5:

Add: 7548645 and 9241693"
Add: Major defects:

"105 Carton damaged to extent that bag liner is exposed when applicable ...Visual.

106 Banding strip improperly located, missing, broken or loose (when applicable)...Visual.

Source: https://assist.dla.mil -- Downloaded: 202610-22T07:13Z
Check the source to verify that this is the currentversion before use.

Add: Minor defect:

205 Contents move when shaken...Manual"

PAGE 5

Add new paragraph:

"4.2.3.3 Gross weight of propellant and bag. Critical Defect. The loaded bag assembly shall be weighed 100 percent. Any bag loading assembly that fails to comply with the requirement as specified in 3.5 shall be calssified defective and removed from the lot."

PAGE 6

★ 5.1.1: Delete paragraph in its entirety and add:

"5.1.1 Level A. The bag loading assemblies shall be packed in heat sealed barrier bags complying with Type I, Class E, of MIL-B-117. The barrier bag size shall be 22 1/2 inches long by 22 1/2 inches wide, nominal. Approximately 15 pounds of propellant shall be packed in each bag and closed by means of heat sealing. Two heat sealed bags shall be packed in a wooden box (suggested inside box dimensions 14 1/2 inches by 14 1/2 inches by 7 1/4 inches) conforming to Grade A, Type I, Class 1 or 2 of MIL-B-2427. Both ends, sides, top and bottom of the wooden box shall be lined with 1/16 inch solid water resistance sheet material conforming to
★ MIL-F-50449. The box shall be closed and strapped in accordance with MIL-B-2427. The net weight shall not exceed 30 pounds of propellant.

5.1.1.1 Alternative Level A. The bag loading assemblies shall be packed in propellant packing boxes M17, M18, M24 or M25 complying with 76-4-56, 76-4-59, 76-4-46, and 7549033 respectively. In lieu of air pressure test, two 4-MIL conductive polyolefin or polyethylene bags can be used for all containers listed herein. Each bag must be individually ties and shall be a lay flat style bag made of conductive material in accordance with 5.1.2.1."

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T07:13Z
Check the source to verify that this is the current version before use.

Add new paragraphs 5.1.2 and 5.1.2.1 as follows:

"5.1.2 Level B. The bag loading assemblies shall be packed in a fiberboard carton conforming to requirements referenced on dwg. 7548645. The liner shall be a lay flat style bag made of conductive material in accordance with 5.1.2.1.

5.1.2.1 Liners. Liners shall be made of conductive polyethylene or polyolefin sheet with a thickness of .004 inch minimum, surface resistivity shall not exceed 1000 ohms per centimeter, wehn tested in accordance with Methods 4049 and 5052 of FED-STD-406. Electrostatic bleed-off shall not exceed 2.00 seconds when tested in accordance with Method 4046 of FED-STD-101. The liner shall be closed by rolling down the top and taped (with pressure tape made in accordance with PPP-T-97 or MIL-T-43036) to preven unrolling or it may be heat sealed. Details not specified herein shall comply with PPP-B-26."

5.2: Delete paragraph in its entirety and substitute the following:

"5.2 Marking"

Add new paragraph 5.2.1 as follows:

"5.2.1 Level A. Exterior containers shall be marked in accordance with dwg. 8796522. The dot marking shall be "Propellant Explosive Class A.""

Add new paragraph 5.2.2 as follows:

"5.2.2 Alternative Level A. The M17, M18 and M24 containers shall be marked in accordance with dwg. 8858848. The M25 container shall be marked in accordance with dwg. 8858577."

Add new paragraph 5.2.3 as follows:

"5.2.3 Level B. The fiberboard carton or other container shall be marked in accordance with dwg. 9241693."

Source: https://assist.dla.mil -- Downloaded: 202610-22T07:13Z
Check the source to verify that this is the currentversion before use.

MIL-C-46907B (AR)
Amendment 8

The margins of this amendment are marked with an asterik or vertical line to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army-AR

Preparing activity:
Army-Ar

(Project 1315-AC10)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T07:13Z
Check the source to verify that this is the current version before use.