MIL-F-46885(MI)
AMENDMENT 1
31 May 1974

MILITARY SPECIFICATION

FABRIC, GLASS, PHENOLIC RESIN IMPREGNATED

This amendment forms a part of MIL-F-46885(MI), dated 14 December 1973, and is approved for use by all Departments and Agencies of the Department of Defense.

Page 2

Paragraph 3.2.1 - Change MIL-G-9084 to MIL-C-9084.

Page 5

Paragraph 4.4.1.3.1 - Fifth line, change "(1150 plus or minus 50 degrees C/" to "(1150 plus or minus 50 degrees F)".

Page 6

Paragraph 4.4.1.3.1 - Third line, change "volantiles" to "volatiles".

Paragraph 4.4.1.4.1 - Line 13 change "wight" to "weight".

Page 7

Paragraph 4.4.2.1.1a - Line 2 change "125" to ".125".

Paragraph 4.4.2.1.1a - Delete the last sentence "The panel shall have a specific gravity of 1.60 minimum and resin content of 30 plus or minus 3 percent.

Paragraph 4.4.2.1.1b - Insert as a second sentence, "Only one specimen in any set of five may fall below the minimum average value required".

Paragraph 4.4.2.1.1b - Last sentence, change the test temperature to 260 degrees C/500 degrees F/ as specified in Table I of Section 3.

Page 9

Paragraph 5.6G change "g" to "h".

Custodian:
Army - MI

Preparing Activity:
Army - MI

Project No. 8305-A431

☆U.S. GOVERNMENT PRINTING OFFICE: 1981 — 703-023/5756

FSC 8305

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T07:10Z
Check the source to verify that this is the current version before use.