MIL-H-46906D(AR)
23 November 1973
SUPERSEDING
MIL-H-46906C(MU)
1 April 1965

MILITARY SPECIFICATION

HOLDERS, INCREMENT M1A1, M2A1 AND M3 PARTS FOR

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers Holder, Increment M1A1 for use with 60MM Mortar Ammunition and M2A1 and M3 for use with 81MM Mortar Ammunition.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-A-2550	-Ammunition and Special Weapons; General Specification for
MIL-P-10025	-Packaging, Packing and Marking for Interplant Shipment of Inert Ammunition Components; General Specification for

STANDARDS

MILITARY

MIL-STD-105	-Sampling Procedures and Tables for Inspection by Attributes (ABC-STD-105)
MIL-STD-109	-Quality Assurance Terms and Definitions
MIL-STD-1235	-Single and Multilevel Continuous Sampling Procedures and Tables for Inspection by Attributes

DRAWINGS

ORDNANCE CORPS

9206823	-Holder, Increment, M1A1 Assembly

FSC: 1315

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T07:13Z
Check the source to verify that this is the current version before use.

9206832 -Holder, Increment, M2A1 Assembly
8865086 -Holder, Increment, M3 Assembly

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Material.-Materials and parts shall be in accordance with applicable drawings and specifications.

3.2 Assembly.-The assemblies shall comply with all requirements specified on Drawings (dwgs.) 9206823, 9206832 and 8865086 and with all requirements specified in applicable specifications.

3.3 Tensile test of collar weld.-The collar shall withstand a load of twenty pounds, minimum, when tested as specified in 4.4.1.

3.4 Workmanship.-All parts shall be fabricated and finished in a thorough, workmanlike manner. They shall be free of burrs, chips, sharp edges, cracks, surface defects, dirt, grease, rust, corrosion products and other foreign matter. The cleaning method used shall not be injurious to any part nor shall the parts be contaminated by the cleaning agent.

4. QUALITY ASSURANCE PROVISIONS

4.1 General quality assurance provisions.-Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements. Reference shall be made to Standard MIL-STD-109 in order to define terms used herein. The provisions of Specification MIL-A-2550 shall apply.

4.1.1 Submission of product.-At the time the completed lot of product is submitted to the Government for acceptance the contractor shall supply the following information accompanied by a certificate which attests that the information provided is correct and applicable to the product being submitted:

a. A statement that the lot complies with all of the quality assurance provisions specified within this specification.
b. Number of units of product inspected.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T07:13Z
Check the source to verify that this is the current version before use.

c. Results obtained for all inspection performed.

d. Drawing, specification number and date, together with an identification and date of changes.

e. Certificates of compliance on all material purchased by the contractor when such material is controlled by Government specifications referenced in any of the contractual documents.

g. Number of items in the lot.

g. Date submitted.

The certificate shall be signed by a responsible agent of the certifying organization. The initial certificate submitted shall be substantiated by evidence of the agent's authority to bind his principal. Substantiation of the agent's authority will not be required with subsequent certificates unless, during the course of the contract, this authority is vested in another agent of the certifying organization.

4.1.2 Government verification.-Using the contractor's written quality assurance procedure, this detail specification, the applicable drawings and other contractual documents as a guide, the Government inspector shall verify at unscheduled intervals all quality assurance operations performed by the contractor. Verification will be performed to the extent necessary to assure compliance with the contractual requirements. Severity of Government inspection of individual characteristics will be directly related to the seriousness of the classification assigned. In no instance will a characteristic classified "critical" be accepted solely on the basis of the contractor's records.

4.2 Initial production inspection

4.2.1 Submission.-Prior to the start of regular production, the contractor shall submit an initial production sample to a Government approved facility as designated by the contracting officer (see 6.3) for evaluation in accordance with the provisions or 4.2.2. The initial production sample shall consist of ten consecutively produced assemblies and ten complete sets of parts which have been produced by the contractor or furnished by a supplier and which have been manufactured using the same production processes, procedures and equipment which will be used in fulfilling the contract. All parts and materials, including packaging and packing, shall be obtained from the same source of supply as will be used in regular production. The sample shall be accompanied by certificates of analyses for materials. An initial production sample, or portion thereof, as directed by the contracting officer, shall also be submitted whenever there is a lapse in production for a period in excess of 90 days, or whenever a change occurs in manufacturing process, material used, drawing, specification or source of supply as to significantly affect product uniformity as determined by the Government. Prior to submission, the contractor shall inspect the sample to the degree necessary to assure that it conforms to the requirements of the contract and submit a record of this inspection with the

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T07:13Z
Check the source to verify that this is the current version before use.

sample. A sample containing known defects will not be submitted unless specifically authorized by the contracting officer.

4.2.2 Inspections to be performed.-Assemblies and components will be subjected by the Government to any or all of the examinations or tests specified in this specification, and any or all requirements of the applicable drawings.

4.2.3 Rejection.-If any assembly or component fails to comply with any or all of the applicable requirements, the initial production sample shall be rejected. The Government reserves the right to terminate its inspection upon any failure of any assembly or component in the sample to comply with any or all of the stated requirements. In the event of rejection, the Government reserves the right to require the contractor to take corrective action and submit a new initial production sample or portion thereof. Until an initial production sample is accepted, the contractor is in no way authorized by the Government to initiate regular production unless otherwise directed by the contracting officer.

4.3 Inspection provisions

4.3.1 Lot formation.-A lot shall consist of assemblies produced by one manufacturer in one unchanged process, in accordance with the same drawing, same drawing revisions, same specification, and same specification revision. Drawing, specification, and process changes not affecting safety, performance or interchangeability, as determined by the Government, shall not necessitate changing the lot interfix number. Lots shall be submitted for inspection in accordance with Standard MIL-STD-105 (or Standard MIL-STD-1235, when applicable).

4.3.2 Examination.-The examinations listed in the following subparagraphs shall be performed on inspection lots (see 4.3.1) of the components or assemblies designated in the applicable paragraph headings. Inspection for critical defects (and major defects, when so specified) shall be 100 percent. Sampling plans for major and minor defects shall be in accordance with MIL-STD-105, except that continuous sampling plans in accordance with MIL-STD-1235, may be used if approved by the Government. An AQL of 0.40 percent for each major defect and an AQL of 0.65 percent for each minor defect shall be applied to all of the major and minor defects listed in the applicable subparagraph of this section, except where 100 percent inspection is specified. Equipment necessary for the performance of the inspections listed shall be in accordance with 4.3.4.

4.3.2.1 Assembly (see dwgs. 9206823, 9206832 and 8865086).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T07:13Z
Check the source to verify that this is the current version before use.

Categories	Defects	Method of Inspection
Critical:	None defined	
Major:		
101.	Clip insecure	Visual-Manual
102.	Crack or deformation	Visual
103.	Any operation missing or improperly performed, including departure from required configuration	Visual
Minor:		
201.	Inside diameter of collar	Gage (CD)
202.	Diameter between clip ends (except M3)	Gage (CD)
203.	Width of collar	Gage (CD)
204.	Protection coating missing or incomplete	Visual
205.	Evidence of poor workmanship (see 3.4)	Visual

4.3.3 Testing

4.3.3.1 Tensile test of collar weld (see 3.3)-Major defect A sample of 50 collars shall be selected from each lot for this test. If more than one collar fails to comply with the applicable requirement, the lot shall be rejected. The test shall be performed as specified in 4.4.1.

4.3.4 The inspection equipment required to perform the examinations and tests prescribed in this section is identified under the "Method of Inspection" headings in 4.3.2 and 4.3.3 (see 6.2).

4.4 Test methods and procedures

4.4.1 Tensile test of collar weld. The collar shall be subjected to a tensile load of twenty pounds at a ninety degree angle to the weld. Deformation causing out-of-roundness during the test shall not be cause for rejection. Samples subjected to this test shall not be returned to the lot.

5. PREPARATION FOR DELIVERY

5.1 Packing and marking

5.1.1 Level C.-Packing and marking shall be in accordance with Specification MIL-P-10025.

5.2 Data cards.-Data cards shall be prepared for each lot in accordance with the information specified in MIL-A-2550.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T07:13Z
Check the source to verify that this is the current version before use.

6. NOTES

6.1 Ordering data.-Procurement documents shall specify title, number and date of this specification.

6.2 Inspection Equipment Designs.-Inspection equipment designs are of two types-Government Special Inspection Equipment (SIE) designs and contractor designs. SIE designs, if available, are designated by drawing numbers under the "Method of Inspection" headings in Section 4. Design responsibility for all other inspection equipment is assigned to the contractor. Equipment to be designed by the contractor is designated "CD". The contractor need not furnish any design when a complete Government SIE design is provided. Unless otherwise specified, however, the contractor may submit alterante or modified contractor designs of SIE in accordance with 6.2.2 and 6.2.3 should he elect to do so.

6.2.1 SIE designs.-SIE designs may consist of any of the following:

a. Detailed drawings which completely depict all information necessary for the fabrication and use of the item of inspection equipment.

b. A source control drawing or a specification control drawing as defined in MIL-STD-100.

c. An envelope drawing, as defined in MIL-STD-100, that envelope drawings are specified, the contractor shall prepare designs which comply with the criteria therein.

6.2.2 Contractor designs.-Contractor designs are required for all inspection equipment for which SIE designs are not specified and may include commercial equipment which the contractor proposes to use. (Commercial equipment is defined as unmodified equipment which is cataloged and available for purchase by the general public). Contractor designs shall include appropriate operating instructions, calibration procedures and maintenance procedures. Commercial equipment shall be fully described by catalog listings or other means which provide sufficient information to permit identification and evaluation by the Government and may include illustrations and engineering data. Designs shall be prepared for any special fixture(s) required to be used with commercial, or with SIE designs if not otherwise covered thereby (see 6.2.1c). Designs shall be of the category and form (per MIL-D-1000) specified in the contract Data Requirements Lists (DD Form 1423). The contractor is referred to MIL-HDBK-204, "Inspection Equipment Design" for guidance. The specification number, paragraph number and defect number if such number has been assigned shall be referenced on each contractor design together with the component or assembly drawing number and revision letter to which the specific design applies.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T07:13Z
Check the source to verify that this is the current version before use.

6.2.3 Submission of designs for approval.-Contractor designs shall be approved by the Government prior to fabricating or procuring the equipment. Designs shall be submitted for approval in accordance with the stipulations, time frame and distribution specified in the Contract Data Requirements List (DD Form 1423) or in the contract. Partial submission of inspection equipment designs is permissible and encouraged However, the completion date for design review will be based on the date of the final submission of designs. Picatinny Arsenal design review will normally be accomplished within one month after receipt.

6.3 Submission of initial production samples.-Instruction as to the location for evaluation of initial production shall be obtained from the contracting officer. Upon receipt of such request, the contracting officer shall advise Picatinny Arsenal and instructions will be issued accordingly. All inquiries should be forwarded to: Commander Picatinny Arsenal, ATTN: SARPA-QA Dover, New Jersey.

Custodian:
ARMY -AR

Preparing Activity:
ARMY-AR

Project Number: 1315-A037

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T07:13Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

COMMANDER
US ARMY ARMAMENT RESEARCH & DEVELOPMENT CENTER
ATTN: DRSMC-QA
DOVER, NJ 07801

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T07:13Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-H-46906D	HOLDERS, INCREMENT M1A1, M2A1 AND M3 PARTS FOR

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR ☐ USER ☐ MANUFACTURER ☐ OTHER *(Specify)*: _____
b. ADDRESS *(Street, City, State, ZIP Code)*	

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T07:13Z
Check the source to verify that this is the current version before use.