NCTICE: OF
CHANGE

DOD-STD-35-82A(MI)
NOTICE 3
18 SEPTEMBER 1992

MILITARY STANDARD

AUTOMATED ENGINEERING
DOCUMENT PREPARATION SYSTEM

CONVERTERS AND INVERTERS

TO ALL HOLDERS OF DOD-STD-35-82A(MI):

1. THE FOLLOWING PAGES OF DOD-STD-35-82A(MI) HAVE BEEN REVISED AND SUPERSEDE THE PAGES LISTED.

NEW PAGE	DATE	SUPERSEDED PAGE	DATE
v	18 SEPTEMBER 1992	v	15 JANUARY 1979
1	15 JANUARY 1979 (Reprinted without change)		
2	18 SEPTEMBER 1992	2	15 JANUARY 1979
3	18 SEPTEMBER 1992	3	15 JANUARY 1979
4	18 SEPTEMBER 1992	4	15 JANUARY 1979
5	18 SEPTEMBER 1992	5	15 JANUARY 1979
6	18 SEPTEMBER 1992	6	15 JANUARY 1979
9	18 SEPTEMBER 1992	9	15 JANUARY 1979
11	18 SEPTEMBER 1992	11	15 JANUARY 1979
12	15 JANUARY 1979 (Reprinted without change)		
103	15 JANUARY 1979 (Reprinted without change)		
104	18 SEPTEMBER 1992	104	15 JANUARY 1979
105	18 SEPTEMBER 1992	105	15 JANUARY 1979
106	15 JANUARY 1979 (Reprinted without change)		
109	15 JANUARY 1979 (Reprinted without change)		
110	18 SEPTEMBER 1992	110	15 JANUARY 1979
111	18 SEPTEMBER 1992	111	15 JANUARY 1979
112	15 JANUARY 1979 (Reprinted without change)		
117	15 JANUARY 1979 (Reprinted without change)		
118	18 SEPTEMBER 1992	118	15 JANUARY 1979
119	18 SEPTEMBER 1992	119	15 JANUARY 1979
120	15 JANUARY 1979 (Reprinted without change)		
157	15 JANUARY 1979 (Reprinted without change)		
158	18 SEPTEMBER 1992	158	15 JANUARY 1979
139	18 SEPTEMBER 1992	159	15 JANUARY 1979
160	15 JANUARY 1979 (Reprinted without change)		

AMSC N/A AREA EGDS

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:00Z
Check the source to verify that this is the current version before use.

2. RETAIN THIS NOTICE PAGE AND INSERT BEFORE THE TABLE OF CONTENTS.

3. Holders of DOD-STD-35-82A(MI) will verify that page changes and additions indicated above have been entered. The notice page will be retained as a check sheet. This issuance, together with appended pages is a separate publication. Each notice is to be retained by stocking points until the Military Standard is completely revised or canceled.

Custodians:
Army-MI

Review activities:
Army - AT, AV, CR, ER
ME, MR, SC

User activity
Army - AR

Preparing activity:
Army - MI

(Project EGDS-A434)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:00Z
Check the source to verify that this is the current version before use.

CONTENTS

			Page
Paragraph	1.	SCOPE	1
	1.1	General	1
	1.2	Purpose	1
	1.3	Utilization	1
	1.4	Military Specification Exception Title Index	1
	2.	APPLICABLE DOCUMENTS	5
	2.1	Government documents	5
	2.2	Non-Government publications	6
	3.	DEFINITIONS	7
	4.	GENERAL REQUIREMENTS	8
	4.1	Introduction	8
	4.2	Specification Requirement Sheet (SRS)	8
	4.3	Configuration	8
	4.3.1	Dimensions	8
	4.3.2	Illustrations	8
	4.4	Units of measure	8
	5	DETAILED REQUIREMENTS	9
	5.1	Introduction	9
	5.2	MSE Formats	9
	5.3	Referenced documents	9
	5.4	Deleted	9
	5.5	Tabulation	12
	5.6	Keyword Code Index (KCI) and Standard Paragraphs	15
	5.6.1	Interrelationship of Codes	15
	5.6.2	Automatic MSE Data	15
	5.6.3	DOD-STD-35 Tables	15

TABLES

Table	I.	Title Index	2
	II.	Deleted	11
	III.	Tabulation Candidates	12

APPENDICES

Appendix	A.	Illustrations	199
	B.	Characteristic Code Index	214
		Index	222

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:00Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:00Z
Check the source to verify that this is the current version before use.

1.1 General. This dash-nunbered part of the Automated Engineering Document Preparation System (AEDPS), provides detailed requirements for the preparation of Military Specification Exception (MSE) documentation for converters and inverters.

1.2 Purpose. This military standard provides the necessary information to prepare a Specification Requirement Sheet (SRS) which will be used to generate an MSE by automated data processing.

1.3 Utilization. General instructions, quality assurance provisions, packaging, and notes, applicable to all AEDPS dash-numbered parts have been included in the basic document (DOD-STD-35) to avoid redundancy. Unless otherwise specified in this dash-numbered part, the following list contains additional subjects that are applicable to all AEDPS dash-numbered parts and are included in DOD-STD-35:

a. Writing Methodology
b. Document and Part Numbering
c. Applicable Documents
d. Single and Multi-item Specifications (Tabulation)
e. Keyword Code Index (KCI)
f. General Requirements of AEDPS

1.4 Military Specification Exception Title Index. The title code for an MSE shall be selected from one of the MSE titles listed in the Title Index (see table I). Data bases have been established for the generation of MSE's for the MSE titles indicated. If a suitable title code is not contained in the Title Index, leave the title code spaces on the SRS blank, and attach a request for the assignment of a title code. Include in the request the desired title and the base document identifier. A code will be assigned and the code, title, and base document will be made a part of the Title Index.

One of the six-digit codes listed in the Title Index, entered on an SRS, will specify that the title of the MSE will be the title shown in the Title Index.

Each MSE title listed in the Title Index is compatible with the document(s) listed with that title under base document. The list of base documents may or may not be a complete listing. The information shown under coverage is intended for the user's reference; when more than one document is listed for an MSE title, this information will be found useful in determining which of the documents is most suitable for use as the base document.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:00Z
Check the source to verify that this is the current version before use.

The MSE title may or may not be the same as the title used in DODISS, FIIG, or the base document. In general, the MSE title uses the basic federal item name listed in Cataloging Handbook H6. However, titles with additional modifying and identifying words are provided to assist in defining the scope of the MSE. Also, less restrictive titles are provided to prevent exclusion of items.

TABLE I. TITLE INDEX

MSE TITLE	TITLE: CODE	BASE DOCUMENT NUMBER	BASE DOCUMENT COVERAGE
CONVERTER	314001	MIL-C-7115	115/200 VAC, 400 HZ, 3-PH TO 28 VDC
		MS3370	100 A, CLASS C STATIC, BLAST COOLED
		MS17976	100 A, CLASS C FAN COOLED
		MS18103	50 A, CLASS C FAN COOLED
		MS18111	150 A, CLASS C BLAST COOLED
		MS28126	200 A, CLASS A
		MS17976	100 A, CLASS A
		MS23132	200 A, CLASS A
		MS28133	50 A, CLASS B
		MIL-C-46369	TSTRZ, 18 TO 30 VDC TO 1.5 VDC
		MIL-C-50329	OUTPUT +6.5, +23, -23, +33, -33, +15, -15 AND +29 VOLTS
		MIL-C-50330	DC/DC, PROVIDES UNREGULATED V TO V REGULATOR
		MIL-C-55666	28 V, 100 A
		MIL-C-81344	SIGNAL DATA CONVERTER

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:00Z
Check the source to verify that this is the current version before use.

TABLE I. TITLE INDEX (CONT)

MSE TITLE	TITLE CODE	BASE DOCUMENT NUMBER	BASE DOCUMENT COVERAGE
CONVERTER	314001 (CONT)	MIL-C-81991	9 T0 28 VDC TO RGLTD 28 VDC
FREQUENCY CHANGER	314002	MIL-F-29000	SOLID STATE, PARALLELABLE 5-KVA
		MIL-F-29001	SOLID STATE, PARALLELABLE 12.5-KVA
INVERTER	314003	MIL-I-7032	29 VDC TO AC AT 400 HZ
		MS16057	100/60 VA, 3/1 PH AND 100 VA, ONE PH, CLASS B
		MS16062	2500 VA, 3/1-PH CLASS B
		MS17404	2500 VA, 3/1-PH 400 HZ, CLASS B
		MS17406	750 VA, 3/1-PH, 750 VA, 3-PH AND 1000 VA, 1-PH, CLASS B
		MS21983	250 VA, 3/1-PH, CLASS B
		MS25202	5000 VA, 3/1-PH CL A, 3500 VA, 3/1-PH, CL B
		MIL-I-12659	350 VA
		MIL-I-14603	DC TO AC
		MTL-I-19028	VOLTAGE INVERT
		MIL-I-27273	POWER, STATIC, 28 VDC TO AC AT 400 HZ

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:00Z
Check the source to verify that this is the current version before use.

TABLE I. TITLE INDEX (CONT)

MSE TITLE	TITLE CODE	BASE DOCUMENT NUMBER	BASE DOCUMENT COVERAGE
INVERTER	314003 (CONT)	MIL-I-52358	24 TO 28 VKC OR 110 TO 120 VAC 60 OR 400 HZ TO 60 VA, 125 VAC
		MIL-I-60166	POWER, STATIC

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:00Z
Check the source to verify that this is the current version before use.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are these listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation.

SPECIFICATIONS

MILITARY

MIL-I-7032	Inverters, Aircraft, General Specification For
MIL-C-7115	Converters, Aircraft, General Specification For
MIL-I-12659	Inverter, 350 Volt Ampere
MIL-I-14603	Inverter, Vibrator
MIL-I-27273	Inverter, Power, Static, General Specification For
MIL-F-29000	Frequency Converter, Solid State, 5 KVA, with Transit Case
MIL-F-29001	Frequency Converter, Solid State, 12.5 KVA with Transit Cover
MIL-C-46369	Converter-Regulator
MIL-I-60166	Inverter, Power, Static

Source: https://assist.dla.mil - Downloaded: 2026-10-23T21:00Z
Check the source to verify that this is the current version before use.

MIL-C-81991	Converters, Aircraft, DC to DC, Boost, General Specification For

STANDARDS

MILITARY

DOD-STD-35	Automated Engineering Document Preparation System
MIL-STD-130	Identification Marking of U.S. Military Property
MIL-STD-202	Test Methods for Electronic and Electrical Component Parts
MIL-STD-461	Electromagnetic Interference Characteristics Requirements for Equipment
MIL-STD-462	Electromagnetic Interference Characteristics, Measurement Of
MIL-STD-704	Aircraft Electric Power Characteristics
MIL-STD-810	Environmental Test Methods
MIL-STD-1285	Marking of Electrical and Electronic Parts

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Standardization Documents order Desk, Bldg 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

2.2 Non-Government publications. The following document(s) form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted are three listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation.

ASTM E 380	Metric Practice Guide

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race St., Philadelphia, Pa. 19103.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:00Z
Check the source to verify that this is the current version before use.

5. DETAILED REQUIREMENTS

5.1 Introduction. This section provides instructions for completion of the SRS and references for instructions on specific requirements contained in DOD-STD-35.

5.2 MSE formats. AEDPS has the capability to prepare a six-section or a single-section document. The six-section document appears similar to a six-section military specification. The single-section document appears similar to a military specification sheet. Specification requirements described in DOD-STD-35 are applicable to either of the formats selected. It is mandatory that one of the two following codes and an "X" be entered on the SRS to create the desired MSE format:

a. 0700 for a six-section format

b. 0800 for a single-section format

5.3 Referenced documents. Section 2 of the MSE may contain a list of all referenced documents within Sections 3, 4, and 5 of the MSE. Instructions for referencing documents to appear in Section 2 of the forthcoming MSE are contained in DOD-STD-35.

5.4 Deleted

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:00Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:00Z
Check the source to verify that this is the current version before use.

THIS IS PAGE DELETED

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:00Z
Check the source to verify that this is the current version before use.

5.5 Tabulation. Instructions for tabulation are provided in DOD-STD-35. Table III provides codes for column headings which may be used for bolts and studs characteristics. When different units of measure within one system (U.S. or SI) are available for specifying a characteristic, only one of the units my be tabulated; e.g. either ounces or pounds.

TABLE III. TABULATION CANDIDATES

CODE	COLUMN HEADING	CODE	COLUMN HEALING	CODE	COLUMN HEADING
1964	MINIMUM EFFICIENCY PERCENT	2150	MIN ISLN RES CPLG MEGOHMS	2152	MAX ISLN CAP PICOFARADS
2154	MIN ISLN BREAKDOWN VOLTS DC	1620	MAX BACK RIPPLE V PERCENT	1638	INPUT ONE VOLTAGE VOLTS AC
1643	INPUT ONE V ADJ RNG VOLTS AC	1644	INPUT ONE VOLTAGE VOLTS DC	1651	INPUT ONE V ADJ RNG VOLTS DC
1654	INPUT ONE FREQ HERTZ	1657	INPUT ONE FREQ ADJ RNG HERTZ	1664	INPTT ONE MAX POWER FACTOR NO.
1666	INPUT ONE IMPD OHMS	1668	INPUT ONE MAX PWR W	1670	INPUT TWO VOLTAGE VOLTS AC
1675	INPUT TWO V ARJ RNG VOLTS AC	1676	INPUT TWO VOLTAGE VOLTS DC	1683	INPUT TWO V ADJ RNG VOLTS DC
1686	INPUT TWO FREQ HERTZ	1689	INPUT TWO FREQ ADJ RNG HERTZ	1696	INPUT TWO MAX POWER FACTOR NO.
1693	INPUT TWO IMPD OHMS	1700	INPUT TWO MAX PWR W	1702	OUTPUT TWO VOLTAGE VOLTS AC
1707	OUTPUT ONE V ADJ RNG VOLTS AC	1708	OUTPUT ONE VOLTAGE VOLTS DC	1715	OUTPUT ONE V ADJ RNG VOLTS DC

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:00Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
2164	THE TEST DURATION SHALL BE 2164 HOUR(S).
2166	THE TEMPERATURE FOR TEST ONE SHALL BE 2166 DEGREES CELSIUS.
2168	THE INPUT VOLTAGE SHALL BE 2168 PERCENT OF THE RATED INPUT VOLTAGE.
2170	THE ELECTRICAL LOAD SHALL BE 2170 PERCENT OF THE RATED LOAD.
2172	THE TEMPERATURE FOR TEST TWO SHALL BE 2172 DEGREES CELSIUS.
2174	THE TEST TEMPERATURE TOLERANCE SHALL BE 2174 DEGREES CELSIUS .
2176	THE DURATION FOR TEST ONE SHALL BE 2176 HOUR(S).
2178	THE DURATION FOR TEST TWO SHALL BE 2178 HOUR(S).
2180	THE VOLTAGE REGULATION SHALL BE MONITORED DURING THE TEST.
2182	THE FREQUENCY REGULATION SHALL BE MONITORED DURING THE TEST .
2201	NUCLEAR RADIATION. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2201•
2203	NUCLEAR RADIATION. THE REQUIREMENT(S) SHALL BE AS FOLLOWS:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:00Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
NUCLEAR RADIATION (CONT)	
AS FOLLOWS: (CONT)	
NO EVIDENCE OF PHYSICAL DAMAGE OR DEGRADATION OF PERFORMANCE.	2202
MINIMUM VOLTAGE REGULATION (PERCENT)	2204
MINIMUM FRIQUENCY REGULATION (PERCENT)	2206
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	2193
PER (DOC DES)	2194
MEASUREMENTS AFTER TEST	
VOLTAGE REGULATION.	2196
FREQUENCY REGULATION.	2198
OPERATING POSITION	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	2223
NO EVIDENCE OF PHYSICAL DAMAGE OR DEGRADATION OF PERFORMANCE.	2224

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:00Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
2202	THERE SHALL BE NO EVIDENCE OF PHYSICAL DAMAGE OR DEGRADATION OF Performance.
2204	THE VOLTAGE REGULATION SHALL BE NOT LESS THAN 2204 PERCENT.
2206	THE FREQUENCY REGULATION SHALL, BE NOT LESS THAN 2206 PERCENT.
2193	NUCLEAR RADIATION. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2193.
2194	NUCLEAR RADIATION. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH 2194.
2196	MEASUREMENTS AFTER TEST SHALL INCLUDE VOLTAGE REGULATION.
2198	MEASUREMENTS AFTER TEST SHALL INCLUDE FREQUENCY REGULATION.
2223	OPERATING POSITION. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2223.
2224	OPERATING POSITION. THERE SHALL BE NO EVIDENCE OF PHYSICAL DAMAGE OR DEGRADATION OF PERFORMANCE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:00Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
OPERATING POSITION (CONT)	
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	2209
PER DOCUMENT (DOC DES)	2210
ANY POSITION OPERATION VERIFIED DURING OTHER TESTS.	2212
ROTATION INCREMENTS (DEGREES)	2214
TOTAL ROTATION (DEGREES)	2216
ROTATION AXIS (SELECT ONE)	
ROTATE FROM NORMAL HORIZONTAL POSITION IN EACH MAJOR AXIS.	2218
EXCEPT AXIS (DESIGNATION)	2220
OUTPUT MODULATION	
REQUIREMENT (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	2237
AS FOLLOWS:	2239
NO SUSTAINED VOLTAGE OSCILLATIONS.	2238

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:00Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
2240	THERE SHALL BE NO SUSTAINED FREQUENCY OSCILLATIONS.
2242	THE FREQUENCY MODULATION SHALL BE NOT GREATER THAN 2242 PERCENT.
2244	THE VOLTAGE MODULATION SHALL BE NOT GREATER THAN 2244 PERCENT.
2246	THE FREQUENCY IN THE MODULATION SHALL BE NOT LESS THAN 2246 HERRTZ.
2248	THE FREQUENCY IN THE MODULATION SHALL BE NOT GREATER THAN 2248 HERTZ.
2227	OUTPUT MODULATION. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2227.
2229	OUTPUT MODULATION . TESTING SHALL BE PERFORMED IN ACCORDANCE WITH 2229.
2230	THE INPUT VOLTAGE SHALL BE 2230 PERCENT OF THE RATED INPUT VOLTAGE.
2232	THE ELECTRICAL LOAD(S) SHALL BE 2232 PERCENT OF RATED LOAD.
2234	THE ELECTRICAL LOAD(S) SHALL BE ADJUSTED FOR A POWER FACTOR OF 2234.
2235	THE OUTPUT MODULATION METHOD SHALL BE 2235.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:00Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
OVERSPEED	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	2261
AS FOLLOW:	2263
NO EVIDENCE OF PHYSICAL DAMAGE OR DEGRADATION.	2262
MINIMUM VOLTAGE REGULATION (PERCENT)	2264
MINIMUM FREQUENCY REGULATION (PERCENT)	2266
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	2251
PER MIL-I-7032.	2253
OVERSPEED (PERCENT)	2254
DURATION (MINUTES)	2255
MEASUREMENTS AFTER TEST	
VOLTAGE REGULATION.	2256
FREQUENCY REGULATION.	2258

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:00Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
2261	OVERSPEED. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2261.
2263	OVERSPEED. THE REQUIREMENT(S) SHALL BE AS FOLLOWS:
2262	THERE SHALL BE NO EVIDENCE OF PHYSICAL DAMAGE OR DEGRATATION OF PERFORMANCE.
2264	THE VOLTAGE REGULATION SHALL BE NOT LESS THAN 2264 PERCENT.
2266	THE FREQUENCY REGULATION SHALL BE NOT LESS THAN 2266 PERCENT.
2251	OVERSPEED. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2251.
2253	OVERSPEED. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH MIL-I-7032.
2254	THE OVERSPEED SHALL BE 2254 PERCENT OF THE RATED SPEED.
2255	DURATION OF OVERSPEED SHALL BE 2255 MINUTE(S).
2256	THE MEASUREMENTS AFTER TEST SHALL INCLUDE VOLTAGE REGULATION.
2258	THE MEASUREMENTS AFTER TEST SHALL INCLUDE FREQUENCY REGULATION.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:00Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
PARALLEL OPERATION	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT _____	2279
AS FOLLOWS:	2281
MAXIMUM LOAD SHARE DIFFERENCE (PERCENT)	2280
MAXIMUM EQUALIZING RESISTANCE (OHMS)	2282
MAXIMUM VOLTAGE DECREASE (VOLTS)	2284
MAXIMUM EQUALIZER TERMINAL CURRENT (AMPERES)	2286
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	2269
PER DOCUMENT (DOC DES)	2271
STEPS (NUMBER)	2272
LOAD PER STEP (PERCENT OF RATED LOAD)	2274
DEVICES IN PARALLEL (NUMBER)	2276

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:00Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
2320	THE POWER FACTOR SHALL BE 2320.
2322	THE MEASURING INSTRUMENT ACCURACY SHALL BE 2322 PERCENT.
2339	PHASE ROTATION . THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2339.
2341	PHASE ROTATION. THE REQUIREMENT(S) SHALL BE AS FOLLOWS:
2340	THE PHASE ROTATION SHALL BE 2340 AT THE OUTPUT CONNECTOR.
2342	THE PHASE ROTATION SHLL BE AT TERMINAL NUMBERS 2342.
2331	PHASE ROTATION. TESTING SHALL BE PERFORMED IN ACC0RDANCE WITH THE BASE DOCUMENT, EXCEPT 2331.
2333	PHASE ROTATION. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH 2333.
2334	THE PHASE ROTATION INDICATING INSTRUMENT SHALL BE CONNECTED TO 2334 CONNECTOR(S).
2336	THE PHASE ROTATION INDICATING INSTRUMENT SHALL BE CONNECTED TO 2336 TERMINAL(S).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:00Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
POLARITY	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	2355
AS FOLLOWS:	2357
OUTPUT VOLTAGE	
POSITIVE (TERMINAL DESIGNATION)	2356
NEGATIVE (TERMINAL DESIGNATION)	2358
GROUND (TERMINAL DESIGNATION)	2360
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	2345
PER (DOC DES)	2347
INPUT VOLTAGE	
POSITIVE (TERMINAL DESIGNATION)	2348
NEGATIVE (TERMINAL DESIGNATION)	2350
GROUND (TERMINAL DESIGNATION)	2352

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:00Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
2355	POLARITY. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2355.
2357	POLARITY. THE REQUIREMENTS(S) SHALL BE AS FOLLOWS:
2356	THE POSITIVE OUTPUT VOLTAGE SALL BE AT TERMINAL NUMBER 2356.
2358	THE NEGATIVE OUTPUT VOLTAGE SHALL BE AT TERMINAL NUMBER 2358.
2360	THE GROUND TERMINAL SHALL BE 2360.
2345	POLARITY. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2345.
2347	POLARITY. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH 2347.
2348	THE POSITIVE INPUT VOLTAGE SHALL BE AT TERMINAL NUMBER 2348.
2350	THE NEGATIVE INPUT VOLTAGE SHALL BE TERMINAL NUMBER 2350.
2352	THE GROUND TERMINAL SHALL BE 2352.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:00Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
RADIO INTERFERENCE	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	2375
PER MIL-STD-461.	2376
NO ADVERSE INTERFERENCE TO ADJACENT EQUIPEMENT.	2378
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT _____	2363
PER MIL-STD-461, METHOD (DESIGNATION)	2364
PER MIL-STD-462.	2370
*TEST METHODS	
CE (NUMBER)	2365
RE (NUMBER)	2367
CS (NUMBER)	2369
RS (NUMBER)	2371
CRE (NUMBER)	2373
LOAD STEPS (NUMBER)	2366
LOAD PER STEP (PERCENT OF RATED LOAD)	2368

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:00Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
2488	THE CURRENT AFTER START SHALL BE 2488 PERCENT OF RATED CURRENT.
2489	DURATION OF CURRENT AFTER START SHALL BE 2489 SECOND(S) .
2490	THE OUTPUT VOLTAGE SHALL BE MEASURED AFTER 2490 SECOND(S) AFTER STARTING.
2492	THE OUTPUT FREQUENCY SHALL BE MEASURED AFTER 2492 SECOND(S) AFTER STARTING.
2494	THE DEVICE(S) SHAL BE STARTED AND STOPPED 2492 TIMES.
2496	THE ON TIME SHALL BE 2496 MINUTE(S).
2498	THE OFF TIEM SHALL BE 2498 MINUTES.
2519	STARTING CONTACTOR DROPOUT VOLTAGE. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2519.
2525	STARTING CONTACTOR DROPOUT VOLTAGE. THE REQUIREMENT(S) SHALL BE AS FOLLOWS:
2520	THE STARTING CONTACTOR SHALL REMAIN CLOSED.
2521	THE STARTING CONTACTOR DROPOUT VOLTAGE SHALL BE 2421 VOLT(S).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:00Z
Check the source to verify that this is the current version before use.

KEYWORD C0DE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
STARTING CONTACTOR DROPOUT VOLTAGE (CONT)	
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	2511
PER MIL-I-7032.	2515
MINIMUM INPUT VOLTAGE (VOLTS)	2514
MINIMUM TEMPERATURE (DEGREES CELSIUS)	2516
SUNSHINE	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	2535
AS FOLLOWS:	2537
NO DEGRADATION OF FINISHES OR MATERIAL.	2536
DEVICES SHALL REMAIN WITHIN SPECIFIED TOLERANCES.	25.38
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	2523
PER MIL-STD-810 , METHOD 505.	2530

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:00Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
2511	STARING CONTACTOR DROPOUT VOLTAGE. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2511.
2515	STARTING CONTACTOR DROPOUT VOLTAGE. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH MIL-I-7032.
2514	THE INPUT VOLTAGE SHALL BE NOT LESS THAN 2514 VOLT(S).
2516	THE TEMPERATURE SHALL BE NOT LESS THAN 2516 DEGREES CELSIUS.
2535	SUNSHINE. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2535.
2537	SUNSHINE. THE REQUIREMENT(S) SHALL BE AS FOLLOWS:
2536	THERE SHALL BE NO DEGRADATION OF FINISHES OR MATERIALS.
2538	THE DEVICE(S) SHALL REMAIN WITHIN SPECIFIED TOLERANCES.
2523	SUNSHINE. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2523.
2530	SUNSHINE. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH METHOD 505 OF MIL-STD-810.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:00Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
SUNSHINE (CONT)	
PER MIL-STD-810 , METHOD 505, (CONT)	
*PROCEDURE (NUMBER)	2524
TEMPERATURE (DEGREES CELSIUS)	2526
TEMPERATURE TOLERANCE (DEGREES CELSIUS)	2527
SOLAR RADIATION (SELECT ONE)	
(WATTS PER QUARE FOOT)	2528
TOLERANCE (WATTS PER SQUARE FOOT)	2529
(WATTS PER SQUARE METER)	2531
TOLERANCE (WATTS PER SQUARE METER)	2533
DEVICE OPERATIONAL DURING TEST.	2532
TEMPERATURE-ALTITUDE	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	2551
AS F0LLOWS:	2553
NO EVIDENCE OF PHYSICAL DAMAGE.	2552
DEVICES SHALL REMAIN WITHIN SPECIFIED TOLERANCES.	2554

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:00Z
Check the source to verify that this is the current version before use.