NOTICE OF
CHANGE

MIL-STD-35-75(MI)
NOTICE 4
18 SEPTEMBER 1992

MILITARY STANDARD

AUTOMATED ENGINEERING
DOCUMENT PREPARATION SYSTEM

MICROWAVE/WAVEGUIDE COMPNENTS

TO ALL HOLDERS OF MIL-STB35-75(MI) :

1. THE FOLLOWING PAGES OF MIL-STD–35-75(MI) HAVE BEEN REVISED AND SUPERSEDE THE PAGES LISTED.

NEW PAGE	DATE	SUPERSEDED PAGE	DATE
2-1	18 SEPTEMBER 1992	2-1	30 JULY 1976
2-2	18 SEPTEMBER 1992	2-2	30 JULY 1976
5-3	31 DECEMBER 1974	(Reprinted without change)	
5-4	18 SEPTEMBER 1992	5-4	30 JULY 1976
5-55	18 SEPTEMBER 1992	5-55	31 DECEMBER 1974
5-56	31 DECEMBER 1974	(Reprinted without change)	
5-125	18 SEPTEMBER 1992	5-125	31 DECEMBER 1974
5-126	18 SEPTEMBER 1992	5-126	30 JULY 1976

2. RETAIN THIS NOTICE PAGE AND INSERT BEFORE THE TABLE OF CONTENTS.

3. Holders of MIL-STD-35-75(MI) will verify that page changes and additions indicated above have been entered. The notice page will be retained as a check sheet. This issuance, together with appended pages is a separate publication. Each notice is to be retained by stocking points until the Military Standard is completely revised or canceled.

Custodians:
Amy-MI

Review activities:
Army-AT, AV, CR, ER
ME, MR, SC

User activity
Army - AR

Preparing activity:
Army-MI

(Project EGDS-A430)

AMSC N/A
DISTRIUBUTION STATEMENT A. Approved for public release; distribution is unlimited.

AREA EGDS

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

SECTION 2

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation.

SPECIFICATIONS

MILITARY

MIL-A-3933	Attenuators, Fixed (Coaxial Line and Waveguide), General Specifications for
MIL-C-15370	Couplers, Directional (Coaxial Line or Waveguide), General Specification for
MIL-A-22641	Adapters, Coaxial to Waveguide, General Specification for
MIL-A-24215	Attenuators, Variable (Coaxial and Waveguide), General Specification for
MIL–S-55041	Switches, Waveguide

STANDARDS

MILITARY

MIL-STD-202	Test Methods for Electronic and Electrical Component Parts
MIL-STD-461	Electromagnetic Interference Characteristics Requirements for Equipment

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

MILITARY (Cent)

MIL-STD-1328	Coupler, Directional (Coaxial and Waveguide), selection of
MIL-STD-1329	Switch, RF Coaxial, Selection of
MIL-STD-1352	Attenuator, Fixed, Selection of
MIL-STD-1358	Waveguides, Rectangular, Ridged and Circular, Selection of
MIL–STD-462	Electromagnetic Interference Characteristics, Measurement of
MIL-STD-81O	Environmental Test Methods

2.1.2 other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

H6	Federal Item Name Directory for Supply Cataloging

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Standardization Documents Order Desk, Bldg 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

"GROUP A INSPECTION. GROUP A INSPECTION SHALL BE PERFORMED AS SPECIFIED IN THE SPECIFICATION REFERENCED IN 3.1 EXCEPT THERMAL SHOCK SHALL BE 175 DEG C HIGH TEMPERATURE."

The test method per 1006 code and requirements per 1006 code from the same test shall not be used together. This condition would indicate no exception is being specified. If a test method code(s) has been selected, it is mandatory that a requirement code be selected; and if a requirement code has been selected, it is mandatory that a test method code(s) be selected.

5.4.2 Approved Item Name Code

The approved item name code to be entered on the SRS with Code 1007 for a Microwave/Waveguide Component is selected from the following list:

APPROVED ITEM NAME	ITEM NAME CODE
Adapter	00186
Fixed Attenuator	14224
Variable Attenuator	00838
Attenuator Assenbly	00350
Directional Coupler	00384
Switch	05118

only the Item Name Code number is entered on the SRS with Code 1007.

5.5 Organization of Design and Test Data

Design data and operating parameters for the four Microwave/waveguide Component types are arranged such that design data and operating parameters common to all four components are covered first followed by design data and operating parameters specific to each in the order of Adapters, Attenuators, Couplers, and Switches.

All tests are arranged in alphabetical order.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

5.6 Dimensions and Figures

All specification requirements for dimensions and figures described in MIL–STD-35 are applicable.

The figures applicable to Microwave/Waveguide Components are contained in Section 7. It is mandatory to enter on the SRS Code 1009 and a figure number.

5.7 Applicable Documents

The documents listed in the Applicable Document List of Section 5 of MIL-STD-35 and appropriate codes from Table B of MIL-STD-35 shall be entered on the SRS. In addition, selected documents shown in the DOCUMENTS column below and applicable codes from Table B of MIL-STD-35 shall be entered on the SRS when the document related codes listed in the CODES column are used to specify tests or requirements. Shown parenthetically in the CODES column is a reference to the applicable test or requirement.

DOCUMENT	CODES
MIL-A-3933	1700 (Attenuation) 1728 (Attenuation Stability) 1738 (Connector Wear Resistance) 1893 (peak Power) 1995 (Sensitivity of Attenuation) 2020 (Voltage Standing Wave Ratio) (VSWR)
MIL-STD-81O	3111 (Temperature/Altitude)
MIL-C-15370	1747 (Ccupling Factor) 1759 (Ccupling Variation) 1782 (Effective Directivity) 1858 (Insertion Loss) 1913 (Power Dissipation) 2020 (VSWR)
MIL-A-22641	1815 (Gage) 1858 (Insertion Loss) 2020 (VSWR)
MIL-A-24215	1701 (Attenuation) 1769 (Dial Calibration) 1806 (Frequency Sensitivity) 1858 (Insertion Loss) 1894 (peak power) 1957 (Repeatability) 2020 (VSWR)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

Code 3218 and an "X", entered on the SRS, will specify the component shall be within tolerance and shall meet design or performance characteristics.

5.52 Switching Time (Switches)

Code 1985 is the 1006 test code (5.4).

Code 1986 is the 1006 except test code (5.4).

Code 1987 and an "X", entered on the SRS, will specify to test in accordance with MIL-S-55041.

Code 1988 is the 1006 requirements code (5.4).

Code 1989 is the 1006 except requirements code (5.4).

Code 1990 and a value, entered on the SRS, will specity the maximum time in milliseconds between energized and unenergized positions of the switch. .

5.53 Temperature/Altitude

Code 3109 is the 1006 test code (5.4).

Code 3110 is the 1006 except test code (5.4).

Code 3111 and an "X", entered on the SRS, will specify to test in accordance with MIL-STD-81O.

Code 3112 is the 1006 requirements code (5.4).

Code 3113 is the 1006 except requirements code (5.4).

Code 3114 and an "X", entered on the SRS, will specify that the component shall show no evidence of voltage breakdown.

Codes 3115, 3116, and 3117 specify performance requirements after the Temperature/Altitude test.

Code 3115 and a value, entered on the SRS, will specify the maximum attenuation in db.

Code 3116 and a value, entered on the SRS, will specify the maximum insertion loss in db.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

Code 3117 and a number, entered on the SRS, will specify the maximum VSWR.

Code 3118 and an "X", entered on the SRS, will specify the power handling capacity shall be exhibited during the test by the application of peak power, average power, and line pressure with no voltage breakdown nor evidence of deterioration.

Code 3119 and an "X", entered on the SRS, will specify that the part shall be within tolerance and shall meet design or performance characteristics.

5.54 Temperature Coefficient

Code 2007 is the 1006 test code (5.4).

Code 2008 is the 1006 except test code (5.4).

Code 2009 and a letter, entered on the SRS, will specify the applicable test condition letter from Method 107 of MIL-STD-202. The use of Code 2009 is mandatory.

Code 2010 and an "X", entered on the SRS, will specify that the temperature coefficient shall be measured at each setting for step type attenuators.

Code 2011 and an 'X", entered on the SRS, will specify that the temperature coefficient shall be measured at minimum and maximum settings for contincusly variable type attenuators.

Code 2012 is the 1006 requirements code (5.4).

Code 2013 is the 1006 except requirements code (5.4).

Code 2014 and a value, entered on the SRS, will specify the temperature coefficient in db/db/degrees Celsius.

5.55 Thermal Shock

Code 4712 is the 1006 test code (5.4).

Code 4713 is the except test code (5.4).

Code 4704 and a value, entered on the SRS, will specify the number of thermal cycles.

To detail a thermal shock test, it is mandatory to use Codes 4714 and 4715 l

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

SPECIFICATION REQUIREMENT LIST (SRL)

CHARACTERISTIC

REF. PARA.	NAME	CODE
5.51 CONT.	SHOCK , SPECIFIED PULSE (CONT)	
	MAXIMUM RESETABILITY ERROR (PLUS, MINUS DB)	3216
	MAXIMUM VSWR	3217
	THE PART SHALL BE WITHIN TOLERANCE AND SHALL MEET DESIGN AND PERFORMANCE CHARACTERISTICS.	3218
5.52	SWITCHING TIME (SWITCHES)	
	(SELECT ONE TEST METHOD)	
	TEST PER 1006 DOCUMENT	1985
	TEST PER 1006 DOCUMENT EXCEPT _____.	1986
	TEST PER MIL-S-55041	1987
	(SELECT ONE REQUIREMENT)	
	REQUIREMENT(S) PER 1006 DOCUMENT	1988
	REQUIREMENT(S) PER 1006 DOCUMENT EXCEPT _____.	1989
	REQUIREMENT(S) AS FOLLOWS:	
	TIME BETWEEN ENERGIZED AND UNENERGIZED POSITIONS SHALL NOT EXCEED _____ MILLISECONDS.	1990
5.53	TEMPERATURE/ALTITUDE	
	(SELECT ONE TEST METHOD)	
	TEST PER 1006 DOCUMENT	3109

Source: https://assistdla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

SPECIFICATION REQUIREMENTS LIST (SRL)

CHARACTERISTIC

REF. PARA*	NAME	CODE
5.53 CONT.	TEMPERATURE/ALTITUDE (CONT)	
	TEST PER 1006 DOCUMENT EXCEPT _____.	3110
	TEST PER MIL-STD-810 , METHOD 520	3111
	(SELECT ONE REQUIREMENT)	
	REQUIREMENT(S) PER 1006 DOCUMENT	3112
	REQUIREMENT(S) PER 1006 DOCUMENT EXCEPT _____.	3113
	REQUIREMENT(S) AS FOLLOWS:	
	NO EVIDENCE OF VOLTAGE BREAKDOWN	3114
	PERFORMANCE REQUIREMENTS (SELECT ONE OR MORE REQUIREMENT(S)	
	AFTER TEST	
	MAXIMUM ATTENUATION (DB)	3115
	MAXIMUM INSERTION LOSS (DB)	3116
	MAXIMUM VSWR	3117
	DURING TEST	
	POWER HANDLING CAPACITY	3118

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:59Z
Check the source to verify that this is the current version before use.