FED. SUP CLASS
9525




TABLE I. DASH NUMBERS.

DASH NO	A	TEMPER
001	.094	O
003	.094	T6
005	.109	O
007	.109	T6
009	.125	O
011	.125	T6
013	.141	O
015	.141	T6
017	.156	O
019	.156	T6
021	.172	O
023	.172	T6
025	.188	O
027	.188	T6
029	.203	O
031	.203	T6
033	.219	O
035	.219	T6
037	.234	O
039	.234	T6
041	.250	O

DASH NO	A	TEMPER
043	.250	T6
045	.266	O
047	.266	T6
049	.281	O
051	.281	T6
053	.297	O
055	.297	T6
057	.313	O
059	.313	T6
061	.328	O
063	.328	T6
065	.344	O
067	.344	T6
069	.359	O
071	.359	T6

USER ACTIVITIES:
NAVY-OS, SH

REVIEWER ACTIVITIES:
AIR FORCE - 84
DLA-IS

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document.

APPROVED 29 Feb 1984 REVISED

P. A.	INTERNATIONAL INTEREST	TITLE	MILITARY STANDARD
Other Cust AS MR 99		WIRE, ROUND, NONELECTRICAL ALUMINUM ALLOY 7075	MS14275
PROCUREMENT SPECIFICATION QQ-A-225	SUPERSEDES		PAGE 1 OF 2

DD FORM 672-1 (COORDINATED) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE 9525-0084

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T13:39Z
Check the source to verify that this is the current version before use.

FED. SUP CLASS
9525


REQUIREMENTS:

1. MATERIAL. ALUMINUM ALLOY 7075, (UNS A97075), AS SPECIFIED IN QQ-A-225/9.

2. FORMING PROCESS. DRAWN.

3. PART NUMBER. THE PART NUMBER CONSISTS OF THE BASIC MS NUMBER, PLUS A FORMING PROCESS CODE, PLUS A DASH NUMBER FROM TABLE I.

EXAMPLE: MS14275D001



4. MARKING. ALUMINUM AND ALUMINUM ALLOYS SHALL BE MARKED WITH THE PRODUCER'S NAME OR REGISTERED TRADE MARK, THE PART NUMBER (MILITARY STANDARD (MS) NUMBER PLUS THE APPLICABLE DASH NUMBER), AND THE LOT NUMBER, AND THIS MARKING SHALL BE APPLIED IN ACCORDANCE WITH FED-STD-184.

NOTES:

1. ALL DIMENSIONS ARE IN INCHES.

2. STANDARD LENGTH OF WIRE FOR TEMPERS "T4" AND "T6" IS 12 FEET NOMINAL, STANDARD LENGTH OF WIRE FOR TEMPER "O" IS 200 LB SPOOLS NOMINAL.

3. REFERENCED DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON DATE OF INVITATIONS FOR BIDS, OR REQUEST FOR PROPOSAL, EXCEPT THE REFERENCED ADOPTED INDUSTRY DOCUMENTS SHALL GIVE THE DATE OF THE ISSUE ADOPTED.

4. FOR DESIGN FEATURE PURPOSES THIS STANDARD TAKES PRECEDENCE OVER PROCUREMENT DOCUMENTS REFERENCED HEREIN.

APPROVED 29 Feb 1984 REVISED

P. A. AS / Other Cust MR 99	INTERNATIONAL INTEREST	TITLE: WIRE, ROUND, NONELECTRICAL ALUMINUM ALLOY 7075	MILITARY STANDARD MS14275
PROCUREMENT SPECIFICATION QQ-A-225	SUPERSEDES:		PAGE 2 OF 2

DD FORM 672-1 (COORDINATED) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE 9525-0084

USER ACTIVITIES: NAVY-OS, SH

REVIEWER ACTIVITIES AIR FORCE-84 DLA-IS

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T13:39Z
Check the source to verify that this is the current version before use.