


FED. SUP CLASS
5310







RECOMMENDED
PANEL HOLE

DASH NO.	THREAD -2B (B)	A DIA ±.015	B MAX	B MIN	C DIA MAX	C DIA MIN	D DIA MAX	D DIA MIN	G MAX	G MIN	H MAX	H MIN	J DIA MIN	K MIN	MATERIAL THICKNESS MAX
1 2 3 4	.190-24UNC .190-32UNF .250-20UNC .250-28UNF	.562	.152	.147	.437	.432	.432	.428	.145	.140	.270	.260	.447	.157	.083
5 6 7 8	.250-20UNC .250-28UNF .3125-18UNC .3125-24UNF	.625	.182	.177	.500	.495	.495	.490	.172	.167	.364	.354	.510	.187	.110
9 10 11 12	.3125-18UNC .3125-24UNF .375-16UNC .375-24UNF	.688	.215	.210	.562	.557	.557	.552	.157	.152	.473	.463	.572	.220	.095
13 14 15 16	.3125-18UNC .3125-24UNF .375-16UNC .375-24UNF	.750	.250	.245	.625	.620	.620	.615	.188	.183	.505	.495	.635	.255	.126
17 18	.4375-14UNC .4375-20UNF	.875	.277	.272	.750	.745	.745	.740	.187	.181	.505	.495	.760	.282	.126
19 20 21 22	.4375-14UNC .4375-20UNF .500-13UNC .500-20UNF	.938	.344	.338	.812	.807	.807	.802	.188	.183	.599	.589	.822	.350	.126
23 24	.500-13UNC .500-20UNF	1.000	.375	.372	.875	.870	.870	.865	.285	.280	.630	.620	.885	.382	.226
25 26 27 28	.5625-12UNC .5625-18UNF .625-11UNC .625-18UNF	1.125	.438	.433	1.000	.995	.995	.990	.234	.229	.693	.683	1.016	.445	.172

NOTES:

1. MATERIAL: Steel, carbon, AISI 1110 or equivalent in accordance with Fed. Std. No. 66.
2. PROTECTIVE COATING: Cadmium plated in accordance with QQ-P-416, Type II, Class 3.
3. THREADS: The threads shall be in accordance with Screw-Thread Standards for Federal Services, Handbook H28.
4. CONCENTRICITY: The threads and clinching section shall be concentric within ±.008 inch.
5. BEARING SURFACE: The bearing surface shall be at right angles to the thread axis within 3°.
6. DIMENSIONS: All dimensions are in inches.
7. PART NUMBER: The MS part number consists of the MS number, plus the dash number. Example: MS21331-1.
8. Referenced documents shall be of the issue in effect on date of invitations for bid.
9. For design feature purposes, this standard takes precedence over procurement documents referenced herein.

REVIEWER: AV, IS, MU
USER: AS, AT, EL, GL, MC, ME, SH

APPROVED 6 JAN 1961 REVISED (A) 14 OCT 1969 (B) 30 SEP 1971

This military standard is mandatory for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document.

P.A. WC
Other Cust OS

TITLE
NUT, PLAIN, CLINCH

MILITARY STANDARD
MS 21331

PROCUREMENT SPECIFICATION
MIL-N-45938 (B)

SUPERSEDES:

SHEET 1 OF 1

Source: https://assist.dla.mil -- Downloaded: 2026-04-14 14:32Z
Check the source to verify that this is the current version before use.

DD FORM 1 SEP 67 672-1 (Coordinated)

PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE.