

MS36371-1 thru -11,
MS36371-46 thru -52



MS36371-12 thru -47, -53



MS36371 54, -55, -56

PART NUMBER	CAPACITY (µL)	ACCURACY (MEAN ERROR, %*	PRECISION (STD DEVIATION) %*
MS36371-1	5	<2 0	<1 0
MS36371-2	10	<1 0	<0 6
MS36371-3	20	<1 0	<0 4
MS36371-4	25	<1.0	<0 4
MS36371-5	50	<1 0	<0 3
MS36371-6	100	<1 0	<0 3
MS36371-7	C A N C E L L E D		
MS36371-8	200	<1 0	<0 3
MS36371-9	250	<1 0	<0 3
MS36371-10	500	<1 0	<0 3
MS36371-11	1000	<1 0	<0 3
MS36371-12	1	<3 0	<2 0
MS36371-13	2	<2 0	<1 5
MS36371-14	3	<1 5	<1 5
MS36371-15	4	<1 0	<1 0
MS36371-16	5	<1 0	<0 5
MS36371-17	10	<1 0	<0 5
MS36371-18	15	<1 0	<0 2
MS36371-19	20	<0 6	<0 2
MS36371-20	25	<0 6	<0 2
MS36371-21	30	<0 6	<0 2
MS36371-22	40	<0 6	<0 2
MS36371-23	50	<0 5	<0 2
MS36371-24	60	<0 5	<0 2
MS36371-25	70	<0 5	<0.2
MS36371-26	75	<0 5	<0 2
MS36371-27	80	<0 5	<0 2
MS36371-28	90	<0 5	<0 2
MS36371-29	100	<0 5	<0 2
MS36371-30	150	<0 5	<0 15
MS36371-31	200	<0 5	<0 15

* Based on water at 20°C

PART NUMBER	CAPACITY (µL)	ACCURACY (MEAN ERROR) %*	PRECISION (STD DEVIATION) %*
MS36371-32	250	<0 5	<0 15
MS36371-33	300	<0 5	<0 15
MS36371-34	400	<0 5	<0 15
MS36371-35	500	<0 5	<0 15
MS36371-36	600	<0 5	<0 15
MS36371-37	700	<0 5	<0 15
MS36371-38	750	<0 5	<0 15
MS36371-39	800	<0 5	<0 15
MS36371-40	900	<0 5	<0 15
MS36371-41	1000	<0 5	<0 15
MS36371-42	10/20/25	<1 2/0 6/0 6	<0 4/0 3/0 3
MS36371-43	20/25/50	<0 6	<0 25
MS36371-44	50/75/100	0 5	<0 2
MS36371-45	100/200/250	<0 5	<0 2
MS36371-46	200/300/500	<0 5	<0 2
MS36371-47	500/750/1000	<0 5	<0 2
MS36371-48	1 - 5	<1 0	<1 0
MS36371-49	5 - 50	<1 0	<1 0
MS36371-50	50 -200	<1 0	<1 0
MS36371-51	200 - 1000	1 0	<1 0
MS36371-52	1000 - 5000	1 0	<1 0
MS36371-53	0 5 - 10	±5 to ±1	±3 to ±0 4
MS36371-54	10 - 100	<0 3 µL @ 10 - 35 µL <0 8% @ 35 - 100 µL	<0 10 µL @ 15 µL <0 12 µL @ 50 µL
MS36371-55	100 - 1000	<3 µL @ 100 - 375 µL <0 8% @ 375 - 1000 µL	<0 15 µL @ 100 µL <0 6 L @ 250 µL <1 0 µL @ 500 µL <1.3 µL @ 1000 µL
MS36371-56	500 - 5000	<12 µL @ 0 5 - 2 mL <0 6% @ 2 - 5 mL	<3 µL @ 1 0 µL <5 µL @ 2 5 µL <8 µL @ 5 0 µL

MATERIAL The pump shall be constructed of polypropylene plastic MS36371-54, -55, and -56 shall have a stainless steel digital micrometer mechanism

DESIGN MS36371-1 thru -11 shall be fixed volume pumps, MS36371-12 thru 41 shall be ejector tip models with fixed volume MS36371-42 thru -47 shall be ejector tip models with multi volume, MS36371-48 thru -52 shall be variable volume pumps and MS36371-53 thru -56 shall be variable volume pumps with tip ejector

Automatic pipet pumps shall be air-displacement type Pumps shall be used with disposable tips that can be filled and emptied by the action of pressing and releasing the control button The ejector models automatically eject the tip by depressing either the control button all the way or a separate tip eject button The pumps shall be color-colored for size recognition

NOTES 1 For pipet tips, refer to MS36372

2 Items differing from this Military Standard by minor variations in design or dimensions are considered standard under this document, provided such variations do not affect performance and are not in conflict with the material requirements specified herein

(A) ENTIRE STANDARD REVISED

P A	EA	INTERNATIONAL INTEREST	TITLE
Other Cust	MS 99		PUMP, PIPET, AUTOMATIC

PROCUREMENT SPECIFICATION	SUPERSEDES
NONE	

MILITARY STANDARD
MS36371
SHEET 1 OF 1

DD FORM 672-1 COORDINATED PREVIOUS EDITION IS OBSOLETE 6840-1531-01

AMSC N/A

DISTRIBUTION STATEMENT A Approved for public release, distribution is unlimited

APPROVED 26 JULY 1982 REVISED (A) 31 OCT 1988

USER ACTIVITIES ARMY - MD, OM

REVIEWER ACTIVITIES ARMY - ME
AIR FORCE - 03

This standard is approved for use by all Departments and Agencies of the Department of Defense
Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, U.S. Army Medical Research and Development Command, ATTN: SGRD-RMS, Fort Detrick, Frederick, MD 21701-5012 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

☆ U S GOVERNMENT PRINTING OFFICE 1989 604-033/11938

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T17:39Z
Check the source to verify that this is the current version before use.