
FED. SUP CLASS
5310



ACCEPTABLE DESIGNS

TABLE I. DASH NUMBERS AND DIMENSIONS.

DASH NUMBER		ØA INSIDE DIAMETER		ØB OUTSIDE DIAMETER		C THICKNESS	
STEEL,CARBON	PHOSPHOR BRONZE	MAX	MIN	MAX	MIN	MAX	MIN
9	10	.123	.115	.260	.245	.019	.015
1	11	.150	.141	.320	.305	.022	.016
2	12	.176	.168	.381	.365	.023	.018
3	13	.204	.195	.410	.395	.025	.020
4	14	.267	.256	.510	.494	.028	.023
5	15	.332	.320	.610	.588	.034	.028
6	16	.398	.384	.694	.670	.040	.032
7	17	.464	.448	.760	.740	.040	.032
8	18	.530	.513	.900	.880	.045	.037

REQUIREMENTS:

1. MATERIAL: STEEL, CARBON, GRADES 1050 (UNS G10500) THRU 1064 (UNS G10640), IN ACCORDANCE WITH PROCUREMENT SPECIFICATION. PHOSPHOR BRONZE, COMPOSITION A, HARD (UNS C51000), IN ACCORDANCE WITH QQ-B-750.

2. PROTECTIVE COATING AND SURFACE TREATMENT: STEEL, CARBON, SHALL BE ZINC COATED IN ACCORDANCE WITH ASTM B633, TYPE II, CLASS Fe/Zn 5. PHOSPHOR BRONZE SHALL BE CADMIUM PLATED IN ACCORDANCE WITH QQ-P-416, TYPE II, CLASS 2.

3. PART NUMBER: THE PART NUMBER SHALL CONSIST OF THE BASIC MS NUMBER FOLLOWED BY A DASH NUMBER FROM TABLE I.

EXAMPLE: MS51414-1
- DASH NUMBER
- BASIC MS NUMBER

MS51414-1 INDICATES - WASHER, LOCK, FLAT-EXTERNAL TOOTH; STEEL, CARBON; INSIDE DIAMETER .150 MAX .141 MIN; OUTSIDE DIAMETER .320 MAX .305 MIN; THICKNESS .022 MAX .016 MIN

NOTES:

1. ALL DIMENSIONS ARE IN INCHES.
2. THE NUMBER OF TEETH SHALL BE AT THE OPTION OF THE CONTRACTOR.
3. WASHERS SHALL BE USED WITH FASTENERS HAVING HEAD BEARING SURFACES LARGE ENOUGH TO CONTACT WASHER TEETH.
4. IN THE EVENT OF A CONFLICT BETWEEN THE TEXT OF THIS STANDARD AND THE REFERENCES CITED HEREIN, THE TEXT OF THIS STANDARD SHALL TAKE PRECEDENCE.
5. REFERENCED GOVERNMENT (OR NONGOVERNMENT) DOCUMENTS OF THE ISSUE LISTED IN THAT ISSUE OF THE DEPARTMENT OF DEFENSE INDEX OF SPECIFICATIONS AND STANDARDS (DoDISS) SPECIFIED IN THE SOLICITATION FORM A PART OF THIS STANDARD TO THE EXTENT SPECIFIED HEREIN.
6. ZINC COATED WASHERS ARE INTENDED FOR USE IN NON-AEROSPACE, HIGH TEMPERATURE/PETROLEUM ENVIRONMENT.

Ⓐ ENTIRE STANDARD REVISED

APPROVED 18 OCT 82 REVISED Ⓐ 17 MAR 86

USER ACTIVITIES: ARMY-ME NAVY-MC,YD

REVIEWER ACTIVITIES: ARMY-EA,ER,GL DLA-IS NSA-NS

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document when applicable

P.A. ARMY-AR Other Cust NAVY-SH AIR FORCE-99	INTERNATIONAL INTEREST	TITLE: WASHER, LOCK, FLAT-EXTERNAL TOOTH	MILITARY STANDARD MS51414
PROCUREMENT SPECIFICATION: FF-W-100	SUPERSEDES:		PAGE 1 OF 1

AMSC N/A DD FORM 672-1 (COORDINATED) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE 5310-1411

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T18:01Z
Check the source to verify that this is the current version before use.