JAN–P–224

31 MAY 1945

JOINT ARMY-NAVY SPECIFICATION

PAPER (FOILING)

Army Number
50-11-24C

Navy Number
53P33

This specification was approved by the War Department and the Navy Department for use of procurement services of the Army and the Navy and supersedes the following specifications:

U. S. Army	Navy Department
50–11–24B	Bureau of Ordnance
5 April 1940	Specification O. S. 1330

A. APPLICABLE SPECIFICATIONS

A–1. The following specifications, of the issue in effect on date of invitation for bids, form a part of this specification:

JOINT ARMY-NAVY SPECIFICATION

JAN–P–106—Packaging and Packing for Overseas Shipment—Boxes; Wood, Nailed.[1]

U. S. ARMY SPECIFICATION

100–2—Standard Specification for Marking Shipments by Contractors.

NAVY DEPARTMENT SPECIFICATION

General Specifications for Inspection of Material.[1]

FEDERAL SPECIFICATION

UU–P–31—Paper, General Specifications.

B. TYPES

B–1. This specification covers the following types of foiling paper as specified in the contract or order. (See par. H–1.)

Type I.—Foiling paper coated, on one side only, with shellac or a suitable shellac substitute.

Type II.—Uncoated foiling paper.

C. MATERIAL AND WORKMANSHIP

C–1. *Material.*—The stock from which this paper shall be made is optional. No loading material such as clay, etc., shall be introduced in the manufacture of the paper.

[1] Applicable only to Navy purchases.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T06:44Z
Check the source to verify that this is the current version before us

C–2. *Workmanship.*—The stock shall be uniformly beaten and refined so that a short fiber is produced. Folling paper shall be so manufactured that the machine direction of the fibers shall be as negative as possible. The method of manufacture shall be such as to produce a well made even paper, free from pinholes and uneven layers of fibers.

D. GENERAL REQUIREMENTS

D–1. *Color.*—White-to-buff, dark red, or dark green, as specified in the contract or order. (See par. H–1.)

D–2. *Finish.*—Folling paper stock shall have machine finish but shall not have a glazed or heavily calendered surface.

D–3. *Form.*—Folling paper stock shall be furnished in roll or strip form as specified in the contract or order. (See par. H–1.)

D–4. *Ash.*—Maximum, 5.0 percent.

D–5. *Colorfastness.*—The colors of dark red and dark green material shall be fast to alcohol and acetone.

D–6. *Combustibility.*—Folling paper shall burn readily.

E. DETAIL REQUIREMENTS

E–1. *Weight.*

Type I.—54±2 pounds per ream of 500 sheets 24 x 36 inches.
Type II.—42±2 pounds per ream of 500 sheets 24 x 36 inches.

E–2. *Dimensions.*—

E–2a. *Thickness.*—

Type I.—0.0040±0.0005 inch.
Type II.—0.0035±0.0005 inch.

E–2b. *Width.*—2⅞ inches.

E–2c. *Length.*—

E–2c (1). Strips 51 inches long, corners bevelled, one end only, at 45 degree angle ¾ inch from each edge.

E–2c (2). Rolls sufficient length to form a roll weighing, core included, approximately 8 or 15 pounds as specified in the contract or order. (See par. H–1.)

F. METHODS OF SAMPLING, INSPECTION, AND TESTS

F–1. *Inspection.*—Inspection shall be at the point of delivery unless otherwise specified in the contract or order.

F–2. *Size of lots.*—Maximum, 3,000 pounds.

F–3. *Sampling.*—Sampling shall be done as prescribed in Federal Specification UU–P–31.

F–4. *Tests.*—Unless otherwise specified the samples, representative of the lot under inspection, shall be subjected to the following tests which shall be made under the supervision of the Government inspector.

F–4a. *Weight.*—Determine in accordance with Federal Specification UU–P–31.

F–4b. *Tickness.*—Determine in accordance with Federal Specification UU–P–31.

F–4c. *Dimensions.*—Determine the required dimensions by any convenient means accurate to at least 0.1 inch. In testing strip paper furnished in rolls determine the weight of roll by any convenient means accurate to at least 0.1 pound.

F–4d. *Ash.*—Determine in accordance with Federal Specification UU–P–31.

Source: https://assist.dla.mil -- Downloaded: 2
Check the source to verify that this is the curren

F–4e. *Colorfastness.*—Immerse one portion of approximately 10 square inches of the sample in 25 ml. of alcohol and another in 25 ml. of acetone, both solvents being at room temperature. Note if the colorfastness of the sample is satisfactory as indicated by the solvents remaining colorless after 15 minutes contact with the sample.

F–4f. *Combustibility.*—Ignite a portion of the sample by means of the flame of a match and note if the combustibility of the sample is satisfactory as indicated by its ready and complete combustion.

G. PACKAGING, PACKING, AND MARKING FOR SHIPMENT

G–1. *Packaging.*—Unless otherwise specified strips and rolls of foiling paper shall be packaged in accordance with the requirements of Federal Specification UU–P–31. Rolls shall be wound on suitable cores. (See par. E–2.)

G–2. *Packing.*—

G–2a. *Army.*—Unless otherwise specified, the packages shall be packed in commercial containers so constructed as to insure acceptance by common or other carriers, for safe transportation, at lowest rate, to point of delivery.

G–2b. *Navy (for domestic shipment).*—Unless otherwise specified, the packages shall be packed in full telescope fiberboard boxes having a minimum Mullen test of 275 pounds or nailed wood boxes conforming to Joint Army-Navy Specification JAN–P–106. No strapping will be required. The gross weight of fiberboard boxes shall not exceed approximately 65 pounds and gross weight of the wood boxes shall not exceed approximately 500 pounds. Boxes shall be designed to fit the contents in a compact manner.

G–3. *Marking.*—

G–3a. *Packages.*—Unless otherwise specified, each package shall be plainly marked with the following information completed:

ARTICLE _____
SIZE _____
TYPE _____
COLOR _____
FORM _____
THICKNESS _____
CONTRACT OR ORDER NO. _____
LOT NO. _____
QUANTITY _____
MANUFACTURER _____

G–3b. *Shipping containers.*—Unless otherwise specified, each shipping container shall be plainly marked in black, with the following information completed:

ARTICLE _____
SIZE _____
TYPE _____
COLOR _____
FORM _____
QUANTITY _____
THICKNESS _____
LOT NO. _____
MANUFACTURER _____
CONTRACT OR ORDER NO. _____
GROSS WEIGHT _____
CUBE _____

Source: https://assist.dla.mil -- Downloaded:
Check the source to verify that this is the curre

G–3c. In addition to the foregoing, shipments for the Army shall be marked in accordance with the requirements of U. S. Army Specification 100–2; for the Navy in accordance with the requirements of the latest issue of the Navy Shipment Marking Handbook.

H. NOTES

H–1. Requests, requisitions, schedules and contracts or orders should contain the following information:

(*a*) Title, number, and date of specification.
(*b*) Type of foiling paper required. (See par. B–1.)
(*c*) Color of foiling paper required. (See par. D–1.)
(*d*) Form in which foiling paper is to be furnished. (See par. D–3.)
(*e*) If foiling paper is furnished in rolls, the required weight of rolls. (See par. E–2.)

H–2. *Uses.*—The material covered by this specification is intended for use in the manufacture of primers.

H–3. *Army.*—The use of this specification, whenever applicable, is mandatory on all procuring agencies of the Army.

H–4. Copies of the Navy Shipment Marking Handbook may be obtained upon application to the Bureau of Supplies and Accounts, Navy Department, Washington 25, D. C.

H–5. Copies of Joint Army-Navy specifications and Federal specifications (required for Army purchases) and U. S. Army specifications may be obtained as indicated in the "Index of United States Army, Joint Army-Navy, and Federal Specifications Used by the War Department." Copies of this Index may be obtained from the Superintendent of Documents, Government Printing Office, Washington 25, D. C. Agencies within the War Department will obtain copies of Joint Army-Navy, U. S. Army, and Federal specifications through established War Department channels. Both the title and identifying symbol number should be stipulated when requesting copies of specifications.

H–6. Copies of Navy Department specifications and Federal specifications (required for Navy purchases) may be obtained upon application to the Bureau of Supplies and Accounts, Navy Department, Washington 25, D. C., except that Naval activities should make application to the Supply Officer in Command, Naval Supply Depot, Bayonne, N. J. Both the title and identifying symbol number should be stipulated when requesting copies of the specifications.

Notice.—When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data, is not to be regarded by implication or otherwise as any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may be in any way related thereto.

Source: https://assist.dla.mil -- Download
Check the source to verify that this is the c

U. S. ARMY
SPECIFICATION

No. 50-11-24B
APRIL 5, 1940
SUPERSEDING
No. 50-11-24A
April 24, 1930

PAPER (FOILING)

A. APPLICABLE SPECIFICATIONS.

A-1. The following specifications, of the issues in effect on the date of invitation for bids, form a part of this specification.

Federal Specification UU-P-31, Paper, General Specifications.
U. S. Army Specification No. 100-2, Standard Specifications for Marking Shipments.

B. TYPES.

B-1. This specification covers one type of foiling paper in the following colors:

White.
Dark red.
Dark green.

C. MATERIAL AND WORKMANSHIP.

C-1. *Material.*—The stock from which this paper is made shall be optional. No loading material such as clay, etc., shall be introduced in the manufacture of the paper.

C-2. *Workmanship.*—The stock shall be uniformly beaten and refined so that a short fiber is produced. Foiling paper shall be so manufactured that the machine direction of the fibers shall be as negative as possible. The method of manufacture shall be such as to produce a well made even paper, free from pinholes and uneven layers of fibers.

D. GENERAL REQUIREMENTS.

D-1. See section E.

E. DETAIL REQUIREMENTS.

E-1. *Color.*—White, dark red, or dark green, as prescribed by the contract.

E-2. *Finish.*—Foiling paper shall have machine finish but shall not have a glazed or heavily calendered surface.

E-3. *Form.*—Foiling paper shall be furnished in sheet or strip form as specified in the contract.

E-4. *Weight.*—18±2 pounds per ream of 500 sheets 17×22 inches.

E-5. *Thickness.*—0.0035±0.0003 inch.

E-6. *Dimensions.*—Sheets: $17 \pm \frac{1}{16} \times 22 \pm \frac{1}{16}$ inches. Strips: Width as specified in the contract. Length sufficient to form rolls weighing approximately 15 pounds.

E-7. *Bursting strength.*—Minimum, 18 points.

F-8. *Ash.*—Maximum, 5.0 percent.

Source: https://assist.dla.mil -- D
Check the source to verify that this

E–9. *Colorfastness.*—The colors of dark red and dark green material shall be fast to alcohol and acetone.

E–10. *Combustibility.*—Foiling paper shall burn readily.

F. METHODS OF SAMPLING, INSPECTION, AND TEST.

F–1. *Inspection.*—Inspection shall be at the point of delivery unless otherwise specified in the contract.

F–2. *Size of lots.*—Maximum, 3,000 pounds.

F–3. *Sampling* shall be done as prescribed in Specification UU–P–31.

F–4. *Laboratory* examination shall be made as follows:

F–4a. *Weight.*—Determine as directed by Specification UU–P–31.

F–4b. *Thickness.*—Determine as directed by Specification UU–P–31.

F–4c. *Dimensions.*—Determine the required dimensions by any convenient means accurate to at least 0.1 inch. In testing strip paper determine the weight of roll by any convenient means accurate to at least 0.1 pound.

F–4d. *Bursting strength.*—Determine as directed by Specification UU–P–31.

F–4e. *Ash.*—Determine as directed by Specification UU–P–31.

F–4f. *Colorfastness.*—Immerse one portion of approximately 10 square inches of the sample in 25 cc. of alcohol and another in 25 cc. of acetone, both solvents being at room temperature. Note if the colorfastness of the sample is satisfactory as indicated by the solvents remaining colorless after 15 minutes contact with the sample.

F–4g. *Combustibility.*—Ignite a portion of the sample by means of the flame of a match and note if the combustibility of the sample is satisfactory as indicated by its ready and complete combustion.

G. PACKING AND MARKING.

G–1. *Packing.*—Unless otherwise specified, foiling paper shall be packed in accordance with Specification UU–P–31.

G–2. *Marking.*—In accordance with U. S. Army Specification No. 100–2.

H. NOTES.

H–1. *Uses.*—The material covered by this specification is intended for use in the manufacture of primers.

H–2. The use of this specification, whenever applicable, is mandatory on all procuring agencies of the Army.

NOTICE.—When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility nor any obligation whatsoever, and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may be in any way related thereto.

NOTE.—Copies of this specification may be obtained from the Office, Chief of Ordnance, Washington, D. C.

[No. 50–11–24B]

Source: https://assist.dla.mil -- Downloaded: 2
Check the source to verify that this is the currer