MIL-F-243E(SHIPS)
1 March 1968
SUPERSEDING
MIL-F-243D
16 May 1962
(See 6.4)

MILITARY SPECIFICATION

FURNITURE, SHIPBOARD, STEEL,

GENERAL SPECIFICATION FOR

1. SCOPE

1.1 This specification covers steel furniture and accessories used on Naval ships.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of the specification to the extent specified herein:

SPECIFICATIONS

FEDERAL
FF-T-77 - Tag and Holder, Key.

MILITARY
MIL-P-8585 - Primer Coating, Zinc Chromate, Low-Moisture Sensitivity.
MIL-E-15090 - Enamel, Equipment, Light-Gray (Formula No. 111).
MIL-P-15328 - Primer, Pretreatment (Formula No. 117 for Metals).
MIL-A-21366 - Adhesives, Plastic Table Top Material To Aluminum Bonding.

STANDARD

MILITARY
MIL-STD-130 - Identification Marking of U.S. Military Property.

DRAWINGS

MILITARY
NAVSEC S3200-860055 - Hardware for Metal Furniture.
NAVSEC 805-1642368 - Metal Furniture Construction Details.
NAVSEC 805-2217424 - Static Load Test for Metal Furniture.

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

AMERICAN IRON AND STEEL INSTITUTE (AISI)
Steel Products Manual.

(Application for copies should be addressed to the American Iron and Steel Institute, 150 East Forty-Second Street, New York, New York 10017.)

UNIFORM CLASSIFICATION COMMITTEE
Uniform Freight Classification Rules.

(Application for copies should be addressed to the Uniform Classification Committee, 202 Union Station, 516 West Jackson Boulevard, Chicago, Illinois 60606.)

(Technical society and technical association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T06:48Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 Material.

3.1.1 The materials used in the construction of furniture covered by this specification and the applicable hull type drawings shall be not less than as specified herein and on the drawings and the use of equivalent commercial materials is acceptable.

3.1.1.1 Unless otherwise specified in the hull type drawings (see 6.1), shapes, sheets and strips shall be of the material specified in table I.

Table I - Material for shapes, sheets and strips.

Shapes	Steel - Commercial open hearth or electric furnace A7 - carbon 0.35 percent maximum.
Sheets and strips for steel parts	Commercial cold rolled steel.
Steel sheet for subbases	Commercial corrosion resisting steel AISI type 304.

3.1.2 Drawer and table runners. All drawer and table runners, including complete suspension frame and roller bearings, shall be of corrosion-resisting steel conforming to AISI types 302, 304, or 430. Hardware in accordance with Drawing S3200-860055 are acceptable alternates for those shown on the hull type drawings.

3.1.3 Desk top linoleum or plastic table top material shall be cemented with adhesive in accordance with MIL-A-21366 to the metal furniture where indicated on the applicable drawings.

3.2 Design.

3.2.1 General requirements. Steel furniture and accessories shall conform to the requirements of this specification, the applicable hull type drawings specified (see 6.1.1) and the construction details shown on drawing 805-1642368. Hull type drawings are NAVSEC drawings illustrating general arrangement of equipment, systems, or components for the Naval Ship Engineering Center. A drawing of the furniture item being procured shall be prepared by the supplier for approval of the design by the Naval procuring activity, or Supervisor of Shipbuilding, USN (SupShip), where applicable. This drawing shall be generally similar to the hull type drawing for the item, except that all dimensions, gages, methods of assembly and material specifications shall be shown. Also, all details which differ from the hull type drawings shall be shown and so noted. The supplier's drawing shall follow standard commercial practice, be legible, complete with a bill of material and be acceptable to the Naval procuring activity or SupShip, where applicable. After the supplier's drawing for an item has been approved it will not require further approval,unless an alteration has been made on the NAVSEC drawing for the item. In the event a drawing previously approved by an activity is not acceptable to a different activity, this matter shall be referred to the Naval Ship Engineering Center for adjudication. All articles shall be complete including hardware, hasps, reinforcement of attaching areas on furniture, and accessories for the securing of hasp pads and subbases. Furniture shall, if necessary, be made in sections or shall be separable so as to pass readily through an opening 26 by 66 inches which has rounded 8-inch radius corners. Furniture for submarines shall be designed to pass through the opening specified in the contract or order. Adjustable stops shall be fitted on all drawers for furniture to prevent accidental withdrawal. Where sheet metal is not available to the thickness shown on the drawing, the next larger thickness which is commercially available shall be used. Furniture shall be constructed to preclude the harboring of vermin in inaccessible locations.

3.2.2 Subbases. Unless otherwise specified (see 6.1), subbases shall be furnished with all articles of furniture except items having legs, and accessories installed on decks.

3.2.3 Sections; riveting, welding, bolting, and spot welding.

3.2.3.1 The different sections for all articles of furniture and accessories shall be fitted with solid backs, also with one partition between sections, either a top for

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T06:48Z
Check the source to verify that this is the current version before use.

the lower section or a bottom for the upper section; and when assembled ready for installation, the pieces of furniture and accessories shall be well braced and rigid, so as not to depend on attachment to the ship to maintain shape.

3.2.3.2 Riveting, welding, bolting, and spot welding are permitted; except where certain types of connections are indicated as mandatory on hull type drawings, the drawings shall be adhered to. Wherever practicable, rivets shall be used in lieu of screwed fastenings, except where the appearance or function of the item will be impaired. When blind rivets are used, they shall be of the solid core type. Suitable lock washers or other means shall be provided to prevent loosening of screws and bolts.

3.2.3.3 Machine screws shall be cadmium plated, and shall tap into material whose thickness is at least equal to the diameter of the machine screw. Pads may be welded for this purpose. Special care shall be taken to secure rigid attachment for hinges and to prevent screws, if used, from backing out. Countersunk points for rivets shall not be used in metal less than 0.05 inch thick. Where countersunk points are used, particular care shall be exercised so as not to weaken the structure.

3.2.3.3.1 Self tapping screws, cadmium plated, shall be used only when specifically stated on the applicable hull type drawing. When used, the screw shall tap into material whose thickness is at least equal to the diameter of the screw. Pads may be welded for this purpose.

3.2.3.4 All threaded parts, such as screws used on hardware and in the assembly of parts requiring dismantling during service of the furniture and accessories, shall be coated before assembly with a commercial antiseize compound.

3.2.4 Weight. The weights shown on the drawings (see 6.1.4) shall not be exceeded by more than 5 percent.

3.2.5 Finish.

3.2.5.1 Coating. Fabricated ferrous parts so specified, shall be cadmium plated, also ferrous parts hidden from view may be cadmium plated. Cadmium plating shall be accomplished by the electrodeposited process. The plating shall be 0.0030 inch (minimum), shall be followed by a clear blue white finish chromate treatment capable of withstanding a 96 hour salt spray test without the appearance of white corrosion products visible to the eye at normal reading distance. Ferrous parts which are cadmium plated and treated with the chromate shall not show any evidence of a yellowish color. Cadmium plating shall be adherent, smooth, free from uncoated spots, injurious lumps, blisters, dross, or flux.

3.2.5.2 After final assembly, a light coat of paraffin shall be applied to the working surfaces of all drawer runners.

3.2.5.3 Cleaning and painting.

3.2.5.3.1 Joints and welds shall be ground or filed smooth and all traces of welding flux, mill scale, rust, oil, and moisture removed before any finishing material is applied. Only those welds exposed to view should be ground or filed smooth. Blemishes sufficient to cause rejection of the finish may result from failure to remove traces of flux or to remove small amounts of oil lodged between faying surfaces.

3.2.5.3.2 Furniture and accessories shall be cleaned prior to assembly, in accordance with best commercial practice. Acids such as phosphoric shall not be used since they may be retained between faying surfaces and cause corrosion or breakdown of finish.

3.2.5.3.3 After fabrication and before assembly, one coat of pretreatment in accordance with MIL-P-15328 shall be applied. This shall be followed by one coat of primer in accordance with MIL-P-8585 and in accordance with best commercial practice. These coverings shall be applied to all surfaces and parts to be painted, except on parts which are plated, made of corrosion-resisting steel, or of bronze. Baking enamel shall then be applied as specified in paragraph 3.2.3.5.4, or if desired, primer MIL-P-8585 shall be omitted, and two coats of baking enamel applied.

3.2.5.3.4 After assembly, a light gray semi-gloss, baking enamel in accordance with type III, class 2 of MIL-E-15090, Navy Formula No.111 shall be applied and baked in accordance with the paint manufacturer's instructions, to all accessible parts of all furniture items except parts which are plated or made of corrosion-resisting steel or of bronze.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T06:48Z
Check the source to verify that this is the current version before use.

3.2.6 Locks and keys.

3.2.6.1 Three keys shall be provided for each unit of furniture fitted with locks; when the unit has two or more locks keyed differently, then 3 keys shall be furnished with each key change (see 6.1.1 and 6.2). Drawer locks shall be secured to drawer fronts as shown on Drawing 805-1642368, sheet 2.

3.2.6.2 When required in the purchase order, three key holders and tags conforming to FF-T-77, engraved or inscribed in accordance with key schedule satisfactory to the Naval procuring activity or Supship, where applicable, shall be supplied for each set of keys, consisting of working and spare keys.

3.2.7 Hardware. All exposed hardware on furniture items for use on Naval ships shall be nickel plated, satin finished. Ferrous hardware hidden from view shall be cadmium plated; brass hardware hidden from view need not be plated. Card clips and holders, tee handles, knobs, drawer pulls, catches and other applicable hardware shall be in accordance with Drawing S3200-860055.

3.3 Marking. Each complete furniture item shall be permanently and legibly marked in an inconspicuous location, not normally visible, in accordance with MIL-STD-130 with only the following:

(a) Manufacturer's identification.
(b) Navy's identifying drawing number, and stock number, if any.
(c) Contract or order number and date.

3.4 Workmanship. The general appearance of the furniture and accessories shall indicate first class workmanship throughout and shall be free from blemishes and defects affecting the appearance or that may affect the serviceability. Also, all moving parts such as doors, drawers, typewriter shelves in typewriter desks, berth pan mechanism in combination-berth transoms, and so forth, shall operate freely, smoothly, as specified and for the purpose intended; this requirement will take precedence over any approved drawings held by the supplier.

3.4.1 Factors considered essential to good workmanship. The following factors are considered essential to good workmanship for construction of steel furniture:

(a) Shearing, notching and punching. All parts requiring shearing, notching and punching should be processed with sharp tools and dies to produce clean edges, free from slivers, burrs, and so forth, which may result in injury to personnel using the finished product. All parts should be square, or true to shape required, to produce uniform good fitting component parts. Open notches of corners of parts requiring the flanging of edges shall be notched so as to permit true forming of flanges and closing of corners. Such notches will not be excessive to show open corners on parts exposed to view after assembly. Holes punched or drilled for bolting up shall be close fit for the screw or bolt being used.

(b) Forming. Flanging and forming of parts should reflect true shapes desired. Radii on the heel of flanges where no specific radii is specified, should be the minimum permissible without fracturing or breaking the material being formed. Formed sections exposed to view will show no signs of tool or die marks which will not be covered or removed with subsequent finishing. Parts requiring cupping or deep drawing will not be reduced in thickness by such drawing as to impair required strength. Also, these parts shall not have visible wrinkles on parts exposed to view in the finished product.

(c) Welding, (including spot welding).

(1) All welding, except resistance spot welding, shall be done by the Arc or Gas welding process without fluxing. However, fluxing welding is permissible provided all traces of flux are removed after welding to prevent oxidation of adjacent material. Sufficient filler metal shall be used where required to insure complete penetration, and to allow for adequate material for cleaning of welds by grinding, or other means, to produce smooth surfaces where exposed to view. Welding is to be accomplished with a view of securing together, permanently, structural members to increase strength and rigidity of the article, not merely as a temporary means of fastening.

(2) Spot welding should be accomplished on reliable automatic-time controlled welding equipment with a suitable source of electrical energy and equipped with electrodes suitable for the specific requirements with a means of adequately cooling the electrodes and a force between the electrodes to fulfill the requirements. The welds shall

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T06:48Z
Check the source to verify that this is the current version before use.

conform to the requirements indicated on applicable hull type drawing as to location, spacing and strength which are the minimum acceptable. The surface of parts to be spot welded shall be free from objectionable oxide films, scale, grease, mill markings, dirt, and so forth which may be detrimental to welding process. The contractor shall provide suitable spot welding shear testing machines as required to certify strength of weld. Testing machines shall be accurate within plus or minus 2 percent of the indicated reading or 10 pounds, whichever is the greater. Prior to undertaking welding on component parts to be used, spot welding machine operations shall be calibrated, using test specimens of material of the same thickness and cleaned in the same manner as the component parts which are to be welded. After correct calibration has been determined and satisfactory welds made on two test specimens, welding operations shall proceed. Provided welding operation continues for more than two hours,additional shear strength test shall be conducted at two hour intervals to certify machine settings. Test specimens shall consist of 2-inch wide strips of material 6 inches long, overlapped 2 inches at the ends and spot welded with a single weld in the center of the 2-inch overlap. Specimens shall be tested to destruction on testing machine and a log made of shear strength. All spot welding machine controls must remain as set for the test specimen. If for any reason the controls are readjusted, two new specimens shall be tested. This does not include cleaning of the electrodes. Electrodes should be cleaned as necessary and be properly proportioned for the work to avoid undue indentation or reduction in thickness of the work piece. Failure of any test specimen conducted during the process of welding will be cause to conduct an examination of welds made in the preceding run to determine soundness of weld. Rejected components may be rewelded to assure proper attachment of parts.

(d) Assembly.

(1) Furniture shall be assembled in sections to pass through openings as required by 3.2.1. Portable sections shall be made up in such manner to provide easy access to machine screws or bolts. Bolts, nuts and washers shall be of a noncorrosive material and tightly secured at assembly. Machine screws shall not be tapped into thin metal. Where tapping in thin metal is required, a backing liner of not less than the diameter of the screw in thickness shall be spot welded to the thinner member. All hinges and bolts should be rigidly secured to prevent screws, if used, from backing out. Countersunk points for rivets should not be used in metal less than 0.050 inch thick. Where countersunk points are used, the work shall be done well so as not to be weakened by grinding for a smooth finish.

(2) All working or moving parts, such as drawers, doors, drop heads for typewriter desks, and similar parts shall operate freely but should be sufficiently snug to prevent rattle of parts during vibration of ship. Drawer fronts shall be fitted in drawer recesses with a space of about 1/16 inch equi-distant between stationary members and periphery of drawer fronts. Mechanical operating fittings, such as hinge pins for secretary bureau drop leafs, hinging mechanism for folding berths, and similar fittings, shall work smoothly and free from galling of parts. Desk top linoleum and table top plastic should be thoroughly bonded to the metallic top of desks, tables, and so forth, free from blisters, air bubbles, and so forth. Metallic edge binding should be neatly fitted at edge of desk and table top to provide for protection of edge of linoleum from damage; also, to hold edge of linoleum firmly against table or desk top.

(3) Component parts should be accurately shaped to permit easy assembly and maintenance of overall dimensions of plus or minus 0.0156 inch.

(4) The latching devices of sectionalized units, such as modular sections, sectional file cabinets, and similar units, should be of uniform construction to permit interchangeability in stacking of the various units.

(5) Metallic edge binders on mess tables should be neatly fitted to preclude crevices which may collect food stuff. Also, tables should have cleanout areas at corners of tables free of obstructions.

(6) Drawer stops. Drawer and case channels shall be secured as shown on Drawing 805-1642368, Sheet 2.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T06:48Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Sampling.

4.2.1 Lot. All units of furniture or accessories of the same type presented for delivery at one time shall be considered a lot.

4.2.2 Sampling for examination. A random sample of units of furniture or accessories shall be selected from each lot in accordance with tables II and III for the examination specified in 4.3.

Table II - Sampling for examination for major defects.

Number of units of furniture or accessories in lot	Number of units of furniture or accessories in the sample	Acceptance number (defective)	Rejection number (defective)
1 to 8	3	0	1
9 to 25	5	0	1
26 to 40	7	0	1
41 to 65	10	0	1
66 to 110	15	1	2
111 to 300	25	1	2
301 to 500	35	2	3
501 to 800	50	3	4
801 to 1300	75	4	5
1301 and over	110	6	7

Table III - Sampling for examination for minor defects.

Number of units of furniture or accessories in lot	Number of units of furniture or accessories in sample	Acceptance number (defective)	Rejection number (defective)
1 to 8	4	0	1
9 to 25	5	0	1
26 to 40	7	0	1
41 to 65	10	1	2
66 to 110	15	1	2
111 to 300	25	2	3
301 to 500	35	3	4
501 to 800	50	4	5
801 to 1300	75	6	7
1301 and over	110	8	9

4.2.3 Sampling for performance tests. The sample units specified in table II shall be tested as specified in 4.4.

4.3 Examination. Each of the sample units of furniture or accessories selected in accordance with 4.2.2 shall be visually and dimensionally examined to verify compliance with the requirements of this specification. Examination shall be conducted as specified in table IV. Any unit of furniture or accessory in the sample containing one or more visual or dimensional defects shall not be offered for delivery, and if the number of defective units of furniture or accessories in any sample exceeds the acceptance number for that sample, this shall be cause for rejection of the lot represented by the sample.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T06:48Z
Check the source to verify that this is the current version before use.

Table IV - Classification of defects.

Categories	Defects
Critical:	
1	Not shock hardened when required in contract or order.
Major:	
101	Item not in accordance with manufacturer's approved drawings.
102	Item not complete; component parts missing.
103	Component parts not new; evidence of reclaimed, used or salvaged components.
104	Evidence of use of unauthorized materials or repairs.
105	Parts broken, distorted, cracked, chipped.
106	Surfaces not smooth; not free of blisters, seams, laps, cracks, oil, scale or porosity.
107	Parts improperly formed, fitted or joined; dimensions not as specified, not free of burrs, raised or sharp edges, or corners, holes not drilled or punched as specified; hole location or size non-conforming.
108	Parts not square, true to shape required to produce uniform good fitting of components.
109	Welding non-conforming; incomplete, missing or evidence of non-fusion, weld cracks, porosity; not finished smooth; free from oil, weld splatter or any flux.
110	Rivets not grade and type specified; missing, cracked; not secured and headed as required.
111	Machine bolts or screws not grade and type specified, missing, cracked, not secured or fitted with lock washers or locking device.
112	Method of securing not as specified.
113	Thickness of metals not as specified.
114	Item not well braced, rigid or properly stiffened.
115	Thickness of material into which machine screws or self tapping screws are tapped is not equal to or greater than the diameter of the screw.
116	Unauthorized use of self tapping screws.
117	Reinforcing pieces missing.
118	Hinges not mounted on rigid backing plates.
119	Countersunk joints not properly used; evidence of weakening of structure.
120	Threaded parts not coated with anti-seize compound prior to assembly.
121	Paint or plating not adherent; not smooth; not free from uncoated spots, injurious lumps, blisters, dross or flux.
122	Exposed joints and welds which affect appearance not ground or filed smooth.
123	All traces of welding flux, mill scale, rust, oil, blemishes, markings and moisture not removed prior to application of any finishing material.
124	Evidence of doors and drawers not conforming to design.
125	Evidence of hardware not conforming to design, finish not correct, not functioning.
126	Weight of item exceeding 5 percent of allowable weight.
127	Inaccessible locations not vermin proof.
128	Upholstery covering or padding not specified approved materials, not properly fitted, sewn and fastened; upholstery covering not color specified; or cracked and rough.
129	Sub-base not as specified or missing.
130	Locks not type specified, fail to function.
131	Mirror glass not type specified.
132	Desk top material not type specified or properly cemented to metal tops.
133	Packaging and packing not as specified.
134	Mandatory requirements of NAVSEC drawing not provided.
135	Failure to pass required tests.
Minor:	
201	Item not free of sharp edges, burrs.
202	Marking, manufacturer's name or trademark missing and contract number illegible or incorrect.
203	Paint or finish scuffed, scratched or dirty.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T06:48Z
Check the source to verify that this is the current version before use.

4.4 Performance tests. Each of the sample units of furniture or accessories selected in accordance with 4.2.3 shall be tested as specified in 4.4.1 through 4.4.5 and the hull type drawing.

4.4.1 Static load tests shall be performed on sample units as selected in accordance with the requirements of Table III, and as specified on drawing 805-2217424.

4.4.2 Tables. Tables shall be set on a true level surface. Pressures shall be applied to each corner separately to detect support point not making contact.

4.4.3 Drawers. Drawers shall be loaded (normal practice) and shall be moved out the full travel distance to detect rough surfaces and binding or looseness.

4.4.4 Adjustable legs. Adjustable legs shall be moved throughout the range of adjustments and locked at one point.

4.4.5 Possible test failures. Possible test failures may be as follows:

(a) Performance test (see 4.4)
(1) Drawers do not properly fit or operate smoothly with load specified on drawing.
(2) Doors do not operate properly.
(3) Hardware and moving parts fail to operate smoothly and properly.
(4) See drawing 805-2217424 for static load tests.

4.5 Inspection of preparation for delivery. Packaging, packing and marking shall be examined to determine conformance with the requirements of Section 5.

5. PREPARATION FOR DELIVERY

(The preparation for delivery requirements specified herein apply only for direct Government procurements. Preparation for delivery requirements of referenced documents listed in section 2 do not apply unless specifically stated in the contract or order. Preparation for delivery requirements for products procured by contractors shall be specified in the individual orders.)

5.1 Domestic shipment and early equipment installation.

5.1.1 Furniture, shipboard.

5.1.1.1 Packaging. Packaging shall be sufficient to afford adequate protection against corrosion, deterioration and physical damage during shipment from the supply source to the using activity and until early installation and may conform to the supplier's commercial practice.

5.1.1.2 Packing. Packing shall be accomplished in a manner which will insure acceptance by common carrier, at lowest rate, and will afford protection against physical or mechanical damage during direct shipment from the supply source to the using activity for early installation. The shipping containers or method of packing shall conform to the Uniform Freight Classification Rules and Regulations or other carrier regulations as applicable to the mode of transportation and may conform to the supplier's commercial practice when such meets these requirements.

5.1.1.3 Marking. Shipment marking information shall be provided on interior packages and exterior shipping containers in accordance with the contractor's commercial practice. The information shall include nomenclature, Federal stock number or manufacturer's part number, contract or order number, contractor's name and destination.

5.2 Domestic shipment and storage or overseas shipment. The requirements and levels of packaging, packing and marking for shipment shall be specified by the procuring activity (see 6.1.1).

(5.2.1 The following provides various levels for protection during shipment and storage, which may be required when procurement is made (see 6.1.1).

5.2.1.1 Packaging.

5.2.1.1.1 Level A.

5.2.1.1.1.1 Furniture and accessories shall be cushioned with excelsior padding, fiberboard pads, cellulosic wadding or comparable material so applied as to prevent

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T06:48Z
Check the source to verify that this is the current version before use.

marring, or any abrasive action to finished surfaces and to prevent damage during handling, shipment and storage. Glass surfaces shall be cushioned to prevent fracture. Drawers and other movable surfaces shall be securely taped in place. When locks are provided, keys shall be packaged in sealed envelopes or bags and securely fastened to the article.

5.2.1.1.2 Level C. Packaging shall be sufficient to afford adequate protection against corrosion, deterioration and physical damage during shipment from the supply source to the using activity for early installation. This level may conform to the supplier's commercial practice when such meets the requirements of this level.

5.2.1.2 Packing.

5.2.1.2.1 Level A. Furniture and accessories shall be packed in wood cleated fiberboard, wood cleated plywood, or fiber boxes conforming to PPP-B-591 (overseas type), PPP-B-601 (overseas type), PPP-B-636, weather resistant type, or PPP-B-640, class 2 respectively, or in unsheathed crates conforming to PPP-C-650 at the option of the supplier. Wood, wood-cleated and fiber boxes shall be provided with caseliners conforming to MIL-L-10547. Caseliners shall be closed and sealed in accordance with the appendix to MIL-L-10547. Items packed in unsheathed crates shall be shrouded in accordance with the appendix to PPP-C-650. Caseliners for fiber boxes conforming to PPP-B-636 may be omitted provided all corner and edge seams and manufacturer's joints are sealed with minimum 1-1/2 inch wide tape conforming to PPP-T-76. Containers shall be closed and strapped in accordance with applicable container specification or appendix thereto. Gross weight of wood or wood cleated boxes shall not exceed 200 pounds; fiber boxes shall not exceed the weight limitations of the applicable fiber box specification.

5.2.1.2.2 Level B. Furniture and accessories shall be packed in wood-cleated fiberboard, cleated plywood, wirebound, or fiber boxes conforming to PPP-B-591 (domestic type), PPP-B-601 (domestic type), PPP-B-585 (class 1), PPP-B-636, weather resistant type, or PPP-B-640, class 2, respectively, or in unsheathed crates conforming to PPP-C-650. The gross weight of the wood or wood cleated boxes shall not exceed approximately 200 pounds; fiber boxes shall not exceed the weight limitations of the applicable box specification. Items packed in unsheathed crates shall be shrouded in accordance with the appendix to PPP-C-650.

5.2.2 Blocking and bracing. The items shall be cushioned, blocked and braced within the container in a manner to prevent marring or other damage to equipment and finished surfaces due to dislodgement or excessive movement during handling, shipment and storage.

5.3 Marking. In addition to any special marking required in the contract or order, interior packages and shipping containers shall be marked in accordance with Level A or C of MIL-STD-129.)

5.4 When required to be of knocked down construction, information as to the method of assembly and disassembling shall be furnished with each article, packaged in an envelope or bag and securely fastened to the subject commodity.

6. NOTES

6.1 Ordering data.

6.1.1 Procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) Applicable drawings (see 3.1.1.1 and 3.2.1).
(c) If subbases are to be furnished (see 3.2.2).
(d) Number of keys to be supplied if more than the three specified (see 3.2.6.1 and 6.2).
(e) If shock hardening is required, give specification number and grade of shock hardening required (see 4.3).
(f) Level of packaging, packing and marking (see 5.2).
(g) Lock combination required (see 6.2).

6.1.2 Provided that all general requirements of this specification are complied with, modifications in design or specification which it may be desired to incorporate in a bid will be considered if clearly stated and illustrated by drawing, sample, or photograph. This applies particularly to details of construction which are not accepted commercial practice and which may be adopted without sacrifice of exterior design or dimensions.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T06:48Z
Check the source to verify that this is the current version before use.

6.1.3 Procurement documents shall state that:

(a) If requested, each bidder shall submit and forward, at his own expense to the place designated by the Naval procuring activity or SupShip, where applicable, a finished article of steel furniture or accessories, to show the character of work, method of connecting and locking parts, and finish proposed by his bid; also such drawings, illustrations, sample sections of articles, hardware, as will further show the character of construction proposed. (The bidder awarded the contract will be required to furnish for approval, two pieces of steel plate, approximately 15 by 15 inches, coated to represent the finished furniture and for comparison with the finished article.)

6.1.4 Procurement documents shall specify, that in the event there are changes approved during manufacture and after the drawing required by 3.2.1 is approved, that one drawing showing assembly, detailed construction, and weight of each type piece of furniture or accessory, as actually built and delivered (see 3.2.1), shall be supplied on the completion of the contract or order.

6.1.5 Procurement documents shall specify that in the event there is an alteration to the NAVSEC drawing after the Invitation for Bid, the supplier may, upon approval of the Naval procuring activity or SupShip, where applicable, and provided there is no increase in cost and no delay in delivery, fabricate the item to the newer design.

6.2 For stocking purposes, each piece of furniture in the same procurement should be fitted with lock(s) of separate key changes. When there is more than one lock required in a single furniture item, then the key change should be the same, unless the drawing specifies otherwise. These requirements are applicable for those furniture items procured for standard Navy stock.

6.3 Sample color chips of linoleum (panels) (see 3.1.3) will be supplied the contractor upon application to the Commander, Naval Ship Engineering Center, Washington, D. C. 20360.

6.4 CHANGES FROM PREVIOUS ISSUE. THE OUTSIDE MARGINS OF THIS DOCUMENT HAVE BEEN MARKED "#" TO INDICATE WHERE CHANGES (DELETIONS, ADDITIONS, ETC.) FROM THE PREVIOUS ISSUE HAVE BEEN MADE. THIS HAS BEEN DONE AS A CONVENIENCE ONLY AND THE GOVERNMENT ASSUMES NO LIABILITY WHATSOEVER FOR ANY INACCURACIES IN THESE NOTATIONS. BIDDERS AND CONTRACTORS ARE CAUTIONED TO EVALUATE THE REQUIREMENTS OF THIS DOCUMENT BASED ON THE ENTIRE CONTENT AS WRITTEN IRRESPECTIVE OF THE MARGINAL NOTATIONS AND RELATIONSHIP TO THE LAST PREVIOUS ISSUE.

Preparing activity:
Navy - SH
(Project 2090-N032)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T06:48Z
Check the source to verify that this is the current version before use.

APPENDIX A

Inspection System Requirements

for

Shipboard Furniture

10. SCOPE

10.1 Scope. This appendix establishes the minimum requirements for the supplier's inspection system. These requirements pertain to the inspections and tests necessary to substantiate product conformance to approved drawings, specifications, contract requirements and the required tests.

10.2 Conflicts. In the event of inconsistency between the requirements of this appendix and the contract, the contract provisions shall control. Also, in case of an inconsistency, this fact shall be brought to the attention of the purchaser, in writing prior to any action on the part of the supplier.

10.3 Options. This appendix has fewer requirements than specifications MIL-Q-9858 and MIL-I-45208. However, the supplier, at his option, may use an established system complying with either of these specifications, provided there is no increase in cost, in lieu of the requirements of this appendix in order to maintain one uniform inspection system in his plant.

20. APPLICABLE DOCUMENTS

20.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of the specification to the extent specified herein.

MIL-Q-9858 - Quality Program Requirements
MIL-I-45208 - Inspection System Requirements

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

30. REQUIREMENTS

30.1 Supplier responsibilities. The supplier shall provide and maintain an effective and economical documented inspection system which will assure that all material submitted to the purchaser for acceptance conforms to all contract requirements, whether manufactured by the supplier or by sub-contractors. The supplier shall perform or have performed the inspections and tests required to substantiate product conformance to approved drawings, specifications, contract requirements and required tests. The supplier's inspection system shall be submitted to the Naval procuring activity or SupShip, where applicable, for review prior to initiation of production. The Government at its option will furnish written notice of the acceptability or non-acceptability of the supplier's inspection system. The supplier's inspection system and all parts of the supplier's facilities shall be available to the Naval procuring activity or SupShip, where applicable, at all times during the manufacturing cycle. The supplier shall notify them, in writing, of any change to his inspection system prior to implementation of the changes. This inspection system shall be subject to disapproval if the changes would result in non-conforming products.

30.2 Documentations and records

30.2.1 Inspection and testing documentation. Inspection and testing shall be prescribed by clear, complete and current instructions which will assure inspection and tests of materials, work in progress, and completed items required by the approved drawings, specifications, contract requirements and required tests. The instructions shall contain the sampling requirements for acceptance or rejection.

30.2.2 Records. The supplier shall document the results of the inspections and tests by maintaining accurate records for his warranty period of all inspections and tests required. These records shall show the type of and number of observations, measurements and tests made, the number and type of deficiences found, and of the quantities sampled, the number accepted and the number rejected and the number of items in the lot.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T06:48Z
Check the source to verify that this is the current version before use.

30.3 Measuring and test equipment. The supplier shall provide and maintain gages and other measuring and testing devices necessary to perform the required inspections and tests. These devices shall be calibrated, at established intervals, against certified standards, to insure continued accuracy. When requested the supplier's measuring and testing equipment shall be made available to the Naval procuring activity or SupShip, where applicable, to determine conformance of the product with contract requirements.

30.4 Indication of inspection status. The supplier shall maintain a positive system for identifying the inspection status of the material. Identification may be accomplished by means of stamps, tags, routing cards, move tickets, tote box cards or other control devices. Such controls shall be of a design distinctly different from the identification of the Naval procuring activity or SupShip, where applicable.

30.5 Non-conforming products. The supplier shall establish and maintain an effective and positive system, including identification, segregation, presentation and/or disposition of reworked or repaired products. All non-conforming products shall be positively identified and segregated to prevent use, shipment or intermingling with conforming products. Areas for non-conforming products shall be designated by the supplier.

30.6 Government inspection. The Government reserves the right to perform any of the required inspections or tests. The fact that the Government does accomplish such inspection or tests does not waive the requirement for the supplier to comply with the requirements of this appendix.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T06:48Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 119-R004

INSTRUCTIONS

This sheet is to be filled out by personnel either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity *(as indicated on reverse hereof)*.

SPECIFICATION

ORGANIZATION *(Of submitter)* | CITY AND STATE

CONTRACT NO. | QUANTITY OF ITEMS PROCURED | DOLLAR AMOUNT $

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES.

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO IF "YES", IN WHAT WAY?

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity)* | DATE

DD FORM 1 APR 63 1426 REPLACES NAVSHIPS FORM 4863, WHICH IS OBSOLETE
(NAVSHIPS OVPRT 12-66)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T06:48Z
Check the source to verify that this is the current version before use.