FEDERAL SPECIFICATION

BRICKS, REFRACTORY: FIRE CLAY

This amendment, which forms a part of Federal Specification HH-B-671f, dated January 3, 1966, was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

PAGE 3

Paragraph 2.2: Insert the following:

"C 107-52 - Panel Spalling Test for High Duty Fireclay Brick."

PAGE 5

Paragraph 4.4.2.4: Delete and substitute:

4.4.2.4 Spalling resistance. The spalling resistance shall be determined in accordance with ASTM C 38-58 and ASTM C 107-52 for class 4 (high duty) brick, and in accordance with ASTM C 38-58 and ASTM C 122-52 for class 5 (super duty) brick. A spalling loss greater than the spalling loss specified in table I shall constitute failure of this test.

MILITARY INTEREST:

Custodians:

Army - MO (ERDL)
Navy - YD
Air Force - 69

Review activities:

Army - MO
Navy - YD
Air Force - 69
Defense Supply Agency - GS

User activities:

Army - None
Navy - SH, MC
Air Force - None

CIVIL AGENCIES INTEREST:

GSA-FSS
HEW
DC
JUS
PO

FSC 9350

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:55Z
Check the source to verify that this is the current version before use.