HH–C–536a
APRIL 20, 1954
SUPERSEDING
Fed. Spec. HH–C–536
5 June 1936

FEDERAL SPECIFICATION

COMPOUND; PLUMBING-FIXTURE-SETTING

This specification was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

1. CLASSIFICATION

1.1 **Grade.**—The plumbing-fixture setting compound shall be of one grade.

1.2 **Types.**—The plumbing-fixture setting compound shall be furnished in the following types as specified:

Type 1.—Nonpreformed (bulk)
Type 2.—Preformed (molded in a ring)

2. APPLICABLE SPECIFICATIONS, AND OTHER PUBLICATIONS

2.1 There are no other specifications applicable to this specification except those referenced in section 7 by individual departments.

(Non-Government activities may obtain copies of Federal Specifications and Standards upon application accompanied by check, money order, cash, or Government Printing Office coupons, to the General Services Administration, Business Service Center, Region 3, Seventh and D Streets SW., Washington 25, D. C. This office will also honor deposit account numbers issued by the Government Printing Office. Copies of the Index of Federal Specifications and Standards may be obtained from the Superintendent of Documents, U. S. Government Printing Office, Washington 25, D. C. Prices may be obtained from the Index of Federal Specifications and Standards or from the GSA Regional Offices.

(Single copies of this specification and other product specifications required by non-Government activities for bidding purposes are available without charge at the GSA Regional Offices in Boston, New York, Atlanta, Chicago, Kansas City, Mo., Dallas, Denver, San Francisco, Los Angeles, Seattle, and Washington, D. C.

(Government activities may obtain copies of Federal Specifications and Standards and the Index of Federal Specifications and Standards through departmental channels from the established sources of supply.)

3. REQUIREMENTS

3.1 **Material.**—The compound shall be nonvolatile and nonasphaltic, with or without asbestos fiber, and shall contain a germicide in a quantity sufficient to prevent the compound from supporting bacterial life.

3.2 **Characteristics.**—The compound shall be gasproof, fumeproof, and watertight when applied on tile or concrete surfaces and shall not rot, harden, shrink, or dry.

3.2.1 Nonstaining.—The compound shall be nonstaining when applied to wood, concrete, or tile surfaces. The compound, when tested in accordance with 4.3.1, shall show no staining on the outside of the ring described in the test.

3.3 **Behavior at 32° F.**—The compound shall not crack or break when subjected to the test specified in 4.3.2.

3.4 **Behavior at 180° F.**—The compound shall remain plastic, smooth, and homogeneous when subjected to the test specified in 4.3.3.

3.5 **Behavior in water.**—The compound shall show no leakage when subjected to the test specified in 4.3.4.

3.6 **Type 1.**

3.6.1 *Condition in container.*—The compound shall be a smooth, homogeneous mixture and shall not lump or liver in the container.

3.6.2 *Workability.*—The compound shall spread readily when applied to vitreous or metal surfaces and shall be capable of being rolled into a ring.

3.7 **Type 2.**

3.7.1 *Shape.*—The compound shall be a smooth homogeneous mixture preformed into a ring of suitable diameter and cross section to insure the proper setting of the plumbing fixture.

4. SAMPLING, INSPECTION, AND TEST PROCEDURES

4.1 **Sampling.**—Unless otherwise specified, at least one package containing not less than one pound of nonpreformed compound from each

271929—54—No. 281

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:55Z
Check the source to verify that this is the current version before use.

lot of 500 packages or less and at least two preformed units equivalent to not less than one pound from each lot of 500 units or less, shall be taken at random by the inspector for inspection and tests.

4.2 **Inspection.**—Compound shall be visually examined for compliance with the requirements of the specification.

4.3 **Tests.**

4.3.1 *Staining.*—A metal ring 1½ inches outside diameter, 1¼ inches inside diameter, ⅜ inch deep shall be placed on a No. 2 Whatman filter paper and the ring filled with the fixture setting compound. The compound shall then be allowed to stand for 72 hours at a temperature between 60° and 80° F. At the end of the 72-hour period no stain shall appear outside the ring. (See 3.2.1.)

4.3.2 *Behavior at 32° F.*—Test pieces ½ inch in diameter and 3 inches long shall be exposed to a temperature of 32° F. for 1 hour, then bent quickly over a mandrel 1 inch in diameter through an arc of 180° without cracking or breaking.

4.3.3 *Behavior at 180° F.*—Test pieces shall be exposed for 1 hour in a well-ventilated room, then in an oven at 180° F. for 5 minutes, then in the room for 1 hour and then examined for plasticity, smoothness and homogeneity.

4.3.4 *Behavior in water.*—A piece of 14-mesh wire cloth bent to form a basin not less than 6 inches deep, shall be thoroughly coated with the compound to a thickness not exceeding 1/16 inch and filled with water. No leakage shall be observed within 72 hours.

4.3.5 *Screen test.*—99.6 percent of the compound shall pass a U. S. Standard 325-mesh sieve.

5. PREPARATION FOR DELIVERY

5.1 **Packaging.**—Unless otherwise specified, commercial packages will be acceptable.

5.2 **Packing.**—Unless otherwise specified, the compound shall be prepared for shipment to permit acceptance by carrier for transportation at the lowest applicable rate, and afford maximum protection from normal hazards of transportation to the point of delivery.

5.3 **Marking.**—Unless otherwise specified, packages shall be marked with the name and type of the material as defined by the contract or order under which the shipment is made, the quantity contained therein, the name of the contractor, the number of the contract or order, the name of the manufacturer and the gross weight.

6. NOTES

6.1 **Intended use.**—The compound covered by this specification is intended for forming a watertight, gastight, odorproof and vermin-proof seal for plumbing fixtures requiring gasket connections to the drainage system.

6.2 **Ordering data.**—Purchasers should specify the type desired and exercise any desired option offered herein. (See 5.1, 5.2 and 5.3.)

6.3 It is believed that this specification adequately describes the characteristics necessary to secure the desired material, and that normally no samples will be necessary prior to award to determine compliance with this specification. If, for any particular purpose, samples with bids are necessary, they should be specifically asked for in the invitation for bids, and the particular purpose to be served by the bid sample should be definitely stated, the specification to apply in all other respects.

6.4 Federal specifications do not include all types, classes, grades, sizes, etc., of the commodities indicated by the titles of the specifications, or which are commercially available, but are intended to cover the types, etc. which are suitable for Federal Government requirements.

6.5 **Transportation description.**—Transportation description applicable to this item is:

Calking compound, not otherwise indexed by name.
In bulk in barrels, kits, pails, tubs or package 589.
Carload weight 36,000 pounds.
In bulk in barrels, kits, pails, tubs or steel drums.
Truckload weight 36,000 pounds.
In containers in barrels, boxes or crates.
Carload weight 36,000 pounds.
Truckload weight 36,000 pounds.

NOTE.—Package number referred to above is defined in the current issue of the Consolidated Freight Classification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:55Z
Check the source to verify that this is the current version before use.

Patent notice.—When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data, is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

7. DEPARTMENTAL REQUIREMENTS

7.1 The following specifications and standard of the issues in effect on date of invitation for bids, and special requirements, form a part of this specification, and shall be applicable to purchases made under this specification by the respective departments:

7.2 **Army and Air Force**

7.2.1 *Applicable specifications.*

Federal Specification:

PPP–B–601—Boxes, Wood, Cleated-Plywood.

Military Specifications:

JAN–P–106—Packaging and Packing for Overseas Shipment—Boxes; Wood, Nailed.

JAN–P–117—Packaging and Packing for Overseas Shipment—Bags, Interior Packaging.

MIL–C–124—Containers (Cans, Pails, and Drums) Metal (for other than subsistence items).

Military Standard:

MIL–STD–129—Marking of Shipments

(Copies of specifications, standards, and drawings required by the contractor in connection with specific procurement functions should be obtained from the procuring agency or as directed by the contracting officer.)

7.2.2 *Packaging and packing for overseas shipment.*

7.2.2.1 *Packaging.*

7.2.2.1.1 *Type 1 compound.*—Unless otherwise specified in the contract or order, type 1 compound shall be packaged in one-pound size metal containers conforming to Military Specification MIL–C–124, type IV.

7.2.2.1.2 *Type 2 compound.*—Unless otherwise specified in the contract or order, type 2 compound shall be individually unit packaged in interior packaging bags conforming to Military Specification JAN–P–117, type II, grade A, class C, with the bags heat sealed.

7.2.2.2 *Packing.*—Unless otherwise specified in the contract or order, compound of like description shall be packed together in quantities not to exceed 200 pounds gross weight in snug-fitting nailed wood boxes conforming to Military Specification JAN–P–106, style 2, 2½, or 3, or wood cleated plywood boxes conforming to Federal Specification PPP–B–601, style A or B, for type 3 load. Suitable cushioning and blocking shall be provided to prevent movement within the boxes. The boxes shall be closed and strapped in conformance with the appendix to the applicable box specification.

7.2.3 *Marking.*

7.2.3.1 *For identification.*—Each can, bag, and box shall be marked or labeled to indicate the item and quantity contained therein.

7.2.3.2. *Marking of shipments.*—Interior packages and exterior shipping containers shall be marked in accordance with Military Standard MIL–STD–129. The nomenclature shall be as follows: Compound, Plumbing Fixture Setting, (*Type 1 "or" 2 Nonpreformed "or" Preformed), Federal Specification HH–C–536.

7.3 **Navy.**

7.3.1 *Applicable specifications and standard.*

Federal Specifications:

NN–B–591—Boxes, Wood-Cleated-Fiberboard.

PPP–B–601—Boxes, Wood, Cleated-Plywood for Domestic Shipment.

NN–B–621—Boxes, Wood, Nailed and Lock-Corner.

NN–B–631—Boxes, Wood, Wire-Bound for Domestic Shipment.

LLL–B–631—Boxes, Fiber, Corrugated (for Domestic Shipment).

LLL–B–636—Boxes, Fiber, Solid (for Domestic Shipment).

Military Specifications:

JAN–P–106—Packaging and Packing for Overseas Shipment—Boxes, Wood, Nailed.

MIL–B–107—Boxes, Wood, Wirebound (Overseas Type).

* Applicable data entered by the contractor.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:55Z
Check the source to verify that this is the current version before use.

JAN-P-108—Packaging and Packing for Overseas Shipment—Boxes, Fiberboard (V-Board and W-Board), Exterior and Interior.

JAN-P-117—Packaging and Packing for Overseas Shipment—Bags, Interior Packaging.

MIL-C-124—Containers (Cans, Pails and Drums) Metal (for other than subsistence items).

JAN-P-138—Packaging and Packing for Overseas Shipment—Boxes, Wood, Fiberboard-Lined, Metal (for other than subsistence items).

Military Standard:

MIL-STD-129—Marking of Shipments.

(Copies of specifications and standards required by contractors in connection with specific procurement functions should be obtained from the procuring agency or as directed by the contracting officer.)

7.3.2 *Packaging and packing for overseas shipment.*

7.3.2.1 *Packaging.*

7.3.2.1.1 *Type 1 compound.*—Unless otherwise specified in the contract or order, type 1 compound shall be packaged in 1-pound size metal containers conforming to Military Specification MIL-C-124, type IV.

7.3.2.1.2 *Type 2 compound.*—Unless otherwise specified in the contract or order, type 2 compound shall be individually unit packaged in interior packaging bags conforming to Military Specification JAN-P-117, type II, grade A, class C, with the bags heat sealed.

7.3.3 *Packing.*

7.3.3.1 *For domestic shipment and storage.*—The subject commodity packaged as described in 7.3.2.1 shall be packed in wood-cleated-fiber-board, wood-cleated-plywood, nailed wood, wire-bound wood, corrugated fiber, or solid fiber boxes conforming to Federal Specification NN-B-591, PPP-B-601, NN-B-621, NN-B-631, LLL-B-631, or LLL-B-636, respectively. The gross weight of wood boxes shall not exceed approximately 200 pounds. The gross weight of fiberboard boxes shall be subject to the limitation of the box specification.

7.3.3.2 *For overseas shipment.*—The subject commodity packaged as described in 7.3.2.1 shall be packed in cleated-plywood, nailed wood, wirebound, fiberboard, or fiber-lined wood boxes conforming to Federal Specification PPP-B-601, Military Specifications JAN-P-106, MIL-B-107, JAN-P-108, or JAN-P-138, respectively. The gross weight of wood boxes shall not exceed approximately 200 pounds, and of fiberboard boxes approximately 70 pounds.

7.3.4 *Marking.*—In addition to any special marking required by the contract or order, interior packages and shipping containers shall be marked in accordance with Military Standard MIL-STD-129.

7.3.5 *Ordering data.*—Procurement documents should specify whether domestic and/or overseas packing and marking are required.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:55Z
Check the source to verify that this is the current version before use.