HH-R-590B
July 28, 1976
SUPERSEDING
Fed. Spec. HH-R-590A
January 8, 1969

FEDERAL SPECIFICATION

ROOFING FELT (ASBESTOS, ASPHALT SATURATED)

This specification was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers smooth-surfaced felt, composed of asbestos and saturated with asphalt, but not coated with asphalt.

1.2 Classification.

1.2.1 Types and classes. Asphalt saturated asbestos felts shall be of the following types and classes, in 36 inch (914 mm) width, as specified (see 6.2):

Type I - Perforated.
Class A - 15 pound

Type II - Plain (imperforate).
Class A - 15 pound
Class B - 30 pound

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issues in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

Federal Specifications:

L-P-378 - Plastic Sheet and Strip, Thin Gauge Polyolefin.
UU-P-268 - Paper, Kraft, Wrapping.
MMM-A-100 - Adhesive, Animal Glue.
MMM-A-260 - Adhesive, Water Resistant (For Sealing Waterproofed Paper).
PPP-B-636 - Boxes, Shipping, Fiberboard.
PPP-B-1055 - Barrier Material, Waterproofed, Flexible.
PPP-T-60 - Tape, Packaging, Waterproof.
PPP-T-97 - Tape, Pressure Sensitive Adhesive, Filament Reinforced.

Federal Standard:

Fed. Std. No. 123 - Marking for Shipment (Civil Agencies).

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.

(Single copies of this specification and other Federal Specifications required by activities outside the Federal Government for bidding purposes are available without charge from Business Service Centers at the General Services Administration Regional Offices in Boston, New York, Washington, DC, Atlanta, Chicago, Kansas City, MO, Fort Worth, Denver, San Francisco, Los Angeles, and Seattle, WA.

FSC 5650

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:55Z
Check the source to verify that this is the current version before use.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids or request for proposal shall apply.

American Society for Testing and Materials (ASTM) Standards:

D 146 - Sampling and Testing Felted and Woven Fabric Saturated with Bituminous Substances for Waterproofing and Roofing.
D 250 - Asphalt-Saturated Asbestos Felts for Use in Waterproofing and in Constructing Built-Up Roofs.

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race St., Philadelphia, PA 19103.)

National Motor Freight Traffic Association, Inc., Agent:

National Motor Freight Classification.

(Application for copies should be addressed to the American Trucking Associations, Inc., Tariff Order Section, 1616 P Street, N.W., Washington, DC 20036.)

Uniform Classification Committee, Agent:

Uniform Freight Classification.

(Application for copies should be addressed to the Uniform Classification Committee, Room 1106, 222 South Riverside Plaza., Chicago, IL 60606.)

3. REQUIREMENTS

3.1 General. Asphalt-saturated asbestos felts covered by this specification shall conform to the requirements of the applicable American Society for Testing and Materials (ASTM) Standards as indicated herein.

3.1.1 Material. Type I, class A felt and type II, class A felt shall conform to the applicable 15-pound type in ASTM D 250. Type II, class B shall conform to the 30-pound type in ASTM D 250.

3.2 Dimensions. Width of roll shall be 36 inches (914 mm) $\pm$ 1/4 inch (6.4 mm). Area of roll (ft^2 or m^2) shall be as specified (see 6.2).

3.3 Workmanship. The felt shall be thoroughly and uniformly saturated and shall be free of visible external defects, such as holes, ragged or untrue edges, breaks, cracks, tears, protuberances, and indentations, except for intentionally provided perforations and the associated protuberances.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

Source: https://assist.dla.mil -- Downloaded: 202640-26T11:55Z
Check the source to verify that this is the current version before use.

4.2 Lot. For the purpose of sampling, a lot shall consist of the same type, class, and size of roofing felt offered for delivery at one time.

4.3 Sampling, inspection and test procedures. Sampling, inspection, and test procedures shall be in accordance with ASTM D 146.

4.4 Inspection of preparation for delivery. The packaging, packing, and marking of the roofing felt shall be examined to determine compliance with the requirements of section 5 of this specification.

5. PREPARATION FOR DELIVERY

5.1 Packing. Packing shall be level A, B, or C, as specified (see 6.2).

5.1.1 Level A. Each roll shall be completely wrapped with waterproof paper conforming to PPP-B-1055, Grade B-2 or B-3, or with plastic sheeting, polyethylene, 4 mil minimum thickness, conforming to L-P-378. The wrap shall be sealed with adhesive conforming to MMM-A-260, with tape conforming to PPP-T-60, class 1, or with heat, as applicable. Alternatively, each roll may be packaged in a box conforming to PPP-B-636, class weather resistant.

5.1.2 Level B. Each roll shall be completely wrapped in paper conforming to UU-P-268, grade B. The wrap shall be sealed with adhesive conforming to MMM-A-100, or with tape conforming to PPP-T-60. Alternatively, each roll may be packaged in a box conforming to PPP-B-636, class domestic.

5.1.3 Level C. Each roll shall be in accordance with the suppliers standard practice provided it complies with the National Motor Freight Classification or the Uniform Freight Classification as applicable.

5.2 Palletization. When specified (6.2) the palletization shall be as required in the contract or order.

5.3 Marking (see 6.2). Individual rolls and pallets shall be marked in accordance with Fed. Std. No. 123.

6. NOTES

6.1 Intended use. Asphalt-saturated felts are intended for use with asphalt plying cement in the construction of built-up roofs. Type II felts may also be used in waterproof membrane construction. Type II class B felt may also be used under slate and as a flashing material.

6.2 Ordering data. Purchasers should select the preferred options permitted herein, and include the following information in procurement documents:

(a) Title, number, and date of this specification.
(b) Type and class of felt (see 1.2).
(c) Area per roll required (see 3.2).
(d) Level of packaging and level of packing required (see 5.1 and 5.2).
(e) Special marking required (see 5.3).
(f) Palletization requirements (see 5.2).

MILITARY INTEREST:

DOD has waived coordination on revisions and amendments to this Federal Specification until further notice.

Preparing activity:

GSA-FSS

CIVIL AGENCY COORDINATING ACTIVITIES:

GSA-FSS
VA

Orders for this publication are to be placed with General Services Administration, acting as an agent for the Superintendent of Documents. See Section 2 of this specification to obtain extra copies and other documents referenced herein. Price 25 cents each.

Source: https://assist.dla.mil -- Downloaded: 202640-26T11:55Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:55Z
Check the source to verify that this is the current version before use.