COMMERCIAL ITEM DESCRIPTION

BATTERY NICKEL-CADMIUM, SECONDARY, ANSI KR334/XXX

The General Services Administration has authorized the use of this commercial item description

This commercial item description covers secondary nickel-cadmium batteries, American National Standards Institute (ANSI) size KR334/XXX(D).

Salient characteristics:

The battery performance shall be in accordance with ANSI C18.2
Terminals - flat contact
Dimensions shall be in accordance with ANSI C18.2
Continuous overcharge capability at C/10 at room temperature (25° C).
Solder tabs when specified
Electrical ratings shall be as indicated in the table as follows:

Type No.	Volts	Current Range	Average Capacity to 0.9V	Rated at
1	1.2	0-4.8 amperes	1.05 ampere hours	1.05 ampere
2	1.2	0-10 amperes	4.0 ampere hours	4.0 ampere

Certification. The contractor shall certify that the product offered meets the salient characteristics of this description and that the product conforms to the producer's own drawings, specifications, standards, and quality assurance practices and is the same product as the product offered for sale in the commercial marketplace. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

Recovered materials. The contractor shall utilize recovered materials to the maximum extent practicable.

Packaging, packing, and marking. The packaging and packing shall be in accordance with normal commercial practice and shall assure acceptance by common carrier and provide product protection against loss and damage during multiple shipments, handling, and storage. The shipping container shall be in compliance with the National Motor Freight Classification and Uniform Freight Classification. Marking shall be as specified in the contract or order.

ANSI Standards are available from the American National Standards Institute, 1430 Broadway, New York, NY 10018.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:12Z
Check the source to verify that this is the current version before use.